TC testing status

netdev 0x15 - TC workshop

Davide Caratti
Software Engineer

Red Hat

what we have in current (k)selftests

- `net/forwarding`, mostly focused on the TC *data* plane
  - using iproute2 JSON output
  - provides coverage for TC (flower) offload
- `tc-testing` (a.k.a. "tdc"), mostly focused on the TC *control* plane
  - matches the output of "human readable" iproute2
  - covers "concurrency" and TC offloads, but this is not suitable for kselftests

https://elixir.bootlin.com/linux/v5.14-rc1/source/tools/testing/selftests/tc-testing
https://elixir.bootlin.com/linux/v5.14-rc1/source/tools/testing/selftests/net/forwarding

Red Hat

more coverage for (k)selftests needed

- `for net/forwarding:`
  - only few qdiscs are actually tested
  - not all classifiers / actions are tested
- `for tc-testing` (a.k.a. “tdc”):
  - fix false negatives with “skipped” selftests
  - kselftests environment should pass the configured timeout to tdc configuration
  - onboard filters (long standing TODO item, requested by Vlad)

Red Hat

current CI platforms

- CKI (Continuous Kernel Integration)
- Linaro's LKFT
- Other? Intel kbuild?

a proper handling of "skipped" tests, ideally also something that also detects iproute2 support, would increase quality of results

Red Hat

open discussion

- performance tests, is it worth doing?
- Shall we use a validator to detect iproute2 JSON output?
- other questions?

Red Hat

Thank you

Red Hat is the world's leading provider of enterprise open source software solutions. Award-winning support, training, and consulting services make Red Hat a trusted adviser to the Fortune 500.


linkedin.com/company/red-hat


youtube.com/user/RedHatVideos


facebook.com/redhatinc


twitter.com/RedHat

Red Hat