IP tunnels metada classifier/action

- cls_flower to support classifying by iptunnel metadata
  - ...flower enc_src_ip 11.11.0.2 enc_dst_ip 11.11.0.1 enc_key_id 0x11 ...
- act_tunnel_key
  - Encap – create metadata
    ...action tunnel_key set src_ip 11.11.0.1 dst_ip 11.11.0.2 id 0x11 \
    action mirred egress redirect dev vxlan0
  - Decap – release metadata
    ..action tunnel_key release \
    action mirred egress redirect dev eth0

VLAN

- cls_flower to support classify by vlan
  - ...flower vlan_ethtype ipv4 vlan_id 100 vlan_prio ...
- Mlx5 to support offloaded cls_flower + act_vlan

Mlx5 TC offloads

- Management flags – same as u32
  - NETIF_F_HW_TC – ethtool -K hw-tc-offload on
  - cls_flower flag: skip_hw/skip_sw/null
- Mlx5 supported actions
  - Drop (NIC/SR-IOV) – ...action drop
  - Mark (NIC) – ...action skbedit mark 0x1234
  - Vlan (NIC) – ...action vlan push id 100 priority 5
  - Redirect (SR-IOV) – ...action mirred redirect
- Mlx5 statistics
  - Bulk probe of HW counters
  - Lastuse emulated by software