

CSE 4650: Systems Programming Lab

Lab 2

Data Lab: Manipulating Bits

Lab Credit: CMU ICS Course

Course Teacher: Imtiaz Ahmed Chowdhury, Lecturer, CSE

1 Introduction

The purpose of this assignment is to become more familiar with bit-level representations of integers. You'll do this by solving a series of programming "puzzles." Many of these puzzles are quite artificial, but you'll find yourself thinking much more about bits in working your way through them.

2 Assignment Instructions

Start by copying `datalab.zip` to a directory on a Linux machine in which you plan to do your work. Then give the command

```
unix> unzip datalab.zip
```

This will cause a number of files to be unpacked in the directory. The only file you will be modifying is `bits.c`. ****Do Not Modify Any Other Files.**** Those files are required to autograde your work. You are encouraged to look at those though :)

The `bits.c` file contains a skeleton for each of the 10 programming puzzles. Your assignment is to complete each function skeleton using only *straightline* code (i.e., no loops or conditionals) and a limited number of C arithmetic and logical operators. Specifically, you are *only* allowed to use the following eight operators:

```
! ~ & ^ | + << >>
```

A few of the functions further restrict this list. Also, you are not allowed to use any constants longer than 8 bits. See the comments in `bits.c` for detailed rules and a discussion of the desired coding style.

3 The Puzzles

This section describes the puzzles that you will be solving in `bits.c`.

Table 1 lists the puzzles in rough order of difficulty from easiest to hardest. The “Rating” field gives the difficulty rating (the number of points) for the puzzle, and the “Max ops” field gives the maximum number of operators you are allowed to use to implement each function. See the comments in `bits.c` for more details on the desired behavior of the functions. You may also refer to the test functions in `tests.c`. These are used as reference functions to express the correct behavior of your functions, although they don’t satisfy the coding rules for your functions.

Name	Description	Rating	Max ops
<code>bitOr(x, y)</code>	$x \mid y$ using only <code>~</code> and <code>&</code>	1	8
<code>minusOne()</code>	return a value of <code>-1</code>	1	2
<code>tmax()</code>	return maximum two’s complement integer	1	4
<code>byteSwap(x, n, m)</code>	swaps the n^{th} byte and the m^{th} byte of <code>x</code>	2	25
<code>copyLSB(x)</code>	set all bits of result to least significant bit of <code>x</code>	2	5
<code>bitMask(h, l)</code>	create a mask consisting of all 1’s in between <code>h</code> and <code>l</code> bits	3	16
<code>conditional(x, y, z)</code>	same as <code>x ? y : z</code>	3	16
<code>isAsciiDigit(x)</code>	return 1 if $0x30 \leq x \leq 0x39$	3	15
<code>absVal(x)</code>	absolute value of <code>x</code>	4	10
<code>isNonZero(x)</code>	Check whether <code>x</code> is nonzero	4	10

Table 1: Datalab puzzles.

4 Evaluation

Your score will be computed out of a maximum of 50 points based on the following distribution:

24 Correctness points.

20 Performance points.

6 Style points.

Correctness points. The puzzles you must solve have been given a difficulty rating between 1 and 4, such that their weighted sum totals to 24. We will evaluate your functions using the `btest` program, which is described in the next section. You will get full credit for a puzzle if it passes all of the tests performed by `btest`, and no credit otherwise.

Performance points. Our main concern at this point in the course is that you can get the right answer. However, we want to instill in you a sense of keeping things as short and simple as you can. Furthermore, some of the puzzles can be solved by brute force, but we want you to be more clever. Thus, for each function we’ve established a maximum number of operators that you are allowed to use for each function. This limit

is very generous and is designed only to catch egregiously inefficient solutions. You will receive two points for each correct function that satisfies the operator limit.

Style points. Finally, we've reserved 6 points for a subjective evaluation of the style of your solutions and your commenting. Your solutions should be as clean and straightforward as possible. Your comments should be informative, but they need not be extensive.

Autograding your work

We have included some autograding tools in the handout directory — `btest`, `dlc`, and `driver.pl` — to help you check the correctness of your work.

- **btest:** This program checks the functional correctness of the functions in `bits.c`. To build and use it, type the following two commands:

```
unix> make
unix> ./btest
```

Notice that you must rebuild `btest` each time you modify your `bits.c` file.

You'll find it helpful to work through the functions one at a time, testing each one as you go. You can use the `-f` flag to instruct `btest` to test only a single function:

```
unix> ./btest -f bitXor
```

You can feed it specific function arguments using the option flags `-1`, `-2`, and `-3`:

```
unix> ./btest -f bitXor -1 4 -2 5
```

Check the file `README` for documentation on running the `btest` program.

- **dlc:** This is a modified version of an ANSI C compiler from the MIT CILK group that you can use to check for compliance with the coding rules for each puzzle. The typical usage is:

```
unix> ./dlc bits.c
```

The program runs silently unless it detects a problem, such as an illegal operator, too many operators, or non-straightline code in the integer puzzles. Running with the `-e` switch:

```
unix> ./dlc -e bits.c
```

causes `dlc` to print counts of the number of operators used by each function. Type `./dlc -help` for a list of command line options.

- **driver.pl:** This is a driver program that uses `btest` and `dlc` to compute the correctness and performance points for your solution. It takes no arguments:

```
unix> ./driver.pl
```

We will use `driver.pl` to evaluate your solution.

5 Handin Instructions

After you're done implementing the functions inside `bits.c`, zip all the files that's given to you and submit the zip file in the google classroom assignment. Rename your zip file as `ID_datalab.zip`. Include your full ID.

6 Advice

- Don't include the `<stdio.h>` header file in your `bits.c` file, as it confuses `dlc` and results in some non-intuitive error messages. You will still be able to use `printf` in your `bits.c` file for debugging without including the `<stdio.h>` header, although `gcc` will print a warning that you can ignore.
- The `dlc` program enforces a stricter form of C declarations than is the case for C++ or that is enforced by `gcc`. In particular, any declaration must appear in a block (what you enclose in curly braces) before any statement that is not a declaration. For example, it will complain about the following code:

```
int foo(int x)
{
    int a = x;
    a *= 3;      /* Statement that is not a declaration */
    int b = a;   /* ERROR: Declaration not allowed here */
}
```