Zajel Merchant API Document v. 1.6

Technical Document

Version: 1.6 – 17th Dec 2024

Document Owner: Mohammed Shaheer

Revised By: Sufiyan Siraj

Contents

Technical Document 1

Contents 2

Introduction 3

Authenticate 3

Endpoints 4

01. Create Shipment 4

02.Track Shipment 11

03.Get Cities 13

04.Get Areas 15

05.GetShipmentLabel 16

Webhooks: 16

01.Update Status (Post Events from Zajel-> Customer) 16

Introduction

We have developed a set of APIs to seamlessly connect two systems, enabling efficient communication and data exchange. This robust integration solution serves as a bridge between Zajel system and customers/merchant's systems, empowering organizations to enhance their workflows, streamline processes, and achieve unparalleled synergy.

Our API facilitates the secure and real-time transfer of essential data, ensuring that both systems operate harmoniously. Whether you are looking to synchronize critical information, automate tasks, or improve overall system interoperability, our API provides a reliable and scalable solution.

Experience the power of simplified integration, reduced manual intervention, and increased operational efficiency. Elevate your business processes by unlocking the potential of interconnected systems with our cutting-edge API.

- Production Base URL: https://api.zajel.com:8443/services/integration
- Staging Base URL: https://api-stg.zajel.com/services/integration

Authenticate

To ensure secure access to our API, we implement API key authentication. This method requires each request to include a unique API key, a secret token that identifies and authenticates the user making the API call.

KEY-NAME : X-AUTH-API-KEY

KEY VALUE: Will be provided by Zajel.

Using Your API Key

Include your API key in the header of every API request you make.

Important Notes

- Keep your API key confidential to prevent unauthorized access.
- Do not embed your API key in publicly accessible areas such as GitHub, client-side code, etc.
- If you believe your API key has been compromised, regenerate a new key immediately from your dashboard.

For further assistance or any queries regarding API key authentication, please contact our support team.

To access the API, you need to include the API key in the request header. The API KEY will be provided by Zajel.

Endpoints

01. Create Shipment

- Request
  - **Method**: POST
  - **Endpoint**: /api/Merchant/CreateShipment
  - **Body**: JSON
  - **Sample Request**: In the above given example, there is a Json with contains 3 objects containing multiple properties.
- CURL

```
curl -X 'POST' \
  'https://api-stg.zajel.com/services/integration/api/Merchant/CreateShipment' \
  -H 'accept: */*' \
  -H 'X-AUTH-API-KEY: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX \
  -H 'Content-Type: application/json' \
  -d '{
  "customer_reference_number": "",
  "weight_in_kg": 1.25,
  "customer_code": "XYZ",
  "service_type_id": "NEXT DAY DELIVERY - DOMESTIC",
  "product_type": "NON-DOCUMENT",
  "description": "toys and gift cards",
  "length_in_cm": 0,
```

```
  "width_in_cm": 0,
  "height_in_cm": 0,
  "num_of_pieces": 0,
  "cod_amount": "0",
  "origin": {
    "name": "John Doe",
    "phone": "9715123456789",
    "company_name": "ABC Store",
    "address_line_1": "Street 6, Block B 123, Burj Khalifa tower, Downtown, Dubai",
    "address_line_2": "Al khawaja building office 122",
    "area": "",
    "city": "DXB",
    "country": "UAE",
    "email": "xyz@yahoo.com",
    "latitude": "",
    "longitude": ""
  },
  "destination": {
    "name": " John Doe",
    "phone": "9715123456788",
    "companyName": "ABC Store",
    "address_line_1": "Street 6, Block B 123, Burj Khalifa tower, Downtown, Dubai",
    "address_line_2": "Al khawaja building office 122",
    "area": "AL GARHOUD",
    "city": "DXB",
    "country": "UAE",
    "email": "XYZD@yahoo.com",
    "latitude": "",
    "longitude": ""
  }
}
'
```

Below are the details of the request

Property Name	Mandatory/ optional	Data type	Max	Remarks

reference_number	Optional	string	30	If reference_number is provided, the system will try to create the shipment with this reference number. If not provided, the system will generate its own reference number. Recommendation: Keep this empty.
customer_reference_number	Optional	string	30	This should be the reference number from the merchant system. If
weight_in_kg	Mandatory	double (max 2 decimals)	0- 999	Example values: 0.05, 1, 1.25
customer_code	Mandatory	string		A unique identifier for customers, provided by Zajel. This code is used to reference customers within the system or API interactions
service_type_id	Mandatory	string		This will be a constant, will be provided by Zajel
product_type	Mandatory	string		"DOCUMENT" or "NON-DOCUMENT"
description	Optional	string	150	This can be used to describe the shipment. This will be displayed in the printed AWB.
length_in_cm	Optional	double (max 2 decimals)	0-1000	Length of the shipment
width_in_cm	Optional	double (max 2 decimals)	0-1000	Width of the shipment
height_in_cm	Optional	double (max 2 decimals)	0-1000	Height of the shipment
cod_amount	Optional	double (max 2 decimals)	0-9999	This is the amount that needs to be collected from the end customer while delivering the shipment as "Cash On Delivery" charges.
num_of_pieces	Optional	integer	0-100	In case of multipiece shipments, the number of pieces should be mentioned. The system will create as many child AWBs as mentioned in this field.

- Sender information to send in with following fields.

Property Name	Mandatory/ optional	Data type	Max	Remarks

Origin.name	Mandatory	string	100	Name of the shipper
Origin.phone	Mandatory	string	20	Allows following format in case the origin country is "UAE" +9715 followed by 8 digits +971[1-46-9] followed by 7 digits 9715 followed by 8 digits without the plus sign 971[1-46-9] followed by 7 digits without the plus sign: 0[1-46-9] followed by 7 digits 05 followed by 8 digits 5 followed by 8 digits: 009715 followed by 8 digits: 00971[1-46-9] followed by 7 digits
Origin.company_name	Optional	string	100	Company name of the shipper
Origin.address_line_1	Mandatory	string	255	Should clearly shows shipper's address like office name, number, street, etc.
Origin.address_line_2	Optional	string	255	Some more related information, to reach the shipper as easily as possible.
Origin.area	Optional	string	100	Area value should be the "area_value" being picked up from the getAreas endpoint.
Origin.city	Mandatory	string	50	City value should be the "city_code" being picked up from the getCities endpoint.
Origin.country	Mandatory	string	50	If domestic then UAE otherwise put the international country name(alpha 3 code)
Origin.email	Optional	string	100	
Origin.latitude	Optional	string	50	
Origin.longitude	Optional	string	50	

- Receiver information to send in with following fields.

Property Name	Mandatory/ optional	Data type	Max	Remarks
destination.name	Mandatory	string	50	Name of the receiver
destination.phone	Mandatory	string	20	+9715 followed by 8 digits +971[1-46-9] followed by 7 digits 9715 followed by 8 digits without the plus sign 971[1-46-9] followed by 7 digits without the plus sign: 0[1-46-9] followed by 7 digits 05 followed by 8 digits 5 followed by 8 digits: 009715 followed by 8 digits: 00971[1-46-9] followed by 7 digits
destination.address_line_1	Mandatory	string	255	Should clearly shows destination's address like office name, number, street, etc.
destination .address_line_2	Optional	string	255	Some more related information, to reach the destination as easily as possible.
destination .area	Optional	string	50	Area value should be the "area_value" being picked up from the getAreas endpoint.
destination .city	Mandatory	string	50	City value should be the "city_code" being picked up from the getCities endpoint.
destination .country	Mandatory	string	50	If domestic then UAE otherwise put the international country name
destination .email	Optional	string	50	

destination .latitude	Optional	string	50	
destination .longitude	Optional	string	50	

Sample Response:

- Success – 201 Created

```
{
  "message": null,
  "success": true,
  "referenceNumber": "9010010050",
  "customerReferenceNumber": "234567111112",
  "pieces": [
    {
      "referenceNumber": "9010010050",
      "productCode": ""
    }
  ],
  "error": null
}
```

Failure – 400 Bad Request

```
{
  "type": "https://tools.ietf.org/html/rfc7231#section-6.5.1",
  "title": "One or more validation errors occurred.",
  "status": 400,
  "traceId": "00-8ea2f7bda41a158a2d1ecfffbe5f85b2-8ef39267eec053d5-00",
  "errors": {
    "ProductType": [
      "Product Type must be 'DOCUMENT' or 'NON-DOCUMENT'."
    ]
  }
}
```

- Failure – 401 · Unauthorized Request – In case of wrong customer_code or api-key.
- Failure – 403 · Method not allowed – In case access to a particular api is not provided.
- Failure – 500 · Internal server error – In case of any internal server errors.

02.Track Shipment

- ## Request
    - **Method**: GET
    - **Endpoint**: /api/Merchant/TrackShipment
    - **Parameters**: 'reference_number' (required): reference_number that was created in create shipment endpoint -> Airwaybill Number.
- CURL

```
curl -X 'GET' \
  'https://api-
stg.zajel.com/services/integration/api/Merchant/TrackShipment?reference_number=9010010051' \
  -H 'accept: */*' \
  -H 'X-AUTH-API-KEY: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Sample Response:

- Success – 200

```
{
  "reference_number": "9010010051",
  "customer_reference_number": "234567111112",
  "status": "pickup_awaited",
  "status_applied_on": "31-Mar-2024 19:35:16"
}
```

- Failure – 401 - Unauthorized Request – In case of wrong customer_code or api-key.
- Failure – 403 - Method not allowed – In case access to a particular api is not provided.
- Failure – 404 - Shipment not found – In case of wrong AWB number.
- Failure – 500 - Internal server error – In case of any internal server errors.

03. Cancel Shipment

For cancelling the shipment. Allows only pickup_awaited shipment

- ## Request
    - **Method**: POST
    - **Endpoint**: /api/Merchant/CancelShipment'
    - **Parameters**: 'reference_number' (required): reference_number that was created in create shipment endpoint -> Airwaybill Number.
- CURL

```
curl --location 'https://api-stg.zajel.com/services/integration/api/Merchant/CancelShipment'
\
--header 'accept: text/plain' \
--header 'X-AUTH-API-KEY:
76s7d8fs76df878sdsd7f876a8s76asdy7asdn1okmb219y2mk21j80021831nb2fc' \
--header 'Content-Type: application/json' \
--data '{
  "reference_number": "9050000818"
}'
```

Sample Response:

- Success – 200

```
{
    "message": "Status of the shipment does not allow cancellation",
    "success": false
}
```

- Failure – 401 - Unauthorized Request – In case of wrong customer_code or api-key.
- Failure – 403 - Method not allowed – In case access to a particular api is not provided.
- Failure – 404 - Shipment not found – In case of wrong AWB number.
- Failure – 500 - Internal server error – In case of any internal server errors.

04.Get Cities

- Request
  - **Method**: GET
  - **Endpoint**: /api/Merchant/GetCities
  - **Parameters**: 'country_code' (optional)
- CURL

```
curl -X 'GET' \
  'https://api-stg.zajel.com/services/integration/api/Merchant/GetCities' \
  -H 'accept: */*' \
  -H 'X-AUTH-API-KEY: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
```

This api is helpful in getting a list of all the available cities.

It doesn't require a parameter by default as it's set to UAE, but if you're looking for international services then you have to search using parameter 'country_code' and type in the country name to get country that country-based information.

Sample Response:

- Success - 200 OK

```
[
  {
    "city_code": "AUH",
    "city_name": "Abu Dhabi",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  },
  {
    "city_code": "AJM",
    "city_name": "Ajman",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  },
  {
    "city_code": "DXB",
    "city_name": "Dubai",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  },
  {
    "city_code": "FUJ",
```

```
    "city_name": "Fujairah",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  },
  {
    "city_code": "SHJ",
    "city_name": "Sharjah",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  },
  {
    "city_code": "UAQ",
    "city_name": "Umm Al Quwain",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  },
  {
    "city_code": "AIN",
    "city_name": "Al Ain",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  },
  {
    "city_code": "RAK",
    "city_name": "Ras Alkhaimah",
    "country_code": "UAE",
    "country_name": "United Arab Emirates"
  }
]
```


- Failure – 401 · Unauthorized Request – In case of wrong customer_code or api-key.
- Failure – 403 · Method not allowed – In case access to a particular api is not provided.
- Failure – 404 · Shipment not found – In case of wrong AWB number.
- Failure – 500 · Internal server error – In case of any internal server errors.

05.Get Areas

- ## Request
  - **Method**: GET
  - **Endpoint**: /api/Merchant/GetAreas
  - **Parameters**: 'city_code' (optional)

- CURL

```
curl -X 'GET' \
  'https://api-stg.zajel.com/services/integration/api/Merchant/GetAreas?city_code=DXB' \
  -H 'accept: */*' \
  -H 'X-AUTH-API-KEY: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
```

  -

- This api provides information of all the areas with all the cities inside UAE, but if you're looking for areas within any particular city then you have to use the parameter "city_code" and type the city code of the location like (DXB, SHJ, AUH, etc).

Sample Response:

- Success - 200 OK

```
[
  {
    "id": 748,
    "area_name": "AL WAHEDA",
    "city_code": "DXB",
    "city_name": "Dubai"
  },
  {
    "id": 1013,
    "area_name": "AL KIFAF",
    "city_code": "DXB",
    "city_name": "Dubai"
  },
  {
    "id": 1044,
    "area_name": "AL SATWA",
    "city_code": "DXB",
    "city_name": "Dubai"
  }
]
```

- Failure – 401 · Unauthorized Request – In case of wrong customer_code or api-key.
- Failure – 403 · Method not allowed – In case access to a particular api is not provided.
- Failure – 404 · Area not found .
- Failure – 500 · Internal server error – In case of any internal server errors.

06.GetShipmentLabel

- Request
  - **Method**: GET
  - **Endpoint**: /api/Merchant/GetShipmentLabel
  - **Parameters**: 'reference_number' (required): reference_number that was created in create shipment endpoint -> Airwaybill Number.
  - **Response**: 200 OK
- CURL

```
curl -X 'GET' \
  'https://api-
stg.zajel.com/services/integration/api/Merchant/GetShipmentLabel?reference_number=9010010049
' \
  -H 'accept: */*' \
  -H 'X-AUTH-API-KEY: XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX'
```

Webhooks:

01.Update Status (Post Events from Zajel-> Customer)

- Request.

  This webhook should be implemented on the customer side to listen to events and details

sent by Zajel regarding their shipment updates.

- **Method**: POST
- **Base URL**: {Customer should provide it to Zajel}
- **Endpoint**: {Customer should provide it to Zajel}
- **Body**: JSON

Sample Request:

The webhook should follow the below request structure. The webhook can be protected by an API-KEY or BASIC AUTH. In both cases, the credentials has to be shared. The webhook will share the following events.

Status	Description
outfordelivery	Sent when the shipment is out for delivery
attempted	Sent after an unsuccessful attempted pickup or delivery
cancelled	Sent when the shipment is cancelled
delivered	Sent when the shipment is delivered successfully to the destination
inscan_at_hub	Sent when the shipment is received and scanned at Zajel's Office
on_hold	Sent when the shipment is held at Zajel's Office
pickup_awaited	Sent when the shipment is ready and available for the pickup
pickup_completed	Sent after a successful pickup
reachedathub	Sent when the shipment arrives at Zajel's Office
rto	Sent when the shipment is ready to be returned to the origin
rto_attempted	Sent when an attempt is made to delivery the shipment back to the origin
rto_delivered	Sent when the shipment is delivered successfully to the origin
softdata_update	Sent as soon as the user updates any information
softdata_upload	Sent as soon as Zajel receives the data for the shipment

```
{
"reference_number": "MER00319",
"customer_reference_number": "ZX00002",
"status": "Receive_at_Hub",
"event_date_time": "2023-11-20 12:34:56",
"description": "Consignment Receive at Hub",
"received_by": "Jane Doe",
"delivery_courier": "John Doe",
"pod": "affobfuvb9+49898fw7897fw...",
"failure_reason": null,
}
```