086761 - Homework 1

Yuri Feldman, 309467801

November 9, 2017

1

1.1

$$f_x(x) = \frac{1}{\sqrt{|2\pi\Sigma_x|}} \cdot e^{-\frac{1}{2}(x-\mu_x)^T \Sigma_x^{-1}(x-\mu_x)}$$
 (1.1)

1.2

 μ_y , Σ_y can be calculated using expectation properties (and do not depend on y being Gaussian):

$$\mu_y = \mathbb{E}Ax + b = A\mathbb{E}x + b = \boxed{A\mu_x + b}$$
 (1.2)

$$\Sigma_y = \mathbb{E}\left[(Ax + b - \mu_y)(Ax + b - \mu_y)^T \right] = \mathbb{E}\left[A(x - \mu_x)(x - \mu_x)^T A^T \right] = \tag{1.3}$$

$$A\mathbb{E}\left[(x-\mu_x)(x-\mu_x)^T\right]A^T = \boxed{A\Sigma_x A^T}$$
(1.4)

Next, we show that y is Gaussian. In the case where A is invertible this can be directly obtained from random vector transformation formula (1-to-1 transformation). Since y = Ax + b the Jacobian matrix is A and since the mapping is one-to-one (A is invertible) according to the transformation theorem:

$$f_Y(y) = \frac{1}{|A|} f_X(A^{-1}(y - b))$$
(1.5)

ignoring the constant normalization factors (since they don't depend on x and only guarantee the distributions' summing to 1) we calculate the exponent in the right hand side:

$$-\frac{1}{2}\left(A^{-1}(y-b) - \mu_x\right)^T \Sigma_x^{-1} \left(A^{-1}(y-b) - \mu_x\right) = \tag{1.6}$$

$$-\frac{1}{2}(y-b-A\mu_x)^T A^{-T} \Sigma_x^{-1} A^{-1} (y-b-A\mu_x) =$$
 (1.7)

$$-\frac{1}{2}(y - (A\mu_x + b))^T (A\Sigma_x A^T)^{-1} (y - (A\mu_x + b)), \qquad (1.8)$$

which exactly gives a Gaussian distribution (in particular, with the mean and variance we calculated beforehand).

We now deal with the case where $A \in \mathbb{R}^{m \times n}$ is not invertible - either rectangular or square with zero determinant. Consider the SVD decomposition of A:

$$A = U\Sigma V^T \tag{1.9}$$

Here, U and V are square invertible matrices of respective sizes $m \times m$ and $n \times n$. Note that $V^T = V^*$ as A is real. Σ is a rectangular matrix the same size as A with the main diagonal containing the singular values (and zero elsewhere). We can now write:

$$y = U\Sigma V^T x + b \tag{1.10}$$

Here, $V^T x$ is Gaussian, since V is invertible. Without loss of generality denote

$$\Sigma = \begin{pmatrix} \Sigma_1 & 0 \\ 0 & 0 \end{pmatrix} \qquad V^T x = \begin{pmatrix} v_1 \\ v_2 \end{pmatrix}, \tag{1.11}$$

where Σ_1 is (square) diagonal, with positive entries (and in particular, is invertible), and has the same number of columns as the length of vector v_1 . We have then that

$$\Sigma V^T x = \begin{pmatrix} \Sigma_1 v_1 \\ 0 \end{pmatrix}, \tag{1.12}$$

where $\Sigma_1 v_1$ is Gaussian since v_1 is and Σ_1 is invertible, and hence $\Sigma V^T x = U^T (y - b)$ is (possibly degenerate) Gaussian (and hence, so is y).

2

2.1

$$p(x \mid z) = \frac{p(z \mid x)p(x)}{p(z)} = \frac{p(z \mid x)p(x)}{\int_{x} p(z \mid x)p(x) \cdot dx} \propto p(z \mid x) \cdot p(x)$$
 (2.1)

2.2

We are interested in the MAP estimate:

$$x_{\text{MAP}}^* \doteq \arg\max_{x} p(x \mid z) = \arg\max_{x} p(z \mid x) \cdot p(x) = \arg\max_{x} \log p(z \mid x) + \log p(x) = \quad (2.2)$$

$$\underset{x}{\arg\min} ||z - Hx||_{R}^{2} + ||x - x_{0}||_{\Sigma_{0}}^{2}$$
(2.3)

Develop the latter:

$$||z - Hx||_R^2 + ||x - x_0||_{\Sigma_0}^2 = \left| \left| R^{-1/2} (Hx - z) \right| \right|^2 + \left| \left| \Sigma_0^{-1/2} (x - x_0) \right| \right|^2 =$$
 (2.4)

$$\left\| \begin{pmatrix} R^{-1/2}(Hx-z) \\ \Sigma_0^{-1/2}(x-x_0) \end{pmatrix} \right\|^2 = \left\| \begin{pmatrix} R^{-1/2}H \\ \Sigma_0^{-1/2} \end{pmatrix} x - \begin{pmatrix} R^{-1/2}z \\ \Sigma_0^{-1/2}x_0 \end{pmatrix} \right\|^2, \tag{2.5}$$

from where x_{MAP}^* can be obtained as the least-squares solution using the pseudoinverse $A^{\dagger}b = (A^TA)^{-1}A^Tb$, or equivalently proceed directly, noting that the function is convex and has a unique extremum which is the minimum. Develop the above into:

$$= x^{T} \left(H^{T} R^{-1} H + \Sigma_{0}^{-1} \right) x - 2 \left(z^{T} R^{-1} H + x_{0}^{T} \Sigma_{0}^{-1} \right) x + \left(z^{T} R^{-1} z + x_{0}^{T} \Sigma_{0}^{-1} x_{0} \right)$$
 (2.6)

find the zero of the gradient:

$$\nabla(\cdot) = 2\left(H^T R^{-1} H + \Sigma_0^{-1}\right) x^* - 2\left(\Sigma_0^{-1} x_0 + H^T R^{-1} z\right) = 0 \tag{2.7}$$

$$\Longrightarrow x_{MAP}^* = \left(H^T R^{-1} H + \Sigma_0^{-1}\right)^{-1} \left(\Sigma_0^{-1} x_0 + H^T R^{-1} z\right)$$
 (2.8)

The associated covariance is

$$\Sigma = \left(H^T R^{-1} H + \Sigma_0^{-1} \right)^{-1} , \tag{2.9}$$

as can be seen from the quadratic term in Eq.(2.6).

3 Code

3.1 Rotations

3.1.1

```
In [14]: def rotx(phi):
    v = phi*np.array([1, 0, 0]);
    return get_rotation_rodriguez(v)

def roty(theta):
    v = theta*np.array([0, 1, 0]);
    return get_rotation_rodriguez(v)

def rotz(psi):
    v = psi*np.array([0, 0, 1]);
    return get_rotation_rodriguez(v)

def angles2rot(phi, theta, psi):
    return rotz(psi)*roty(theta)*rotx(phi)
```

3.1.2

```
In [16]: print('R= \n' + str(angles2rot(phi=pi/4, theta=pi/5, psi=pi/7)))
R=
[[ 0.72889912554     0.06766479742     0.68126906578]
[ 0.35101931853     0.81741496597     -0.45674742629]
[-0.58778525229     0.57206140282     0.57206140282]]
```

3.1.3

Development here is based on [1].

We first write the rotation matrix as the product of individual axis rotation matrices:

$$\begin{pmatrix}
\cos(\psi)\cos(\theta) & \cos(\psi)\sin(\phi)\sin(\theta) - \cos(\phi)\sin(\psi) & \sin(\phi)\sin(\psi) + \cos(\phi)\cos(\psi)\sin(\theta) \\
\cos(\theta)\sin(\psi) & \cos(\phi)\cos(\psi) + \sin(\phi)\sin(\psi)\sin(\theta) & \cos(\phi)\sin(\psi)\sin(\theta) - \cos(\psi)\sin(\phi) \\
-\sin(\theta) & \cos(\theta)\sin(\phi) & \cos(\phi)\cos(\theta)
\end{pmatrix}$$
(3.1)

Given rotation matrix R, we will want to extract angles by demanding per-element equality. We treat separately the case where $\cos(\theta) = 0$. For the case $\theta = \frac{\pi}{2}$ we obtain the matrix:

$$\begin{pmatrix}
0 & \cos(\psi)\sin(\phi) - \cos(\phi)\sin(\psi) & \sin(\phi)\sin(\psi) + \cos(\phi)\cos(\psi) \\
0 & \cos(\phi)\cos(\psi) + \sin(\phi)\sin(\psi) & \cos(\phi)\sin(\psi) - \cos(\psi)\sin(\phi) \\
-1 & 0 & 0
\end{pmatrix} (3.2)$$

$$= \begin{pmatrix} 0 & \sin(\phi - \psi) & \cos(\phi - \psi) \\ 0 & \cos(\phi - \psi) & -\sin(\phi - \psi) \\ -1 & 0 & 0 \end{pmatrix}$$
(3.3)

For the case $\theta = -\frac{\pi}{2}$:

$$\begin{pmatrix}
0 & -\cos(\psi)\sin(\phi) - \cos(\phi)\sin(\psi) & \sin(\phi)\sin(\psi) - \cos(\phi)\cos(\psi) \\
0 & \cos(\phi)\cos(\psi) - \sin(\phi)\sin(\psi) & -\cos(\phi)\sin(\psi) - \cos(\psi)\sin(\phi) \\
1 & 0 & 0
\end{pmatrix} (3.4)$$

$$= \begin{pmatrix} 0 & -\sin(\phi + \psi) & -\cos(\phi + \psi) \\ 0 & \cos(\phi + \psi) & -\sin(\phi + \psi) \\ 1 & 0 & 0 \end{pmatrix}$$

$$(3.5)$$

From here we proceed extracting the angles (see code and [1]).

```
In [17]: def rot2angles(M):
           sin_{theta} = -M[2, 0];
           theta = asin(sin_theta);
           if sin_theta==1:
              psi = 0; # arbitrary
              phi = atan2(M[0,1],M[0,2]);
                  sin_theta==-1:
              psi = 0; # arbitrary
              phi = atan2(-M[0,1],-M[0,2]);
           else:
              # another valid solution: pi-theta.
              cos_theta = cos(theta);
              phi = atan2(M[2,1]/cos_theta, M[2, 2]/cos_theta);
              psi = atan2(M[1,0]/cos_theta, M[0, 0]/cos_theta);
           return phi, theta, psi
3.1.4
```

```
In [22]: phi, theta, psi = (degrees(x) for x in rot2angles(
np.mat(' 0.813797681 -0.440969611 0.378522306; \
                                       0.882564119 0.0180283112; \
                          0.46984631
                          -0.342020143 0.163175911 0.925416578')))
print('phi=' + str(phi), 'theta=' + str(theta), 'psi=' + str(psi))
```

phi=9.99999994217536 theta=19.999999980143038 psi=29.99999998990158

3.2 3D Rigid Transformation

$$l^{C} = R_{G}^{C}l^{G} + t_{C \to G}^{C} = R_{G}^{C}(l^{G} + t_{C \to G}^{G})$$
In [23]: trans = np.mat([-451.2459, 257.0322, 400])
rot = np.mat('0.5363 -0.8440 0; 0.8440 0.5363 0; 0 0 1');

pt = np.mat([450, 400, 50])

Tgl = rot.dot((pt + trans).T)
print(Tgl)

[[-555.20335297]
[351.31482926]
[450.]]

3.3 Pose Composition

Commanded:

$$x_{k+1}^c = x_k + \begin{pmatrix} 1 \\ 0 \end{pmatrix} {3.7}$$

$$R_{k+1}^c = R_k^c \tag{3.8}$$

$$R_{k+1}^{c} = R_{k}^{c}$$

$${}^{k+1}_{k}T^{(commanded)} = \left(I \quad {1 \choose 0}\right)$$

$$(3.8)$$

Actual:

$$x_{k+1}^a = x_k + \begin{pmatrix} 1.01\\0 \end{pmatrix} \tag{3.10}$$

$$R_{k+1}^{a} = R(\theta = 1^{\circ}) \cdot R_{k}^{c} \tag{3.11}$$

$$R_{k+1}^{a} = R(\theta = 1^{\circ}) \cdot R_{k}^{c}$$

$${}^{k+1}_{k} T^{(actual)} = \left(R(\theta^{\circ}) \quad {1.01 \choose 0} \right)$$

$$(3.11)$$

In [24]: for ii in range(10):

Bibliography

[1] Gregory G Slabaugh. Computing euler angles from a rotation matrix. Retrieved on August, 6(2000):39-63, 1999.