

# 1 Question 1

Moving robot gets odometry measurements at each step. Additionally, gets image observations of a single landmark at time steps 1 and 4.

## 1.1

Develop posterior at time 4 in terms of measurement and motion models, assume prior exists for  $x_1$

## 1.2

Draw corresponding factor graph. Detail what every node and edge correspond to.

## 1.3

Eliminate factor graph into a Bayes net, assuming elimination order  $x_1, x_2, x_3, x_4, l$ . Detail your calculations. Draw obtained Bayes net and square root information  $\mathbf{R}$  matrix sparsity pattern.

# 2 Question 2

Given:

- camera 6 DoF pose  $R_C^G, t_{G \rightarrow C}^G$
- camera calibration matrix  $K$
- landmark  $l^G$  **given** (in global frame)

## 2.1

Develop projection matrix  $M^r$  for camera  $r$ , note all dimensions.

## 2.2

Express projected pixel coordinates  $\begin{pmatrix} u \\ v \end{pmatrix}$  of a point  $\begin{pmatrix} x \\ y \\ z \end{pmatrix}^G$  in terms of  $M^r$  components.

## 2.3

Given  $n$  observations of the landmark  $\{(u_i, v_i)\}_{i=1}^n$  and the corresponding camera projection matrices  $M^i$ , describe a way to estimate it.

## 2.4

Failed to reverse engineer