



## BANGLADESH OFFICE :

HOUSE-16, ROAD- 13, BLOCK –G, NIKETON, GULSHAN -1 , DHAKA.

BANGLADESH PHONE: +880 1672993247 , EMAIL:

irfan.af.bd@gmail.com

# ZRST-200P-48

## Electrical Characteristics

Model	200Wp
Maximum Power at STC (Pmax)	200W±0-3%
Optimum Operating Voltage(Vmp)	24.00V
Optimum Operating Current(Imp)	8.33A
Open-Circuit Voltage(Voc)	22.50V
Short-Circuit Current(Isc)	11.82A
Operating Temperature	-40°C to +85 °C
Maximum System Voltage	1000Vdc(IEC) / 600 Vdc(UL)
Maximum Series Fuse Rating	15A
Power Tolerance	± 3%
NOCT	47±2°C
Temperature Coefficient Pmax	-0.47% / °C
Voc	-0.346% / °C
Isc	+0.036% / °C

STC: Irradiance 1000W/m<sup>2</sup> , Module Temperature 25°C , AM=1.5

## Mechanical Characteristics

Cell Type	Polycrystalline (156mm)
Cell Arrangement	48 (6*8)
Dimensions (LxWxH)	1320*992*35mm
Weight	13.2 kgs
Front Glass	3.2 mm (0.13 inches) tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP65 rated
Wind Loads	2400 Pascal certified
Output Cables	Double insulated solar cable 4.0 mm <sup>2</sup> (0.006 inches <sup>2</sup> ), symmetrical lengths (-) 900 mm (35.4 inches) and (+) 900 mm (35.4 inches), MC 4 or its compatible connectors

## Quality and Warranty

- ◆ Rigorous quality control meets the highest international standard
- ◆ 5 years limited warranty on material and workmanship
- ◆ 25-year performance guarantee at 80% of the minimal rated power output
- ◆ 10-year performance guarantee at 90% of the minimal rated power output

## Packing Configuration

Container	20"GP	40"GP	40"HC
Pieces Per Box			
Box Dimensions (LxWxH)			
Pieces Per Container			

## Statement:

- Specifications are subject to change without further notifications
- Please read the product information, installation guide, quality warranty and any other related information

