

AEGetInteractionAllowed

Get user interaction preferences

#include <AppleEvents.h>

Apple Event ManagerOSErr **AEGetInteractionAllowed**(*level*);AEGetInteractionAllowed **level*; see below**returns** Error Code; 0 = no error

You can use the **AEGetInteractionAllowed** function to get the current user interaction preferences for responding to an Apple event.

The **AEGetInteractionAllowed** function returns a value in the *level* parameter that indicates the user interaction preferences for responding to an Apple event.

The value returned is the interaction level set by a previous call to **AESetInteractionAllowed**. The default value of kAEInteractWithLocal is returned if your application has not used **AESetInteractionAllowed** to explicitly set the interaction level.

The *level* parameter returns one of the following flags: kAEInteractWithSelf, kAEInteractWithLocal, or kAEInteractWithAll.

The kAEInteractWithSelf flag indicates that the server application may interact with the user in response to an Apple event only when the client application and server application are the same—that is, only when the application is sending the Apple event to itself.

The kAEInteractWithLocal flag indicates that the server application may interact with the user in response to an Apple event only if the client application is on the same computer as the server application. This is the default if your application has not used the **AESetInteractionAllowed** function to explicitly set the interaction level.

The kAEInteractWithAll flag indicates that the server application may interact with the user in response to an Apple event sent from any client

Result codes

noErr (0) No error