

SFindDevBase Return a pointer to the base of a device

#include <Slots.h>

Slot Manager

```
OSErr      SFindDevBase(spBlkPtr);
SpBlockPtr spBlkPtr ;    address of 56-byte Slot Parameter Block
                        structure
returns      Error Code; 0=no error
```

SFindDevBase returns a pointer in spResult to the base of a device whose slot number is in spSlot and whose sResource ID is in spID.

spBlkPtr is the address of a 56-byte **Slot Parameter Block** structure.
The relevant fields are as follows:

Out-In	Name	Type	Size	Offset	Description
←	spResult	<u>long</u>	4	0	FUNCTION result
→	spID	<u>char</u>	1	50	sResource list ID
→	spSlot	<u>char</u>	1	49	Slot number

Returns: an operating system Error Code. It will be one of:

noErr	(0)	No error
smEmptySlot	(-300)	No card in slot.
smCRCFail	(-301)	CRC check failed.
smFormatErr	(-302)	FHeader format is not Apple's
smRevisionErr	(-303)	The revision of the card's declaration ROM is wrong.
smNoDir	(-304)	Directory offset is NIL
smNosInfoArray	(-306)	The SDM could not allocate memory for the slInfo array.
smResrvErr	(-307)	A reserved field of the declaration ROM was used.
smUnExBusErr	(-308)	An unexpected bus error occurred.
smBLFieldBad	(-309)	A valid <u>ByteLanes</u> field was not found.
smDisposePErr	(-312)	An error occurred during execution of DisposPointer.
smNoBoardSRsrc	(-313)	There is no board sResource.
smGetPRErr	(-314)	Error during execution of sGetPRAMRec.
smNoBoardId	(-315)	There is no board ID.
smInitStatVErr	(-316)	The InitStatus_V field was negative after Primary or Secondary Init.
smInitTblVErr	(-317)	Error while trying to initialize the sResource Table.
smNoJmpTbl	(-318)	Slot Manager jump table could not be created
smBadBoardId	(-319)	Board ID was wrong; reinit the PRAM record

Notes: The base address of a device may be in either slot or superslot space but not in both. Slot or superslot slot spaces are discussed in the book *Designing Cards and Drivers for Macintosh II and Macintosh SE*.