

FXInfo structure

#include <Files.h>

typedef struct FXInfo {		<u>Size</u>	<u>Offset</u>	<u>Description</u>
<u>short</u> fdlconID;		2	0	File's icon resource (see Notes)
<u>short</u> fdUnused[3];		8	2	(reserved)
<u>char</u> fdScript;		1	10	
<u>char</u> fdXFlags;		1	11	
<u>short</u> fdComment;		2	12	Resource ID of file comment (type 'FCMT')
<u>long</u> fdPutAway;		4	14	Dir ID of file's home directory
} FXInfo ;		18		

Notes: An FXInfo named ioFIXFndrInfo is embedded in the HFileInfo structure obtained by **PBGetCatInfo**. Field values in it can be set via **PBSetCatInfo**.

The fdlconID field may be related to icons in some indirect way. However, it is NOT the resource ID of any 'ICN#' resource in the desktop file.

The fdComment field contains the resource ID of an 'FCMT' in the Desktop file. It identifies a p-string displayed/modified in the Finder's "Get Info" menu item dialog. See **PBSetCatInfo** for an example which changes a file's comment.

The fdPutAway field is a 'hard' directory ID of the folder in which the file is normally displayed. If the file gets moved to the desktop, the Finder uses this field to implement its "Put Away" menu item.