

**PlotClconHandle**

Display an icon image with System 7 icon resource types

#include &lt;Icons.h&gt;

**Finder Interface**

<u>OSErr</u>	<b>PlotClconHandle</b> ( <i>theRect</i> , <i>align</i> , <i>transform</i> , <i>theResID</i> );	
<u>Rect</u>	* <i>theRect</i> ;	rectangle to draw in, in local coordinates
<u>short</u>	<i>alignment</i> ;	icon alignment type
<u>short</u>	<i>transform</i> ;	icon transform type
<u>short</u>	<i>theClconH</i> ;	color icon handle.

**PlotClconHandle** plots an icon image in the current GrafPort at local coordinates specified by a rectangle.

*theRect* is the address of an 8-byte Rect structure, expressed in local coordinates.

*alignment* alignment method used in case the icon does not exactly fit the rectangle give. See the Notes section below.

*transform* desired appearance of the icon on the screen. See the Notes section below.

*theClconH* handle to a standard QuickDraw color icon. Use **GetClcon** to load a color icon. Don't forget to dispose of it when you are done with **DisposClcon** (sometimes they can take up quite a bit of memory).

**Returns:** error code

---

Notes: **PlotClconHandle** takes a parameter which specifies the alignment of the icon in the destination rectangle. Most icons do not fully fill their rectangle, and it is sometimes necessary to draw the icon relative to other data (like menu text). For this reason, you can specify one of these standard alignment values for the *alignment* parameter. You can add a vertical alignment to a horizontal alignment to create a composite alignment value.

atNone  
atVerticalCenter  
atTop  
atBottom  
atHorizontalCenter  
atLeft  
atRight

The *transform* parameter specifies the mode or "transform" in which the icon should be drawn. Transforms are analogous to certain Finder states for the icons. For example the transform that you would use to show an icon of a disk that has been ejected is ttOffline. The following transforms are available.

ttNone  
ttDisabled  
ttOffline  
ttOpen  
ttSelected

ttSelectedDisabled  
ttSelectedOffline  
ttSelectedOpen

Note that the ttSelected transform can be added to any of the other transform types.

Macintosh Technote #306 states that the actual appearance of the icon drawn by each transform type may vary with future system software, so you should always try to use the transform type that best fits the state it represents in your application.

Additional transform types exist for displaying the icon of a file inside your application that use the Finder's label colors to color the icon. To determine the proper label for a file's icon, you can check bits 1-3 of the fdFlags in the file's Finder Info (obtained using **GetFInfo** or **PBGetFInfo**). The bits contain a number from 0 to 7. Simply add the corresponding ttLabel value to the transform that you pass to **PlotClconHandle**. The label values are

<u>ttLabel0</u>	<u>ttLabel4</u>
<u>ttLabel1</u>	<u>ttLabel5</u>
<u>ttLabel2</u>	<u>ttLabel6</u>
<u>ttLabel3</u>	<u>ttLabel7</u>

**PlotClconHandle** chooses the appropriate icon based primarily on size; once the proper icon size is determined (based on the destination rectangle), the present member of that size with the deepest bit depth that the current device can use is selected. A size category is considered present if the black and white member (with mask) was present, 'ICN#', 'ics#', or 'icm#'. **PlotClconHandle** can be used for both picture accumulation and printing.

This routine is not currently documented in MPW header files (hence, it is not in any THINK C or THINK Pascal header file either). The information given above comes from Macintosh Technical Note #306. This tech. note also gives the inline glue for the call as follows:

```
pascal OSErr PlotClconHandle (Rect * theRect, short alignment,  
    short transform, ClconHandle theResID)  
    = {0x303C, 0x061F, 0xABC9};
```