

PPCInformPBRec structure

#include <PPCToolBox.h>

typedef struct PPCInformPBRec {		<u>Size</u>	<u>Offset</u>	<u>Description</u>
<u>PPCHeader</u>		38	0	Common fields of PPC param blocks
<u>unsigned long</u>	Reserved[5];	20	18	Reserved for PPC, Don't use
<u>PPCPortRefNum</u>	portRefNum;	2	38	Port reference number of this session
<u>PPCSessRefNum</u>	sessRefNum;	4	40	Session reference number of session
<u>PPCServiceType</u>	serviceType;	1	44	Service type of this session
<u>Boolean</u>	autoAccept;	1	45	If <u>TRUE</u> , session is accepted automatically
<u>PPCPortPtr</u>	portName;	4	46	Pointer to <u>PPCPortRec</u> , may be <u>NIL</u>
<u>LocationNamePtr</u>	locationName;	4	50	Pointer to <u>LocationNameRec</u> , may be <u>NIL</u>
<u>StringPtr</u>	userName;	4	54	pointer to Str32, may be <u>NIL</u>
<u>unsigned long</u>	userData;	4	58	application-specific data
<u>PPCSessionOrigin</u>	requestType;	1	62	network or local request
} PPCInformPBRec ;		64		

typedef PPCInformPBRec ***PPCOpenPBPtr**;