

**PSetSelfSend** Enable or disable intranode delivery

#include <AppleTalk.h>

**AppleTalk Manager**

OSErr            **PSetSelfSend**(*thePBptr*, *async*);  
MPPPBPtr        *thePBptr*;            address of an MPPParamBlock structure  
Boolean         *async*;                0=await completion; 1=immediate return  
**returns**           Error Code; 0=no error

**PSetSelfSend** enables or disables the intranode deliver feature of the **AppleTalk Manager**.

*thePBptr* is a pointer to an MPPParamBlock structure. The relevant fields are as follows:

<u>Out-InName</u>	<u>Type</u>	<u>Size</u>	<u>Offset</u>	<u>Description</u>
→ csCode	<u>short</u>	2	26	Always PSetSelfSend
→ newSelfFlag	<u>short</u>	2	28	New SelfSend flag
← oldSelfFlag	<u>char</u>	1	29	Old SelfSend flag

*async* is a Boolean value. Use FALSE for normal (synchronous) operation or TRUE to enqueue the request and resume control immediately. See Async I/O.

**Returns:** an operating system Error Code. It will be one of:  
noErr (0)            No error

---

Notes: If newSelfFlag is nonzero, the feature will be enabled; otherwise it will be disabled. The previous value of the flag will be returned in oldSelfFlag.