

AESetTheCurrentEvent

Specify Apple Event to be handled

#include <AppleEvents.h>

Apple Event Manager

```
OSErr      AESetTheCurrentEvent(theAppleEvent );
AppleEvent *theAppleEvent ;      the Apple Event to be handled
          returns      Error Code; 0 = no error
```

You can use the **AESetTheCurrentEvent** function to specify the Apple event to be handled.

The **AESetTheCurrentEvent** function specifies the Apple event to be handled. There is generally no reason for your application to use this function. Instead of calling this function, your application should let the **Apple Event Manager** go through the dispatch tables to set the current Apple event.

The parameter *theAppleEvent* is the Apple event that is to be handled.

The **AESetTheCurrentEvent** function is used only to avoid going through the dispatch tables, and is used only in the following way:

1. An application suspends handling of an Apple event by calling the **AESuspendTheCurrentEvent** function.
2. The application calls the **AESetTheCurrentEvent** function to inform the **Apple Event Manager** that it is handling the Apple event that was previously suspended. It thereby makes the identity of the Apple event currently being handled available to routines that call the **AEGetTheCurrentEvent** function.
3. The application handles the Apple event. When it is finished, it calls the **AEResumeTheCurrentEvent** function with the value kAENoDispatch to tell the **Apple Event Manager** that the processing of the event is complete and that the Apple event does not need to be dispatched.

Result codes

noErr (0) No error