

Rebooting Supercompilation for Haskell

Ömer S. Ağacan
oagacan@indiana.edu

Ryan R. Newton
rrnewton@indiana.edu

August 25, 2015

Rebooting Supercompilation for Haskell - Talk outline

- An overview of supercompilation.

Rebooting Supercompilation for Haskell - Talk outline

- An overview of supercompilation.
- What's interesting about it in the context of Haskell? Current state-of-the-art.

Rebooting Supercompilation for Haskell - Talk outline

- An overview of supercompilation.
- What's interesting about it in the context of Haskell? Current state-of-the-art.
- Overview of how it works.

Rebooting Supercompilation for Haskell - Talk outline

- An overview of supercompilation.
- What's interesting about it in the context of Haskell? Current state-of-the-art.
- Overview of how it works.
- "But where's my supercompiler for Haskell?" My preliminary work and research goals.

Supercompilation: An overview

- The paper that describes the idea in English: "The Concept of a Supercompiler" Turchin [1986].

Supercompilation: An overview

- The paper that describes the idea in English: "The Concept of a Supercompiler" Turchin [1986].
- High-level idea:

Supercompilation: An overview

- The paper that describes the idea in English: "The Concept of a Supercompiler" Turchin [1986].
- High-level idea:
 - Evaluate programs in compile-time, while making the most out of known inputs and definitions.

Supercompilation: An overview

- The paper that describes the idea in English: "The Concept of a Supercompiler" Turchin [1986].
- High-level idea:
 - Evaluate programs in compile-time, while making the most out of known inputs and definitions.
 - Definitions of used functions.

Supercompilation: An overview

- The paper that describes the idea in English: "The Concept of a Supercompiler" Turchin [1986].
- High-level idea:
 - Evaluate programs in compile-time, while making the most out of known inputs and definitions.
 - Definitions of used functions.
 - Statically known arguments of functions.

Supercompilation: An overview

- The paper that describes the idea in English: "The Concept of a Supercompiler" Turchin [1986].
- High-level idea:
 - Evaluate programs in compile-time, while making the most out of known inputs and definitions.
 - Definitions of used functions.
 - Statically known arguments of functions.
 - When branching, propagate learned information through branches and make use of that information while compiling branches. (case expressions)

Supercompilation: An overview

- The paper that describes the idea in English: "The Concept of a Supercompiler" Turchin [1986].
- High-level idea: (contd)
 - Evaluate programs in compile-time, while making the most out of known inputs and definitions.
 - Most of the time the goal is to generate more efficient programs.
(but see Klyuchnikov and Romanenko [2010] for a different use of supercompilation)

Supercompilation in the context of Haskell

- Why is it interesting?
- In a sense, it's the "ultimate" optimization. ("-O99")
- This optimizes in the sense that:
If we have a programs \mathcal{P}_1 and \mathcal{P}_2 , and
 $\mathcal{P}_1 \Downarrow v$ in N steps and
 $\mathcal{P}_2 \Downarrow v$ in M steps,
we consider \mathcal{P}_2 optimized if $M < N$.
- An approximation, but works well in practice.

Supercompilation in the context of Haskell

- It generalizes:
 - Deforestation(Wadler [1988])
 - Partial evaluation
 - Call-pattern specialization(Peyton Jones [2007])
 - Ad-hoc optimizations via rewrite rules, e.g. shortcut fusion (Gill et al. [1993]) or library-specific rewrite rules
 - "Optimizing SYB is Easy!" (Adams et al. [2014]) and "Optimizing Generics is Easy!" (Magalhães et al. [2010]) style "domain-specific" partial evaluators
 - Function specialization(SPECIALIZE pragmas)
 - ... and many more

Current state-of-the-art

- Bolingbroke [2013] shows some great potential:
 - Up to 95.1% reduction in runtime.
 - Up to 100.0% reduction in allocation.
- But it also suffers from problems that are inherent to supercompilation:
 - "We do not attempt to supercompile the full Nofib suite because the other Nofib benchmarks are considerably more complicated and generally suffer from extremely long supercompilation times."
(Jonsson [201?] focuses on compilation performance, and reports *<3 seconds* for all the small programs from Nofib)
 - Up to +132002.0% in compile time.
 - Up to +188.9% in generated code size.

How it works? An overview

Bolingbroke [2013] laid out a great framework for supercompiling Haskell:

- **Driving:** Take steps according to operational semantics. Some additional steps like case-of-case transformation (Jones and Santos [1998]).

How it works? An overview

Bolingbroke [2013] laid out a great framework for supercompiling Haskell:

- **Driving:** Take steps according to operational semantics. Some additional steps like case-of-case transformation (Jones and Santos [1998]).
- **Splitting:** When stuck, keep evaluating sub-expressions. Propagate information. After evaluating sub-expressions combine results.

How it works? An overview

Bolingbroke [2013] laid out a great framework for supercompiling Haskell:

- **Driving:** Take steps according to operational semantics. Some additional steps like case-of-case transformation (Jones and Santos [1998]).
- **Splitting:** When stuck, keep evaluating sub-expressions. Propagate information. After evaluating sub-expressions combine results.
- **Matching:** Evaluating open terms lead to loops. Matcher tries to detect loops, returns information about how to refer to this new loop.

How it works? An overview

Bolingbroke [2013] laid out a great framework for supercompiling Haskell:

- **Driving:** Take steps according to operational semantics. Some additional steps like case-of-case transformation (Jones and Santos [1998]).
- **Splitting:** When stuck, keep evaluating sub-expressions. Propagate information. After evaluating sub-expressions combine results.
- **Matching:** Evaluating open terms lead to loops. Matcher tries to detect loops, returns information about how to refer to this new loop.
- **Termination checking:** Because perfect matcher is not possible, and some programs just loop.

mapOfMap f g = map f . map g

h1 f g a = map f (map g a)

...

h4 f g a =

case (case a of

 [] -> []

 h1 : t1 -> g h1 : map g t1) of

 [] -> []

 h0 : t0 -> f h0 : map f t0

...

h6 f g a =

case a of

 [] -> []

 h : t -> f (g h) : map f (map g t)

h7 f g a =

case a of

 [] -> []

 h : t -> f (g h) : h7 f g t

How it works? An overview

```
mapOfMap f g = (.) (map f) (map g)
```

```
h1 f g a = map f (map g a)
```

```
h2 f g a =  
  (\f lst -> case lst of  
    []      -> []  
    h : t   -> f h : map f t) f (map g a)
```

```
h3 f g a =  
  case (map g a) of  
    []      -> []  
    h : t   -> f h : map f t
```

How it works? An overview

```
h3 f g a =  
  case (map g a) of  
    []      -> []  
    h : t -> f h : map f t
```

```
h4 f g a =  
  case (case a of  
    []      -> []  
    h1 : t1 -> g h1 : map g t1) of  
    []      -> []  
    h0 : t0 -> f h0 : map f t0
```

How it works? An overview

```
h4 f g a =  
  case (case a of  
        []      -> []  
        h1 : t1 -> g h1 : map g t1) of  
    []      -> []  
    h0 : t0 -> f h0 : map f t0
```

Case-of-case transformation: (Jones and Santos [1998])

```
h5 f g a =  
  case a of  
    [] -> case [] of  
        []      -> []  
        h0 : t0 -> f h0 : map f t0  
    h1 : t1 ->  
      case (g h1 : map g t1) of  
        []      -> []  
        h0 : t0 -> f h0 : map f t0
```

How it works? An overview

```
h5 f g a =  
  case a of  
    [] -> case [] of  
            [] -> []  
            h0 : t0 -> f h0 : map f t0  
    h1 : t1 ->  
      case (g h1 : map g t1) of  
        [] -> []  
        h0 : t0 -> f h0 : map f t0
```

```
h6 f g a =  
  case a of  
    [] -> []  
    h : t -> f (g h) : map f (map g t)
```


How it works? An overview

```
h6 f g a =  
  case a of  
    []      -> []  
    h : t  -> f (g h) : map f (map g t)
```

How it works? An overview

```
h6 f g a =  
  case a of  
    []      -> []  
    h : t   -> f (g h) : map f (map g t)
```

map f (map g t)

Looks similar to:

```
h1 f g a = map f (map g a)
```

How it works? An overview

At this point splitter tells us there's a loop.

```
h7 f g a =  
  case a of  
    []      -> []  
    h : t -> f (g h) : h7 f g t
```

Supercompiled version doesn't generate intermediate list.

Problems with supercompilation operations

Each operation has hard problems to solve.

Problems with supercompilation operations

Each operation has hard problems to solve.

Splitter: (from Bolingbroke [2013])

Problems with supercompilation operations

Each operation has hard problems to solve.

Splitter: (from Bolingbroke [2013])

Propagating too much information may lead to work duplication.

```
let n = fib 100
    b = n + 1
    c = n + 2
in (b, c)
```

Problems with supercompilation operations

Each operation has hard problems to solve.

Splitter: (from Bolingbroke [2013])

Propagating too much information may lead to work duplication.

```
let n = fib 100
    b = n + 1
    c = n + 2
in (b, c)
```

Propagating too little information may lead to missing optimization opportunities.

```
let map = . . .
    ys = map f zs
    xs = map g ys
in Just xs
```

Problems with supercompilation operations

Each operation has hard problems to solve.

Problems with supercompilation operations

Each operation has hard problems to solve.

Matcher:

Problems with supercompilation operations

Each operation has hard problems to solve.

Matcher:

May lead to work sharing, which may increase memory residency. (Chitil [1997])

```
S0 =  
  let a = fib y  
      b = fib y  
  in (a, b)
```

```
S1 =  
  let a = fib y  
  in (a, a)
```

Problems with supercompilation operations

Each operation has hard problems to solve.

Matcher:

May lead to work sharing, which may increase memory residency. (Chitil [1997])

```
S0 =  
  let a = fib y  
      b = fib y  
  in (a, b)
```

```
S1 =  
  let a = fib y  
  in (a, a)
```

Or:

Problems with supercompilation operations

Each operation has hard problems to solve.

Matcher:

May lead to work sharing, which may increase memory residency. (Chitil [1997])

```
S0 =  
  let a = fib y  
      b = fib y  
  in (a, b)
```

```
S1 =  
  let a = fib y  
  in (a, a)
```

Or:

```
S0 = sum [1 .. 1000] + prod [1 .. 1000]  
S1 = let l = [1 .. 1000] in sum l + prod l
```

Problems with supercompilation operations

Each operation has hard problems to solve.

Problems with supercompilation operations

Each operation has hard problems to solve.

Termination checker:

Problems with supercompilation operations

Each operation has hard problems to solve.

Termination checker:

Some programs just loop.

```
loop n = loop (n + 1)
```

```
countFrom n = n : countFrom (n + 1)
```

Problems with supercompilation operations

Each operation has hard problems to solve.

Termination checker:

Some programs just loop.

```
loop n = loop (n + 1)
countFrom n = n : countFrom (n + 1)
```

Sometimes detecting loops is not so easy: (growing arguments)

```
reverse_acc [] acc = acc
reverse_acc (h : t) acc = reverse_acc t (h : acc)
goal lst = reverse_acc (reverse_acc lst []) []
...
h_ lst = ... reverse_acc t1 (h1 : []) ...
...
h_ lst = ... reverse_acc t2 (h2 : h1 : []) ...
...
```


"Where's my supercompiler for Haskell?"

- I'm rebooting the supercompiler!

"Where's my supercompiler for Haskell?"

- I'm rebooting the supercompiler!
- The goal here is to distribute it as a package, downloadable from Hackage.

"Where's my supercompiler for Haskell?"

- I'm rebooting the supercompiler!
- The goal here is to distribute it as a package, downloadable from Hackage.
- Then the research will follow.

Current status and problems

There has been some changes in GHC:

- Some changes in the Core theory: Roles.
- Lots of refactoring.

GHC API related problems:

- Some needed internals are not exposed by GHC – requires some modifications in GHC.
- No easy ways to do most basic stuff: Moving terms around(substitutions), known-case reduction, case-of-case, etc. (all done in some parts of Core-to-Core passes, need to reverse engineer)
- No easy way to annotate Core syntax. Duplicating the syntax means duplicating huge amounts of code.
- Working on Core is hard: Invariants are encoded as partial functions without any helpful error messages – if we're lucky, there's a NOTE.
- Some things are not clear. (Types are first-class, but can I use them wherever I want? The Core definition allows this)

Conclusions

Have a working implementation of supercompiler described in Bolingbroke [2013].

Conclusions

Have a working implementation of supercompiler described in Bolingbroke [2013].

(Maybe) Improve GHC plugin API on the way.

Conclusions

Have a working implementation of supercompiler described in Bolingbroke [2013].

(Maybe) Improve GHC plugin API on the way.

Collecting benchmark programs - send yours! (with expected optimizations)

We can create a benchmark suite like Nofib, but for supercompilation-specific problems. (pathological cases, programs with lots of intermediate data structures)

Once we have a working implementation:

- Focus on specific parts(matcher, splitter etc.). Try other ideas from the literature(e.g. homeomorphic embedding).
- Work on some of the obvious improvements, like parallelizing the matcher.
- More experimental ideas:
 - Can we formulate it as a search problem and apply ideas from the literature?
 - Are profile-driven decision making possible?
 - Are machine learning algorithms applicable?

Thanks!

Github: [osa1/sc-plugin](#)

IRC: osa1

Email me your slow programs: oagacan@indiana.edu

References I

- M. D. Adams, A. Farmer, and J. P. Magalhães. Optimizing SYB is Easy! In *Proceedings of the ACM SIGPLAN 2014 Workshop on Partial Evaluation and Program Manipulation*, PEPM '14, New York, NY, USA, 2014. ACM. ISBN 978-1-4503-2619-3. doi: 10.1145/2543728.2543730.
- M. C. Bolingbroke. Call-by-need supercompilation. Technical Report UCAM-CL-TR-835, University of Cambridge, Computer Laboratory, May 2013. URL <http://www.cl.cam.ac.uk/techreports/UCAM-CL-TR-835.pdf>.
- O. Chitil. Common Subexpression Elimination in a Lazy Functional Language, 1997.

References II

- A. Gill, J. Launchbury, and S. L. Peyton Jones. A Short Cut to Deforestation. In *Proceedings of the Conference on Functional Programming Languages and Computer Architecture*, FPCA '93, pages 223–232, New York, NY, USA, 1993. ACM. ISBN 0-89791-595-X. doi: 10.1145/165180.165214. URL <http://doi.acm.org/10.1145/165180.165214>.
- S. L. P. Jones and A. L. Santos. A transformation-based optimiser for Haskell. In *SCIENCE OF COMPUTER PROGRAMMING*, pages 3–47. Elsevier North-Holland, Inc., 1998.
- P. A. Jonsson. Time- and Size-Efficient Supercompilation, 201?
- I. Klyuchnikov and S. Romanenko. Proving the Equivalence of Higher-Order Terms by Means of Supercompilation. In A. Pnueli, I. Virbitskaite, and A. Voronkov, editors, *Perspectives of Systems Informatics*, volume 5947 of *Lecture Notes in Computer Science*, pages 193–205. Springer Berlin Heidelberg, 2010. ISBN 978-3-642-11485-4. doi: 10.1007/978-3-642-11486-1_17. URL http://dx.doi.org/10.1007/978-3-642-11486-1_17.

References III

- J. P. Magalhães, S. Holdermans, J. Jeuring, and A. Löh. Optimizing Generics is Easy! In *Proceedings of the 2010 ACM SIGPLAN Workshop on Partial Evaluation and Program Manipulation*, PEPM '10, pages 33–42, New York, NY, USA, 2010. ACM. ISBN 978-1-60558-727-1. doi: 10.1145/1706356.1706366. URL <http://doi.acm.org/10.1145/1706356.1706366>.
- S. Peyton Jones. Call-pattern Specialisation for Haskell Programs. In *Proceedings of the 12th ACM SIGPLAN International Conference on Functional Programming*, ICFP '07, pages 327–337, New York, NY, USA, 2007. ACM. ISBN 978-1-59593-815-2. doi: 10.1145/1291151.1291200. URL <http://doi.acm.org/10.1145/1291151.1291200>.
- V. F. Turchin. The Concept of a Supercompiler. *ACM Transactions on Programming Languages and Systems*, 8:292–325, 1986.

References IV

P. Wadler. Deforestation: Transforming Programs to Eliminate Trees. *Theor. Comput. Sci.*, 73(2):231–248, Jan. 1988. ISSN 0304-3975. doi: 10.1016/0304-3975(90)90147-A. URL [http://dx.doi.org/10.1016/0304-3975\(90\)90147-A](http://dx.doi.org/10.1016/0304-3975(90)90147-A).