Public Documentation - API get Transactions

API Documentation

GET /transactions

Generates a list of random banking transactions. Results are deterministic when a seed is provided, allowing reproducible data across calls.

Query Parameters

Parameter	Type	Default	Description
`results`	Integer	`10`	Number of transactions to return. Clamped to the range `[1, 100]`.
`page`	Integer	`1`	Page number for pagination. Clamped to the range `[1, 10000]`.
`seed`	String	random	Seed for deterministic generation. Accepts an integer or an arbitrary string.

Seed Behavior

- **No seed**: A random seed is generated for each request.
- **Integer seed**: Used directly as the random seed.
- **String seed**: Converted to a numeric seed using a Java-compatible hash function, allowing the same string to always produce the same data.

The seed value is returned in the `info.seed` field of the response.

Example Request

```
GET/transactions?results=2&page=1&seed=demo
```

Response Format


```
{ "results": [ { "id": "a1b2c3d4-e5f6-7890-abcd-ef1234567890", "am
ount": { "value": "1234.56", "currency": "EUR" }, "counterpartyNam
e": "Acme Corp", "emittedAt": "2025-06-15T10:30:00.000Z", "settled
At": "2025-06-15T10:30:45.000Z", "side": "DEBIT", "status": "COMPL
ETED", "operationMethod": "CARD", "operationType": "CARD", "descri
ption": "Office supplies", "activityTag": "OTHER_EXPENSE", "note":
null, "initiator": { "id": "f1e2d3c4-b5a6-7890-abcd-ef1234567890",
"fullName": "Alice Martin" }, "bankAccount": { "id": "acc-001", "n
ame": "Main Account" } } ], "info": { "seed": "demo", "results":
2, "page": 1, "version": "1.0" } }
```


Response Fields

Transaction

Field	Type	Description
`id`	String	UUID of the transaction.
`amount.value`	String	Transaction amount (0.50 to 50000.00), two decimal places.
`amount.currency`	String	Always `"EUR"`.
`counterpartyName`	String	Name of the counterparty.
`emittedAt`	String (ISO 8601)	Timestamp when the transaction was emitted.
`settledAt`	String or null	Timestamp when the transaction was settled. `null` if not completed.
`side`	String	`"CREDIT"` or `"DEBIT"`.
`status`	String	`"COMPLETED"`, `"PENDING"`, or `"DECLINED"`.
`operationMethod`	String	`"TRANSFER"`, `"CARD"`, or `"DIRECT_DEBIT"`.
`operationType`	String	`"INCOME"`, `"TRANSFER"`, or `"CARD"`.
`description`	String	Description of the transaction.
`activityTag`	String	One of `"OTHER_INCOME"`, `"OTHER_EXPENSE"`, `"OTHER_SERVICE"`, `"REFUND"`, `"FEES"`.
`note`	String or null	Optional note attached to the transaction (~20% chance of being set).
`initiator`	Object or null	Person who initiated the transaction (~70% chance of being set).
`initiator.id`	String	UUID of the initiator.
`initiator.fullName`	String	Full name of the initiator.
`bankAccount.id`	String	ID of the bank account.

`bankAccount.name`	String	Name of the bank account.

Info

Field	Type	Description
`seed`	String	The seed used for generation.
`results`	Integer	Number of results returned (after clamping).
`page`	Integer	Current page number (after clamping).
`version`	String	API version (`"1.0"`).