

555 Oak Street East, North Bay, Ontario P1B 8L3 North Bay (Ontario) P1B 8L3 Telephone: (705) 472-4500 Téléphone: (705) 472-4500 Fax: (705) 476-5598

555, rue Oak est Télécopieur: (705) 467-5598

**ONR Signal Standards** Signal System Inspections & Tests (SSIT)

# **SSIT-1103 Inspecting Painted Surfaces**

#### **Purpose**

Painted surfaces are inspected for proper upkeep to ensure the equipment is kept clean and protected against excessive weathering.

#### **Test Intervals**

Painted surfaces shall be inspected at time of installation and routinely when inspecting other elements of equipment with painted surfaces. Refer to SSIT-7 Signal System Inspection and Test Intervals for all test intervals.

## Rail Safety

Employee shall ensure the site is safe for employees, the public, vehicular traffic and train operations as defined in SSIT-8 Protecting Train Operations prior to performing tests and inspections.

## **Equipment Manuals**

A copy of relevant equipment manufacturer's manuals should be referred to for type and application of paint as defined by manufacturer.

#### **Procedure**

The following tests are to be performed at each painted surface:

Step	Procedure
Check Painted     Surfaces	<ul> <li>→ Check painted surfaces aren't excessively worn.</li> <li>→ Check rust is not coming through painted surface.</li> <li>→ Check paint is not cracking or peeling.</li> <li>→ Check paint is not covered with grease, grime, or graffiti.</li> </ul>
2. Check Surfaces for Paint	<ul> <li>→ Check that there is not paint on the following types of surfaces:         <ul> <li>Lenses</li> <li>Gaskets</li> <li>Vents</li> <li>Concrete foundations</li> <li>Aluminum surfaces</li> <li>Cotter and connecting pins</li> <li>Adjustable equipment</li> <li>Cedar &amp; chemically treated wood</li> </ul> </li> </ul>
3. Perform Touch Ups	<ul> <li>Obtain necessary colours and finishes for equipment as outlined in AREMA guidelines.</li> <li>Avoid painting temperature sensitive equipment or housings with colours and finishes that may increase equipment surface temperature.</li> <li>Prepare surfaces for painting through sanding or stripping, as required.</li> <li>Apply necessary paint to painted surfaces showing wear.</li> <li>Remove paint from surfaces that should not be painted.</li> </ul>

July 29th, 2016 Rev. A.02 Approved: R. Morris (HATCH)