

CREATING A UNIVERSAL INFORMATION LANGUAGE

OSCAR BENDER-STONE

ABSTRACT. Welkin is a formalized programming language to store information. We introduce its use cases and rigorously define its syntax and semantics. From there, we introduce the bootstrap, making Welkin completely self-contained under the meta-theory of Goedel’s System T (equi-consistent to Peano Arithmetic).

CONTENTS

- 1. Introduction 1
 - 1.1. Goals 3
 - 1.2. Organization 3
- 2. Foundations 4
 - 2.1. Logic of Proofs 4
 - 2.2. Computability 4
 - 2.3. Verifiers 4
- 3. Information Systems 5
 - 3.1. Motivating Examples and Definition 6
 - 3.2. Constructions and Reflection 6
 - 3.3. Universality 7
- 4. Syntax 7
- 5. Semantics 7
 - 5.1. Terms 7
- 6. Bootstrap 8
- 7. Conclusion 8
- References 8

1. INTRODUCTION

Undergraduates are taught many things in lecture, books, and papers, but there is one unspoken truth: researchers have extremely *diverse* communities. Each community has their own approaches, their own conferences, and their own formatting. They even have a distinct preference to chalk, dry erase marker, or neither. For a long time, I didn’t notice this aspect about research. I started my mathematics journey in secondary education, independently reading papers from set theory, logic, and more. I was fortunate to have vast archives available on the internet, but my ability to *collaborate* in research was limited. This quickly changed in college[TODO: maybe make this a stronger sentence?]. Everywhere I went, I saw the multitude of research groups, from those mentioned in lecture to the experiences I worked in to the faculty panels in the COSMOS math club. I worked in several research groups and found how rich and fulfilling each was. This fundamentally changed my perception of research as a whole. I learned that diversity *drives* research, including in the sciences, liberal arts, and many more subjects I have hardly explored.

Because of how diverse research is, these communities are extremely independent and build separate repositories of knowledge. For example, I wrote a poster for a cryptography class, concerning an MIT researcher who created programs of common cryptographic schemes and mathematically proved their correctness. I met this

TODO: Create a stronger connection to the fact that the papers I read were ONLINE. This is crucial!

TODO: clean up transitions with examples

researcher at a conference and discovered that *neither* knew about the other! They provided their own contributions, but I initially assumed that *everyone* contributing to cryptography work on common projects. As another example, at my time in the Budapest Semesters in Mathematics, I adopted a key tool in program verification to find proofs for a combinatorial problem. According to my advisor, that approach had *never* been considered before in his group. The boundaries between these communities isn't so clear, and it seems to take years to begin to *remotely* find them.

The separation of these communities raises a key question: *can* knowledge across disciplines be bridged together?

In addition to this [FIRST CLASS OF PROBLEMS NAME], another major hurdle is truth management. [DISCUSS Problems with truth + corrections from papers don't propagate!] What can be done is addressing *information*, the storage of the *asserted* facts themselves, regardless of truth. As one example, suppose a scientist claims, "X is true about Y". One could debate the veracity of that claim, but what we can say is, "This scientist claims, 'X is true about Y'". Even if we doubt that, we could do: "This claim can be formulated: 'This scientist claims 'X is true about Y''". By using these justifications, stating that a claim is expressible, the *syntactic expression* of the claim can be separated from its *semantic truth value*.¹ I will make this more rigorous in later sections, but this means we can build knowledge bases on top of information systems using flexible extensions.

Information has been extensively studied through *measurements* in Algorithmic Information Theory (AIT). The founding idea of AIT is the Minimum Description Length (MDL) principle, that the best definition for an object is the smallest description that describes it. To formalize this idea, Kolmogorov defined a description as a *program*, and the Kolmogorov complexity of a string as the length of the *smallest program* that computes that string (see [1]). This program is defined via a Turing-computable programming language, and there is a different constant factor depending on the language, but AIT focuses on the asymptotic complexity. A cornerstone of this framework is providing the reason underlying cause of Gödel's incompleteness theorems, Turing's halting problem, Tarski's undefinability of truth, and more: *not all information can be compressed into a finite description*. This view was articulated by Chaitin on information compression. He defined Ω as the probability that a random Turing machine will halt and proved that it cannot be compressed computably. This result is a major theme in AIT, to address the limits of computation.

In addition to addressing these limits, Chaitin's results have profound consequences for the nature of mathematics. He explains:

Mathematics...has infinite complexity, whereas any individual theory would have only finite complexity and could not capture all the richness of the full world of mathematical truth. [2]

¹One might be worried about a paradox, such as "This claim is expressible: this claim is not expressible." We will avoid this using a clear separation of the overarching metatheory and object theory, with the former being syntactical in nature. To express this separation, we write quotes around the claim itself.

TODO: cite main claims about journals/research communities/etc as needed

TODO: REWORD as needed + merge with discussions on FAIR.

Chaitin's claim extends beyond mathematics; the extent of research areas are so vast that the idea of a *single* theory would fail to faithfully reproduce these disciplines. The study of the areas *themselves* is needed to faithfully represent them. This has been explored in Béziau's field of Universal Logic [3], where the aim is to study *logics* and not a *single* logic. In short, Chaitin's result, and the works in Universal Logic and others, demonstrate that research must be represented *flexibly* as well as faithfully.

The problem with a flexible representation system is precisely *how* to accomplish this. AIT provides asymptotic results on information *measurement*, but does not provide a guide on the fixed representation to use. Chaitin created a LISP variant, designed specifically for the ease of implementation and analysis [4], but this does not address the faithful representations of other languages. Additionally, Universal Logic provides a single definition of a logic, one which can be tedious in exotic logics. Each of these issues underly the importance of *organization* itself, which emerge in the proliferation of general-purpose programming languages.

As a concrete example of organizational challenges, consider a Python program in Listing 1.

```
int main() {
    return 0;
}

def main():
    pass

if __init__ == "__main__":
    pass
```

LISTING 1. Example programs in C (left) and Python (right).

In light of the persistence of organizational issues, another step is required beyond Chaitin's reasoning: we must consider *universal building blocks* themselves. Sticking to Turing machines is sufficient in AIT and studying asymptotics, but the *actual* storage must take place. This is the motivation and driving force of this thesis.

1.1. Goals.

The aim of this thesis is to create a universal information language to standardize *all* formal representations. I call this language **Welkin**, an old German word meaning cloud [5]. This aim will be made more precise in the later sections, where we will formally define a verifier for a programming language.

- **Goal 1:** universality. This language applies to ANY checker. Needs to be extremely flexible towards this goal, so we can **ONLY** assume, at most, we are getting a TM as an input, or it's somehow programmed.
- **Goal 2:** standardized. Needs to be rigorously and formally specified.
- **Goal 3:** optimal reuse. With respect to some criterion, enable *as much* reuse on information as possible.
- **Goal 4:** efficiency. Checking if we have enough information *given* a database much be efficient!

1.2. Organization.

- Section 2. Foundations: define the meta-theory used + verifiers. Also outline the Trusted Computing Base.
- Section 3. Information Systems: explore information in the context of verifiers. Then synthesize a definition to satisfy Goal 1.

TODO: Explain all claims concretely but concisely, as well as cite other possibilities (e.g., HoTT for logics)! And add anything else in AIT.

TODO: Finish transpilation example! Just show we care about storing the underlying semantics.

- Section 4. Information Reuse. Develops the optimal informal system (w.r.t to a metric defined in this system) to satisfy Goal 3.
- Section 5. Syntax: Go over the simple LL(1) grammar, which is similar to JSON and uses python syntax for modules.
- Section 6. Semantics: Defines information graphs and their correspondence with the optimal informal system in Section 3.
- Section 7. Bootstrap. Fulfill Goal 2 with both the Standard AND the complete bootstrap.
- Section ?. Prototype. Time permitting, develop a prototype to showcase the language, implemented in python with a GUI frontend (Qt) and possibly a hand-made LL(1) parser.
- Section 8. Conclusion. Reviews the work done in the previous sections. Then outlines several possible applications.

2. FOUNDATIONS

Our first step is to define the set of verifiers, a subset of the computable functions. Based on our architecture to separate *query* from *search*, we focus this subset to primitive recursive functions.

To explore verifiers, we need a reliable metatheory, establishing our logical TCB. How can we establish what *reliable* means? [TODO: cite that ZFC, or ZFC + inaccessible cardinals, is common in literature.] However, each of these are *specific theories*, and while ZFC + inaccessible cardinals likely suffices for, e.g., formal verification, what about other subjects? We want to make this *as extensible* as possible, akin to an infinite hierarchy of theories via reflection. So we will need a different approach.

The key problem to reliability is, while we can easily verify if a given input is accepted by a verifier, how do we tell when there is *no* such input? We use a novel criterion developed by Artemov's Logic of Proofs [6]. [TODO: bridge this with selector proofs. Also, make sure to explain WHY the arithmetic hierarchy is enough. We JUST want to explore properties of naturals. We can't do beyond. But we should prove this!]

This is where our metatheory come in. [TODO: explore arithmetic hierarchy briefly? How do we know *which* results on computability are trustworthy? This is ESSENTIAL for the TCB!]

2.1. Logic of Proofs.

2.2. Computability.

2.3. Verifiers.

Given a partial computable function φ , let $L(\varphi)$ be the language recognized by φ .

Definition 2.3.0. An **effective verifier** is a Turing machine that runs in linear time and it accepts an input *must* have read the entire input.

In a refined form of Kleene representability, we show that every RE set corresponds to an effective verifier in an important way.

Lemma 2.3.1. *For every RE set S with recognizer φ , there is an effective verifier V_φ such that $x \in S$ iff there is some trace t that starts with x and $t \in L(V_\varphi)$.*

For the rest of this thesis, all verifiers mentioned will be effective. Note that we will return to practical verifiers, those with realistic constants.

3. INFORMATION SYSTEMS

Now with our meta-theory in Section 2, we can proceed to discuss information systems.

- Now can study the set of *verifiers*. A universal verifier is a verifier of a UTM. So we only need *one* such verifier. We encode the TM AND the input in question, and then simulate the whole TM.

- Same problems as before: *how* do we organize this?
- Instead of asking what information is broadly (we'll come back to that in the overarching semantics), we want to ask, what is information *for verifiers*?

- * Recall translation from before: we *define* things by how they *are checked*. To information on mathematical objects corresponds to *information on how they are checked*.

- . By how, this includes:

- *what* things are/are not checked.
- If it speeds it up/is a slow route.

- . We capture this how by defining information *as* a relation between an input and a language *per* a trace.

- . Current idea in a formal setting: *information are traces*.

- Broadly treat information *as* a relation. Manifested as traces to include source, target, *and* steps inbetween.

- Problem: this isn't efficient! Come up with non-trivial examples that, while we discern here, doesn't resolve the problem!

- Also note: may not be *nice* w.r.t. certain systems. E.g., for sequent calculus, composition may not be guaranteed! So we can say a composite exist if *some* steps inbetween do, but this isn't always nice! Not *isomorphic* to sequent calculus proofs (depending on the system)! TODO: cite Strassburger deep inference paper to cite this issue and his approach.
- Currently: we treat *proofs* as being traces. Need to resolve in the meta-theory!

- Assuming we have a representation for traces (maybe via lambda terms? Review!),

we can look at the space of *all* these traces.

- HOW do we organize them? They are *base* information, but pretty dense.

- Inefficient with equivalence modulo labeling

- So we explore information systems based on these bounds:

(1) explicit = trace(s) \leq faster trace 1 \leq faster trace 2 \leq ... \leq

implicit = statement of problem (x in S)

- * TODO: create diagram that highlights this! Make the outer circle the problem, Halting instance, and then the center is the set of explicit traces. When we union these, then the an explicit trace

in one machine is the implicit one for another - maybe show this in a simple lemma?

* ... ensured by Blum's speedup theorem - we will make this result self-contained + define Blum complexity measures!

* Consider *statement* of problem to be "most implicit" by fiat: even if we use a proof search approach (so this may NOT halt) or use more uncomputable means, that still adds "extra" to the search itself.

* Note that \leq here is NOT necessarily implication; we are more thinking about a rough *measure* of being an *exact* trace of a TM

* Blum [7] says you can always do better (*in general*).

. Cite example: palindromes! Easy to discuss on efficiency

* TODO: show that this corresponds to *shorter traces*, fixing the main measure as the size of the trace. Again, to separate *query* from *search*, we do NOT want to involve any aspect of time, so the main other attribute is the space itself.

– Our goal: how to organize when we have a **space** of things like (1) that are *interconnected*?

– Old approach (diagram!): show that people had *different* ways to tackle the stuff in-between. That's where most theories like (e.g., dependently typed theories, HOL, etc.)

– New approach: separate *query* from *search*! Unify the previous approaches by focusing on optimizing the *left side* that we *can* control effectively

3.1. Motivating Examples and Definition.

We start with simple informal examples to explore the concept of information:

- Statements about the world.
- Taxonomies.
- Mathematical relations.
- More sophisticated: formal theories.

Each of the previous examples suggests a common definition: *information is a relation*. However, we want to express any formalizable kind of information. A binary relation *can* encode any other computable one, but not without clear reasons or connections. We add this missing component by using triadic relations instead, building off of semiotics and related schools of thought.

Definition 3.1.0. An **information system** is a pair (D, I) , where:

- D is the **domain**, a finite, computable set of **data** in \mathbb{N}
- I is **(partial) information**, a partially computable subset of $D \times D \times D$. This information is **complete** if I is totally computable.

3.2. Constructions and Reflection.

Let **Info** be the set of all information systems.

A natural construction to include is a system with *indexed information*, akin to indexed families of sets. But we want to have information between information as well. We can think of a disjoint union of systems as the weakest transformation between systems.

Definition 3.2.1. Let $\mathcal{S} = \{(D_i, I_i)\}_{i \in \mathbb{N}}$ be a family of information systems, indexed by a partial computable function. Then the **sum** of \mathcal{S} is $(\bigcup D_i, \bigcup I_i)$. A **transformation** on \mathcal{S} is an information system $(\bigcup D_i, I')$ such that for each $i \in I$, $I' \cap (D_i \times D_i \times D_i) = I_i$.

As another construction, we can naturally model formal systems by asserting that I is reflexive and transitive in a general sense, formalized by below.

Definition 3.2.2. A **formal system** is an information system such that the information relation is reflexive and “transitive in a general sense” (WIP).

This construction is **information compressing**: we can computably encode information into a different representation and computably decode it back.

Special systems:

- (\emptyset, \emptyset) is the **null information system**
- $(\mathbb{N}, \mathbb{N} \times \mathbb{N} \times \mathbb{N})$ is the **discrete information system**

Lemma 3.2.3. Let $\mathcal{H} \equiv (\text{Info}, \leq)$, where $(D_1, I_1) \leq (D_2, I_2)$ iff $D_1 \subseteq D_2$ and $I_1 \subseteq I_2$. Then \mathcal{H} forms a Heyting Algebra, with bottom element being the null information system and the top element being the discrete one.

Theorem 3.2.4.

- The discrete information system cannot represent \mathcal{H} .
- \mathcal{H} can represent any extension of this structure and therefore induces an idempotent operator.

TODO: Show that a formal system provides a proof system that is a way to optimize the search space of information systems.

3.3. Universality.

Theorem 3.3.5. Every universal formal system induces a framework \mathbb{F}' , as the image of the functor $\mathcal{G} : \mathbb{F} \rightarrow \mathbb{F}'$, given by $\mathcal{G}(\mathcal{S}) = (\text{Image}(G_{\mathcal{S}}), \mathcal{R}_{\mathcal{U}} \cap \text{Image}(G_{\mathcal{S}})^2)$. Conversely, every framework induces a universal formal system.

Proof. We must show that \mathbb{F}' is a framework for \mathbb{F} . Clearly this is a computable sub-category. To prove \mathcal{G} is an equivalence, notice that \mathcal{G} is full and faithful as a full sub-category of \mathbb{F} . Additionally, \mathcal{G} is essentially surjective precisely by construction. This completes the forwards direction.

Conversely, a universal framework can be formed from a system by creating a computable encoding of the formulas and rules of a system. The family G can then be defined from an equivalence from \mathbb{F} to \mathbb{F}' , which can be easily verified to preserve and reflection derivations. \square

4. SYNTAX

5. SEMANTICS

5.1. Terms.

We expand upon to analyze the ASTs generated from Section 4.

6. BOOTSTRAP

7. CONCLUSION

REFERENCES

1. Li, M., Vitanyi, P.: An Introduction to Kolmogorov Complexity and Its Applications. Springer Publishing Company, Incorporated (2019)
2. Chaitin, G.: The Limits of Reason. *Scientific American*. 294, 74–81 (2006). <https://doi.org/10.1038/scientificamerican0306-74>
3. Béziau, J.-Y.: Universal Logic: Evolution of a Project. *Logica Universalis*. 12, 1–8 (2018). <https://doi.org/10.1007/s11787-018-0194-7>
4. Chaitin, G.: Elegant Lisp Programs. (2003). https://doi.org/10.1007/978-1-4471-0015-7_2
5. Dictionary, O.E.: welkin, n., https://www.oed.com/dictionary/welkin_n
6. Artemov, S.N.: Explicit Provability and Constructive Semantics. *Bulletin of Symbolic Logic*. 7, 1–36 (2001). <https://doi.org/10.2307/2687821>
7. Blum, M.: A Machine-Independent Theory of the Complexity of Recursive Functions. *J. Acm*. 14, 322–336 (1967). <https://doi.org/10.1145/321386.321395>

DEPARTMENT OF MATHEMATICS, UNIVERSITY OF COLORADO AT BOULDER, BOULDER, CO
Email address: oscar-bender-stone@protonmail.com

DRAFT