Designing a Universal Information Language

Oscar Bender-Stone

March 26, 2026

DRAFT

Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph
32	20	Space	48	30	0	64	40	@	80	50	P	96	60	`	112	70	p
33	21	!	49	31	1	65	41	A	81	51	Q	97	61	a	113	71	q
34	22	"	50	32	2	66	42	B	82	52	R	98	62	b	114	72	r
35	23	#	51	33	3	67	43	C	83	53	S	99	63	c	115	73	s
36	24	$	52	34	4	68	44	D	84	54	T	100	64	d	116	74	t
37	25	%	53	35	5	69	45	E	85	55	U	101	65	e	117	75	u
38	26	&	54	36	6	70	46	F	86	56	V	102	66	f	118	76	v
39	27	'	55	37	7	71	47	G	87	57	W	103	67	g	119	77	w
40	28	(	56	38	8	72	48	H	88	58	X	104	68	h	120	78	x
41	29	)	57	39	9	73	49	I	89	59	Y	105	69	i	121	79	y
42	2A	*	58	3A	:	74	4A	J	90	5A	Z	106	6A	j	122	7A	z
43	2B	+	59	3B	;	75	4B	K	91	5B	[	107	6B	k	123	7B	{
44	2C	,	60	3C	<	76	4C	L	92	5C	\	108	6C	l	124	7C	|
45	2D	-	61	3D	=	77	4D	M	93	5D	]	109	6D	m	125	7D	}
46	2E	.	62	3E	>	78	4E	N	94	5E	^	110	6E	n	126	7E	~
47	2F	/	63	3F	?	79	4F	O	95	5F	_	111	6F	o			

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Background

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]
    - Data ⇒ Information ⇒ Wisdom

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]
    - Data ⇒ Information ⇒ Wisdom
  - **Buckland:** Based on usage[2]

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]
    - Data ⇒ Information ⇒ Wisdom
  - **Buckland:** Based on usage[2]
    - Can be a *process*, or *knowledge*
    - Most useful as *thing*
  - **Floridi:** Information is **truthful**[3]

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]
    - Data ⇒ Information ⇒ Wisdom
  - **Buckland:** Based on usage[2]
    - Can be a *process*, or *knowledge*
    - Most useful as *thing*
  - **Floridi:** Information is **truthful**[3]

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Problems

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). “The sum of all human knowledge”: A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]
- **Breadth:** different kinds of data

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]
- **Breadth:** different kinds of data
  - Example: Wikipedia[2]

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]
- **Breadth:** different kinds of data
  - Example: Wikipedia[2]
- **Standardization:** ambiguous interpretations
  - Related issue: being **interoperable**
  - **Interoperable:** a portable data format
  - Example: US health records[3]

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Existing Solutions

DRAFT

[1]Hitzler et al. (2009). *OWL 2 Web Ontology Language Primer*. W3C.
[2]Robinson, Webber & Eifrem (2015). *Graph Databases* (2nd ed.). O'Reilly.
[3]Lenat (1995). *CYC: A large-scale investment in knowledge infrastructure*. CACM 38(11).

Existing Solutions

- **Resource Description Language (RDF):**[1]
  - ▸ Used in Web Ontology Language **(OWL)**
  - \+ Built to be **interoperable**
  - — No built-in logic engine
- **Labeled Property Graphs (LPGs):**[2]
  - ▸ Stores **properties** (node/edge metadata)
  - \+ Efficient queries
  - — No logic engine. Hacky tooling/scripts
- **Cyc:**[3]
  - ▸ Largest **knowledge base** to date
  - \+ Sophisticated logic engine
  - — Hard-coded, proprietary rules

[1] Hitzler et al. (2009). *OWL 2 Web Ontology Language Primer*. W3C.
[2] Robinson, Webber & Eifrem (2015). *Graph Databases* (2nd ed.). O'Reilly.
[3] Lenat (1995). *CYC: A large-scale investment in knowledge infrastructure*. CACM 38(11).

DRAFT

Proposed Solution

DRAFT

[1] Oxford English Dictionary (2025), s.v. “welkin, n.”

Proposed Solution

- **Welkin**: an information language
  - Pronounced: “VEL-KIN”
  - Old German word, meaning “cloud”, “sky”[1]
- **Goals:**

DRAFT

[1] Oxford English Dictionary (2025), s.v. “welkin, n.”

Proposed Solution

- **Welkin**: an information language
  - Pronounced: "VEL-KIN"
  - Old German word, meaning "cloud", "sky"[1]
- **Goals:**
  - **Universality:** be completely expressive(**done**)
    - *Any* computer program
    - *Any* "reliable" proof
  - **Scalability:** work at any size (**WIP**)
    - Be efficient
    - Support: future optimizations
    - Describe improvements *in* Welkin
  - **Standardization:** be completely *unambiguous*(**WIP**)

DRAFT

[1] Oxford English Dictionary (2025), s.v. "welkin, n."

Proposed Solution

- **Welkin**: an information language
  - Pronounced: "VEL-KIN"
  - Old German word, meaning "cloud", "sky"[1]
- **Goals:**
  - **Universality:** be completely expressive(**done**)
    - *Any* computer program
    - *Any* "reliable" proof
  - **Scalability:** work at any size (**WIP**)
    - Be efficient
    - Support: future optimizations
    - Describe improvements *in* Welkin
  - **Standardization:** be completely *unambiguous*(**WIP**)
    - Have a formal specification

[1] Oxford English Dictionary (2025), s.v. "welkin, n."

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

General Requirements

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*
   - Avoid empty symbols!

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*
   - Avoid empty symbols!
   - Symbol Grounding Problem[2]

DRAFT

[1] Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2] Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*
   - Avoid empty symbols!
   - Symbol Grounding Problem[2]

- Achieve both through **representations**

DRAFT

[1] Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2] Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

Representations

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**
  - b: **referent**

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**
  - b: **referent**
  - c: **context**

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**
  - b: **referent**
  - c: **context**
- Track *faithfulness* of representations through **truth**

DRAFT

Units

DRAFT

Units

- **Finitely defined**

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning
  - User's goal: correctly specify!

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning
  - User's goal: correctly specify!
- Representations are units

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning
  - User's goal: correctly specify!
- Representations are units
- Each unit has its own **context**

DRAFT

Information

- Representations

DRAFT

Information

- Representations ~ **Truth**
- Information

DRAFT

Information

- Representations ~ **Truth**
- Information ~ **Proofs**
-

DRAFT

Rules

- **Internal Transitivity:**
- **Contextual Lifting:**

DRAFT

Rules

- **Internal Transitivity:**
- **Contextual Lifting:**
- **Lattice Laws:**
  - Units as sets

DRAFT

Turing Completeness

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:**

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation:

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation: $a - c \to b$ iff $\varphi_c(\langle\varphi_a\rangle) = \langle\varphi_b\rangle$
  - $\langle\varphi_a\rangle$:

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation: $a - c \to b$ iff $\varphi_c(\langle\varphi_a\rangle) = \langle\varphi_b\rangle$
  - $\langle\varphi_a\rangle$: encodes φ_a as a string
- Later:

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation: $a - c \to b$ iff $\varphi_c(\langle\varphi_a\rangle) = \langle\varphi_b\rangle$
  - $\langle\varphi_a\rangle$: encodes φ_a as a string
- Later: completeness for **proofs**!

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Overview

DRAFT

Encoding

- Characters written in `type-writer font`[1]
- Define US-ASCII: Printable (codes: 32-126) + `EOF` (code: 127)
- **Token:** collection of contiguous characters
  - Simplifies grammar

DRAFT

[1]Font used: Intel One Mono (https://github.com/intel/intel-one-mono), licensed under OFL 1.1 (https://github.com/intel/intel-one-mono/blob/main/OFL.txt).

US-ASCII

Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph
32	20	Space	46	2E	.	60	3C	<	74	4A	J	88	58	X	102	66	f	116	74	t
33	21	!	47	2F	/	61	3D	=	75	4B	K	89	59	Y	103	67	g	117	75	u
34	22	"	48	30	0	62	3E	>	76	4C	L	90	5A	Z	104	68	h	118	76	v
35	23	#	49	31	1	63	3F	?	77	4D	M	91	5B	[	105	69	i	119	77	w
36	24	$	50	32	2	64	40	@	78	4E	N	92	5C	\	106	6A	j	120	78	x
37	25	%	51	33	3	65	41	A	79	4F	O	93	5D	]	107	6B	k	121	79	y
38	26	&	52	34	4	66	42	B	80	50	P	94	5E	^	108	6C	l	122	7A	z
39	27	'	53	35	5	67	43	C	81	51	Q	95	5F	_	109	6D	m	123	7B	{
40	28	(	54	36	6	68	44	D	82	52	R	96	60	`	110	6E	n	124	7C	|
41	29	)	55	37	7	69	45	E	83	53	S	97	61	a	111	6F	o	125	7D	}
42	2A	*	56	38	8	70	46	F	84	54	T	98	62	b	112	70	p	126	7E	~
43	2B	+	57	39	9	71	47	G	85	55	U	99	63	c	113	71	q			
44	2C	,	58	3A	:	72	48	H	86	56	V	100	64	d	114	72	r			
45	2D	-	59	3B	;	73	49	I	87	57	W	101	65	e	115	73	s			

Table 1: Printable US-ASCII codes and glyphs.

DRAFT

Character Classes

Set Name	Characters
PRINTABLE	Listed in Table 1
WHITESPACE	\t | \r | Space
DELIMITER	{ | } | ' | " | . | ,
RESERVED	DELIMITER | * | @
SQ_CHAR	Any PRINTABLE except ' and \
DQ_CHAR	Any PRINTABLE except " and \
ID_CHAR	Any PRINTABLE not in RESERVED or WHITESPACE

Table 2: Key character classes.

DRAFT

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]
  - **Printer**: converts a data structure into a string
  - Identity: when parser succeeds, is "reversible" with printer.
- Need **maximal munch:**

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]
  - **Printer**: converts a data structure into a string
  - Identity: when parser succeeds, is "reversible" with printer.
- Need **maximal munch:** consume tokens, not characters

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]
  - **Printer**: converts a data structure into a string
  - Identity: when parser succeeds, is "reversible" with printer.
- Need **maximal munch:** consume tokens, not characters
  - Simplifies grammar

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

The Welkin Grammar

```
start := units - lexeme -> EOF,
units := "" | {unit - lexeme -> *{"",
"," - lexeme -> units}},
unit := node - lexeme -> *{
  ":=" - lexeme -> choices,
  *{"", arc - lexeme -> chain}
},
choices := *{"", "|"} - lexeme ->
choices_list,
choices_list := *{"",
  chain - lexeme -> *{"", "|" - lexeme
-> choice_list}
},
chain := *{"", "*"} - seq -> path -
lexeme -> *{"", arc - lexeme ->
chain},
arc := right_arc | other_arc,
right_arc := "-" - seq -> node - seq -
> "->",
other_arc := "<-" - seq -> node - seq
-> *{"-", "->"},
node := *{"", "*"} - seq -> path,
path := *{"", modifiers} - seq ->
trailer - seq -> *{"", graph},
modifiers := *{
  "@",
  "~" - seq -> *{"", "@"}
},
trailer := segment - seq -> *{"", "."
- seq -> trailer},
segment := HANDLE - lexeme -> *{"",
graph},
graph :=  "{" - lexeme -> units -
lexeme -> "}",
HANDLE := ID | STRING,
STRING := SQ_STRING | DQ_STRING,
SQ_STRING := "'" - seq -> *{SQ_CHAR,
"\'"} - seq_many_till -> "'",
DQ_STRING := '"' - seq -> *{DQ_CHAR,
'\"'} - seq_many_till -> '"',
ID := ID_CHAR - seq_many_till ->
*{RESERVED, WHITESPACE}
```

Listing 1: Full Welkin grammar.

DRAFT

Outline of Unambiguity

- Simple grammar class: LL(1)

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:[2]
  - Involves recursive equations on sets

DRAFT

[1] Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2] Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:[2]
  - Involves recursive equations on sets
  - Need: certain sets are djsoint

DRAFT

[1] Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2] Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:[2]
  - Involves recursive equations on sets
  - Need: certain sets are djsoint
  - For details, refer to thesis

DRAFT

[1] Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2] Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Comparisons to Existing Solutions

DRAFT

Future Work

DRAFT