Designing a Universal Information Language

Oscar Bender-Stone

March 26, 2026

DRAFT

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Background

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**

DRAFT

[1]Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2]Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3]Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]
    - Data ⇒ Information ⇒ Wisdom

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]
    - Data ⇒ Information ⇒ Wisdom
  - **Buckland:** Based on usage[2]

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Background

- Information Management: studies how to **store** and **organize** data
  - Throughout *all* history: so much data!
  - Organize through **information**
- What *is* information?
  - Depends on who you ask!
  - **Ackoff:** Data-to-Wisdom Hierarchy[1]
    - Data ⇒ Information ⇒ Wisdom
  - **Buckland:** Based on usage[2]
    - Can be a *process*, or *knowledge*
    - Most useful as *thing*
  - **Floridi:** Information is **truthful**[3]

DRAFT

[1] Ackoff, R. L. (1989). *From Data to Wisdom*. J. Appl. Syst. Anal., 16, 3–9.
[2] Buckland, M. K. (1991). *Information as thing*. JASIS, 42(5), 351–360.
[3] Floridi, L. (2010). *Information: A Very Short Introduction*. Oxford University Press.

Problems

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). “The sum of all human knowledge”: A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]
- **Breadth:** different kinds of data

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]
- **Breadth:** different kinds of data
  - Example: Wikipedia[2]

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Problems

- How to *actually* manage information?
  - **Information base:** a database of information
- **Depth:** domain specific data
  - Example: Amazon (product suggestions)[1]
- **Breadth:** different kinds of data
  - Example: Wikipedia[2]
- **Standardization:** ambiguous interpretations
  - Related issue: being **interoperable**
  - **Interoperable:** a portable data format
  - Example: US health records[3]

DRAFT

[1]Smith & Linden (2017). Two Decades of Recommender Systems at Amazon.com. IEEE Internet Comput. 21(3).
[2]Mesgari, M., et al. (2015). "The sum of all human knowledge": A systematic review of Wikipedia. JASIST, 66(2).
[3]Reisman, M. (2017). EHRs: The challenge of making electronic data usable. P & T, 42(9), 572–575.

Existing Solutions

DRAFT

[1]Hitzler et al. (2009). *OWL 2 Web Ontology Language Primer*. W3C.
[2]Robinson, Webber & Eifrem (2015). *Graph Databases* (2nd ed.). O'Reilly.
[3]Lenat (1995). *CYC: A large-scale investment in knowledge infrastructure*. CACM 38(11).

Existing Solutions

- **Resource Description Language (RDF):**[1]
  - ▸ Used in Web Ontology Language **(OWL)**
  - \+ Built to be **interoperable**
  - — No built-in logic engine
- **Labeled Property Graphs (LPGs):**[2]
  - ▸ Stores **properties** (node/edge metadata)
  - \+ Efficient queries
  - — No logic engine. Hacky tooling/scripts
- **Cyc:**[3]
  - ▸ Largest **knowledge base** to date
  - \+ Sophisticated logic engine
  - — Hard-coded, proprietary rules

[1] Hitzler et al. (2009). *OWL 2 Web Ontology Language Primer*. W3C.
[2] Robinson, Webber & Eifrem (2015). *Graph Databases* (2nd ed.). O'Reilly.
[3] Lenat (1995). *CYC: A large-scale investment in knowledge infrastructure*. CACM 38(11).

DRAFT

Proposed Solution

DRAFT

[1] Oxford English Dictionary (2025), s.v. “welkin, n.”

Proposed Solution

- **Welkin**: an information language
  - Pronounced: “VEL-KIN”
  - Old German word, meaning “cloud”, “sky”[1]
- **Goals:**

DRAFT

[1] Oxford English Dictionary (2025), s.v. “welkin, n.”

Proposed Solution

- **Welkin**: an information language
  - Pronounced: "VEL-KIN"
  - Old German word, meaning "cloud", "sky"[1]
- **Goals:**
  - **Universality:** be completely expressive (**done**)
    - *Any* computer program
    - *Any* "reliable" proof
  - **Scalability:** work at any size (**WIP**)
    - Be efficient
    - Support: future optimizations
    - Describe improvements *in* Welkin
  - **Standardization:** be completely *unambiguous* (**WIP**)

DRAFT

[1] Oxford English Dictionary (2025), s.v. "welkin, n."

Proposed Solution

- **Welkin**: an information language
  - Pronounced: "VEL-KIN"
  - Old German word, meaning "cloud", "sky"[1]
- **Goals:**
  - **Universality:** be completely expressive (**done**)
    - *Any* computer program
    - *Any* "reliable" proof
  - **Scalability:** work at any size (**WIP**)
    - Be efficient
    - Support: future optimizations
    - Describe improvements *in* Welkin
  - **Standardization:** be completely *unambiguous* (**WIP**)
    - Have a formal specification

[1] Oxford English Dictionary (2025), s.v. "welkin, n."

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

General Requirements

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*
   - Avoid hollow symbols!

DRAFT

[1]Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2]Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*
   - Avoid hollow symbols!
   - Symbol Grounding Problem[2]

DRAFT

[1] Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2] Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

General Requirements

1. Express any computer program
   - Need effective operations
   - Established notion: **Turing machines**[1]
2. Enable user-defined *meaning*
   - Avoid hollow symbols!
   - Symbol Grounding Problem[2]

- Achieve both via **representations**

DRAFT

[1] Turing, A. M. (1936). On Computable Numbers. Proc. Lond. Math. Soc., 42, 230–265.
[2] Harnad, S. (1990). *The Symbol Grounding Problem.* Physica D, 42, 335–346.

Representations

DRAFT

Representations

- Centered around *representing* things

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**
  - b: **referent**

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**
  - b: **referent**
  - c: **context**

DRAFT

Representations

- Centered around *representing* things
- $a - c \to b$: a **represents** b **in context** c
  - a: **sign**
  - b: **referent**
  - c: **context**
- Track *faithfulness* of representations via **truth**

DRAFT

Units

DRAFT

Units

- **Finitely defined**

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning
  - User's goal: correctly specify!

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning
  - User's goal: correctly specify!
- Representations are units

DRAFT

Units

- **Finitely defined**
- Can be broken down, combined
  - Written with braces $\{a, b, \ldots, z\}$
- Built from **Handles**
  - Name origin: file/resource handles (programs)
  - Enables user-defined meaning
  - User's goal: correctly specify!
- Representations are units
- Each unit has its own **context**

DRAFT

Information

DRAFT

Information

- Representations

DRAFT

Information

- Representations $\sim$ **Truth**

DRAFT

Information

- Representations ~ **Truth**
- Information

DRAFT

Information

- Representations ~ **Truth**
- Information ~ **Proofs**

DRAFT

Information

- Representations ~ **Truth**
- Information ~ **Proofs**
  - Includes simple facts

DRAFT

Information

- Representations ~ **Truth**
- Information ~ **Proofs**
  - Includes simple facts
  - Expands to complex truth systems

DRAFT

Information

- Representations ~ **Truth**
- Information ~ **Proofs**
  - Includes simple facts
  - Expands to complex truth systems
- Major result: can express *any* "reliable" proof

DRAFT

Information

- Representations ~ **Truth**
- Information ~ **Proofs**
  - Includes simple facts
  - Expands to complex truth systems
- Major result: can express *any* "reliable" proof
  - More details later! (Metatheory)

DRAFT

Rules

- **Internal Transitivity:** $a - c \to b$ and $b - c \to d$ imply $a - c \to d$
- **Contextual Lifting:**

DRAFT

Rules

- **Internal Transitivity:** $a - c \to b$ and $b - c \to d$ imply $a - c \to d$
- **Contextual Lifting:**
- **Lattice Laws:**
  - Units as sets

DRAFT

Turing Completeness

DRAFT

Turing Completeness

- Part of Universality

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:**

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation:

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation: $a - c \to b$ iff $\varphi_c(\langle\varphi_a\rangle) = \langle\varphi_b\rangle$
  - $\langle\varphi_a\rangle$:

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation: $a - c \to b$ iff $\varphi_c(\langle\varphi_a\rangle) = \langle\varphi_b\rangle$
  - $\langle\varphi_a\rangle$: encodes φ_a as a string
- Later:

DRAFT

Turing Completeness

- Part of Universality
- **Theorem:** *every unit corresponds to some program, and vice versa.*
  - φ: some mapping between units and programs
  - Interpretation: $a - c \to b$ iff $\varphi_c(\langle\varphi_a\rangle) = \langle\varphi_b\rangle$
  - $\langle\varphi_a\rangle$: encodes φ_a as a string
- Later: completeness for **proofs**!

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Overview

DRAFT

Encoding

- Characters written in `type-writer font`[1]
- Define US-ASCII: Printable (codes: 32-126) + `EOF` (code: 127)
- **Token:** collection of contiguous characters
  - Simplifies grammar

DRAFT

[1]Font used: Intel One Mono (https://github.com/intel/intel-one-mono), licensed under OFL 1.1 (https://github.com/intel/intel-one-mono/blob/main/OFL.txt).

US-ASCII

Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph	Dec.	Hex.	Glyph
32	20	Space	46	2E	.	60	3C	<	74	4A	J	88	58	X	102	66	f	116	74	t
33	21	!	47	2F	/	61	3D	=	75	4B	K	89	59	Y	103	67	g	117	75	u
34	22	"	48	30	0	62	3E	>	76	4C	L	90	5A	Z	104	68	h	118	76	v
35	23	#	49	31	1	63	3F	?	77	4D	M	91	5B	[	105	69	i	119	77	w
36	24	$	50	32	2	64	40	@	78	4E	N	92	5C	\	106	6A	j	120	78	x
37	25	%	51	33	3	65	41	A	79	4F	O	93	5D	]	107	6B	k	121	79	y
38	26	&	52	34	4	66	42	B	80	50	P	94	5E	^	108	6C	l	122	7A	z
39	27	'	53	35	5	67	43	C	81	51	Q	95	5F	_	109	6D	m	123	7B	{
40	28	(	54	36	6	68	44	D	82	52	R	96	60	`	110	6E	n	124	7C	|
41	29	)	55	37	7	69	45	E	83	53	S	97	61	a	111	6F	o	125	7D	}
42	2A	*	56	38	8	70	46	F	84	54	T	98	62	b	112	70	p	126	7E	~
43	2B	+	57	39	9	71	47	G	85	55	U	99	63	c	113	71	q			
44	2C	,	58	3A	:	72	48	H	86	56	V	100	64	d	114	72	r			
45	2D	-	59	3B	;	73	49	I	87	57	W	101	65	e	115	73	s			

Table 1: Printable US-ASCII codes and glyphs.

DRAFT

Character Classes

Set Name	Characters
PRINTABLE	Listed in Table 1
WHITESPACE	\t | \r | Space
DELIMITER	{ | } | ' | " | . | ,
RESERVED	DELIMITER | * | @
SQ_CHAR	Any PRINTABLE except ' and \
DQ_CHAR	Any PRINTABLE except " and \
ID_CHAR	Any PRINTABLE not in RESERVED or WHITESPACE

Table 2: Key character classes.

DRAFT

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]
  - **Printer**: converts a data structure into a string
  - Identity: when parser succeeds, is "reversible" with printer.
- Need **maximal munch:**

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]
  - **Printer**: converts a data structure into a string
  - Identity: when parser succeeds, is "reversible" with printer.
- Need **maximal munch:** consume tokens, not characters

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

Building Blocks

- **Invertible Syntax Descriptions:** pairs of functions:[1]
  - **Parser**: takes (*consumes*) tokens, converts into a data structure[2]
  - **Printer**: converts a data structure into a string
  - Identity: when parser succeeds, is "reversible" with printer.
- Need **maximal munch:** consume tokens, not characters
  - Simplifies grammar

DRAFT

[1] Rendel & Ostermann (2010). Invertible syntax descriptions. Haskell '10.
[2] For computer scientists: this is an AST.

The Welkin Grammar

```
start := units - lexeme -> EOF,
units := "" | {unit - lexeme -> *{"",
"," - lexeme -> units}},
unit := node - lexeme -> *{
  ":=" - lexeme -> choices,
  *{"", arc - lexeme -> chain}
},
choices := *{"", "|"} - lexeme ->
choices_list,
choices_list := *{"",
  chain - lexeme -> *{"", "|" - lexeme
-> choice_list}
},
chain := *{"", "*"} - seq -> path -
lexeme -> *{"", arc - lexeme ->
chain},
arc := right_arc | other_arc,
right_arc := "-" - seq -> node - seq -
> "->",
other_arc := "<-" - seq -> node - seq
-> *{"-", "->"},
node := *{"", "*"} - seq -> path,
path := *{"", modifiers} - seq ->
trailer - seq -> *{"", graph},
modifiers := *{
  "@",
  "~" - seq -> *{"", "@"}
},
trailer := segment - seq -> *{"", "."
- seq -> trailer},
segment := HANDLE - lexeme -> *{"",
graph},
graph :=  "{" - lexeme -> units -
lexeme -> "}",
HANDLE := ID | STRING,
STRING := SQ_STRING | DQ_STRING,
SQ_STRING := "'" - seq -> *{SQ_CHAR,
"\'"} - seq_many_till -> "'",
DQ_STRING := '"' - seq -> *{DQ_CHAR,
'\"'} - seq_many_till -> '"',
ID := ID_CHAR - seq_many_till ->
*{RESERVED, WHITESPACE}
```

Listing 1: Full Welkin grammar.

DRAFT

Outline of Unambiguity

- Simple grammar class: LL(1)

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:

DRAFT

[1]Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2]Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:[2]
  - Involves recursive equations on sets

DRAFT

[1] Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2] Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:[2]
  - Involves recursive equations on sets
  - Need: certain sets are djsoint

DRAFT

[1] Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2] Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Outline of Unambiguity

- Simple grammar class: LL(1)
- Desirable properties:
  - Unambiguous: every valid input produces *one* output
  - Efficient parsing[1]
- For our parsers, need Edelmann et. al:[2]
  - Involves recursive equations on sets
  - Need: certain sets are djsoint
  - For details, refer to thesis

DRAFT

[1] Consult: Aho et al. (2006). *Compilers: Principles, Techniques, and Tools* (2nd ed.).
[2] Edelmann et al. (2020). *Zippy LL(1) parsing with derivatives*. PLDI 2020.

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Primer

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything

DRAFT

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything
    - **Second**: PA cannot prove *own* consistency

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything
    - **Second**: PA cannot prove *own* consistency
  - Tarski undefinability

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything
    - **Second**: PA cannot prove *own* consistency
  - Tarski undefinability
  - Etc.

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything
    - **Second**: PA cannot prove *own* consistency
  - Tarski undefinability
  - Etc.
- Usual approach: *chain of stronger theories*

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything
    - **Second**: PA cannot prove *own* consistency
  - Tarski undefinability
  - Etc.
- Usual approach: *chain of stronger theories*
  - Keep adding Con (PA)

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything
    - **Second**: PA cannot prove *own* consistency
  - Tarski undefinability
  - Etc.
- Usual approach: *chain of stronger theories*
  - Keep adding Con (PA)
  - *Technically* enough, based on Feferman's work[TODO: cite!]

DRAFT

Primer

- Terminology
  - **Peano Arithmetic** (PA): natural numbers + induction
  - Important: corresponds to a Turing machine, $\mathrm{TM}_{\mathrm{PA}}$
  - **Consistency:** no proofs contain falsehood ($\perp$)
- Many theorems on limit:s
  - **Gödel incompleteness**
    - **First:** PA can't prove everything
    - **Second**: PA cannot prove *own* consistency
  - Tarski undefinability
  - Etc.
- Usual approach: *chain of stronger theories*
  - Keep adding Con (PA)
  - *Technically* enough, based on Feferman's work[TODO: cite!]
  - Problem: want *constructive* & *solid* foundations

DRAFT

Artëmov's Selector Proofs

DRAFT

Artëmov's Selector Proofs

- Artëmov *changes* this paradigm

DRAFT

Artëmov's Selector Proofs

- Artëmov *changes* this paradigm
  - There is a *weaker* proof: **selectors**

DRAFT

Artëmov's Selector Proofs

- Artëmov *changes* this paradigm
  - There is a *weaker* proof: **selectors**
- **Selector:** algorithm that takes proofs as inputs

DRAFT

Artëmov's Selector Proofs

- Artëmov *changes* this paradigm
  - There is a *weaker* proof: **selectors**
- **Selector:** algorithm that takes proofs as inputs
  1. Takes in *any* proof

DRAFT

Artëmov's Selector Proofs

- Artëmov *changes* this paradigm
  - There is a *weaker* proof: **selectors**
- **Selector:** algorithm that takes proofs as inputs
  1. Takes in *any* proof
  2. If it accepts a proof, no $\perp$ appears

DRAFT

Artëmov's Selector Proofs

- Artëmov *changes* this paradigm
  - There is a *weaker* proof: **selectors**
- **Selector:** algorithm that takes proofs as inputs
  1. Takes in *any* proof
  2. If it accepts a proof, no $\perp$ appears
- Artëmov

DRAFT

Serial-Soundness

DRAFT

[1]TODO: cite

Serial-Soundness

- Extend Artëmov to **serial-soundness:**
  - Secret: *same* technique!
  - Use Tarski's **partial truh predicates**[1]
  - Partial truth predicate: [TODO: define!]
- **Serial soundness:** a RE theory $T \supseteq$ PA with a selector s.t.:
  - Accepts all proofs + preserves truth

DRAFT

[1] TODO: cite

Serial-Soundness

- Extend Artëmov to **serial-soundness:**
  - Secret: *same* technique!
  - Use Tarski's **partial truh predicates**[1]
  - Partial truth predicate: [TODO: define!]
- **Serial soundness:** a RE theory $T \supseteq$ PA with a selector s.t.:
  - Accepts all proofs + preserves truth
  - *cannot* be proven with:
    - Excluded Middle: $\varphi \vee \neg\varphi$

DRAFT

[1] TODO: cite

Serial-Soundness

- Extend Artëmov to **serial-soundness:**
  - Secret: *same* technique!
  - Use Tarski's **partial truh predicates**[1]
  - Partial truth predicate: [TODO: define!]
- **Serial soundness:** a RE theory $T \supseteq$ PA with a selector s.t.:
  - Accepts all proofs + preserves truth
  - *cannot* be proven with:
    - Excluded Middle: $\varphi \vee \neg\varphi$
    - Explosion: $\bot \Rightarrow \varphi$

[1] TODO: cite

DRAFT

Serial-Soundness

- Extend Artëmov to **serial-soundness:**
  - Secret: *same* technique!
  - Use Tarski's **partial truh predicates**[1]
  - Partial truth predicate: [TODO: define!]
- **Serial soundness:** a RE theory $T \supseteq$ PA with a selector s.t.:
  - Accepts all proofs + preserves truth
  - *cannot* be proven with:
    - Excluded Middle: $\varphi \vee \neg\varphi$
    - Explosion: $\bot \Rightarrow \varphi$
- **Self-verifying**: *in* PA, T can prove its own serial-soundness
  - PA $\vdash_T \varphi$ if $T \vdash \varphi$, T self-verifying

[1] TODO: cite

DRAFT

Reliable Proofs

- How to generalize to *any* theory?

DRAFT

Reliable Proofs

- How to generalize to *any* theory?
  - Example: Naive Set Theory

DRAFT

Reliable Proofs

- How to generalize to *any* theory?
  - Example: Naive Set Theory
    - Can't *fully* trust b/c, e.g., Russell's Paradox

DRAFT

Reliable Proofs

- How to generalize to *any* theory?
  - Example: Naive Set Theory
    - Can't *fully* trust b/c, e.g., Russell's Paradox
    - But can trust, e.g., $x \in X \Leftrightarrow x \in X$

DRAFT

Reliable Proofs

- How to generalize to *any* theory?
  - Example: Naive Set Theory
    - Can't *fully* trust b/c, e.g., Russell's Paradox
    - But can trust, e.g., $x \in X \Leftrightarrow x \in X$
    - Idea: check for sound *restricted* theory
- Let $T_1 \supseteq \mathrm{PA}$, φ a sentence

DRAFT

Reliable Proofs

- How to generalize to *any* theory?
  - Example: Naive Set Theory
    - Can't *fully* trust b/c, e.g., Russell's Paradox
    - But can trust, e.g., $x \in X \Leftrightarrow x \in X$
    - Idea: check for sound *restricted* theory
- Let $T_1 \supseteq \mathrm{PA}$, φ a sentence
- **Reliable proof**: a triple (S, p_S, p_φ) s.t:
  - $S \supseteq T_1$

DRAFT

Reliable Proofs

- How to generalize to *any* theory?
  - Example: Naive Set Theory
    - Can't *fully* trust b/c, e.g., Russell's Paradox
    - But can trust, e.g., $x \in X \Leftrightarrow x \in X$
    - Idea: check for sound *restricted* theory
- Let $T_1 \supseteq \mathrm{PA}$, φ a sentence
- **Reliable proof**: a triple (S, p_S, p_φ) s.t:
  - $S \supseteq T_1$
  - p_S: constructs some self-verifying $S' \supseteq S$

DRAFT

Reliable Proofs

- How to generalize to *any* theory?
  - Example: Naive Set Theory
    - Can't *fully* trust b/c, e.g., Russell's Paradox
    - But can trust, e.g., $x \in X \Leftrightarrow x \in X$
    - Idea: check for sound *restricted* theory
- Let $T_1 \supseteq \mathrm{PA}$, φ a sentence
- **Reliable proof**: a triple (S, p_S, p_φ) s.t:
  - $S \supseteq T_1$
  - p_S: constructs some self-verifying $S' \supseteq S$
  - p_φ: S-proof of φ

DRAFT

Proof Completeness

- **Note:** still has incompletness!

DRAFT

Proof Completeness

- **Note:** still has incompletness!
  - Proofs are limited! (Not surprising)

DRAFT

Proof Completeness

- **Note:** still has incompletness!
  - Proofs are limited! (Not surprising)
  - Also: not a *single* theory suffices

DRAFT

Proof Completeness

- **Note:** still has incompletness!
  - Proofs are limited! (Not surprising)
  - Also: not a *single* theory suffices
  - But, a theories *can* be self-verifying!

DRAFT

Proof Completeness

- **Note:** still has incompletness!
  - Proofs are limited! (Not surprising)
  - Also: not a *single* theory suffices
  - But, a theories *can* be self-verifying!
- How to prove?
  - Basic idea: ZFC is self-verifying!
    - Again, same proof from Artëmov!
  - HUGE leap; how to generalize?
  - Answer: comprehension!

DRAFT

Crash Course: Recursive Ordinals

- Roughly: certain transitive sets ($x \in y \in z \Rightarrow x \in z$)

DRAFT

Crash Course: Recursive Ordinals

- Roughly: certain transitive sets ($x \in y \in z \Rightarrow x \in z$)
  - Contents can be enumerated by some program

DRAFT

Crash Course: Recursive Ordinals

- Roughly: certain transitive sets ($x \in y \in z \Rightarrow x \in z$)
  - Contents can be enumerated by some program
- Limit: **Church Kleene Ordinal** (ω_1^{CK})

DRAFT

Crash Course: Recursive Ordinals

- Roughly: certain transitive sets ($x \in y \in z \Rightarrow x \in z$)
  - Contents can be enumerated by some program
- Limit: **Church Kleene Ordinal** (ω_1^{CK})
- **Proof-theoretic ordinal:** measures theory strength
  - Important: this is recursive if T is RE *and* sound

DRAFT

Crash Course: Recursive Ordinals

- Roughly: certain transitive sets ($x \in y \in z \Rightarrow x \in z$)
  - Contents can be enumerated by some program
- Limit: **Church Kleene Ordinal** (ω_1^{CK})
- **Proof-theoretic ordinal:** measures theory strength
  - Important: this is recursive if T is RE *and* sound
  - Bounded below ω_1^{CK}!

DRAFT

Crash Course: Recursive Ordinals

- Roughly: certain transitive sets ($x \in y \in z \Rightarrow x \in z$)
  - Contents can be enumerated by some program
- Limit: **Church Kleene Ordinal** (ω_1^{CK})
- **Proof-theoretic ordinal:** measures theory strength
  - Important: this is recursive if T is RE *and* sound
  - Bounded below ω_1^{CK}!

DRAFT

Proof Completeness (con't)

- Need to construct comprehension
  - Use Simpson's comprehension axiom:

$$\exists X.\forall n.(n \in X \Leftrightarrow \Phi(n))$$

  - Φ: very complex formula (Δ^1_1)
- Let:
  - λ be limit of recursive $\beta_1, \beta_2, \ldots$
  - Each T_{β_i} self-verifying
  - $T' = \bigcup_{\beta<\lambda} T_\beta$
  - $\mathrm{Comp}_\lambda(\Delta^1_1) = \exists X_{\varphi,\lambda}.\forall n.(n \in X_{\varphi,\lambda} \Leftrightarrow \mathrm{PA} \vdash_{T'} \varphi(n))$
- Our construction: T_λ
  - ✓ Eventually reaches limit
  - ✓ Self-verifying
  - ✓ **Constructive**
- TL;DR: Artëmov + Simpson + Reliability = Proofs 💯

DRAFT

Agenda

Introduction

Language Overview

Syntax

Metatheory

Conclusion

DRAFT

Comparisons to Existing Solutions

- **Resource Description Framework:**
  - Similar ideas/terms about representations
  - Welkin:
    - Higher order terms
    - Better ogical reasoning
- **Labeled Property Graphs:**
  - Simple core idea + expressive
  - Welkin:
    - Formal definitions and grammar
    - Logical engine
- **Cyc:**
  - Similarly depend on contexts
  - Welkin:
    - Flexible data format

DRAFT

- Open specification

DRAFT

Future Work

DRAFT

Future Work

- Write the Standard

DRAFT

Future Work

- Write the Standard
- Create a Fast Implementation

DRAFT

Future Work

- Write the Standard
- Create a Fast Implementation
- Query Solvers

DRAFT

Future Work

- Write the Standard
- Create a Fast Implementation
- Query Solvers
- Revision System

DRAFT

Future Work

- Write the Standard
- Create a Fast Implementation
- Query Solvers
- Revision System
- Package Management

DRAFT

Future Work

- Write the Standard
- Create a Fast Implementation
- Query Solvers
- Revision System
- Package Management

DRAFT

Thank you!

Questions?

DRAFT