Planetary Gearhead GP 32 C Ø32 mm, 1.0 - 6.0 Nm, Ceramic Version Ceramic Version

Part number 166932



▶ Compare product

Add to wish list

Make a request

Price scales

Price per unit 1-4 CHF 140.20
5-19 CHF 100.60
20-49 CHF 91.70
from 50 On request

Prices excluding VAT

Gears can be purchased only as a component of a combination.

Start combination

Print specifications


Description

Enlarge image

Precision spur- and planetary gearheads matched to maxon motors. Gears are advantageously adapted directly to the desired motors in the delivery plant. The motor pinion is the input gearweel for the first stage and is rigidly affixed to the motor shaft.

Specifications

Technical illustrations



General information		
Gearhead type	GP	
Outer diameter	32 mm	
Version	С	
Gearhead Data		
Reduction	5.8 : 1	
Absolute reduction	23/4	
Max. motor shaft diameter	3 mm	
Number of stages	1	
Max. continuous torque	1 Nm	
Max. intermittent torque	1.25 Nm	

=		
80 %		
0.7 °		
1.5 gcm ²		
26.5 mm		
140 W		
180 W		
max. 0.14 mm, 5 mm from flange		
max. 0.4 mm		
140 N, 10 mm from flange		
120 N		
120 N		
8000 rpm		
8000 rpm		
-40+100 °C		
0		
Product		
110 g		

Downloads

▲ Catalog page

➤ Catalog pages (deutsch, PDF 498 KB) ➤ Catalog page (englisch, PDF 496 KB) ➤ カタログのページ (日本語, PDF 122 KB) Version 2014 Version 2014 Version 2014

▶ CAD-Files (STEP)

> CAD drawing (STEP) (ZIP 54 KB)

Version 2012