

Meltdown and Spectre Samples

Written in Assembly

U. Plonus
u.plonus@gmail.com

March 28, 2018

Copyright (C) 2018 U. Plonus.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Contents

1	Introduction	5
1.1	Overview	5
1.2	Conventions	5
1.2.1	Introduction	5
1.2.2	Data Sections	5
1.3	Nasm	5
2	Cache Access Timing	7
2.1	Introduction	7
2.2	Detect Cache Access Time	7
2.2.1	High Resolution Timer	7
2.2.2	Cache Access Time Routine	8
2.3	Measure Cache Access Time	8
2.3.1	Setup	8
2.3.2	Measure Time	10
2.4	Read Array via Cache Access Time	13
2.4.1	Introduction	13
2.4.2	Setup	13
2.4.3	Reading Bytes via Cache	14
2.4.4	Printing the Results	19
3	Signals	25
3.1	Basics	25
3.2	Detecting Signals	25
3.3	Handling Signals	25
4	Utilities	27
4.1	Introduction	27
4.2	Exit Program	27
4.3	Random Number Generator	28
4.4	Printing Strings	29
4.4.1	Printing Strings with Length	29
4.4.2	Printing C-Strings	29
4.5	Printing Numbers	31
4.5.1	Printing a Decimal 64bit Unsigned Integer	31
4.5.2	Printing a Hexadecimal 8bit Integer	34
A	Glossary	37

Contents

B	Acronyms	39
C	x86-Instructions	41
D	Code Chunks	43
E	License	45
E.1	GNU Free Documentation License	45
E.2	Code License	54
E.2.1	GNU GENERAL PUBLIC LICENSE	54
E.2.2	Code Chunk of GPL	68

1 Introduction

1.1 Overview

TBD

1.2 Conventions

1.2.1 Introduction

In this section we define some convention that are specific for this document.

1.2.2 Data Sections

The data is divided into three parts: read-only data, initialized data and uninitialized data. Code chunks with this type of data will all have defined suffices.

Definition 1 *Read-only data is data that is not modified during program execution. The suffix for read-only data is **-rodata**.*

Definition 2 *Initialized data is data that is changeable during program execution. The data is already initialized with data when the program starts. The suffix for initialized data is **-idata**.*

Definition 3 *Uninitialized data is data that is changeable during program execution. The data is not initialized. The suffix for uninitialized data is **-udata**.*

1.3 Nasm

TBD

5 `<preamble 5>≡` (12 24)
`bits 64`

`<license 68>`

```
global      _start
pagesize   equ 4096
```

Defines:

`_start`, used in chunks 9c and 13a.
`pagesize`, used in chunks 8, 9, 13, 14, 17–19, and 24.

2 Cache Access Timing

2.1 Introduction

TBD

2.2 Detect Cache Access Time

2.2.1 High Resolution Timer

First we need a high resolution timer to determine the cache access time. For this we use the time stamp counter. The time stamp counter is monotonically incrementing. When reading the time stamp counter (with `rdtsc`) the result is delivered back in the registers `EDX` and `EAX` forming a 64bit value. The time stamp counter is not an absolute value but a relative value, meaning that you cannot (easily) calculate from the time stamp counter to some time units (e.g. ns). But this is no problem as we only want to measure relative times.

To retrieve a 64bit value for the time we shift the value in `EDX` 32 bits to the left and add the value of `EAX` to this.

7 $\langle tsc-64bit \ 7 \rangle \equiv$ (8a)

```
rdtsc
shl    RDX,32
add    RAX,RDX
```

2.2.2 Cache Access Time Routine

Next we need a routine that calculates the cache access time for us.

First we have to ensure in this routine that the speculative execution of the processor does not interfere with our time measurement. For this we use the instruction `lfence` which ensures that all previous reads are done before executing the next instructions.

Next we access a memory location with the address `RDI` by loading this into `RCX` and measure the time before and after the access.

The command `lfence` before reading the time stamp counter is needed because we have to ensure that all reads before the time measurements are done.

At last we calculate the relative time needed to access the memory location. In theory we should see a difference whether the memory location is accessed before or not.

Parameters

`RDI` the address of the memory which is loaded either from the cache or from memory

```
8a  <calculate-cache-access-time 8a>≡ (12 24)
    _calccachetime:
        lfence
        <tsc-64bit 7>
        mov     R8,RAX
        mov     RCX,[RDI]
        lfence
        <tsc-64bit 7>
        sub     RAX,R8
        ret
```

Defines:

`_calccachetime`, used in chunks 10c, 11b, and 16.

2.3 Measure Cache Access Time

2.3.1 Setup

To measure the cache timing we create a standalone program that shows us the time for a cached and for an uncached memory access.

First we need some area in memory with data which we can later read from. This data area goes into the area `.bss` which contains uninitialized data. We align the data at a page boundary and reserve one pages for our data.

```
8b  <cache-data 8b>≡ (9b 24)
    data:          resb pagesize
```

Defines:

`data`, used in chunks 9–11, 13a, 14b, 18b, 23b, and 24.

Uses `pagesize` 5.

From time to time we need a small scratch area so we define an area with 32 bytes.

9a $\langle \text{scratch-udata } 9a \rangle \equiv$ (9b)
`scratch: resb 32`

Defines:

`scratch`, used in chunks 11, 20b, and 21.

9b $\langle \text{cachetiming-udata } 9b \rangle \equiv$ (12)
`align pagesize`
 $\langle \text{cache-data } 8b \rangle$
 $\langle \text{scratch-udata } 9a \rangle$

Uses `pagesize` 5.

The program begins with the label `_start`.

9c $\langle \text{cachetiming-program } 9c \rangle \equiv$ (12) 9d \triangleright
`_start:`

Uses `_start` 5.

Now we start with initialising the `data` area with some random data. For this we load RDI with the address of the `data` area.

9d $\langle \text{cachetiming-program } 9c \rangle + \equiv$ (12) $\langle 9c \ 9e \rangle$
`mov RDI, data`

Uses `data` 8b.

Next we load the number of bytes to fill into RSI. For this we load the `pagesize` into RSI.

9e $\langle \text{cachetiming-program } 9c \rangle + \equiv$ (12) $\langle 9d \ 9f \rangle$
`mov RSI, pagesize`

Uses `pagesize` 5.

At last we load EDX with some random seed. For this we use `rdtsc` and only use the lower 32 bit of the value.

9f $\langle \text{cachetiming-program } 9c \rangle + \equiv$ (12) $\langle 9e \ 9g \rangle$
`rdtsc`
`mov EDX, EAX`

Now we call `_xorshift` to fill the `data` area.

9g $\langle \text{cachetiming-program } 9c \rangle + \equiv$ (12) $\langle 9f \ 10a \rangle$
`call _xorshift`

Uses `_xorshift` 28a.

2.3.2 Measure Time

Now that we have setup our `data` area we can now cache data from the first page by loading it into a register which also loads this into the cache.

For this we load `RDI` with the address of the `data` area.

```
10a  <cachetiming-program 9c>+≡ (12) <9g 10b>
      mov      RDI,data
Uses data 8b.
```

Before we load the data into a register now we will clear the cache lines with the given address. For this we use the instruction `clflush`. After flushing the cache line we ensure (with `lfence`) that all reads from memory are finished before we load the data into a register again (and filling the cache).

```
10b  <cachetiming-program 9c>+≡ (12) <10a 10c>
      clflush   [RDI]
      lfence
      mov      RCX,[RDI]
```

Now we can determine the time that is needed to load this data once again. We do not need to load `RDI` again because it has not changed.

```
10c  <cachetiming-program 9c>+≡ (12) <10b 10f>
      call     _calccachetime
Uses _calccachetime 8a.
```

Now we have the relative cache access time in register `RAX`. We store this value to the stack and print out an explaining text.

For this we define the text to print.

```
10d  <cachetiming-rodata 10d>≡ (12) 11c>
      <common-rodata 10e>
      scached:      db "Cached Access Time: ",0x00
Defines:
      scached, used in chunk 10f.
```

Additionally we define some helper data, in this case `carriage return (CR)`.

```
10e  <common-rodata 10e>≡ (10d 19d)
      scr:           db 0x0a
Defines:
      scr, used in chunks 11 and 22.
```

Now we can print the text.

```
10f  <cachetiming-program 9c>+≡ (12) <10c 11a>
      push      RAX
      mov      RDI,scached
      call     _print
Uses _print 30a and scached 10d.
```

2.3 Measure Cache Access Time

Then we restore the value and print the measured time to `stdout`. At last we append a **CR** to the output.

11a `<cachetiming-program 9c>+≡` (12) <10f 11b>
 pop RDI
 mov RSI,scratch
 call _printdu64bit
 mov RSI,scr
 mov RDI,1
 call _nprint

Uses `_nprint 29b`, `_printdu64bit 31a`, `scr 10e`, and `scratch 9a`.

Now we do the same with an uncached value. The difference is that we do not load the value before.

11b `<cachetiming-program 9c>+≡` (12) <11a 11d>
 mov RDI,data
 clflush [RDI]
 lfence
 call _calccachetime

Uses `_calccachetime 8a` and `data 8b`.

Now we have the time of the uncached data access in `RAX` and can print it out with some explaining text.

11c `<cachetiming-rodata 10d>+≡` (12) <10d
 suncached: db "Uncached Access Time: ",0x00

Defines:

 suncached, used in chunk 11d.

11d `<cachetiming-program 9c>+≡` (12) <11b 11e>
 push RAX
 mov RDI,suncached
 call _print
 pop RDI
 mov RSI,scratch
 call _printdu64bit
 mov RSI,scr
 mov RDI,1
 call _nprint

Uses `_nprint 29b`, `_print 30a`, `_printdu64bit 31a`, `scr 10e`, `scratch 9a`, and `suncached 11c`.

At last we exit the program.

11e `<cachetiming-program 9c>+≡` (12) <11d
 <exitProgram 27b>

2 Cache Access Timing

Now we can put everything together and have our `cachetiming` program that we can now execute.

```
12  <cachetiming.asm 12>≡  
    <preamble 5>  
  
    section .rodata  
    <cachetiming-rodata 10d>  
  
    section .bss  
    <cachetiming-udata 9b>  
  
    section .text  
    <cachetiming-program 9c>  
  
    <calculate-cache-access-time 8a>  
  
    <xorshift-prng 28a>  
  
    <utilities 27a>
```

The program is placed in `asm/`. With `make` in the folder we can create an executable which is moved to `bin/`. There we can execute this program.

```
$ ./cachetiming
Cached Access Time: 72
Uncached Access Time: 372
$
```

2.4 Read Array via Cache Access Time

2.4.1 Introduction

Now that we have seen that we can determine if a value was in the cache or not (see [2.3 Measure Cache Access Time](#)) we will read a complete array of data by only measuring the cache access time.

2.4.2 Setup

For this we start with some `data` area that we can read later as defined before.

So start with the program and fill the `data` area with some random data (similar to the chunks [9c](#), [9d](#), [9e](#), [9f](#) and [9g](#)).

```
13a <cacheread-program 13a>≡ (24) 14a>
    _start:
        mov     RDI,data
        mov     RSI,pagesize
        rdtsc
        mov     EDX,EAX
        call    _xorshift
```

Uses `_start 5`, `_xorshift 28a`, `data 8b`, and `pagesize 5`.

Next we will create a probe area that is $256 * \text{pagesize}$. We only access the first byte of each page but we divide the data over such a large area (1 MiB) to ensure that the cache lines that we use do not interfere each other.

```
13b <cacheread-udata 13b>≡ (24) 17b>
    probe:      times 256 resb pagesize
```

Defines:

`probe`, used in chunks [14](#) and [18](#).

Uses `pagesize 5`.

2 Cache Access Timing

Next we fill this area also with some random data.

```
14a  <cacheread-program 13a>+≡ (24) <13a 19c>
      mov     RDI,probe
      mov     RAX,pagesize
      mov     RCX,256
      mul     RCX
      mov     RSI,RCX
      rdtsc
      mov     EDX,EAX
      call    _xorshift
```

Uses `_xorshift` 28a, `pagesize` 5, and `probe` 13b.

2.4.3 Reading Bytes via Cache

As we saw we can determine if a memory datum is in cache or not. For reading a complete byte we have to do a little bit more. Basically we use the byte accessed to index a different `probe` area. Because the memory is not cached byte by byte but in so called cache lines we cannot use a simple 256 bytes sized probe array but must at least have a space between the accessed bytes that is larger than a cache line size. This is the reason why we use a probe array of $256 * \text{pagesize}$ bytes of size.

Basically we use the following code to access the data. We load the content of the address we want to probe into a register. Then we multiply the register with some arbitrary value (we use `pagesize`) and then access the probe area with the calculated offset. We can then test the cache which page was cached and have our value from the `data`.

```
14b  <cacheread-sample 14b>≡
      mov     RAX,[data]
      mul     RAX,pagesize
      mov     RBX,[probe+RAX]
```

Uses `data` 8b, `pagesize` 5, and `probe` 13b.

First we write a subroutine to clear the cache lines from data from our `probe` area. We assume that we use 256 values ($0 \dots 255$) for the indexing into the probe array. Also the `probe` area must be at least $256 * RSI$ bytes in size.

Parameters

RDI the address of the probe array

RSI the interval between the probe addresses used

15 $\langle \text{clear-cache 15} \rangle \equiv$ (24)
 `_clearcache:`
 `cld`
 `mov RCX,256`
 `xor RAX,RAX`
 `.clear_next:`
 `clflush [RDI+RAX]`
 `add RAX,RSI`
 `loop .clear_next`
 `lfence`
 `ret`

Defines:

`_clearcache`, used in chunk 18a.

2 Cache Access Timing

Next we need a subroutine that determines the cache line access times for the data in the `probe` area. So we create a subroutine that loops similar to the `_clearcache` subroutine over all addresses and measures the cache access time for each page.

Parameters

RDI the address of the probe array

RSI the interval between the probe addresses used

RDX the address of the results of the cache measurements. The area needs to be 256 * 8 bytes in size

16 $\langle \text{detect-cache-area-time } 16 \rangle \equiv$ (24)

```
_calcareacachetime:
    xor     RCX,RCX
.next_timing:
    push    RCX
    push    RDX
    push    RDI
    push    RSI
    call    _calccachetime
    pop     RSI
    pop     RDI
    pop     RDX
    pop     RCX
    mov     [RDX+8*RCX],RAX
    add     RDI,RSI
    inc     RCX
    cmp     RCX,256
    jb     .next_timing
    ret
```

Defines:

`_calcareacachetime`, used in chunk 17a.

Uses `_calccachetime` 8a.

We now can determine the cache line with the lowest access time. This is the cache line that was cached before.

Parameters

RDI the address of the probe array

RSI the interval between the probe addresses used

RDX the address of the results of the cache measurements. The area needs to be 256 * 8 bytes in size

Return

RAX the byte (in AL) which is found by cache timing analysis

TBD

17a $\langle detect\text{-}byte\ 17a \rangle \equiv$ (24)

```

_detectbytebycl:
    push    RDI
    call    _calcareacachetime
    pop     RDI
    mov     RSI, RDX
    xor     RCX, RCX
    mov     R8, 0xffffffffffffffff
    xor     R9, R9
.nextbyte:
    mov     RAX, [RDI+8*RCX]
    cmp     RAX, R8
    jb      .foundbyte
    inc     RCX
    cmp     RCX, 256
    jae     .done
.foundbyte:
    mov     R8, RAX
    mov     R9, RCX
    jmp     .nextbyte
.done:
    mov     RAX, R9
    ret

```

Uses `_calcareacachetime` 16.

Now we need some area to store all the data. Once we use an area for the timing data and another area for the read memory data.

17b $\langle cacheread\text{-}udata\ 13b \rangle + \equiv$ (24) <13b 20b>

```

    result:    resb    pagesize
    timing:    resq    256

```

Uses `pagesize` 5.

Now we have the base for reading a complete memory area via a cache covert channel.

We now create a subroutine to loop over the memory we want to read and read the values back via the cache access time.

First we create a area where we can store the read bytes.

17c $\langle readback\text{-}udata\ 17c \rangle \equiv$ (24)

```

    readback:    align    pagesize, resb    pagesize

```

Defines:

`readback`, used in chunk 23b.

Uses `pagesize` 5.

2 Cache Access Timing

Now we create the subroutine that reads the bytes from the source array `data` and writes the results from the cache access time into `readback`.

First we setup a counter in `R8` and clear the cache.

18a $\langle \text{cache-readback } 18a \rangle \equiv$ (24) 18b \triangleright

```
_cachereadback:
    xor     R8,R8
.nextbyte:
    push    R8
    mov     RDI,probe
    mov     RSI,pagesize
    call    _clearcache
    pop     R8
```

Defines:

`_cachereadback`, used in chunk 19c.

Uses `_clearcache` 15, `pagesize` 5, and `probe` 13b.

Next we read in the data from the array.

18b $\langle \text{cache-readback } 18a \rangle + \equiv$ (24) $\triangleleft 18a \ 18c \triangleright$

```
mov     RSI,data
xor     RAX,RAX
mov     AL,[RSI+R8]
```

Uses `data` 8b.

Next we use the read byte to index into our probe array.

18c $\langle \text{cache-readback } 18a \rangle + \equiv$ (24) $\triangleleft 18b \ 18d \triangleright$

```
mov     RDX,pagesize
mul     RDX
mov     RSI,probe
mov     AL,[RSI+RAX]
```

Uses `pagesize` 5 and `probe` 13b.

Now we have put data into the cache that depends on the value read from `data`. Next we will read the cache access times to determine the data read.

18d $\langle \text{cache-readback } 18a \rangle + \equiv$ (24) $\triangleleft 18c \ 19a \triangleright$

```
mov     RDI,probe
mov     RSI,pagesize
mov     RDX,timing
push    R8
call    _detectbytebycl
pop     R8
```

Uses `pagesize` 5 and `probe` 13b.

Next we store the read byte into our result array.

```
19a  <cache-readback 18a>+≡ (24) <18d 19b>
      mov     RDI,result
      mov     [RDI+R8],AL
```

Now we can increment our counter and check if there are more bytes to read. If no more bytes need to be read we leave our subroutine.

```
19b  <cache-readback 18a>+≡ (24) <19a
      inc     R8
      cmp     R8,pagesize
      jb     .nextbyte
      ret
```

Uses `pagesize` 5.

After all we can now call this new subroutine and read our data by detecting the cache access times.

```
19c  <cacheread-program 13a>+≡ (24) <14a 23b>
      call    _cachereadback
```

Uses `_cachereadback` 18a.

2.4.4 Printing the Results

Now we want to see the results so we now read a byte from the origin (`data`) and from our read back data (`readback`).

First we define some helpful data for colorizing the output.

```
19d  <cacheread-rodata 19d>≡ (24)
      <common-rodata 10e>
      sbgred:      db 0x1b,"[1;41m",0x00
      sresetstyle: db 0x1b,"[0m",0x00
      sseparator:  db "- ",0x00
      sblank:      db " "
```

Defines:

`sbgred`, never used.

`sresetstyle`, never used.

`sseparator`, used in chunk 22.

2 Cache Access Timing

First we define a subroutine which prints out up to 16 bytes each side by side on the screen. If two bytes in the arrays are different then the value at the right side (from the second array) will be printed with read background.

Parameters

RDI the address of the first array

RSI the address of the second array

RDX number of bytes to print (up to 16). If the value is above 16 then nothing is printed out

20a $\langle \textit{print-comparision16 } 20a \rangle \equiv$ (24) 20c▷
 `_printcompare16:`

Defines:

`_printcompare16`, used in chunk 23a.

 Additionally we need some scratch area for the printing.

20b $\langle \textit{cacheread-udata } 13b \rangle + \equiv$ (24) <17b
 `scratch: resb 64`

 Uses `scratch 9a`.

 At the start of the subroutine we prepare a stack frame for further operations as we will need to save and restore the registers RDI, RSI, RDX and RCX multiple times

20c $\langle \textit{print-comparision16 } 20a \rangle + \equiv$ (24) <20a 20d▷
 `push RBP`
 `mov RBP,RSP`
 `sub RSP,32`
 `mov [RBP-8],RDI`
 `mov [RBP-16],RSI`
 `mov [RBP-24],RDX`

 Now we first start and check that no more than 16 bytes should be printed, otherwise we will end the subroutine immediately.

20d $\langle \textit{print-comparision16 } 20a \rangle + \equiv$ (24) <20c 21▷
 `cmp RDX,0x10`
 `ja .done`

Next we can start and handle the "left" side of the output. We output up to 16 bytes and then continue at `.leftbytesdone` (22).

```

21  <print-comparison16 20a>+≡ (24) <20d 22>
    xor     RCX,RCX
    .nextbyteleft:
    cmp     RCX,RDX
    ja      .leftbytesdone
    mov     [RBP-32],RCX
    mov     DI,[RDI+RCX]
    mov     RSI,scratch
    call    _printh8bit
    mov     RDI,1
    mov     RSI,sblank
    call    _nprint
    mov     RDI,[RBP-8]
    mov     RDX,[RBP-24]
    mov     RCX,[RBP-32]
    inc     RCX
    jmp     .nextbyteleft

```

Uses `_nprint` 29b, `_printh8bit` 34a, and `scratch` 9a.

22 $\langle \text{print-comparison16 } 20a \rangle + \equiv$ (24) $\triangleleft 21$

```

.leftbytesdone:
    cmp     RCX,0x10
    jae     .leftdone
    inc     RCX
    jmp     .leftbytesdone
.leftdone:
    mov     RDI,sseparator
    call    _print
    mov     RDX,[RBP-24]
    xor     RCX,RCX
.nextbyteright:
    cmp     RCX,RDX
    ja      .rightbytesdone
    inc     RCX
    jmp     .nextbyteright
.rightbytesdone:
    cmp     RCX,0x10
    jae     .rightdone
    inc     RCX
    jmp     .rightbytesdone
.rightdone:
.done:
    mov     RDI,1
    mov     RSI,scr
    call    _nprint
    mov     RSP,RBP
    pop     RBP
    ret

```

Uses `_nprint` 29b, `_print` 30a, `scr` 10e, and `sseparator` 19d.

TBD

Parameters

RDI the address of the first array

RSI the address of the second array

RDX number of bytes to print. In each line 16 bytes from the first and 16 bytes from the right side are printed

23a $\langle \textit{print-comparision } 23a \rangle \equiv$ (24)

```

    _printcompare:
        call    _printcompare16
        ret

```

Defines:

_printcompare, used in chunk 23b.

Uses _printcompare16 20a.

TBD

23b $\langle \textit{cacheread-program } 13a \rangle + \equiv$ (24) <19c

```

    mov     RDI,data
    mov     RSI,readback
    mov     RDX,16
    call    _printcompare

```

Uses _printcompare 23a, data 8b, and readback 17c.

2 Cache Access Timing

24 $\langle \text{cacheread.asm } 24 \rangle \equiv$
 $\langle \text{preamble } 5 \rangle$

```
section .bss
    align      pagesize
 $\langle \text{cache-data } 8b \rangle$ 
 $\langle \text{cacheread-udata } 13b \rangle$ 
 $\langle \text{readback-udata } 17c \rangle$ 

section .data
 $\langle \text{cacheread-rodata } 19d \rangle$ 

section .text
 $\langle \text{cacheread-program } 13a \rangle$ 

 $\langle \text{exitProgram } 27b \rangle$ 

 $\langle \text{print-comparision } 23a \rangle$ 

 $\langle \text{print-comparision16 } 20a \rangle$ 

 $\langle \text{cache-readback } 18a \rangle$ 

 $\langle \text{clear-cache } 15 \rangle$ 

 $\langle \text{calculate-cache-access-time } 8a \rangle$ 

 $\langle \text{detect-cache-area-time } 16 \rangle$ 

 $\langle \text{detect-byte } 17a \rangle$ 

 $\langle \text{xorshift-prng } 28a \rangle$ 

 $\langle \text{utilities } 27a \rangle$ 
Uses data 8b and pagesize 5.
```


3 Signals

3.1 Basics

TBD

3.2 Detecting Signals

TBD

3.3 Handling Signals

TBD

4 Utilities

4.1 Introduction

TBD

27a $\langle utilities\ 27a \rangle \equiv$ (12 24)
 $\langle nprint\ 29b \rangle$

 $\langle print\ 30a \rangle$

 $\langle printdu64bit\ 31a \rangle$

 $\langle printh8bit\ 34a \rangle$

4.2 Exit Program

TBD

27b $\langle exitProgram\ 27b \rangle \equiv$ (11e 24)
 xor RDI,RDI
 mov RAX,60
 syscall

4.3 Random Number Generator

To initialize the data a [random number generator \(RNG\)](#) is used. The sample programs use [xorshift](#)¹ as [RNG](#).

First we clear the direction flag to ensure that we are incrementing the data pointer RDI.

Next we move the number of values to be generated to RCX (which is a counter in [x86](#) processors) and divide it by 4 (because we use a 32bit [RNG](#)). Additionally we move the seed to EAX.

Parameters

RDI	the address of the memory which is to be filled with random numbers
RSI	the number of bytes that are filled with random numbers. This must be a multiple of 4
EDX	the seed of the RNG

28a $\langle \text{xorshift-prng } 28a \rangle \equiv$ (12 24) 28b \triangleright

```

_xorshift:
    cld
    mov     RCX,RSI
    shr     RCX,2
    mov     EAX,EDX

```

Defines:

`_xorshift`, used in chunks 9g, 13a, and 14a.

Now we can generate the next 32bit random number.

28b $\langle \text{xorshift-prng } 28a \rangle + \equiv$ (12 24) $\triangleleft 28a \ 29a \triangleright$

```

.next_random:
    mov     EBX,EAX
    shl     EAX,13
    xor     EAX,EBX
    mov     EBX,EAX
    shr     EAX,17
    xor     EAX,EBX
    mov     EBX,EAX
    shl     EAX,5
    xor     EAX,EBX

```

¹<https://en.wikipedia.org/wiki/Xorshift>

Because we want to generate multiple random numbers we store the value of `EAX` to `[RDI]` and loop for the next random number.

29a `<xorshift-prng 28a>+≡` (12 24) <28b

```

    stosd
    loop    .next_random
    ret

```

4.4 Printing Strings

4.4.1 Printing Strings with Length

The routine `_nprint` prints a string with the given length to `stdout`.

We move the number of bytes to print to `RDX` which is the 3rd parameter to the systemcall. Next we move the address of the bytes to print to `RSI` which is the 2nd parameter to the systemcall. The 1st argument (in `RDI`) to the systemcall is the file descriptor (1 is `stdout`). Additionally the number of the systemcall (1) is passed in `RAX`. The systemcall (`syscall`) now prints `RDX` bytes from `[RSI]` to the file descriptor `RDI`.

At the end we return to the caller.

Parameters

`RDI` the number of bytes to print to `stdout`

`RSI` the address to the bytes to print to `stdout`

29b `<nprint 29b>≡` (27a)

```

_nprint:
    mov     RDX,RDI
    mov     RDI,1
    mov     RAX,1
    syscall
    ret

```

Defines:

`_nprint`, used in chunks 11, 21, 22, 30d, 33b, and 34c.

4.4.2 Printing C-Strings

The routine `_print` prints a null-terminated string to `stdout`.

First we clear the direction flag to increment the address in `RDI` while scanning the data.

Next we start with clearing `AL` (setting it to null) and saving the address of the string to `RSI`. We're using `RSI` because we later need the address to calculate the length of the string.

Parameters

RDI the address to the null-terminated bytes to print to **stdout**

30a $\langle \textit{print 30a} \rangle \equiv$ (27a) 30b \triangleright
 `_print:`
 `cld`
 `xor` `AL,AL`
 `mov` `RSI,RDI`

Defines:

`_print`, used in chunks 10f, 11d, and 22.

Next we search for the terminating **null** (`'\0'`) character. For this we use the instruction **scasb** (scan string byte) which compares the byte at the address `[RDI]` with the value in `AL` and sets the flags accordingly. When the byte at `[RDI]` is not the value of `AL` the next instruction (**jne**) jumps to the given label (`.next_char` in this case).

scasb additionally increments **RDI** so that we go through the string until `'\0'` is found.

30b $\langle \textit{print 30a} \rangle + \equiv$ (27a) \triangleleft 30a 30c \triangleright
 `.next_char:`
 `scasb`
 `jne` `.next_char`

After we have found the string termination we calculate the number of bytes that the string has. In **RSI** we now have the starting address of the bytes to print and in **RDI** we have the end address of the bytes to print. After that we calculate the number of bytes to print.

30c $\langle \textit{print 30a} \rangle + \equiv$ (27a) \triangleleft 30b 30d \triangleright
 `sub` `RDI,RSI`

Now we have the address of the string in **RDI** and the length of the string in **RSI** which are the 1st and 2nd argument in the call of `_nprint`.

30d $\langle \textit{print 30a} \rangle + \equiv$ (27a) \triangleleft 30c
 `call` `_nprint`
 `ret`

Uses `_nprint` 29b.

4.5 Printing Numbers

4.5.1 Printing a Decimal 64bit Unsigned Integer

The routine `_printdu64bit` prints a given 64bit integer as unsigned decimal number to `stdout`.

To print a decimal number we have to divide the number by 10 and get the remainder for printing (from right to left). For this we move the divisor to a register and the dividend to `RAX`. We have to use `RAX` because this is the only register we can use for division.

Additionally we need the address of the scratch area in `RDI` for storing the result. We also save the address of the scratch area to `R8` for later use.

To increment the address during the processing we clear the direction flag.

Parameters

`RDI` the number number to print to `stdout`

`RSI` the address of a scratch area with a size of at least 20 bytes

```

31a  <printdu64bit 31a>≡ (27a) 31b>
    _printdu64bit:
        mov     RAX,RDI
        mov     RDI,RSI
        mov     R8,RDI
        mov     RCX,10
        cld

```

Defines:

`_printdu64bit`, used in chunk 11.

Now we define a label to jump back when we see that there are still more digits to print. Then we test `RAX` for 0 and end the processing of the digits.

```

31b  <printdu64bit 31a>+≡ (27a) <31a 31c>
    .next:
        cmp     RAX,0
        je      .done

```

Next we divide `RAX` by `RCX`. For this we have to clear `RDX` because this is the higher value of the dividend. The result is then placed into `RAX` and the remainder into `RDX`.

```

31c  <printdu64bit 31a>+≡ (27a) <31b 32a>
        xor     RDX,RDX
        div     RCX

```

4 Utilities

We now exchange the result and the remainder because we now need the remainder in RAX (or AL) for further processing. Now we can add the [ASCII](#) character '0' to AL and have the correct [ASCII](#) value in AL. Now we can store the [ASCII](#) character to the scratch area.

```
32a  <printdu64bit 31a>+≡ (27a) <31c 32b>
      xchg      RDX,RAX
      add       AL,'0'
      stosb
```

Now we restore RAX (which we saved to RDX) to go into the next round.

```
32b  <printdu64bit 31a>+≡ (27a) <32a 32c>
      mov       RAX,RDX
      jmp       .next
```

Now that we have all the numbers as [ASCII](#) characters we are nearly done. We now have to reverse the number in memory because the number saved at the lowest address is the digit with the least significance.

We now start with checking if we have written any character. If not then we write the [ASCII](#) character '0' into the memory. We use the instruction `stosb` for this to adjust the address in RDI at the same time.

```
32c  <printdu64bit 31a>+≡ (27a) <32b 32d>
      .done:
      cmp       RDI,RSI
      jne       .printout
      mov       AL,'0'
      stosb
      .printout:
```

Next we calculate the number of digits that the number has. For this we move the address of the last digit to RDX and subtract the start of the scratch area from this. Next we adjust RDI because it points to the first address after the number.

```
32d  <printdu64bit 31a>+≡ (27a) <32c 33a>
      mov       RDX,RDI
      sub       RDX,RSI
      dec       RDI
```


We now have `RSI` with the address of the start of the number and `RDI` with the address of the end. We now have to exchange the digits from the front and the end to get the right number. For this we increment `RSI` and decrement `RDI` after each exchange and when the addresses pass each other we are done.

```
33a  <printdu64bit 31a>+≡ (27a) <32d 33b>
      .reverse:
      mov     AL,[RSI]
      mov     AH,[RDI]
      mov     [RSI],AH
      mov     [RDI],AL
      dec     RDI
      inc     RSI
      cmp     RSI,RDI
      jb      .reverse
```

Now we restore the address of the scratch area to `RSI` and move the number of digits (which we stored in `RDY`) to `RDI` and can the call `_nprint` to print the number.

```
33b  <printdu64bit 31a>+≡ (27a) <33a
      mov     RSI,R8
      mov     RDI,RDX
      call    _nprint
      ret
```

Uses `_nprint` 29b.

4.5.2 Printing a Hexadecimal 8bit Integer

The routine `_printh8bit` prints a given 8bit integer as hexadecimal number to `stdout`.

To print a hexadecimal number we mask a nibble (4bit) and have the number to print.

First we clear the register `RAX` and move the number to `AX` for further processing and clear the higher 8bit (`AH`). Additionally we move it to `R8` for later restore.

Additionally we need the address of the scratch area in `RDI` for storing the result.

To increment the address during the processing we clear the direction flag.

Parameters

`DI` the number number to print to `stdout`. Only the lower 8bit are used.

`RSI` the address of a scratch area with a size of at least 2 bytes

```

34a  <printh8bit 34a>≡ (27a) 34b>
      _printh8bit:
          xor     RAX,RAX
          mov     AX,DI
          xor     AH,AH
          mov     R8,RAX
          mov     RDI,RSI
          cld

```

Defines:

`_printh8bit`, used in chunk 21.

Now we mask the higher 4 bit of `AL` by shifting it 4 bits to the right and mask out all but the lower 4 bit. Next we call the internal method `printh8bit.printh4bit` to print out this nibble.

```

34b  <printh8bit 34a>+= (27a) <34a 34c>
          shr     AL,4
          and     AL,0x0f
          call    .printh4bit

```

Next we restore the number and print out the lower 4 bits.

```

34c  <printh8bit 34a>+= (27a) <34b
          mov     RAX,R8
          and     AL,0x0f
          call    .printh4bit
          mov     RDI,2
          call    _nprint
          ret
      <printh8bit.printh4bit 35a>

```

Uses `_nprint` 29b.

Now we define the internal method to print a hexadecimal digit.

First we test if the digit is above or equal to 10. In this case we have to print out a character between 'a' and 'f' else we print out a decimal digit (between '0' and '9').

Parameters (internal)

AL the lower 4 bit contain the hexadecimal digit print to `stdout`

RDI the address of a scratch area

```
35a  <printh8bit.printh4bit 35a>≡ (34c) 35b>
      .printh4bit:
          cmp     AL,10
          jae     .printa2f
```

Defines:

`printh8bit.printh4bit`, never used.

Now we add '0' to get the code for the digit between '0' and '9'.

```
35b  <printh8bit.printh4bit 35a>+≡ (34c) <35a 35c>
      add     AL,'0'
      jmp     .printout
```

Else we print a digit between 'a' and 'f'. We first subtract 10 because the value in AL is now between 10 and 15.

```
35c  <printh8bit.printh4bit 35a>+≡ (34c) <35b 35d>
      .printa2f:
          sub     AL,10
          add     AL,'a'
```

Now we store the character into the storage area.

```
35d  <printh8bit.printh4bit 35a>+≡ (34c) <35c
      .printout:
          stosb
          ret
```


A Glossary

x86 x86 denotes a microprocessor architecture based on the 8086/8088 [28](#)

B Acronyms

ASCII American Standard Code for Information Interchange [32](#)

CR carriage return [10](#), [11](#)

RNG random number generator [28](#)

C x86-Instructions

`clflush` Flush Cache Line, introduced with Intel® Pentium® 4 [10](#)

`lfence` Load Fence, introduced with Intel® Pentium® 4 [8](#), [10](#)

`rdtsc` Read Time Stamp Counter, introduced with Intel® Pentium® [7](#), [9](#)

D Code Chunks

<cache-data 8b>
<cache-readback 18a>
<cacheread-program 13a>
<cacheread-rodata 19d>
<cacheread-sample 14b>
<cacheread-udata 13b>
<cacheread.asm 24>
<cachetiming-program 9c>
<cachetiming-rodata 10d>
<cachetiming-udata 9b>
<cachetiming.asm 12>
<calculate-cache-access-time 8a>
<clear-cache 15>
<common-rodata 10e>
<detect-byte 17a>
<detect-cache-area-time 16>
<exitProgram 27b>
<license 68>
<nprint 29b>
<preamble 5>
<print 30a>
<print-comparision 23a>
<print-comparision16 20a>
<printdu64bit 31a>
<printh8bit 34a>
<printh8bit.printh4bit 35a>
<readback-udata 17c>
<scratch-udata 9a>
<tsc-64bit 7>
<utilities 27a>
<xorshift-prng 28a>

E License

E.1 GNU Free Documentation License

This license applies to this documentation as a whole.

GNU Free Documentation License
Version 1.3, 3 November 2008

Copyright (C) 2000, 2001, 2002, 2007, 2008 Free Software Foundation, Inc.
<<https://fsf.org/>>

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a

E License

world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain

ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

The "publisher" means any person or entity that distributes copies of the Document to the public.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

E License

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements",

and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the

E License

Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, or distribute it is void, and will automatically terminate your rights under this License.

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, receipt of a copy of some or all of the same material does not give you any rights to use it.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <https://www.gnu.org/licenses/>.

Each version of the License is given a distinguishing version number.

E.1 GNU Free Documentation License

If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation. If the Document specifies that a proxy can decide which future versions of this License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Document.

11. RELICENSING

"Massive Multiauthor Collaboration Site" (or "MMC Site") means any World Wide Web server that publishes copyrightable works and also provides prominent facilities for anybody to edit those works. A public wiki that anybody can edit is an example of such a server. A "Massive Multiauthor Collaboration" (or "MMC") contained in the site means any set of copyrightable works thus published on the MMC site.

"CC-BY-SA" means the Creative Commons Attribution-Share Alike 3.0 license published by Creative Commons Corporation, a not-for-profit corporation with a principal place of business in San Francisco, California, as well as future copyleft versions of that license published by that same organization.

"Incorporate" means to publish or republish a Document, in whole or in part, as part of another Document.

An MMC is "eligible for relicensing" if it is licensed under this License, and if all works that were first published under this License somewhere other than this MMC, and subsequently incorporated in whole or in part into the MMC, (1) had no cover texts or invariant sections, and (2) were thus incorporated prior to November 1, 2008.

The operator of an MMC Site may republish an MMC contained in the site under CC-BY-SA on the same site at any time before August 1, 2009, provided the MMC is eligible for relicensing.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright (c) YEAR YOUR NAME.

Permission is granted to copy, distribute and/or modify this document

E License

under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with...Texts." line with this:

with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

E.2 Code License

E.2.1 GNU GENERAL PUBLIC LICENSE

This license applies to all program code generated from this document.

GNU GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<http://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The GNU General Public License is a free, copyleft license for software and other kinds of works.

The licenses for most software and other practical works are designed to take away your freedom to share and change the works. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change all versions of a program--to make sure it remains free software for all its users. We, the Free Software Foundation, use the GNU General Public License for most of our software; it applies also to any other work released this way by its authors. You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not

price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for them if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs, and that you know you can do these things.

To protect your rights, we need to prevent others from denying you these rights or asking you to surrender the rights. Therefore, you have certain responsibilities if you distribute copies of the software, or if you modify it: responsibilities to respect the freedom of others.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must pass on to the recipients the same freedoms that you received. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

Developers that use the GNU GPL protect your rights with two steps: (1) assert copyright on the software, and (2) offer you this License giving you legal permission to copy, distribute and/or modify it.

For the developers' and authors' protection, the GPL clearly explains that there is no warranty for this free software. For both users' and authors' sake, the GPL requires that modified versions be marked as changed, so that their problems will not be attributed erroneously to authors of previous versions.

Some devices are designed to deny users access to install or run modified versions of the software inside them, although the manufacturer can do so. This is fundamentally incompatible with the aim of protecting users' freedom to change the software. The systematic pattern of such abuse occurs in the area of products for individuals to use, which is precisely where it is most unacceptable. Therefore, we have designed this version of the GPL to prohibit the practice for those products. If such problems arise substantially in other domains, we stand ready to extend this provision to those domains in future versions of the GPL, as needed to protect the freedom of users.

Finally, every program is threatened constantly by software patents. States should not allow patents to restrict development and use of software on general-purpose computers, but in those that do, we wish to avoid the special danger that patents applied to a free program could make it effectively proprietary. To prevent this, the GPL assures that patents cannot be used to render the program non-free.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS

E License

0. Definitions.

"This License" refers to version 3 of the GNU General Public License.

"Copyright" also means copyright-like laws that apply to other kinds of works, such as semiconductor masks.

"The Program" refers to any copyrightable work licensed under this License. Each licensee is addressed as "you". "Licensees" and "recipients" may be individuals or organizations.

To "modify" a work means to copy from or adapt all or part of the work in a fashion requiring copyright permission, other than the making of an exact copy. The resulting work is called a "modified version" of the earlier work or a work "based on" the earlier work.

A "covered work" means either the unmodified Program or a work based on the Program.

To "propagate" a work means to do anything with it that, without permission, would make you directly or secondarily liable for infringement under applicable copyright law, except executing it on a computer or modifying a private copy. Propagation includes copying, distribution (with or without modification), making available to the public, and in some countries other activities as well.

To "convey" a work means any kind of propagation that enables other parties to make or receive copies. Mere interaction with a user through a computer network, with no transfer of a copy, is not conveying.

An interactive user interface displays "Appropriate Legal Notices" to the extent that it includes a convenient and prominently visible feature that (1) displays an appropriate copyright notice, and (2) tells the user that there is no warranty for the work (except to the extent that warranties are provided), that licensees may convey the work under this License, and how to view a copy of this License. If the interface presents a list of user commands or options, such as a menu, a prominent item in the list meets this criterion.

1. Source Code.

The "source code" for a work means the preferred form of the work for making modifications to it. "Object code" means any non-source form of a work.

A "Standard Interface" means an interface that either is an official standard defined by a recognized standards body, or, in the case of interfaces specified for a particular programming language, one that

is widely used among developers working in that language.

The "System Libraries" of an executable work include anything, other than the work as a whole, that (a) is included in the normal form of packaging a Major Component, but which is not part of that Major Component, and (b) serves only to enable use of the work with that Major Component, or to implement a Standard Interface for which an implementation is available to the public in source code form. A "Major Component", in this context, means a major essential component (kernel, window system, and so on) of the specific operating system (if any) on which the executable work runs, or a compiler used to produce the work, or an object code interpreter used to run it.

The "Corresponding Source" for a work in object code form means all the source code needed to generate, install, and (for an executable work) run the object code and to modify the work, including scripts to control those activities. However, it does not include the work's System Libraries, or general-purpose tools or generally available free programs which are used unmodified in performing those activities but which are not part of the work. For example, Corresponding Source includes interface definition files associated with source files for the work, and the source code for shared libraries and dynamically linked subprograms that the work is specifically designed to require, such as by intimate data communication or control flow between those subprograms and other parts of the work.

The Corresponding Source need not include anything that users can regenerate automatically from other parts of the Corresponding Source.

The Corresponding Source for a work in source code form is that same work.

2. Basic Permissions.

All rights granted under this License are granted for the term of copyright on the Program, and are irrevocable provided the stated conditions are met. This License explicitly affirms your unlimited permission to run the unmodified Program. The output from running a covered work is covered by this License only if the output, given its content, constitutes a covered work. This License acknowledges your rights of fair use or other equivalent, as provided by copyright law.

You may make, run and propagate covered works that you do not convey, without conditions so long as your license otherwise remains in force. You may convey covered works to others for the sole purpose of having them make modifications exclusively for you, or provide you with facilities for running those works, provided that you comply with the terms of this License in conveying all material for which you do

E License

not control copyright. Those thus making or running the covered works for you must do so exclusively on your behalf, under your direction and control, on terms that prohibit them from making any copies of your copyrighted material outside their relationship with you.

Conveying under any other circumstances is permitted solely under the conditions stated below. Sublicensing is not allowed; section 10 makes it unnecessary.

3. Protecting Users' Legal Rights From Anti-Circumvention Law.

No covered work shall be deemed part of an effective technological measure under any applicable law fulfilling obligations under article 11 of the WIPO copyright treaty adopted on 20 December 1996, or similar laws prohibiting or restricting circumvention of such measures.

When you convey a covered work, you waive any legal power to forbid circumvention of technological measures to the extent such circumvention is effected by exercising rights under this License with respect to the covered work, and you disclaim any intention to limit operation or modification of the work as a means of enforcing, against the work's users, your or third parties' legal rights to forbid circumvention of technological measures.

4. Conveying Verbatim Copies.

You may convey verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice; keep intact all notices stating that this License and any non-permissive terms added in accord with section 7 apply to the code; keep intact all notices of the absence of any warranty; and give all recipients a copy of this License along with the Program.

You may charge any price or no price for each copy that you convey, and you may offer support or warranty protection for a fee.

5. Conveying Modified Source Versions.

You may convey a work based on the Program, or the modifications to produce it from the Program, in the form of source code under the terms of section 4, provided that you also meet all of these conditions:

- a) The work must carry prominent notices stating that you modified it, and giving a relevant date.
- b) The work must carry prominent notices stating that it is released under this License and any conditions added under section

7. This requirement modifies the requirement in section 4 to "keep intact all notices".

c) You must license the entire work, as a whole, under this License to anyone who comes into possession of a copy. This License will therefore apply, along with any applicable section 7 additional terms, to the whole of the work, and all its parts, regardless of how they are packaged. This License gives no permission to license the work in any other way, but it does not invalidate such permission if you have separately received it.

d) If the work has interactive user interfaces, each must display Appropriate Legal Notices; however, if the Program has interactive interfaces that do not display Appropriate Legal Notices, your work need not make them do so.

A compilation of a covered work with other separate and independent works, which are not by their nature extensions of the covered work, and which are not combined with it such as to form a larger program, in or on a volume of a storage or distribution medium, is called an "aggregate" if the compilation and its resulting copyright are not used to limit the access or legal rights of the compilation's users beyond what the individual works permit. Inclusion of a covered work in an aggregate does not cause this License to apply to the other parts of the aggregate.

6. Conveying Non-Source Forms.

You may convey a covered work in object code form under the terms of sections 4 and 5, provided that you also convey the machine-readable Corresponding Source under the terms of this License, in one of these ways:

a) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by the Corresponding Source fixed on a durable physical medium customarily used for software interchange.

b) Convey the object code in, or embodied in, a physical product (including a physical distribution medium), accompanied by a written offer, valid for at least three years and valid for as long as you offer spare parts or customer support for that product model, to give anyone who possesses the object code either (1) a copy of the Corresponding Source for all the software in the product that is covered by this License, on a durable physical medium customarily used for software interchange, for a price no more than your reasonable cost of physically performing this conveying of source, or (2) access to copy the Corresponding Source from a network server at no charge.

c) Convey individual copies of the object code with a copy of the written offer to provide the Corresponding Source. This alternative is allowed only occasionally and noncommercially, and only if you received the object code with such an offer, in accord with subsection 6b.

d) Convey the object code by offering access from a designated place (gratis or for a charge), and offer equivalent access to the Corresponding Source in the same way through the same place at no further charge. You need not require recipients to copy the Corresponding Source along with the object code. If the place to copy the object code is a network server, the Corresponding Source may be on a different server (operated by you or a third party) that supports equivalent copying facilities, provided you maintain clear directions next to the object code saying where to find the Corresponding Source. Regardless of what server hosts the Corresponding Source, you remain obligated to ensure that it is available for as long as needed to satisfy these requirements.

e) Convey the object code using peer-to-peer transmission, provided you inform other peers where the object code and Corresponding Source of the work are being offered to the general public at no charge under subsection 6d.

A separable portion of the object code, whose source code is excluded from the Corresponding Source as a System Library, need not be included in conveying the object code work.

A "User Product" is either (1) a "consumer product", which means any tangible personal property which is normally used for personal, family, or household purposes, or (2) anything designed or sold for incorporation into a dwelling. In determining whether a product is a consumer product, doubtful cases shall be resolved in favor of coverage. For a particular product received by a particular user, "normally used" refers to a typical or common use of that class of product, regardless of the status of the particular user or of the way in which the particular user actually uses, or expects or is expected to use, the product. A product is a consumer product regardless of whether the product has substantial commercial, industrial or non-consumer uses, unless such uses represent the only significant mode of use of the product.

"Installation Information" for a User Product means any methods, procedures, authorization keys, or other information required to install and execute modified versions of a covered work in that User Product from a modified version of its Corresponding Source. The information must suffice to ensure that the continued functioning of the modified object code is in no case prevented or interfered with solely because modification has been made.

If you convey an object code work under this section in, or with, or specifically for use in, a User Product, and the conveying occurs as part of a transaction in which the right of possession and use of the User Product is transferred to the recipient in perpetuity or for a fixed term (regardless of how the transaction is characterized), the Corresponding Source conveyed under this section must be accompanied by the Installation Information. But this requirement does not apply if neither you nor any third party retains the ability to install modified object code on the User Product (for example, the work has been installed in ROM).

The requirement to provide Installation Information does not include a requirement to continue to provide support service, warranty, or updates for a work that has been modified or installed by the recipient, or for the User Product in which it has been modified or installed. Access to a network may be denied when the modification itself materially and adversely affects the operation of the network or violates the rules and protocols for communication across the network.

Corresponding Source conveyed, and Installation Information provided, in accord with this section must be in a format that is publicly documented (and with an implementation available to the public in source code form), and must require no special password or key for unpacking, reading or copying.

7. Additional Terms.

"Additional permissions" are terms that supplement the terms of this License by making exceptions from one or more of its conditions. Additional permissions that are applicable to the entire Program shall be treated as though they were included in this License, to the extent that they are valid under applicable law. If additional permissions apply only to part of the Program, that part may be used separately under those permissions, but the entire Program remains governed by this License without regard to the additional permissions.

When you convey a copy of a covered work, you may at your option remove any additional permissions from that copy, or from any part of it. (Additional permissions may be written to require their own removal in certain cases when you modify the work.) You may place additional permissions on material, added by you to a covered work, for which you have or can give appropriate copyright permission.

Notwithstanding any other provision of this License, for material you add to a covered work, you may (if authorized by the copyright holders of that material) supplement the terms of this License with terms:

- a) Disclaiming warranty or limiting liability differently from the

E License

terms of sections 15 and 16 of this License; or

- b) Requiring preservation of specified reasonable legal notices or author attributions in that material or in the Appropriate Legal Notices displayed by works containing it; or
- c) Prohibiting misrepresentation of the origin of that material, or requiring that modified versions of such material be marked in reasonable ways as different from the original version; or
- d) Limiting the use for publicity purposes of names of licensors or authors of the material; or
- e) Declining to grant rights under trademark law for use of some trade names, trademarks, or service marks; or
- f) Requiring indemnification of licensors and authors of that material by anyone who conveys the material (or modified versions of it) with contractual assumptions of liability to the recipient, for any liability that these contractual assumptions directly impose on those licensors and authors.

All other non-permissive additional terms are considered "further restrictions" within the meaning of section 10. If the Program as you received it, or any part of it, contains a notice stating that it is governed by this License along with a term that is a further restriction, you may remove that term. If a license document contains a further restriction but permits relicensing or conveying under this License, you may add to a covered work material governed by the terms of that license document, provided that the further restriction does not survive such relicensing or conveying.

If you add terms to a covered work in accord with this section, you must place, in the relevant source files, a statement of the additional terms that apply to those files, or a notice indicating where to find the applicable terms.

Additional terms, permissive or non-permissive, may be stated in the form of a separately written license, or stated as exceptions; the above requirements apply either way.

8. Termination.

You may not propagate or modify a covered work except as expressly provided under this License. Any attempt otherwise to propagate or modify it is void, and will automatically terminate your rights under this License (including any patent licenses granted under the third paragraph of section 11).

However, if you cease all violation of this License, then your license from a particular copyright holder is reinstated (a) provisionally, unless and until the copyright holder explicitly and finally terminates your license, and (b) permanently, if the copyright holder fails to notify you of the violation by some reasonable means prior to 60 days after the cessation.

Moreover, your license from a particular copyright holder is reinstated permanently if the copyright holder notifies you of the violation by some reasonable means, this is the first time you have received notice of violation of this License (for any work) from that copyright holder, and you cure the violation prior to 30 days after your receipt of the notice.

Termination of your rights under this section does not terminate the licenses of parties who have received copies or rights from you under this License. If your rights have been terminated and not permanently reinstated, you do not qualify to receive new licenses for the same material under section 10.

9. Acceptance Not Required for Having Copies.

You are not required to accept this License in order to receive or run a copy of the Program. Ancillary propagation of a covered work occurring solely as a consequence of using peer-to-peer transmission to receive a copy likewise does not require acceptance. However, nothing other than this License grants you permission to propagate or modify any covered work. These actions infringe copyright if you do not accept this License. Therefore, by modifying or propagating a covered work, you indicate your acceptance of this License to do so.

10. Automatic Licensing of Downstream Recipients.

Each time you convey a covered work, the recipient automatically receives a license from the original licensors, to run, modify and propagate that work, subject to this License. You are not responsible for enforcing compliance by third parties with this License.

An "entity transaction" is a transaction transferring control of an organization, or substantially all assets of one, or subdividing an organization, or merging organizations. If propagation of a covered work results from an entity transaction, each party to that transaction who receives a copy of the work also receives whatever licenses to the work the party's predecessor in interest had or could give under the previous paragraph, plus a right to possession of the Corresponding Source of the work from the predecessor in interest, if the predecessor has it or can get it with reasonable efforts.

You may not impose any further restrictions on the exercise of the

E License

rights granted or affirmed under this License. For example, you may not impose a license fee, royalty, or other charge for exercise of rights granted under this License, and you may not initiate litigation (including a cross-claim or counterclaim in a lawsuit) alleging that any patent claim is infringed by making, using, selling, offering for sale, or importing the Program or any portion of it.

11. Patents.

A "contributor" is a copyright holder who authorizes use under this License of the Program or a work on which the Program is based. The work thus licensed is called the contributor's "contributor version".

A contributor's "essential patent claims" are all patent claims owned or controlled by the contributor, whether already acquired or hereafter acquired, that would be infringed by some manner, permitted by this License, of making, using, or selling its contributor version, but do not include claims that would be infringed only as a consequence of further modification of the contributor version. For purposes of this definition, "control" includes the right to grant patent sublicenses in a manner consistent with the requirements of this License.

Each contributor grants you a non-exclusive, worldwide, royalty-free patent license under the contributor's essential patent claims, to make, use, sell, offer for sale, import and otherwise run, modify and propagate the contents of its contributor version.

In the following three paragraphs, a "patent license" is any express agreement or commitment, however denominated, not to enforce a patent (such as an express permission to practice a patent or covenant not to sue for patent infringement). To "grant" such a patent license to a party means to make such an agreement or commitment not to enforce a patent against the party.

If you convey a covered work, knowingly relying on a patent license, and the Corresponding Source of the work is not available for anyone to copy, free of charge and under the terms of this License, through a publicly available network server or other readily accessible means, then you must either (1) cause the Corresponding Source to be so available, or (2) arrange to deprive yourself of the benefit of the patent license for this particular work, or (3) arrange, in a manner consistent with the requirements of this License, to extend the patent license to downstream recipients. "Knowingly relying" means you have actual knowledge that, but for the patent license, your conveying the covered work in a country, or your recipient's use of the covered work in a country, would infringe one or more identifiable patents in that country that you have reason to believe are valid.

If, pursuant to or in connection with a single transaction or arrangement, you convey, or propagate by procuring conveyance of, a covered work, and grant a patent license to some of the parties receiving the covered work authorizing them to use, propagate, modify or convey a specific copy of the covered work, then the patent license you grant is automatically extended to all recipients of the covered work and works based on it.

A patent license is "discriminatory" if it does not include within the scope of its coverage, prohibits the exercise of, or is conditioned on the non-exercise of one or more of the rights that are specifically granted under this License. You may not convey a covered work if you are a party to an arrangement with a third party that is in the business of distributing software, under which you make payment to the third party based on the extent of your activity of conveying the work, and under which the third party grants, to any of the parties who would receive the covered work from you, a discriminatory patent license (a) in connection with copies of the covered work conveyed by you (or copies made from those copies), or (b) primarily for and in connection with specific products or compilations that contain the covered work, unless you entered into that arrangement, or that patent license was granted, prior to 28 March 2007.

Nothing in this License shall be construed as excluding or limiting any implied license or other defenses to infringement that may otherwise be available to you under applicable patent law.

12. No Surrender of Others' Freedom.

If conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot convey a covered work so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not convey it at all. For example, if you agree to terms that obligate you to collect a royalty for further conveying from those to whom you convey the Program, the only way you could satisfy both those terms and this License would be to refrain entirely from conveying the Program.

13. Use with the GNU Affero General Public License.

Notwithstanding any other provision of this License, you have permission to link or combine any covered work with a work licensed under version 3 of the GNU Affero General Public License into a single combined work, and to convey the resulting work. The terms of this License will continue to apply to the part which is the covered work, but the special requirements of the GNU Affero General Public License, section 13, concerning interaction through a network will apply to the combination as such.

14. Revised Versions of this License.

The Free Software Foundation may publish revised and/or new versions of the GNU General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies that a certain numbered version of the GNU General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that numbered version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of the GNU General Public License, you may choose any version ever published by the Free Software Foundation.

If the Program specifies that a proxy can decide which future versions of the GNU General Public License can be used, that proxy's public statement of acceptance of a version permanently authorizes you to choose that version for the Program.

Later license versions may give you additional or different permissions. However, no additional obligations are imposed on any author or copyright holder as a result of your choosing to follow a later version.

15. Disclaimer of Warranty.

THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. Limitation of Liability.

IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MODIFIES AND/OR CONVEYS THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

17. Interpretation of Sections 15 and 16.

If the disclaimer of warranty and limitation of liability provided above cannot be given local legal effect according to their terms, reviewing courts shall apply local law that most closely approximates an absolute waiver of all civil liability in connection with the Program, unless a warranty or assumption of liability accompanies a copy of the Program in return for a fee.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively state the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

```
<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>
```

```
This program is free software: you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by
the Free Software Foundation, either version 3 of the License, or
(at your option) any later version.
```

```
This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.
```

```
You should have received a copy of the GNU General Public License
along with this program. If not, see <http://www.gnu.org/licenses/>.
```

Also add information on how to contact you by electronic and paper mail.

If the program does terminal interaction, make it output a short notice like this when it starts in an interactive mode:

```
<program> Copyright (C) <year> <name of author>
This program comes with ABSOLUTELY NO WARRANTY; for details type 'show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type 'show c' for details.
```

The hypothetical commands 'show w' and 'show c' should show the appropriate parts of the General Public License. Of course, your program's commands might be different; for a GUI interface, you would use an "about box".

You should also get your employer (if you work as a programmer) or school, if any, to sign a "copyright disclaimer" for the program, if necessary. For more information on this, and how to apply and follow the GNU GPL, see <<http://www.gnu.org/licenses/>>.

The GNU General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Lesser General Public License instead of this License. But first, please read <<http://www.gnu.org/philosophy/why-not-lgpl.html>>.

E.2.2 Code Chunk of GPL

This is a code chunk to be included by the generated asm files.

```
68  <license 68>≡ (5)
;   Meltdown and Spectre - Samples Written in Assembly
;   Copyright (C) 2018 U. Plonus
;
;   This program is free software: you can redistribute it and/or modify
;   it under the terms of the GNU General Public License as published by
;   the Free Software Foundation, either version 3 of the License, or
;   (at your option) any later version.
;
;   This program is distributed in the hope that it will be useful,
;   but WITHOUT ANY WARRANTY; without even the implied warranty of
;   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
;   GNU General Public License for more details.
;
;   You should have received a copy of the GNU General Public License
;   along with this program. If not, see <http://www.gnu.org/licenses/>.
```