

AUTOMATIC ANALYSIS AND GRADING OF UTML UML DIAGRAMS

Douwe Osinga

d.r.osinga@student.utwente.nl

Supervisor

dr. ir. Vadim Zaytsev

v.zaytsev@utwente.nl

Supervisor

dr. Nacir Bouali

n.bouali@utwente.nl



ABSTRACT

During computer science studies, students are often required to submit UML diagrams. The grading of these diagrams is often done by humans, resulting in a costly, lengthy, and error-prone process. In this paper, we investigate the theoretical feasibility of automatically grading UML diagrams, focusing on the UTML variant developed at the University of Twente. In the final thesis, we compare the most suitable autograder from our related works to human grading.

1. INTRODUCTION

UML diagrams play a significant role in computer science, as they allow for communicating system designs in a standardised format. During technical studies, students are often required to make a UML diagram for a graded assignment or exam.

However, the grading of these diagrams can often be a costly and lengthy process, involving multiple paid members of staff [1]¹.

Additionally, this process is prone to grading inconsistencies [1], as humans are inherently unreliable when grading [2]. Letting the process of determining a grade based on a rubric be performed by a (deterministic) program instead of a human reduces these inconsistencies [3].

In this Research Topics paper, I examine the current state of autograding diagrams and propose a plan for the implementation of *Seshat*, an automatic diagram grader that combines concepts from related works (Section 3), which is to be implemented and verified in the final thesis.

2. PROBLEM STATEMENT

The grading of (UML) diagram submissions by students can often be a costly and lengthy process, involving multiple paid members of staff¹, which can take multiple hours of active work. Additionally, human grading is inherently

subject to inconsistencies in grading, according to [M. Meadows et al. \[2\]](#), who pose two possible solutions: either “report the level of reliability associated with marks/grades, or find alternatives to marking.” We propose a third alternative: what if, instead of finding alternatives to marking/grading, we find alternatives to the grading *process*?

The automatisisation of grading diagrams provides an grading marking method that could both reduce the cost and time required for institutions and reduce the inherently present inconsistencies in human grading². This could result in similar performance compared to human grading in terms of **accuracy** and **process transparency**, while improving **consistency**.

With accuracy, we mean the percentage of points assigned to a submission that are prescribed by the rubric for a particular exercise. With consistency, we mean both the extent to which similar grades are given to similar submissions, and the difference between consecutive runs (i.e. determinism). With transparency, we mean the extent to which the reasoning for a particular grade is explained. These properties are desirable in the grading process, as it means that students are graded in a way that reflects their performance.

For this research, we focus on the automatic grading of *UTML* UML diagrams, a recent, in-house developed diagram format of the University of Twente [4], [5]. However, as *UTML* is just a representation format and tool for creating UML diagrams, we aim to generalise these results to provide advice on the automatic grading of UML diagrams as a whole.

2.1. Research Questions

In order to examine the feasibility of automatically grading *UTML* UML diagrams, we provide a main research question (**MRQ**):

To what extent can UML diagrams be graded automatically while keeping or improving the accuracy, consistency, and transparency of human grading?

¹Also from personal experience.

²Given that the process is deterministic

We aim to answer the main research question with the following sub-research questions:

RQ1: What existing work can be found for automatically analysing and/or grading UML diagrams?

- **RQ1a:** What correction models are employed by existing works?
- **RQ1b:** To what extent can Intended Learning Objectives be translated into different types of autograder correction models?

RQ2: To what extent are existing solutions suitable for use in autograding UTML diagrams with regards to (1) accuracy, (2) consistency, (3) transparency, (4) availability of source code, (5) extent of linking ILOs to grading instructions, (6) ease of integration into the grading process, and (7) UTML support?

RQ3: To what extent can a suitable autograder be constructed from previous work to be able to grade UTML UML diagrams?

RQ4: To what extent does the autograder compare to human grading in the context of grading first-year UML exam questions?

RQ1 is answered in [Section 3](#), giving us an overview of existing solutions and their grading methodologies. **RQ2** is answered in [Section 3](#) by analysing these works for suitability of grading. Finally, **RQ3** and **RQ4** are to be answered in the final thesis, where we grade UTML diagrams using an implementation based on related work and compare it to human grading.

3. RELATED WORK

In order to answer research questions **RQ1** until **RQ4**, we have conducted a small-scale study covering roughly 40 works. These works were collected from sources such as Google Scholar³ and ResearchGate⁴, using terms such as “automatically grading UML diagrams”, “autograder diagram”, and “UML diagram assessment” for autograder-based related works, and terms such as “ILO translation”,

“intended learning objective grading”, and [more terms and stuff about ILOs](#)

3.1. Autograders

3.1.1. Non-ML/LLM

The automatic analysis of diagrams seems to be a relatively new field, having started somewhere in the early 2000s [\[6\]](#). Multiple types of diagrams are researched, including UML diagrams [\[3\]](#), [\[7\]](#), [\[8\]](#), [\[9\]](#), [\[10\]](#), [\[11\]](#), [\[12\]](#), [\[13\]](#), [\[14\]](#), [\[15\]](#), [\[16\]](#), [\[17\]](#), Entity-Relation Diagrams (including UML ERDs) [\[6\]](#), [\[18\]](#), [\[19\]](#), [\[20\]](#), [\[21\]](#), [\[22\]](#), [\[23\]](#).

[W. Bian et al. \[10\]](#) establishes a metamodel to map submissions to example solutions and proposes a metamodel to grade submissions. It suggests using syntactic matching, semantic matching, and structural matching, with the goal to optimally match parts of a student submission with those of a teacher, considering spelling mistakes, synonyms and related words, and neighbours / inheritance, respectively. They expand their work in a paper from 2020 which expands the work with a case study. Their main findings are that multiple teacher solutions result in more accurate grades, that grading configurations change per exam if you want similar grades to the teacher, and that their autograding “has shown to be more consistent and able to ensure fairness in the grading process” [\[3, p.11\]](#).

[M. Hosseinibaghdadabadi et al. \[7\]](#) implements the work of [W. Bian et al. \[10\]](#) by comparing UML use case diagrams to one or multiple example solutions, preferring the maximum grade. It uses a graph similarity strategy which matches nodes based on structural matching, along with syntactic and semantic word matching. Syntactic matching with Levenshtein distance, semantic matching with WordNet similarity score (uses HSO, WUP, LIN metrics). It achieves high correlation with human grades. [more?](#)

[O. Anas et al. \[8\]](#) compares UML class diagram submissions to an example solution. It uses graph similarity scores based on structural

³<https://scholar.google.com>

⁴<https://www.researchgate.net>

matching along with syntactic and semantic matching. Syntactic matching is done with substring matching, semantic matching is done with neighbour similarity (“the comparison of the neighboring classes” [8, p.1585]), relationship name, type, multiplicity, and inheritance. It achieves high correlation with human grading (more than 80% is perfectly similar, over 90% had a correlation >0.85 , no correlation was lower than 0.7).

3.1.2. ML/LLM-driven

Work on AI [24], [25] .

N. Bouali *et al.* [24] uses various Large Language Models (Llama, GPT o1-mini, Claude) to grade

3.1.3. Other

More focused on interactivity: [19]

F. Batmaz [9] takes a broader look at the process of grading, identifying and developing techniques to reduce repetitive actions, focusing on database ER diagrams. It proposes a semi-automatic grading system which identifies identical segments between a submission and the solution. Assuming multiple submission revisions are available, it suggests to “not only [use] the reference text but also the intermediate diagrams” for identifying semantic matches [9, p.40] .

3.2. ILO translation

3.3. Suitability of autograders

Further proof of unreliability of using Large Language Models (LLMs) for automatic grading: “In the evaluation based on UC4, GPT deducts points for missing relationships between specified actors and use cases, but theses relationships existed in the UML use case” [26, p.13] , and “While the models would provide a final score as requested in the prompt’s response format, this core often did not match the actual sum of points awarded in their criterion-by-criterion assessment, where N. Bouali *et al.* [24, p.164] identify the problem perfectly, stating that “This discrepancy can be attributed to the autoregressive nature of LLMs, where they generate responses token by token”.

I believe that the observation from N. Bouali *et al.* [24] highlights the underlying problem of

using LLMs for automatic grading. Because these models are in their very essence based on predicting tokens [27] , there is no formal guarantee that grades are produced with accuracy. The fact that LLMs produce grades that correlate with human grading does not mean that this grading is done in a fair, consistent, or reliable manner. In particular, reliability is affected by the nondeterminism introduced into LLMs, either deliberately, with ‘temperature’ controls per model, or accidentally, because batch processing ordering for large-scale LLM deployments can introduce nondeterminism [28], [29] .

While [24] attempts to lower the amount of nondeterminism by setting the model’s temperature to zero, nondeterminism can still occur due to

Nondeterminism of AI [28], [29], [30] + counterarg: inherent lack of transparency, risks of nondeterminism in grading (see sources) == bad because same solution might not give same grade), lack of consistency (context window, importance of reducing prompt length, ...).

Experience on TAs [1]

Reliability of human marking/grading in general [2]

4. TOOLS AND TECHNIQUES

Adopt existing tool(s), make own tool, what frameworks/languages, ...

5. PLANNING

TODO: Graduation planning. Phases, goals per phase.

BIBLIOGRAPHY

- [1] F. Ahmed, N. Bouali, and M. Gerhold, "Teaching Assistants as Assessors: An Experience Based Narrative," 2024. [Online]. Available: <https://research.utwente.nl/files/457355611/126242.pdf>
- [2] M. Meadows and L. Billington, "A Review Of The Literature On Marking Reliability." [Online]. Available: https://assets.publishing.service.gov.uk/media/5a820a57e5274a2e87dc0d5a/0505_Meadows_and_Billington_CERP_RP.pdf
- [3] W. Bian, O. Alam, and J. Kienzle, "Is automated grading of models effective?: assessing automated grading of class diagrams," in *Proceedings of the 23rd ACM/IEEE International Conference on Model Driven Engineering Languages and Systems*, in MODELS '20. ACM, Oct. 2020, pp. 365–376. doi: [10.1145/3365438.3410944](https://doi.org/10.1145/3365438.3410944) .
- [4] D. Huistra, "UTML - internal GitLab repository." [Online]. Available: <https://gitlab.utwente.nl/ewi/eduapps/UTML/>
- [5] "UTML - old student repository." [Online]. Available: <https://github.com/andrewjh9/UTML>
- [6] P. Thomas, "Grading Diagrams Automatically," 2004. [Online]. Available: https://oro.open.ac.uk/90155/1/2004_01.pdf
- [7] M. Hosseinibaghdadabadi, O. A. N. Almerge, and J. Kienzle, "Automated Grading of Use Cases," in *2023 ACM/IEEE 26th International Conference on Model Driven Engineering Languages and Systems (MODELS)*, IEEE, 2023. [Online]. Available: <https://ieeexplore.ieee.org/iel7/10343461/10343549/10343598.pdf>
- [8] O. Anas, T. Mariam, and L. Abdelouahid, "New method for summative evaluation of UML class diagrams based on graph similarities," 2021. [Online]. Available: https://www.academia.edu/download/66135135/70_22270_EM_26aug_20feb_L.pdf
- [9] F. Batmaz, "Semi-Automatic Assessment of Students' Graph-Based Diagrams," 2010. [Online]. Available: https://www.academia.edu/download/66135135/70_22270_EM_26aug_20feb_L.pdf
- [10] W. Bian, O. Alam, and J. Kienzle, "Automated Grading of Class Diagrams," in *2019 ACM/IEEE 22nd International Conference on Model Driven Engineering Languages and Systems Companion (MODELS-C)*, IEEE, Sept. 2019, pp. 700–709. doi: [10.1109/models-c.2019.00106](https://doi.org/10.1109/models-c.2019.00106) .
- [11] R. Jebli, J. E. Bouhdidi, and M. Y. Chkouri, "Assessing Students' UML Class Diagrams: a New Automated Solution," in *2023 7th IEEE Congress on Information Science and Technology (CiSt)* |, IEEE, 2023. [Online]. Available: <https://ieeexplore.ieee.org/iel7/10409867/10409868/10409936.pdf>
- [12] S. Modi, H. A. Taher, and H. Mahmud, "A Tool to Automate Student UML diagram Evaluation," 2021. [Online]. Available: <https://www.academia.edu/download/72488756/575.pdf>
- [13] N. H. Ali, Z. Shukur, and S. Idris, "Assessment System For UML Class Diagram Using Notations Extraction," 2007. [Online]. Available: https://www.researchgate.net/profile/Zarina-Shukur/publication/253243639_Assessment_System_For_UML_Class_Diagram_Using_Notations_Extraction/links/55487af30cf2b0cf7acec2e4/Assessment-System-For-UML-Class-Diagram-Using-Notations-Extraction.pdf
- [14] N. H. Ali, Z. Shukur, and S. Idris, "A Design of an Assessment System for UML Class Diagram," in *2007 International Conference on Computational Science and its Applications (ICCSA 2007)*, IEEE, Aug. 2007, pp. 539–546. doi: [10.1109/iccsa.2007.2](https://doi.org/10.1109/iccsa.2007.2) .

- [15] H. AlRawashdeh, S. Idris, and A. M. Zin, "Using Model Checking Approach for Grading the Semantics of UML Models," 2014. [Online]. Available: https://iieng.org/images/proceedings_pdf/8684E0114567.pdf
- [16] V. Vachharajani and J. Pareek, "A Proposed Architecture for Automated Assessment of Use Case Diagrams," in *International Journal of Computer Applications (0975 – 8887)*, 2014. [Online]. Available: <https://www.academia.edu/download/67672696/pxc3900193.pdf>
- [17] M. Striewe and M. Goedicke, "Automated Checks on UML Diagrams," in *ITiCSE'11*, in ITiCSE '11. ACM, June 2011, pp. 38–42. doi: [10.1145/1999747.1999761](https://doi.org/10.1145/1999747.1999761) .
- [18] S. Foss, T. Urazova, and R. Lawrence, "Learning UML database design and modeling with AutoER," in *Proceedings of the 25th International Conference on Model Driven Engineering Languages and Systems: Companion Proceedings*, in MODELS '22. ACM, Oct. 2022, pp. 42–45. doi: [10.1145/3550356.3559091](https://doi.org/10.1145/3550356.3559091) .
- [19] S. Foss, "AutoER: A System for the Automatic Generation and Evaluation of UML Database Design Diagrams," 2022. [Online]. Available: <https://open.library.ubc.ca/media/download/pdf/24/1.0421624/4>
- [20] P. Thomas, N. Smith, and K. Waugh, "An approach to the automatic grading of imprecise diagrams," technical report, 2006. doi: [.org/10.21954/ou.ro.00016046](https://doi.org/10.21954/ou.ro.00016046) .
- [21] P. Thomas, N. Smith, and K. Waugh, "Automatically Assessing Diagrams," in *Proceedings of the IADIS International Conference on e-Learning*, 2009. [Online]. Available: https://www.researchgate.net/profile/Pete-Thomas/publication/42799920_Automatically_assessing_diagrams/links/0fcfd5060076dd8ba2000000/Automatically-assessing-diagrams.pdf
- [22] P. Thomas, N. Smith, and K. Waugh, "Automatically assessing graph-based diagrams," *Learning, Media and Technology*, vol. 33, no. 3, pp. 249–267, 2008, doi: [10.1080/17439880802324251](https://doi.org/10.1080/17439880802324251) .
- [23] N. Smith, P. Thomas, and K. Waugh, "Automatic Grading of Free-Form Diagrams with Label Hypernymy," in *2013 Learning and Teaching in Computing and Engineering*, IEEE, Mar. 2013, pp. 136–142. doi: [10.1109/latice.2013.33](https://doi.org/10.1109/latice.2013.33) .
- [24] N. Bouali, M. Gerhold, T. U. Rehman, and F. Ahmed, "Toward Automated UML Diagram Assessment: Comparing LLM-Generated Scores with Teaching Assistants," 5220. [Online]. Available: <https://research.utwente.nl/files/496461589/134819.pdf>
- [25] D. R. Stikkolorum, P. van der Putten, C. Sperandio, and M. R. Chaudron, "Towards Automated Grading of UML Class Diagrams with Machine Learning," 2019. [Online]. Available: <https://ceur-ws.org/Vol-2491/paper80.pdf>
- [26] C. Wang, B. Wang, P. Liang, and J. Liang, "Assessing UML Diagrams by GPT: Implications for Education," technical report, 2025. [Online]. Available: https://www.researchgate.net/publication/397720325_Assessing_UML_Diagrams_by_GPT_Implications_for_Education
- [27] A. F. Ferraris, D. Audrito, L. D. Caro, and C. Poncibò, "The architecture of language: Understanding the mechanics behind LLMs," *Cambridge Forum on AI: Law and Governance*, vol. 1, pp. 1–19, 2025, doi: [10.1017/cfl.2024.16](https://doi.org/10.1017/cfl.2024.16) .
- [28] M. Brenndoerfer, "Why Temperature=0 Doesn't Guarantee Determinism in LLMs," 2025, [Online]. Available: <https://mbrenndoerfer.com/writing/why-llms-are-not-deterministic>
- [29] B. Atil *et al.*, "Non-Determinism of "Deterministic" LLM Settings," 2025. [Online]. Available: <https://arxiv.org/pdf/2408.04667>

- [30] H. He and T. Machines, “Defeating Nondeterminism in LLM Inference,” 2025, [Online]. Available: <https://thinkingmachines.ai/blog/defeating-nondeterminism-in-llm-inference/>

6. APPENDICES

6.1. Autograder suitability table

Author	Di	Ac	Co	Tr	OSS	ILO	Int	UTML
M. Hosseinibaghdadabadi et al. [7]	UML Use Case	H	H	H	N	N	?	N

Table 1: Autograders and their suitability scores.

*Di(*agram type*), Ac(*curacy*), Co(*nsistency*), Tr(*ansparency*), OSS = *availability of source code*, ILO = *ease of linking grading to ILOs*, Int(*egration ease*), UTML *support*.

Scoring is divided into “N” (*No Support*), “L” (*Low*), “M” (*Medium*), “H” (*High*), and “?” (*Unknown*), which gives an indication of suitability w.r.t. that particular criterium.