Nutan Maharashtra Vidya Prasarak Mandal's

NUTAN MAHARASHTRA INSTITUTE OF ENGINEERING & TECHNOLOGY

Samarth Vidya Sankul, Vishnupuri, Talegaon Dabhade, Pune - 410507



DEPARTMENT OF COMPUTER APPLICATION (BCA & MCA)

MINI PROJECT REPORT

ON

"TESTORA – SMART APTITUDE PREPARATION AND ONLINE TEST SYSTEM"

Submitted in partial fulfillment of the requirements for the course

MINI PROJECT

Group No.	[Group No.]
Student Name(s)	[Student 1, Student 2, Student 3]
Roll No. / PRN / Exam Seat No.	[Enter details]
Class / Division	MCA – [A/B]
Project Guide	[Guide Name]

ACADEMIC YEAR 2026-27

Nutan Maharashtra Vidya Prasarak Mandal's

NUTAN MAHARASHTRA INSTITUTE OF ENGINEERING & TECHNOLOGY

Samarth Vidya Sankul, Vishnupuri, Talegaon Dabhade, Pune - 410507

CERTIFICATE

Department of Computer Application

This is to certify that **[Student 1, Student 2, Student 3]**, Roll No./PRN/Exam Seat No. **[Enter details]**, of MCA has satisfactorily completed the Mini Project entitled **"Testora – Smart Aptitude Preparation and Online Test System"** under the guidance of **[Guide Name]** during the Academic Year 2026-27. The work presented in this report is approved for submission as part of the Mini Project requirements.

Project Guide **Project Coordinator** **Head of Department** **Principal**

Date: ____ / ____ / 2026

STUDENT DECLARATION

We hereby declare that the Mini Project report entitled “Testora – Smart Aptitude Preparation and Online Test System” submitted to the Department of Computer Application, Nutan Maharashtra Institute of Engineering & Technology, is an original record of the work carried out by us under the guidance of [Guide Name] during the Academic Year 2026-27.

We further declare that this work has not been submitted, either in full or in part, to any other university or institute for the award of any degree, diploma, or certificate. All sources of information used in this project have been properly acknowledged and cited.

We understand that any form of plagiarism, fabrication of results, or misrepresentation of work may lead to disciplinary action as per institute rules.

Sr. No.	Student Name	Roll No. / PRN	Signature
1			
2			
3			

Place: _____ Date: ____ / ____ / 2026

ACKNOWLEDGEMENT

We take this opportunity to express our sincere gratitude to everyone who supported us during the development of our Mini Project, “Testora – Smart Aptitude Preparation and Online Test System”.

We are thankful to Nutan Maharashtra Institute of Engineering & Technology, Talegaon Dabhade, Pune, for providing the academic environment and the laboratory facilities needed to complete this work. We express our respectful thanks to the Principal for encouraging students to undertake practical projects, and to the Head of the Department of Computer Application for continuous support and guidance to the students of the department.

We are deeply grateful to our Project Guide, [Guide Name], for the valuable guidance, regular reviews and constructive suggestions given at every stage of the project, from problem identification and requirement analysis to design, implementation and testing. The corrections suggested during the progress presentations helped us to improve both the system and this report. We also thank the Project Coordinator for organising the schedule and the review sessions of the Mini Project.

We thank all the faculty members and the non-teaching staff of the department for their cooperation and for the facilities provided to us. Our sincere thanks are due to our classmates, who tested the application, gave honest feedback on its usability and shared useful ideas. We also acknowledge the open-source communities behind React, Node.js, Express, MongoDB and the other tools used in this project, whose documentation made it possible for us to learn and build quickly.

Finally, we thank our families for their patience, encouragement and moral support throughout the course of this work.

[Student 1, Student 2, Student 3]

ABSTRACT

Preparing for campus placement examinations requires regular practice of aptitude questions, but students usually depend on scattered websites that offer static question lists, while teachers and colleges have no simple way to set their own timed tests, assign them to students and measure the results. This project, Testora, is a web-based aptitude preparation and online test system that brings learning, practice, assessment and analytics together on one platform for three types of users: students, teachers and administrators.

The objective was to build a secure, role-based application in which content is organised as Category, Topic and Question; students can study concept notes, practise topic-wise questions with instant feedback and attempt timed tests; teachers can create and assign quizzes; and administrators can manage users and content. Testora is implemented as a single-page application using React, Vite and Tailwind CSS, a REST API built with Node.js and Express, and a MongoDB database accessed through Mongoose. Authentication uses JSON Web Tokens and bcrypt-hashed passwords, and every protected route is checked for both login status and role.

The major features include timed mock tests created by administrators; teacher quizzes created through a three-step workflow that generates question forms dynamically and assigns the quiz to all active students; server-side evaluation with configurable marks per question and optional negative marking; correct answers that are never sent to the browser before submission; immediate blocking of deactivated accounts; topic-wise performance analytics that flag weak topics; validated JSON import of questions with duplicate detection and no partial imports; and CSV export.

The system was verified with forty-one automated API test cases and a scripted walkthrough of every user role in a real browser; all forty-one test cases passed on an isolated test database. The results show that the objectives were met and that the platform can serve as a practical, low-cost aptitude practice and assessment tool for a college. Future work includes restoring interrupted mock tests, PDF export, question randomisation, proctoring support and an automated regression suite.

Keywords: Aptitude Assessment, Online Test System, MERN Stack, Role-Based Access Control, Performance Analytics

TABLE OF CONTENTS

Section	Title	Page No.
	Certificate	ii
	Student Declaration	iii
	Acknowledgement	iv
	Abstract	v
	List of Figures	vii
	List of Tables	viii
	List of Abbreviations	ix
1	Introduction	1
2	Literature Survey & Existing System	5
3	Requirement Analysis & System Design	8
4	Implementation	20
5	Testing & Results	31
6	Conclusion & Future Scope	36
	References	38
	Appendices	40

LIST OF FIGURES

Figure No.	Figure Caption	Page No.
Fig. 3.1	System Architecture of Testora	11
Fig. 3.2	Use Case Diagram – Student Module	12
Fig. 3.3	Use Case Diagram – Teacher Module	12
Fig. 3.4	Use Case Diagram – Admin Module	13
Fig. 3.5	Data Flow Diagram – Level 0 (Context Diagram)	13
Fig. 3.6	Data Flow Diagram – Level 1	14
Fig. 3.7	Entity-Relationship Diagram of Testora	15
Fig. 4.1	Test Attempt and Evaluation Flowchart	24
Fig. 4.2	Login Screen	25
Fig. 4.3	Student Dashboard	25
Fig. 4.4	Topic Detail with Concept Cards	26
Fig. 4.5	Timed Exam Screen with Question Palette	26
Fig. 4.6	Result Screen	26
Fig. 4.7	Performance Analysis	27
Fig. 4.8	Create Quiz – Step 2: Quiz Details	27
Fig. 4.9	Create Quiz – Step 3: Set Questions	27
Fig. 4.10	Admin Dashboard	28
Fig. 4.11	Admin – Import Questions via JSON	28
Fig. 4.12	Request Authentication and Authorization Pipeline	29

LIST OF TABLES

Table No.	Table Title	Page No.
Table 2.1	Comparison of Existing Systems with Testora	7
Table 3.1	Functional Requirements of Testora	8
Table 3.2	Non-Functional Requirements of Testora	9
Table 3.3	Hardware and Software Requirements	9
Table 3.4	User Collection	16
Table 3.5	Category and Topic Collections	16
Table 3.6	Concept Collection	16
Table 3.7	Question Collection	16
Table 3.8	MockTest Collection	17
Table 3.9	TeacherQuiz Collection	17
Table 3.10	QuizAssignment Collection	17
Table 3.11	TestAttempt Collection	17
Table 3.12	Module Overview	18
Table 4.1	Development Environment	20
Table 4.2	Topic Classification Rules	24
Table 4.3	Environment Variables of the Server	28
Table 4.4	Module Inputs and Outputs	30
Table 5.1	Test Cases and Results	31
Table 5.2	Test Results by Module	33
Table 5.3	Objectives and Outcome	34
Table 5.4	Handling of Invalid Inputs and Exceptions	34
Table A.1	Demonstration Accounts	40
Table B.1	Test Evidence by Module	41

LIST OF ABBREVIATIONS

Abbreviation	Full Form
API	Application Programming Interface
CORS	Cross-Origin Resource Sharing
CRUD	Create, Read, Update, Delete
CSS	Cascading Style Sheets
CSV	Comma-Separated Values
DFD	Data Flow Diagram
ER	Entity-Relationship
FR	Functional Requirement
HTTP	Hypertext Transfer Protocol
JSON	JavaScript Object Notation
JWT	JSON Web Token
MCQ	Multiple-Choice Question
MERN	MongoDB, Express.js, React, Node.js
ODM	Object Document Mapper
OWASP	Open Worldwide Application Security Project
PDF	Portable Document Format
RBAC	Role-Based Access Control
REST	Representational State Transfer
SPA	Single-Page Application
TC	Test Case
UI	User Interface
XSS	Cross-Site Scripting

CHAPTER 1
INTRODUCTION

1.1 Background / Overview

Aptitude tests covering quantitative ability, logical reasoning and verbal ability are a standard first round in campus placements and in many competitive examinations. Candidates are expected to solve a large number of questions accurately inside a strict time limit. Success depends less on one-time learning and more on regular topic-wise practice, repeated timed test-taking and honest feedback about weak areas.

Colleges support this preparation through training sessions and teacher-made tests, while students rely mostly on public websites, books and commercial test-series platforms. These resources are useful, but they are separate from one another and from the college. A student reads concepts in one place, practises on another website and takes mock tests on a third, and no single system records progress or lets the college's own teachers set, assign and monitor tests. A web-based platform that integrates these activities, and that the institution itself controls, addresses a clear need.

1.2 Problem Statement

Students preparing for aptitude examinations do not have one integrated, institution-controlled platform that combines concept learning, topic-wise practice, timed tests with fair scoring and objective feedback on weak topics. Teachers have no simple way to create a timed quiz, assign it to their students and see class results without using heavy learning-management software or manual paper evaluation, and administrators have no unified place to manage users, subjects and the question bank. This project addresses these gaps by building *Testora*, a secure role-based web application for students, teachers and administrators.

1.3 Project Objectives

The project was planned around the following measurable objectives:

1. Provide separate, secure portals for students, teachers and administrators using JSON Web Token authentication and server-side role checks on every protected API route.
2. Organise content as Category → Topic → Question, with administrator-managed categories, topics, concept notes and a question bank. The demonstration data set delivered with the project contains 3 categories, 22 topics, 58 questions and 5 mock tests.

3. Deliver timed mock tests and teacher quizzes that are evaluated on the server with configurable marks per question and optional negative marking, and never send correct answers to the browser before submission.
4. Let a teacher create a quiz through a guided three-step workflow (category, details, questions) in which question forms are generated from the chosen question count, and assign the quiz automatically to all active students.
5. Report each student's performance topic-wise and classify topics as Weak, Needs Practice or Strong using a minimum of five attempted questions per topic.
6. Support bulk content management through validated JSON import (at most 2 MB and 500 questions per import, all-or-nothing, duplicate-safe) and CSV export, and verify the system with at least 40 documented test cases.

1.4 Scope of the Project

Included in the scope:

- Three user roles (student, teacher, administrator) with registration, login, profile management and password change.
- Student features: browsing categories and topics, reading concept notes, untimed practice with instant feedback, timed mock tests and assigned quizzes, results with answer review, performance analytics and test history.
- Teacher features: dashboard, guided quiz creation with dynamic question forms, marks and optional negative marking, automatic assignment, quiz management and class results.
- Administrator features: dashboard counts, student and teacher management (activation and deactivation), categories, topics, concepts, question bank, JSON/CSV import, CSV export and mock test management.
- A responsive single-page web interface backed by a REST API and a MongoDB database.

Excluded from the scope:

- PDF export or printing of questions (only CSV export is provided).
- Online proctoring such as webcam monitoring or tab-switch detection.
- Question types other than single-answer multiple-choice questions with four options.
- Payments or subscriptions, native mobile applications, and e-mail or SMS notifications.

- Hard deletion of users: accounts are deactivated so that historical quizzes and results are preserved.
- Manual selection of individual students for a quiz: every quiz is assigned to all active students by design.
- Public hosting: the system was developed and tested in a local development environment against a cloud MongoDB database.

1.5 Proposed Solution

Testora is a three-tier web application. A React single-page application provides role-specific portals; a Node.js and Express REST API implements authentication, authorization, validation, test evaluation and analytics; and a MongoDB database stores users, subjects, questions, tests, assignments and attempts. The central idea is that all learning and assessment activity is tied to the Category → Topic → Question hierarchy, so that every answer a student gives can be traced back to a topic. This makes topic-wise feedback possible without any extra effort from teachers.

Tests are evaluated only on the server. The browser receives questions without their correct answers and the correct answers are revealed only in the result review after the attempt has been submitted. Marks are calculated as correct answers multiplied by the marks per question, minus wrong answers multiplied by the negative mark, so that negative marking can be switched on for any test.

1.6 Key Features

- **Student portal (12 screens):** dashboard, topics, topic detail with concept cards, practice mode, mock tests, timed exam with question palette and mark-for-review, assigned quizzes, result page with answer review, performance analysis, test history and profile.
- **Teacher portal (5 screens):** dashboard, quiz management, three-step quiz creator with dynamically generated question forms, quiz results and profile with specialization.
- **Admin portal (8 screens):** dashboard with live counts, students, teachers, categories, topics, concepts, questions with import and export, and mock tests with publish control.
- **Marks and negative marking** configurable per mock test and per quiz, with the maximum marks stored with each attempt.
- **Security controls:** bcrypt password hashing, JWT sessions, role-based authorization, immediate rejection of deactivated accounts, input validation, secure HTTP headers and restricted CORS.

- **Data tools:** JSON import with full validation and duplicate detection, CSV import, and CSV export of all or filtered questions.

1.7 Organization of the Report

Chapter 1 introduces the problem, objectives, scope and the proposed solution. Chapter 2 reviews the technologies used and existing systems and identifies the development gap. Chapter 3 presents the functional and non-functional requirements, the system architecture, the use case, data flow and entity-relationship diagrams, the database design and the module design. Chapter 4 explains the implementation, the core algorithms, the user interface with screenshots, integration and deployment steps, and the security and validation controls. Chapter 5 describes the testing strategy, the test cases and their results, and the limitations of the current system. Chapter 6 concludes the report and lists the future scope. The References and Appendices (installation guide, test evidence and supporting documents) follow.

CHAPTER 2
LITERATURE SURVEY & EXISTING SYSTEM

2.1 Literature / Technology Survey

Computer-based assessment replaces paper tests with software that presents questions, measures time, evaluates answers automatically and stores the outcome. For aptitude preparation the most useful properties are immediate evaluation, repeatable timed practice and analysis of results by topic. The following technologies were surveyed and selected to build such a system; together they form the widely used MERN stack (MongoDB, Express.js, React and Node.js).

React. React is a component-based JavaScript library for building user interfaces, in which the screen is described as a tree of reusable components that re-render when their state changes [1]. It suits Testora because the three portals share many components (tables, modals, spinners, confirmation dialogs) and because test-taking screens need frequent local state updates such as the running timer and the selected answers.

Node.js and Express. Express is a minimal web framework for Node.js whose request handling is built around a pipeline of middleware functions [2]. Testora uses this pipeline for security headers, authentication, role authorization and input validation before a request reaches the business logic. Using JavaScript on both client and server also lets the team work in one language.

MongoDB and Mongoose. MongoDB is a document database that stores records as flexible JSON-like documents [3]. Mongoose adds schemas, validation, default values, indexes and object references on top of MongoDB [4]. Questions with embedded option arrays, and attempts with embedded answer and topic-performance arrays, map naturally to documents and avoid many table joins.

JSON Web Tokens. A JSON Web Token is a compact, digitally signed token that carries claims between two parties [5]. After login Testora issues a token containing the user identifier; the client sends it with every request and the server verifies the signature. The server additionally re-reads the user record on each request so that a deactivated account is rejected immediately.

bcrypt. bcrypt is an adaptive password-hashing scheme that adds a random salt and a configurable work factor, making stored passwords resistant to brute-force and rainbow-table attacks [6]. Testora stores only the bcrypt hash of each password.

Tailwind CSS, Vite and Recharts. Tailwind CSS is a utility-first styling framework that makes it easy to build consistent, responsive layouts [7]. Vite is a build tool and

development server that provides fast start-up, hot module replacement and optimised production builds [8]. Recharts provides composable chart components for React and is used for the topic-accuracy chart on the performance screen [9].

express-validator and Multer. express-validator supplies validation and sanitisation chains for Express routes, which Testora uses to reject malformed input before it reaches the controllers [10]. Multer is the Express middleware for multipart file uploads and is used, with size and file-type limits, for the CSV and JSON import files [11].

2.2 Existing System

Aptitude preparation and testing is currently handled in four main ways. The following observations about public systems are based on the pages listed in the References.

- **Manual and paper-based tests.** Teachers prepare question papers, students answer on paper and the evaluation and result compilation are done by hand. Feedback is slow and topic-wise analysis is rarely produced.
- **Learning-management systems.** The Moodle Quiz activity lets teachers build quizzes inside a course from questions stored in a reusable question bank [12]. It is a module of a Moodle course, so it can be used only after a course has been set up in Moodle.
- **Form-based quizzes.** Google Forms can auto-grade quizzes using an answer key, point values and answer feedback, and its summaries include frequently missed questions and score statistics [13]. Individual grading and score e-mails depend on collecting respondents' e-mail addresses.
- **Free aptitude websites.** Sites such as IndiaBIX publish topic-wise aptitude questions with solved answers and explanations, and offer PDF or e-book downloads [14]. The content is created and controlled by the site owner.
- **Commercial test-series platforms.** Platforms such as Testbook offer large mock-test series with score analysis and a strengths-and-weaknesses breakdown, but many tests are paid and the content is controlled by the vendor [15].

2.3 Limitations of Existing System

- No single system joins concept notes, topic-wise practice, timed tests and per-student analytics; students must move between several tools.
- Public aptitude websites and commercial platforms are controlled by their owners, so a college cannot add its own questions, schedule its own tests or monitor its own students.

- General-purpose learning-management systems are organised around courses and typically need hosting and administration, which is more than a department needs for aptitude practice alone.
- Form-based quizzes are simple to create, but the documentation reviewed does not describe a timed exam mode or topic-level analytics [13].
- Paper-based tests need manual evaluation, which delays feedback and makes weak-topic identification difficult.
- Many commercial services require payment, which limits access for students who need regular practice.

2.4 Comparative Analysis

Table 2.1 compares the four approaches reviewed with the proposed system. Only features that are stated on the cited pages are listed for the existing systems.

Table 2.1 Comparison of Existing Systems with Testora

System / Reference	Main Features	Technology	Limitations	How Proposed System Improves
Moodle Quiz activity [12]	Teacher-built quizzes; reusable question bank; teachers review attempts and grades	Activity module of a Moodle course	Used inside a Moodle course, which must be set up first; negative marking and topic analytics not described on the page reviewed	Purpose-built, lightweight; marks, negative marking and topic analytics available out of the box
Google Forms quizzes [13]	Answer-key auto-grading; point values; answer feedback; missed-question and score summaries	Web-based form and quiz feature	Individual grading needs e-mail collection; timed mode and topic analytics not described	Timed exam with question palette, practice mode and topic-wise analytics
IndiaBIX aptitude section [14]	Topic-wise questions with solved explanations; PDF and e-book downloads	Public website	Content controlled by the site owner; no per-user analytics shown on the page reviewed	College-owned content; teachers author quizzes; per-student results
Testbook [15]	Mock-test series; detailed score analysis; strengths and weaknesses; live tests	Commercial exam-preparation platform	Many tests are paid; content controlled by the vendor; focus on government and entrance exams	Free for the institution; aptitude-focused; teacher-created assigned quizzes

2.5 Identified Research / Development Gap

The review shows that good tools exist for individual activities — question banks, auto-graded quizzes, practice websites and large test series — but none of them gives a college a single, self-controlled system in which administrators manage subjects and content, teachers author and assign timed quizzes, and students learn, practise, take tests and see topic-wise feedback. Testora fills this gap with a small, open and extensible platform built on a common technology stack that the department can host, modify and extend.

CHAPTER 3
REQUIREMENT ANALYSIS & SYSTEM DESIGN

3.1 Functional Requirements

Requirements are commonly classified as functional requirements, which describe what the system must do, and non-functional requirements, which describe the qualities it must have [16]. The functional requirements of Testora are numbered in Table 3.1.

Table 3.1 Functional Requirements of Testora

ID	Module	Requirement
FR1	Authentication	A new student can register with name, e-mail, mobile number, password, college, course and year; the role is always set to student by the server.
FR2	Authentication	Users log in with e-mail and password and receive a signed token; deactivated users cannot log in.
FR3	Authentication	Users can update their profile and change their password after entering the current password.
FR4	Admin	The dashboard shows live counts of students, teachers, topics and questions (plus mock tests and attempts) and recent test attempts.
FR5	Admin	The admin can list students (name, college, course, year, status) and activate or deactivate any student; deactivation blocks all further API access.
FR6	Admin	The admin can create teacher accounts with specialization, edit teachers and activate or deactivate them.
FR7	Admin	The admin can create, edit and deactivate categories and topics; each topic belongs to one category.
FR8	Admin	The admin can create, edit and delete concept notes (explanation, formulas, examples, important points) for a topic.
FR9	Admin	The admin can create, edit and deactivate questions with four options, one correct answer and an optional explanation, and can filter by category and topic and search by text.
FR10	Admin	The admin can import questions from a JSON file or pasted JSON; the whole import is rejected if any item is invalid or a duplicate.
FR11	Admin	The admin can import questions from CSV and export all or filtered questions to CSV.
FR12	Admin	The admin can create, edit, delete, publish and unpublish mock tests with duration, marks per question and optional negative marking.
FR13	Teacher	The teacher creates a quiz in three steps: select category, enter details (title, description, question count, duration, marks, optional negative marking, dates) and set questions.
FR14	Teacher	The system generates one question form per requested question; each question needs a topic, text, four options, a correct answer and an optional explanation.
FR15	Teacher	A created quiz is assigned automatically to all active students; no individual student selection is required.
FR16	Teacher	The teacher can list and delete own quizzes and view each quiz’s results, completion count and average accuracy.
FR17	Student	The student can browse categories and topics and read concept notes for a topic.
FR18	Student	The student can practise topic questions one at a time and receive immediate correctness feedback and explanation.
FR19	Student	The student can attempt a published mock test once within its time limit, using a question palette, mark-for-review and automatic submission on timeout.
FR20	Student	The student can attempt an assigned quiz only inside its start–end date window and only once.

ID	Module	Requirement
FR21	Student	The server evaluates every attempt and stores marks obtained, maximum marks, counts of correct, wrong and skipped answers, accuracy and topic-wise performance.
FR22	Student	The result page shows marks, accuracy, time taken, topic performance and an answer review that reveals correct answers only after submission.
FR23	Student	The student can view performance analytics with weak-topic recommendations and a filterable, paginated test history.
FR24	System	All write requests are validated on the server and invalid input is rejected with a clear message.
FR25	System	Every protected route checks the user's role; correct answers are never included in question payloads sent before submission.

3.2 Non-Functional Requirements

Table 3.2 lists the non-functional requirements. The security requirements are aligned with the guidance of the OWASP Top 10 [17].

Table 3.2 Non-Functional Requirements of Testora

Category	Requirement
Performance	List endpoints for students and questions are paginated; queries populate only the references they need; the production client bundle is about 778 kB minified (about 217 kB gzipped).
Security	Passwords are stored as bcrypt hashes; sessions use signed JWTs with a 7-day default expiry; role authorization on every protected route; deactivated accounts rejected on each request; secure HTTP headers (helmet); CORS restricted to the client origin; input validation; correct answers withheld before submission. These controls follow the principles in the OWASP Top 10 [17].
Usability	Role-specific navigation; a guided three-step quiz creator; confirmation dialogs for destructive actions; loading, empty, success and error states; toast notifications.
Reliability	Test evaluation is performed on the server and attempts are persisted; quiz creation and JSON import validate the whole request before any write; uploaded temporary files are deleted after parsing; a central error handler returns JSON error messages.
Scalability	The API is stateless (JWT), so several server instances can run behind a load balancer; MongoDB Atlas can be scaled independently; code is split into routes, controllers, services and models.
Compatibility	Works in current Chrome, Edge and Firefox on desktop and mobile widths (layouts verified at 1280 px and 390 px); requires Node.js 18 or later.
Maintainability	Separation of concerns, reusable React components, documented set-up in the README and in this report.

3.3 Hardware and Software Requirements

Table 3.3 gives the minimum hardware and the software, frameworks and libraries needed to build and run the system.

Table 3.3 Hardware and Software Requirements

Component	Specification / Technology	Purpose
Processor	Dual-core 2.0 GHz or higher	Runs the Node.js server, Vite dev server and browser
Memory (RAM)	4 GB minimum, 8 GB recommended	Development tools and testing in the browser
Storage	About 1 GB free space	Source code and node_modules dependencies

Component	Specification / Technology	Purpose
Operating system	Windows 10/11, Linux or macOS (developed and tested on Windows 10 Pro)	Development and runtime platform
Runtime	Node.js 18 or later with npm (tested with Node.js 20.19.4)	Executes the backend and build tools
Database	MongoDB Atlas cluster or local MongoDB 6.x or later	Persistent storage of all application data
Browser	Current Google Chrome, Microsoft Edge or Mozilla Firefox	Access to the web application
Development tools	Visual Studio Code, Git and GitHub	Coding, version control and collaboration
Frontend libraries	React 18, React Router 6, Axios 1.6, Recharts 2.10, react-hot-toast 2.4, react-icons 5, Tailwind CSS 3.4, Vite 4.5	User interface, routing, API calls, charts and styling
Backend libraries	Express 5, Mongoose 8, jsonwebtoken 9, bcryptjs 3, express-validator 7, Multer 2, csv-parser 3, helmet 8, cors, morgan, dotenv, nodemon	REST API, security, validation, uploads and logging
Network	Internet access when using MongoDB Atlas	Connectivity to the cloud database

3.4 System Architecture

Testora follows a three-tier architecture, shown in Fig. 3.1. The **presentation tier** is a React single-page application served by Vite; it contains the public pages, the three role portals, an authentication context, protected routes and an Axios client that attaches the JWT to every request and redirects to the login page when the server answers 401. The **application tier** is an Express REST API: each request passes through security middleware, authentication and role authorization, validation chains and then a controller, which uses Mongoose models and, for analytics, a small service module. The **data tier** is a MongoDB database holding nine collections.




Fig. 3.1 System Architecture of Testora

During development the Vite server proxies every request beginning with /api to the Express server on port 5000, so the browser always talks to a single origin. In production the built static files can be served from any web server while the API runs on a Node.js host.

3.5 Data Flow / UML / Use Case / ER Diagram

3.5.1 Use Case Diagrams

Fig. 3.2, Fig. 3.3 and Fig. 3.4 show the use cases of the three actors. Every actor must first log in; the student additionally registers a new account, while teachers are created only by an administrator.




Fig. 3.2 Use Case Diagram – Student Module




Fig. 3.3 Use Case Diagram – Teacher Module




Fig. 3.4 Use Case Diagram – Admin Module

3.5.2 Data Flow Diagrams

The context diagram in Fig. 3.5 shows Testora as a single process exchanging data with the three external entities. Fig. 3.6 decomposes it into six processes and four data stores: authentication and user management (1.0), content management (2.0), mock test management (3.0), quiz management (4.0), test attempt and evaluation (5.0) and results and analytics (6.0).





Fig. 3.5 Data Flow Diagram – Level 0 (Context Diagram)



Processes 2.0, 4.0 and 5.0 also read D2 / D3 where required (arrows omitted for clarity).

Fig. 3.6 Data Flow Diagram – Level 1

3.5.3 Entity-Relationship Diagram

Fig. 3.7 shows the nine collections and their relationships. A category has many topics; a topic has many concept notes and many questions; mock tests and teacher quizzes each reference many questions; a teacher quiz has many assignments, one per student; and a user has many test attempts.




Fig. 3.7 Entity-Relationship Diagram of Testora

3.6 Database Design

Testora uses MongoDB, so each entity is a collection of documents. The primary key of every collection is the automatically generated `_id` (ObjectId) and foreign keys are stored as ObjectId references that Mongoose can populate. Every collection also has `createdAt`

and `updatedAt` timestamps. Unique indexes are defined on `User.email`, `Category.name` and on the pair (`quizId`, `studentId`) of `QuizAssignment`, which guarantees one assignment per quiz per student. Table 3.4 to Table 3.11 describe the collections.

Table 3.4 User Collection

Field	Type	Constraints / Description
firstName, lastName	String	Required, trimmed
email	String	Required, unique, lower-cased
mobile	String	Optional 10-digit mobile number
passwordHash	String	Required; bcrypt hash, removed from every JSON response
role	String	student | teacher | admin (default student)
college, course, year	String	Student details
specialization	String	Teacher's area of specialization
profilePhoto	String	Default empty
isActive	Boolean	Default true; false blocks all access

Table 3.5 Category and Topic Collections

Field	Type	Constraints / Description
Category.name	String	Required, unique
Category.description, isActive	String, Boolean	isActive default true (soft delete)
Topic.categoryId	ObjectId	Required; reference to Category
Topic.name, description	String	name required
Topic.isActive	Boolean	Default true (soft delete)

Table 3.6 Concept Collection

Field	Type	Constraints / Description
topicId	ObjectId	Required; reference to Topic
title	String	Required
content	String	Explanation text
formulas, examples, importantPoints	[String]	Lists shown on the topic detail page
isActive	Boolean	Default true

Table 3.7 Question Collection

Field	Type	Constraints / Description
categoryId	ObjectId	Required; reference to Category
topicId	ObjectId	Required; reference to Topic
question	String	Required, trimmed
options	[{label, text}]	Four options labelled A–D (enforced by validation)
correctAnswer	String	Required; one of A, B, C, D
explanation	String	Optional; default empty

Field	Type	Constraints / Description
isActive	Boolean	Default true; false hides the question
createdBy	ObjectId	Reference to User (admin or teacher)

Table 3.8 MockTest Collection

Field	Type	Constraints / Description
title, description	String	title required
questionIds	[ObjectId]	References to Question
durationMinutes	Number	Required, default 30
marksPerQuestion	Number	Required, default 1
negativeMarksPerQuestion	Number	Required, default 0 (0 = no negative marking)
isPublished	Boolean	Default false; students see only published tests
createdBy	ObjectId	Reference to User (admin)

Table 3.9 TeacherQuiz Collection

Field	Type	Constraints / Description
title, description	String	title required
categoryId	ObjectId	Required; reference to Category
questionIds	[ObjectId]	References to Question
durationMinutes	Number	Required, default 20
marksPerQuestion, negativeMarksPerQuestion	Number	Defaults 1 and 0
startDate, endDate	Date	Required; the quiz can be started only inside this window
createdBy	ObjectId	Required; reference to User (teacher)
status	String	draft | published | expired (default draft)

Table 3.10 QuizAssignment Collection

Field	Type	Constraints / Description
quizId	ObjectId	Required; reference to TeacherQuiz
studentId	ObjectId	Required; reference to User (student)
assignedBy	ObjectId	Required; reference to User (teacher)
status	String	assigned | started | completed | expired
assignedAt, completedAt	Date	assignedAt defaults to the current time
(quizId, studentId)	Unique index	One assignment per quiz per student

Table 3.11 TestAttempt Collection

Field	Type	Constraints / Description
userId	ObjectId	Required; reference to User (student)
testType, testId	String, ObjectId	mockTest | teacherQuiz; id of the MockTest or TeacherQuiz
testTitle	String	Copied at start so history survives edits
answers	[Object]	questionId, topicId, categoryId, selectedAnswer (null = skipped), correctAnswer, isCorrect
score, maxMarks	Number	Marks obtained and maximum possible marks

Field	Type	Constraints / Description
totalQuestions	Number	Required
correctAnswers, wrongAnswers, skippedAnswers	Number	Counts
accuracy	Number	Percentage = correct ÷ (correct + wrong)
startedAt, submittedAt, timeTakenSeconds	Date, Number	Timing information
topicPerformance	[Object]	Per-topic attempted, correct and accuracy
status	String	inProgress | completed | expired

3.7 Module Design

The application is divided into ten modules. Each module has a clear responsibility, is reachable only by the roles shown, and communicates with other modules through the REST API and the shared database. Table 3.12 summarises them and Table 4.4 in Chapter 4 lists their inputs and outputs.

Table 3.12 Module Overview

Module	Responsibility	Roles	Screens / API prefix
Authentication & Authorization	Register, login, token verification, role checks, deactivation check	All roles	/api/auth; Login, Register, ProtectedRoute
User Management	List students and teachers, create teachers, activate or deactivate accounts	Admin	/api/admin; Students, Teachers
Content Management	Categories, topics, concept notes and the question bank	Admin	/api/categories, /topics, /concepts, /questions
Import / Export	JSON import, CSV import, CSV export of questions	Admin	/api/questions/import-json, /import, /export
Mock Test Management	Create, edit, publish and delete timed mock tests with marking scheme	Admin	/api/mock-tests; Mock Tests screen
Quiz Management	Three-step quiz creation, automatic assignment, quiz list, results	Teacher	/api/quizzes; Create Quiz, Quiz Results
Test Attempt & Evaluation	Start attempt, serve questions without answers, timer, submit, evaluate and score	Student	/api/mock-tests/:id/start|submit, /api/quizzes/:id/start|submit
Practice & Learning	Topic browsing, concept notes, untimed practice with instant feedback	Student	/api/questions/practice; Topics, Practice
Performance Analytics	Overview, topic-wise accuracy, weak-topic detection, history, result review	Student	/api/performance; Performance, History, Result
Common UI Services	Layout, loading and empty states, confirmation dialog, toasts, API client	All roles	DashboardLayout, ConfirmDialog, api.js

Authentication and authorization verifies the token, loads the user and rejects the request if the account is missing or deactivated, then compares the user's role with the roles allowed for the route. **User management** and **content management** give the administrator control over accounts and subjects. **Import/export** moves questions in and out of the system in bulk. **Mock test** and **quiz management** define the tests; **test attempt and evaluation** runs them and produces the score; **practice and learning** and **performance**

analytics give students feedback; and the **common UI services** keep the interface consistent.

CHAPTER 4
IMPLEMENTATION

4.1 Development Environment

The system was developed in a local environment with the frontend and the backend running as two separate Node.js processes and a MongoDB Atlas database. Table 4.1 summarises the environment.

Table 4.1 Development Environment

Item	Details
Operating system	Windows 10 Pro
Runtime	Node.js 20.19.4 with npm
Code editor / VCS	Visual Studio Code; Git with a GitHub repository
Database	MongoDB Atlas cloud cluster (Mongoose ODM 8)
Frontend toolchain	React 18, React Router 6, Tailwind CSS 3.4, Vite 4.5 (development server on port 5173)
Backend	Express 5 started with nodemon on port 5000; configuration read from a .env file
Test tooling	Python 3 (requests) for API tests; Playwright with Google Chrome for the browser walkthrough; vite build for build verification

4.2 Module-wise Implementation

4.2.1 Authentication and Session Handling

Registration is open only to students: the controller ignores any role sent in the request and always stores `role: 'student'`. Teachers are created only by an administrator. At login the server finds the user by e-mail, rejects deactivated accounts, compares the password with the stored bcrypt hash and returns a JWT whose payload contains only the user id; the token lifetime is read from `JWT_EXPIRE` (7 days by default). The React `AuthContext` keeps the token and user in `localStorage`, re-validates the session with `GET /api/auth/me` on start-up, and `ProtectedRoute` redirects visitors without a session to the login page and users with the wrong role to their own dashboard. The Axios client adds the `Authorization` header to every request and, on any 401 response, clears the stored session and redirects to the login page.

On the server, the `protect` middleware verifies the token and then reloads the user from the database, so a deactivated account is rejected on its very next request even if its token has not expired. The `authorize` middleware then compares the role with the roles allowed for the route.

Excerpt: server/middleware/auth.js

```
const protect = async (req, res, next) => {
  let token;

  if (req.headers.authorization && req.headers.authorization.startsWith('Bearer')) {
    token = req.headers.authorization.split(' ')[1];
  }

  if (!token) {
    return res.status(401).json({ success: false, message: 'Not authorized, no token'
        });
  }

  try {
    const decoded = jwt.verify(token, process.env.JWT_SECRET);
    const user = await User.findById(decoded.id);

    if (!user) {
      return res.status(401).json({ success: false, message: 'User not found' });
    }

    if (!user.isActive) {
      return res.status(401).json({ success: false, message: 'Account is deactivated'
          });
    }
```

4.2.2 User Management

The administrator's student list is paginated and searchable, and the toggle endpoint flips the `isActive` flag. Because `protect` checks this flag on each request, deactivation takes effect immediately (verified by test case TC11). Teachers are created with name, e-mail, mobile, password and specialization and are validated by `express-validator`. The dashboard obtains its counts in one `Promise.all` of `countDocuments` calls, so the numbers always reflect the database.

4.2.3 Content Management

Categories, topics, concepts and questions use the same pattern of route, validator, controller and model. Deleting a category, topic or question sets `isActive` to false instead of removing the document, so past quizzes and attempts that refer to it remain valid. The question list accepts `categoryId`, `topicId`, a case-insensitive text search and paging parameters. The raw question list, which contains correct answers, is reachable only by administrators and teachers; students receive questions only through the practice, mock test and quiz endpoints, which remove `correctAnswer` and `explanation`.

4.2.4 Import and Export

The JSON importer first validates every item (question text, four options, a correct answer of A–D, an existing category and an existing topic that belongs to that category) and checks for duplicates inside the file and against the database. If any item fails, the whole request is rejected with a list of item numbers and reasons and nothing is saved; only a fully valid batch is inserted with a single `insertMany`. The uploaded file is limited to 2 MB and to the

`.json` type by Multer, and an import may contain at most 500 questions. The CSV importer reports row-level errors but imports the valid rows.

CSV export builds a header row and one row per question and quotes every value that contains a comma, a double quote or a line break, doubling embedded quotes, as required by the CSV format specification [18]. The export accepts the same `categoryId`, `topicId` and `search` filters as the question list, so either all or filtered questions can be exported.

4.2.5 Mock Test Management

The administrator selects questions from the bank (optionally filtered by category), sets the duration, the marks per question and an optional negative mark and saves the test. A test is invisible to students until it is published; publishing is a partial update that changes only `isPublished`, which is why the update route validates only the fields that were sent.

4.2.6 Teacher Quiz Creation

The Create Quiz page is a wizard with three steps. Step 1 loads the categories created by the administrator, so any new category appears immediately. Step 2 collects the quiz details and validates the dates and numeric limits. When the teacher continues, step 3 generates as many question forms as the chosen question count (1 to 50). On submission the client sends one request containing the quiz details and all questions. The server validates the payload, confirms that the category exists and that every selected topic belongs to it, inserts the questions with `insertMany`, creates the quiz with the new question ids, and the client then calls the assignment endpoint with `assignAll: true`.

4.2.7 Test Attempt and Evaluation

Starting a test checks the rules for that test type: a mock test must be published and not already completed; a quiz must be assigned to the student, published and inside its start–end window. A new attempt with status `inProgress` is stored and the questions are returned without `correctAnswer` and `explanation`. On submission the server loads the questions with their correct answers, compares each submitted answer, counts correct, wrong and skipped answers, calculates the marks, builds the topic-wise performance and saves the completed attempt. The correct answers are copied into the attempt, so the review stays accurate even if a question is edited later.

Excerpt: server/controllers/mockTestController.js (submitMockTest)

```
    test.questionIds.forEach((q) => {
      questionMap[q._id.toString()] = q;
    });

    const processedAnswers = [];
    let correct = 0;
    let wrong = 0;
    let skipped = 0;
    // ...
```

```
    const marksPerQuestion = test.marksPerQuestion || 1;
    const negativeMarksPerQuestion = test.negativeMarksPerQuestion || 0;
    const obtainedMarks = Math.round((correct * marksPerQuestion - wrong *
        negativeMarksPerQuestion) * 100) / 100;
    const maxMarks = Math.round(test.questionIds.length * marksPerQuestion * 100) / 100;
```

4.2.8 Practice and Learning

The topic detail page reads the topic, its concept cards and the question count from a single endpoint. Practice mode loads the topic's questions without answers and checks each answer through `POST /api/questions/practice/submit`, which returns whether the answer is correct, the correct option and the explanation. Practice answers are not stored as attempts.

4.2.9 Performance Analytics

Every completed attempt stores a per-topic summary. The analytics endpoints add these summaries over all of a student's attempts, compute the accuracy for each topic and classify it with the function below. Topics with fewer than five attempted questions are shown as "Not Enough Data".

4.2.10 Common Interface Components

Shared components keep the three portals consistent: a role-aware `DashboardLayout` with a collapsible sidebar, `LoadingSpinner` and `EmptyState` components, toast notifications from react-hot-toast and a promise-based `ConfirmDialog` hook that replaces the browser's `confirm()` for destructive actions such as deleting a quiz or deactivating a user.

4.3 Algorithms / Business Logic

4.3.1 Test Evaluation and Scoring

Fig. 4.1 shows the life cycle of an attempt. The scoring rule is applied on the server for both mock tests and quizzes:

Pseudocode: scoring

```
for each question q in the test:
    selected = answer submitted for q, or null
    if selected is null:            skipped = skipped + 1
    else if selected == q.correct:  correct = correct + 1
    else:                           wrong   = wrong + 1

score     = correct x marksPerQuestion  -  wrong x negativeMarksPerQuestion
maxMarks  = numberOfQuestions x marksPerQuestion
accuracy  = round(100 x correct / (correct + wrong))    // 0 if nothing attempted
```

Skipped questions never reduce the score. For example, with 2 marks per question and a negative mark of 0.5, one correct and one wrong answer in a two-question test give 2 − 0.5 = 1.5 marks out of 4 (test cases TC23 and TC27).




Fig. 4.1 Test Attempt and Evaluation Flowchart

4.3.2 Topic Classification

After at least five attempted questions in a topic, the aggregate accuracy decides its status, as shown in Table 4.2.

Table 4.2 Topic Classification Rules

Condition (aggregate over all attempts)	Status shown to the student
Fewer than 5 attempted questions	Not Enough Data
Accuracy below 60 %	Weak
Accuracy from 60 % to 80 %	Needs Practice
Accuracy above 80 %	Strong

4.3.3 All-or-Nothing JSON Import

Pseudocode: JSON import

```
errors = []; seen = {}
for each item i in questions:
    check question text, options A-D, correctAnswer in {A,B,C,D}
    check category exists and topic exists and topic belongs to category
    key = category + topic + lower-case(question)
    if key already in seen: error "duplicate in file"
    otherwise remember key
if errors is not empty:  reject whole request (400) with errors; save nothing
if any key exists in database: reject whole request (400); save nothing
insertMany(all items)    // only reached when the whole batch is valid
```

4.3.4 Quiz Creation and Assignment

Pseudocode: quiz creation

```
validate request fields (express-validator)
verify category exists; verify each topic exists and belongs to the category
questions  = insertMany(question forms)
quiz       = create TeacherQuiz(categoryId, questionIds = questions._id, marks, dates)
assign     : for every active student  upsert QuizAssignment(quiz, student)
             and set quiz.status = published
```

4.4 User Interface / Screens

The main screens of each portal are shown below. All screenshots were captured from the running application with the demonstration data set.




Fig. 4.2 Login Screen

The login screen validates that both fields are filled and shows the server's message (for example "Invalid credentials" or "Account is deactivated. Contact admin.") as a notification. After a successful login the user is redirected to the dashboard of their own role.




Fig. 4.3 Student Dashboard

The student dashboard summarises tests attempted, questions solved, average accuracy and correct answers, lists topics to improve with a direct "Practice Now" link, shows pending quizzes and the most recent results.




Fig. 4.4 Topic Detail with Concept Cards

A topic page shows its description, the number of concepts and questions and expandable concept cards containing the explanation, formulas, worked examples and important points.




Fig. 4.5 Timed Exam Screen with Question Palette

The exam screen shows a countdown timer, one question at a time, navigation buttons, a mark-for-review button and a palette in which answered, marked and unanswered questions have different colours.




Fig. 4.6 Result Screen

After submission the result screen shows accuracy, the number of correct, wrong and skipped answers, the time taken, the marks obtained out of the maximum (here 20.5 out of 30 with negative marking) and the topic-wise performance.




Fig. 4.7 Performance Analysis

The performance screen aggregates all completed attempts into overall statistics, a topic-accuracy chart, a classification of each topic and a list of recommended practice topics.




Fig. 4.8 Create Quiz – Step 2: Quiz Details

In step 2 the teacher enters the title, description, number of questions, duration, marks per question, optional negative marking and the start and end date-time of the quiz.




Fig. 4.9 Create Quiz – Step 3: Set Questions

Step 3 generates one form for each requested question. Each form requires a topic, the question text, four options, the correct option and optionally an explanation; submitting creates the questions, creates the quiz and assigns it to all active students.




Fig. 4.10 Admin Dashboard

The admin dashboard shows live database counts in the order Total Students, Total Teachers, Total Topics and Total Questions, followed by mock test and attempt counts and the most recent attempts.




Fig. 4.11 Admin – Import Questions via JSON

The import dialog documents the JSON format, accepts a .json file of up to 2 MB or pasted JSON and explains that nothing is imported if any question fails validation or is a duplicate.

4.5 Integration and Deployment

The client and server are integrated through the REST API. In development, the Vite server forwards requests whose path starts with `/api` to the Express server, so the React code simply calls relative URLs such as `/api/auth/login`. The Express server connects to MongoDB through Mongoose when it starts and reads its settings from environment variables, listed in Table 4.3. The values shown are the placeholders from the `.env.example` file; real secrets must never be committed.

Table 4.3 Environment Variables of the Server

Variable	Purpose	Example / placeholder
PORT	Port of the Express server	5000
MONGODB_URI	MongoDB connection string (local or Atlas)	mongodb://localhost:27017/testora
JWT_SECRET	Secret used to sign and verify tokens (must be long and private)	your_super_secret_jwt_key_change_in_production
JWT_EXPIRE	Token lifetime	7d

Variable	Purpose	Example / placeholder
CLIENT_URL	Browser origin allowed by CORS	http://localhost:5173
NODE_ENV	Environment name	development

The steps to run the system are: (1) install dependencies in the `server` and `client` folders with `npm install`; (2) copy `.env.example` to `.env` and set the values; (3) optionally load the demonstration data with `npm run seed`, which first clears the target database; (4) start the API with `npm run dev` in `server`; (5) start the client with `npm run dev` in `client` and open `http://localhost:5173`. A production build of the client is produced with `npm run build` and is a set of static files that can be hosted on any web server, while the API can be run with `npm start` on any Node.js host; `CLIENT_URL` must then be set to the public address of the client. The server creates the `uploads` folder used for temporary import files when it starts. No public deployment was carried out for this mini project; the complete installation guide is given in Appendix A.

4.6 Security and Validation

Fig. 4.12 shows the path of a request through the security controls of the API.




Fig. 4.12 Request Authentication and Authorization Pipeline

- **Authentication.** Passwords are hashed with bcrypt (10 salt rounds) before storage and the hash is removed from every JSON response. Tokens are signed with `JWT_SECRET`.
- **Authorization.** Every route except registration, login and the health check calls `protect`, and routes that belong to one role also call `authorize`. A student cannot read the question bank, create a quiz or open the admin dashboard (test cases TC06 to TC09).

- **Role protection.** The registration endpoint always stores the role `student`, so a user cannot make themselves an administrator by adding a role to the request (TC04).
- **Answer secrecy.** Question payloads sent before submission never include `correctAnswer` or `explanation` (TC22, TC31); the review is available only from the stored attempt of the same student (TC29, TC30).
- **Input validation.** `express-validator` chains validate registration, login, teachers, categories, topics, questions, quizzes (including 1–50 questions, valid dates and numeric marks) and mock tests; failures return HTTP 400 with the first message and a list of field errors.
- **File upload control.** Multer limits CSV files to 5 MB and JSON files to 2 MB and 500 questions, accepts only the `.json` type for JSON, and the temporary file is deleted after it has been read.
- **Transport and headers.** `helmet` sets secure HTTP headers, CORS allows only the configured client origin and the JSON body size is limited.
- **Exception handling.** Controllers catch errors and a central error handler converts Mongoose cast, duplicate-key and validation errors and upload errors into clear JSON messages with suitable status codes.
- **Data protection.** Content is soft-deleted (`isActive`) so history is preserved, and deactivated accounts are blocked immediately.

Table 4.4 Module Inputs and Outputs

Module	Purpose	Input	Output
Authentication	Create and verify user sessions	E-mail, password, registration details, token	Signed JWT, user profile, 401/403 errors
User Management	Control accounts and teacher records	Student or teacher id, teacher details	Updated user record, status message
Content Management	Maintain categories, topics, concepts, questions	Names, descriptions, question text, options, correct answer	Stored records, filtered question lists
Import / Export	Bulk load and export questions	JSON body or .json file, CSV file, filters	Import summary or error list, CSV download
Mock Test Management	Define and publish timed tests	Title, question ids, duration, marks, negative marks	Mock test record, published state
Quiz Management	Create and assign teacher quizzes	Category, details, question forms, dates	Quiz, new questions, assignments, results table
Test Attempt & Evaluation	Run and score attempts	Test id, answers, time taken	Attempt with score, maxMarks, counts, topic performance
Practice & Learning	Learn and practise by topic	Topic id, selected answer	Concept cards, correctness, explanation
Performance Analytics	Summarise results	Student’s completed attempts	Overview, topic accuracy, weak topics, history
Common UI Services	Shared interface behaviour	User actions	Layout, dialogs, toasts, spinners

CHAPTER 5
TESTING & RESULTS

5.1 Testing Strategy

Testing combined four activities, following the usual progression from component checks to system-level validation [16]:

- **API functional testing.** A script of 41 test cases called the REST API with valid and invalid inputs for every role and recorded the actual response of each call. The script was run against a separate demonstration database seeded with the sample data, so the working data was never modified.
- **Browser walkthrough.** A scripted Google Chrome session logged in as a student, a teacher and an administrator and used the real screens: a student took a mock test and another student took a quiz through the "Start" buttons, a teacher created a quiz through the three-step wizard and an administrator opened every management screen. The screenshots in Chapter 4 come from this session.
- **Security testing.** Role restrictions, answer secrecy, role injection at registration and immediate blocking of deactivated users were tested explicitly.
- **Build and responsiveness checks.** The client was compiled with `vite build` and the main screen was captured at a phone-sized viewport (390 × 844).

No automated unit-test framework or load-testing tool was used; this is listed under the limitations in Section 5.5.

5.2 Test Cases

Table 5.1 lists the executed test cases with the actual result recorded by the script.

Table 5.1 Test Cases and Results

Test Case ID	Module	Input / Condition	Expected Result	Actual Result	Status
TC01	Authentication	Valid admin e-mail and password	200, JWT token and role = admin	200, token issued, role = admin	Pass
TC02	Authentication	Valid e-mail, wrong password	401 Invalid credentials	401, "Invalid credentials"	Pass
TC03	Authentication	Empty login payload	400 with validation message	400, "Valid email is required"	Pass
TC04	Authentication	Register with extra field role = "admin"	201 and role forced to student	201, role = student	Pass
TC05	Authentication	Protected route without token	401 Not authorized	401, "Not authorized, no token"	Pass
TC06	Authorization	Student calls GET /admin/dashboard	403 Forbidden	403, "Role 'student' is not authorized to access this route"	Pass
TC07	Authorization	Student calls GET /questions (answer bank)	403 Forbidden (answers not exposed)	403	Pass
TC08	Authorization	Student calls POST /quizzes	403 Forbidden	403	Pass

Test Case ID	Module	Input / Condition	Expected Result	Actual Result	Status
TC09	Authorization	Teacher calls GET /admin/teachers	403 Forbidden	403	Pass
TC10	Admin dashboard	Compare dashboard counts with list endpoints	Counts equal database records	students 5/5, topics 22/22, questions 61/61	Pass
TC11	Student management	Deactivate student; reuse existing token and try login	401 for old token and for new login	token: 401 "Account is deactivated"; login: 401 "Account is deactivated. Contact admin."	Pass
TC12	Teacher management	Admin creates teacher with specialization	201 and specialization saved	201, specialization = Logical Reasoning	Pass
TC13	Teacher management	Create teacher with invalid data	400 validation error	400, "First name is required"	Pass
TC14	Categories	Create category with empty name	400 Category name is required	400, "Category name is required"	Pass
TC15	Categories	Create category (admin)	201 and category saved	201, name = Data Interpretation	Pass
TC16	Quiz creation	End date earlier than start date	400 End date must be after start date	400, "End date must be after start date"	Pass
TC17	Quiz creation	Topic does not belong to selected category	400 topic/category mismatch	400, "Topic 'Percentages' does not belong to the selected category"	Pass
TC18	Quiz creation	Quiz with zero questions	400 validation error	400, "Between 1 and 50 questions are required"	Pass
TC19	Quiz creation	Valid quiz, 2 inline questions, 2 marks, -0.5	201; 2 new questions saved; marks stored	201; questions 61->63; marks 2/-0.5	Pass
TC20	Quiz assignment	Assign with assignAll = true	Assigned to every active student	200, 4 assignments / 4 active students	Pass
TC21	Quiz attempt	Start a quiz before its start date	400 Quiz has not started yet	400, "Quiz has not started yet"	Pass
TC22	Quiz attempt	Start assigned quiz; inspect question payload	Questions returned without correctAnswer / explanation	200, 2 questions, answer fields present = False	Pass
TC23	Scoring (quiz)	1 correct + 1 wrong, 2 marks each, -0.5 negative	score = 1.5, maxMarks = 4	score = 1.5, maxMarks = 4, accuracy = 50%	Pass
TC24	Quiz results	Teacher opens results of the quiz	Completed student with marks obtained / max marks	Arjun: 1.5/4	Pass
TC25	Mock tests	Partial update: isPublished = true	200 and only that field changes	200, isPublished = True, title kept = TC Mock	Pass
TC26	Mock tests	Update with invalid isPublished	400 validation error	400, "isPublished must be true or false"	Pass
TC27	Scoring (mock test)	1 correct + 1 wrong, 2 marks each, -0.5 negative	score = 1.5, maxMarks = 4	score = 1.5, maxMarks = 4	Pass
TC28	Mock tests	Start the same mock test a second time	400 already attempted	400, "You have already attempted this test"	Pass
TC29	Results	Student opens own result after submission	Review shows correct answers only after submission	200, correctAnswer in review = B	Pass
TC30	Results	Another student requests this attempt	404 (attempts are private)	404	Pass
TC31	Practice	Load practice questions for a topic	No answer fields before answering	200, 12 questions, answer fields present = False	Pass
TC32	Practice	Submit one practice answer	Feedback with isCorrect, correctAnswer, explanation	200, keys = ['correctAnswer', 'explanation', 'isCorrect']	Pass
TC33	JSON import	Valid JSON body (1 question)	201, 1 question imported	201, "Imported 1 questions successfully."	Pass
TC34	JSON import	Re-import the same question	400, rejected as duplicate	400, "Import rejected: 1 question(s) already exist in the question bank. No questions were imported."	Pass

Test Case ID	Module	Input / Condition	Expected Result	Actual Result	Status
TC35	JSON import	Batch of 2: one valid, one missing option D	400, nothing imported (no partial import)	400, question count 65 -> 65; error: Missing option D	Pass
TC36	JSON import	Unknown category name	400, category not found	400, "Category 'Nope' not found"	Pass
TC37	JSON import	Upload a .txt file	400 Only .json files are allowed	400, "Only .json files are allowed"	Pass
TC38	JSON import	Upload a 3797 KB .json file (limit 2 MB)	400 File too large	400, "File too large"	Pass
TC39	JSON import	501 questions in one import (limit 500)	400 import limit exceeded	400, "Import limit exceeded: a single import supports at most 500 ..."	Pass
TC40	CSV export	Export question containing comma, quotes and newline	CSV with header; special characters quoted/escaped (RFC 4180)	200, text/csv; charset=utf-8, escaped correctly = True	Pass
TC41	CSV export	Export filtered by category	Only that category's rows exported	16 rows exported / 16 questions in category	Pass

5.3 Results / Output

All 41 test cases passed (41 of 41). Table 5.2 shows the results by module.

Table 5.2 Test Results by Module

Module	Test Cases	Passed
Authentication	5	5
Authorization	4	4
Admin dashboard	1	1
Student management	1	1
Teacher management	2	2
Categories	2	2
Quiz creation	4	4
Quiz assignment	1	1
Quiz attempt	2	2
Scoring (quiz)	1	1
Quiz results	1	1
Mock tests	3	3
Scoring (mock test)	1	1
Results	2	2
Practice	2	2
JSON import	7	7
CSV export	2	2
Total	**41**	**41**

In the browser walkthrough every screen of the three portals loaded with data, the student completed a mock test (11 correct, 3 wrong, 1 skipped in a 15-question test with 2 marks per question and a negative mark of 0.5, giving 20.5 out of 30 marks) and a quiz, the teacher’s quiz results showed the completed student’s marks (for example 4.25 out of 8 for

5 correct and 3 wrong answers at 1 mark and a negative mark of 0.25), and the production build of the client completed successfully. Table 5.3 compares the outcome with the objectives set in Chapter 1.

Table 5.3 Objectives and Outcome

No.	Objective (summary)	Outcome
1	Role-based portals with JWT and server-side role checks	Achieved – TC01 to TC09 passed; three portals implemented
2	Category → Topic → Question hierarchy with admin-managed content	Achieved – demonstration data: 3 categories, 22 topics, 58 questions, 5 mock tests
3	Server-side evaluation, marks, negative marking, answer secrecy	Achieved – TC22, TC23, TC27, TC29 to TC32 passed
4	Three-step quiz creation with dynamic forms and auto-assignment	Achieved – TC16 to TC20 passed; screens in Fig. 4.8 and Fig. 4.9
5	Topic-wise analytics with Weak / Needs Practice / Strong	Achieved – performance screen verified in the browser walkthrough
6	Validated JSON import, CSV export and at least 40 test cases	Achieved – 41 test cases executed, TC33 to TC41 cover import and export

5.4 Error Handling and Validation Results

Table 5.4 shows how the system responds to invalid input and exceptional situations; the test case numbers refer to Table 5.1.

Table 5.4 Handling of Invalid Inputs and Exceptions

Situation	Observed system behaviour
Wrong password at login	401 with the message “Invalid credentials”; the user stays on the login page (TC02)
Empty or malformed input	400 with the first validation message and the list of field errors (TC03, TC13, TC14, TC18)
Quiz end date before start date	400 “End date must be after start date”; nothing is saved (TC16)
Topic from a different category	400 “Topic … does not belong to the selected category” (TC17)
Deactivated account	Existing token and new login are both rejected with “Account is deactivated” (TC11)
Access to another role’s route	403 “Role … is not authorized to access this route” (TC06 to TC09)
Starting a quiz too early / test twice	400 “Quiz has not started yet” and “You have already attempted this test” (TC21, TC28)
Invalid or duplicate JSON import	400 with an item-wise error list or a duplicate message; question count unchanged (TC34 to TC36)
Wrong file type, too large file, too many items	400 “Only .json files are allowed”, “File too large”, “Import limit exceeded” (TC37 to TC39)

5.5 Limitations

- **Resuming a mock test is not supported.** If a student reloads the page while a mock test is in progress, the start endpoint returns the stored attempt record instead of the question set, so the exam screen cannot be restored and the timer is not recovered.

Quiz attempts do not have this problem. This is the most important defect found and is the first item of the future work.

- **No automated test suite in the repository.** The test script used for this report ran outside the project and is not part of it; there are no unit or integration tests and no continuous integration.
- **Password rule is enforced only in the browser.** The registration form requires at least one upper-case letter, but the server enforces only a minimum length of six characters.
- **Session handling is simple.** The token is kept in `localStorage`, there is no refresh token, rate limiting, account lockout, e-mail verification or password reset; the 7-day token lifetime is mitigated only by the per-request active-user check.
- **Limited question model.** Only single-answer multiple-choice questions with four options are supported, question order is not randomised and each mock test or quiz can be attempted once.
- **CSV and JSON imports differ.** The CSV importer imports valid rows and reports invalid ones, whereas the JSON importer is all-or-nothing.
- **Scope of testing.** The interface was tested in Chrome only, the load and concurrency behaviour was not measured, and the system was not deployed to a public server.
- **Teachers and students cannot be deleted**, only deactivated, by design.

CHAPTER 6
CONCLUSION & FUTURE SCOPE

6.1 Conclusion

Students preparing for aptitude examinations lacked one integrated platform that the college could control, and teachers lacked a simple way to set and monitor timed tests. This project delivered *Testora*, a role-based web application in which administrators manage users, subjects, questions and mock tests, teachers create and assign quizzes through a guided workflow, and students learn concepts, practise, take timed tests and receive marks-based results with topic-wise feedback.

The objectives set in Chapter 1 were met. The three portals are secured with JWT authentication and server-side role checks, content is organised as Category → Topic → Question, tests are evaluated on the server with configurable marks and negative marking without exposing correct answers, quiz creation generates question forms dynamically and assigns the quiz automatically to all active students, performance is analysed topic by topic, and questions can be imported from validated JSON and exported to CSV. All 41 documented test cases passed and the complete user flows were demonstrated in a browser.

The work also showed the importance of validating on the server, of deciding explicitly which data a student may see, and of testing role boundaries as carefully as normal functions. The known limitations, in particular the missing resume support for in-progress mock tests, are listed in Section 5.5.

6.2 Future Scope

- Restore an in-progress mock test after a page reload, including the remaining time, and expire abandoned attempts automatically.
- Add PDF export or printing of question sets and result sheets.
- Randomise question and option order, add question difficulty levels and more question types such as multiple-answer and numeric answers.
- Add proctoring aids such as full-screen enforcement and tab-switch detection, and allow re-attempts under teacher control.
- Add an automated regression suite (unit, API and end-to-end tests) and a continuous-integration pipeline.
- Strengthen account security with refresh tokens, rate limiting, e-mail verification, password reset and server-side enforcement of the password strength rule.

- Add notifications (e-mail or in-app) when a quiz is assigned, leaderboards and downloadable analytics for teachers.
- Reduce the size of the client bundle with route-based code splitting and deploy the application to a public host with HTTPS.

REFERENCES

[1] Meta Platforms, Inc., “React documentation,” React. Accessed: [DD-MMM-2026]. [Online]. Available: https://react.dev/

[2] OpenJS Foundation, “Express – Node.js web application framework,” Express.js. Accessed: [DD-MMM-2026]. [Online]. Available: https://expressjs.com/

[3] MongoDB, Inc., “MongoDB manual,” MongoDB Documentation. Accessed: [DD-MMM-2026]. [Online]. Available: https://www.mongodb.com/docs/manual/

[4] Mongoose contributors, “Mongoose documentation,” Mongoose ODM. Accessed: [DD-MMM-2026]. [Online]. Available: https://mongoosejs.com/docs/

[5] M. Jones, J. Bradley, and N. Sakimura, “JSON Web Token (JWT),” Internet Engineering Task Force, RFC 7519, May 2015. [Online]. Available: https://www.rfc-editor.org/rfc/rfc7519

[6] N. Provos and D. Mazières, “A future-adaptable password scheme,” in Proc. USENIX Annual Technical Conf. (FREENIX Track), Monterey, CA, USA, 1999, pp. 81–91.

[7] Tailwind Labs, “Tailwind CSS documentation,” Tailwind CSS. Accessed: [DD-MMM-2026]. [Online]. Available: https://tailwindcss.com/docs

[8] Vite contributors, “Vite – Getting started,” Vite. Accessed: [DD-MMM-2026]. [Online]. Available: https://vite.dev/guide/

[9] Recharts contributors, “Recharts – a redefined chart library built with React and D3,” Recharts. Accessed: [DD-MMM-2026]. [Online]. Available: https://recharts.org/

[10] express-validator contributors, “express-validator documentation,” express-validator. Accessed: [DD-MMM-2026]. [Online]. Available: https://express-validator.github.io/docs/

[11] Express.js contributors, “Multer – Node.js middleware for handling multipart/form-data,” GitHub. Accessed: [DD-MMM-2026]. [Online]. Available: https://github.com/expressjs/multer

[12] Moodle Pty Ltd, “Quiz activity,” MoodleDocs. Accessed: 30-Oct-2026. [Online]. Available: https://docs.moodle.org/en/Quiz_activity

[13] Google LLC, “Create & grade quizzes with Google Forms,” Google Docs Editors Help. Accessed: 30-Oct-2026. [Online]. Available: https://support.google.com/docs/answer/7032287

[14] IndiaBIX Technologies, “Aptitude questions and answers,” IndiaBIX. Accessed: 30-Oct-2026. [Online]. Available: https://www.indiabix.com/aptitude/questions-and-answers/

[15] Testbook Edu Solutions Pvt. Ltd., “Testbook.com – India’s No.1 Govt Exam Preparation Site | Online Course | Mock Test,” Testbook. Accessed: 30-Oct-2026. [Online]. Available: https://testbook.com/

[16] I. Sommerville, Software Engineering, 10th ed. Harlow, U.K.: Pearson Education, 2016.

[17] OWASP Foundation, “OWASP Top 10:2021,” OWASP. Accessed: [DD-MMM-2026]. [Online]. Available: https://owasp.org/Top10/

[18] Y. Shafranovich, “Common format and MIME type for comma-separated values (CSV) files,” Internet Engineering Task Force, RFC 4180, Oct. 2005. [Online]. Available: https://www.rfc-editor.org/rfc/rfc4180

APPENDICES

Appendix A – User Manual / Installation Guide

Prerequisites. Node.js 18 or later with npm, Git, and either a MongoDB Atlas account or a local MongoDB server.

1. Get the source code: `git clone https://github.com/oskhamkar/Testora` and open the folder.
2. Backend: `cd server`, run `npm install`, copy `.env.example` to `.env` and set `MONGODB_URI`, `JWT_SECRET` (a long random value), `JWT_EXPIRE`, `PORT` and `CLIENT_URL` (see Table 4.3).
3. Optional demonstration data: run `npm run seed` in `server`. This clears the target database first and then creates the demonstration users, 3 categories, 22 topics, 5 concepts, 58 questions, 5 mock tests and one teacher quiz.
4. Start the API: `npm run dev` in `server`. The message "Testora server running on port 5000" and "MongoDB Connected" confirm that it is ready; `GET /api/health` returns a JSON status.
5. Frontend: `cd client`, run `npm install` and `npm run dev`, then open `http://localhost:5173` in a browser.

Demonstration accounts (created by the seed script; change the passwords before any real use):

Table A.1 Demonstration Accounts

Role	E-mail	Password
Admin	admin@testora.com	Admin@123
Teacher	teacher@testora.com	Teacher@123
Student	rahul@testora.com	Student@123
Student	sneha@testora.com	Student@123

Using the system. *Student:* register or log in, open Topics to read concepts, use Practice for untimed questions, take a published mock test from Mock Tests or an assigned quiz from My Quizzes, then open the result for the answer review and use Performance to see weak topics. *Teacher:* open Quiz Management, choose Create Quiz, select a category, enter the details, fill in the generated question forms and submit; open Results on a quiz to see the class. *Administrator:* use the sidebar to manage students, teachers, categories, topics, concepts, questions (including Import JSON, Import CSV and Export CSV) and mock tests; use the eye button on a mock test to publish or unpublish it.

Appendix B – Test Evidence

Table B.1 shows the test cases grouped by module; the full list with inputs and actual results is in Table 5.1.

Table B.1 Test Evidence by Module

Module	Test case IDs
Authentication	TC01, TC02, TC03, TC04, TC05
Authorization	TC06, TC07, TC08, TC09
Admin dashboard	TC10
Student management	TC11
Teacher management	TC12, TC13
Categories	TC14, TC15
Quiz creation	TC16, TC17, TC18, TC19
Quiz assignment	TC20
Quiz attempt	TC21, TC22
Scoring (quiz)	TC23
Quiz results	TC24
Mock tests	TC25, TC26, TC28
Scoring (mock test)	TC27
Results	TC29, TC30
Practice	TC31, TC32
JSON import	TC33, TC34, TC35, TC36, TC37, TC38, TC39
CSV export	TC40, TC41

Appendix C – Supporting Documents

No supporting documents such as an internship or company confirmation, survey or questionnaire, publication or certificate, or third-party API permission were required for this mini project, so this appendix is not applicable. The information about existing systems in Chapter 2 is taken from the public web pages listed in the References.