

Analysis

Bernd Bruegge, Stephan Krusche, Andreas Seitz, Jan Knobloch
Chair for Applied Software Engineering — Faculty of Informatics





Learning Goals

- 1) Understand the term analysis
- 2) Understand three different concepts of analysis
- 3) Apply three different major analysis activities

Purpose of Analysis

Analysis focuses on producing a model of the system, called the *analysis model*, which is *correct, complete, consistent, and verifiable*.



An optical illusion

Ambiguity in drawings; we need to be consistent in our models

Formalization during analysis

Formalization helps identify areas of ambiguity as well as inconsistencies and omissions

We can deal with ambiguity by using standardized **notations** instead of **drawings**

For Analysis we use the following **UML** diagram types:

use case diagram, class diagram, state machine diagram and sequence diagram



not covered
in this course



not covered
in this course


Analysis concepts overview

Analysis model: the functional, (analysis) object and dynamic model of a system to be developed

Entity, boundary and control objects: objects can be divided into three major categories describing their use inside the system

Generalization and specialization: hierarchies can be detected in two different ways to adopt OOP principles like inheritance/polymorphism and abstraction

Analysis model




Entity, boundary and control objects

The (analysis) object model consists of entity, boundary, and control objects [JA99]

Entity objects represent the persistent information tracked by the system.

(e.g. a student object with its containing attributes firstName and LastName)


UML notation:



Boundary objects represent the interactions between the actors and the system.

(e.g. a view with buttons and icons)


UML notation:



Control objects are in charge of realizing use cases.

(e.g. a CourseController which handles the registration of students to courses)

UML notation:



Generalization and specialization

Generalization

- Identifies abstract concepts from lower-level ones
- Noticing common features among different concepts, we create an abstract concept

Common speech: “From low level to high level”

Specialization

- Identifies specialized concepts from higher level ones
- is the activity that identifies more specific concepts from a high-level one

Common speech: “From high level to low level”

Analysis activities overview

- 1) Identify entity, boundary and control objects
- 2) Identify associations, aggregates and attributes
- 3) Model inheritance relationships

1) Identify entity, boundary and control objects



Abbott's heuristics for mapping parts of speech to model components [AB83]

Part of speech	Model component	Example
Proper noun	Instance	Alice
Common noun	Class	Student
Doing verb	Operation	Creates, submits, selects
Being verb	Inheritance	Is a kind of, is one of either
Having verb	Aggregation	Has, consists of, includes
Modal verb	Constraints	Must be
Adjective	Attribute	Incident description

Example Abbott's technique applied

FR1: Search for available courses: A student can see all courses of the current semester in his major and minor subject. He is able to join the course which saves it into his course list. He can also drop a course.

Common noun
Adjective
Adjective



Common noun

Doing verb
Doing verb

Having verb

2a) Identify associations

An **association** shows a relationship between two or more classes

Associations have the following properties: name, role, multiplicity

The following heuristics can be used to identify associations:

- Examine verb phrases
- Name associations and roles precisely
- Eliminate any association that can be derived from other associations
- Too many associations make a model unreadable

2b) Identify aggregates

Aggregations are special types of associations denoting a whole–part relationship

There are two types of aggregation:

1) **Composition aggregation:**

➡ The existence of the parts depends on the whole.

UML notation: 

2) **Shared aggregation:**

➡ The whole and the part can exist independently.

UML notation: 

2c) Identify attributes

Attributes are properties of individual objects.


Attributes have the following properties: name, type

Properties that are represented by relationships to other objects are not shown as attributes - they are shown as associations

Heuristic for identifying attributes:


Start with associations and then insert attributes

implicit property:
courses



3) Model inheritance relationships

- Generalization is used to eliminate redundancy from the (analysis) object model
- If two or more classes share attributes or behavior, the similarities are consolidated into a superclass



Summary of analysis

Analysis highlights key aspects of a system:

Functional model + (analysis) object model + dynamic model = analysis model

Entity, boundary and control objects categorize objects:

- Entity objects are (persistently) stored
- Boundary objects interact with users
- Control objects handle functionality (use cases) of the system

Generalization and specialization:

Reusing existing structure and behavior with either a “top-down” or “bottom-up” approach

Analysis

Bernd Bruegge, Stephan Krusche, Andreas Seitz, Jan Knobloch
Chair for Applied Software Engineering — Faculty of Informatics

