

# Apply filters to SQL queries

## Project description

My organization is working to make their system more secure. It is my job to ensure the system is safe, investigate all potential security issues, and update employee computers as needed. The following steps provide examples of how I used SQL with filters to perform security-related tasks.

## Retrieve after hours failed login attempts

There was a potential security incident that occurred after business hours (after 18:00). All after hours login attempts that failed need to be investigated.

The following code demonstrates how I created a SQL query to filter for failed login attempts that occurred after business hours.

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE login_time > '18:00' AND success = 0;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0

## Retrieve login attempts on specific dates

A suspicious event occurred on 2022-05-09. All login attempts of that day and the day before(2022-05-08) must be investigated. The following SQL query produced the logins requested by the organization.

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0

## Retrieve login attempts outside of Mexico

The team has determined that the suspicious login activity did not originate in Mexico. Now the team must investigate all login attempts that occurred outside of Mexico. The following shows the SQL query used to do so, considering the 'country' column contains 'Mex' and 'Mexico' to describe Mexico..

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE country NOT LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1

## Retrieve employees in Marketing

The team wants to perform security updates on specific employee machines in the Marketing department that are also located in the East office. The following SQL query pulls information on the employee's machines who are part of the Marketing department and also located in the East office.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

```
7 rows in set (0.001 sec)
```

```
MariaDB [organization]>
```

## Retrieve employees in Finance or Sales

The team needs to perform a specific security update only on machines of employees in the Sales and Finance departments. The following SQL query pulls the needed information of employees in those departments.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'finance' OR department = 'sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271

## Retrieve all employees not in IT

The team needs to make one more update to employee machines. Because employees who are in the IT department already had this update, the update must be pushed to those in other departments. The following SQL query pulls the information of employees who are not in the IT department.

```
MariaDB [organization]> SELECT * FROM employees WHERE department != 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406