Introduction to pandas: Takeaways 🖻

by Dataquest Labs, Inc. - All rights reserved © 2020

Syntax

PANDAS DATAFRAME BASICS

• Reading a file into a dataframe:

```
f500 = pd.read_csv('f500.csv',index_col=0)
```

• Returning a dataframe's data types:

```
col_types = f500.dtypes
```

• Returning the dimensions of a dataframe:

```
dims = f500.shape
```

SELECTING VALUES FROM A DATAFRAME

• Selecting a single column:

```
f500["rank"]
```

• Selecting multiple columns:

```
f500[["country", "rank"]]
```

• Selecting the first n rows:

```
first_five = f500.head(5)
```

• Selecting rows from a dataframe by label:

```
drink_companies = f500.loc[["Anheuser-Busch InBev", "Coca-Cola", "Heineken Holding"]]
big_movers = f500.loc[["Aviva", "HP", "JD.com", "BHP Billiton"], ["rank", "previous_rank"]]
middle_companies = f500.loc["Tata Motors":"Nationwide", "rank":"country"]
```

Concepts

- NumPy provides fundamental structures and tools that make working with data easier, but there are several things that limit its usefulness as a single tool when working with data:
 - The lack of support for column names forces us to frame the questions we want to answer as multi-dimensional array operations.
 - Support for only one data type per ndarray makes it more difficult to work with data that contains both numeric and string data.

- There are lots of low level methods however, there are many common analysis.
 The **pandas** library provides solutions to all of these pain points and more. Pandas is not patterns that don't have pre-built methods. so much a replacement for NumPy as an *extension* of NumPy. The underlying code for pandas uses the NumPy library extensively. The main objects in pandas are **Series** and **Dataframes**. Series is equivalent to a 1D Ndarray while a dataframe is equivalent to a 2D Ndarray.
- Different label selection methods:

| Select by Label | Explicit Syntax | Shorthand Convention |
|---------------------------------|---------------------------|----------------------|
| Single column from dataframe | df.loc[:,"col1"] | df["col1"] |
| List of columns from dataframe | df.loc[:,["col1","col7"]] | df[["col1","col7"]] |
| Slice of columns from dataframe | df.loc[:,"col1":"col4"] | |
| Single row from dataframe | df.loc["row4"] | |
| List of rows from dataframe | df.loc[["row1", "row8"]] | |
| Slice of rows from dataframe | df.loc["row3":"row5"] | df["row3":"row5"] |
| Single item from series | s.loc["item8"] | s["item8"] |
| List of items from series | s.loc[["item1","item7"]] | s[["item1","item7"]] |
| Slice of items from series | s.loc["item2":"item4"] | s["item2":"item4"] |

Resources

• Dataframe.loc[]

• Indexing and Selecting Data



Takeaways by Dataquest Labs, Inc. - All rights reserved © 2020