



1. FABRICATE PCB FROM GERBER DATA CONTAINED IN ZIP FILE
2. CLASS 3 PCB PER IPC-6011
3. TYPE 3 PCB PER IPC-6012A WITH AMENDMENT 1
4. TYPE 1C ASSEMBLY PER IPC-2222
5. MATERIAL REQUIREMENTS
 - HIGH TEMP. FR4
 - SEE STACK-UP DETAIL FOR AREA WEIGHT PER SQUARE FOOT
6. PINK RING IS NOT PERMITTED
7. PLATING IN THROUGH HOLES SHALL BE 0.001 INCH MINIMUM
8. PREPREG LAYERS SHALL BE 2 PLYS MINIMUM
9. SOLDER MASK -GREEN PHOTO- IMAGEABLE SOLDER MASK PER IPC-SM-840C CLASS H
SHALL BE APPLIED TO BOTH SIDES OF THE PCB (SMOBC)
10. FINISH - ALL EXPOSED COPPER AREAS NOT COVERED WITH SOLDER MASK
SHALL BE GOLD PLATED
11. TOLERANCES:
 - BOW AND TWIST SHALL NOT EXCEED 0.5%
 - CONDUCTOR WIDTH AND SPACING SHALL BE WITHIN 0.001 INCH OF GERBER FILE DATA
 - FINAL PWB THICKNESS SHALL BE AS SHOWN IN STACK-UP DETAIL
 - SURFACE MOUNT PADS SHALL BE FLAT AND SHALL NOT EXTEND MORE THAN 0.003 INCH ABOVE THE PCB SURFACE
12. PLATED THROUGH HOLES:
 - HOLE SIZES IN DRILL CHART ARE IN MILS AND SPECIFY FINISHED DIAMETERS
 - LAYER TO LAYER REGISTRATION SHALL BE WITHIN 0.003 INCH
 - HOLE LOCATION SHALL BE WITHIN 0.004 RADIUS OF TRUE POSITION (RTP)
 - ALL HOLES SHALL BE ON FIRST DRILL. SECOND DRILL IS NOT PERMITTED
 - TOLERANCE FOR COMPONENT LEAD HOLES IS +/- 0.003 INCH
 - TOLERANCE FOR VIA HOLES IS +0.002 / -0.010 INCH
13. CONTROLLED IMPEDANCE OF 100 OHMS +/- 10% TO BE MATCHED ON ALL LAYERS(5/5/5 FOR INNER AND 7/5/7 FOR TOP)
14. FILL ALL VIAS
15. CROSS SECTION CUT REQUIRED

BOARD CHARACTERISTICS

Copper Layer Count: 8 Board Thickness: 62.99 mils

Board overall dimensions: 4330.70 mils x 7155.91 mils

Min track/spacing: 5.00 mils / 5.00 mils Min hole diameter: 8.00 mils

Copper Finish: ENIG Impedance Control: Yes

Castellated pads: No Plated Board Edge: No

Edge card connectors: No

Layer Name	Type	Material	Thickness (mils)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Not specified	0 mils	Green	1	0
F.Paste	Top Solder Paste		0 mils		1	0
F.Mask	Top Solder Mask	Not specified	0.3937 mils	Not specified	3.3	0
F.Cu	copper		0.67098 mils		1	0
Dielectric 1	prepreg	FR4	4.4 mils	FR4 natural	4.5	0.02
In1.Cu	copper		1.37 mils		1	0
Dielectric 2	core	FR4	8 mils	FR4 natural	4.5	0.02
In2.Cu	copper		0.67098 mils		1	0
Dielectric 3	prepreg	FR4	8.6 mils	FR4 natural	4.5	0.02
In3.Cu	copper		1.37 mils		1	0
Dielectric 4	core	FR4	8 mils	FR4 natural	4.5	0.02
In4.Cu	copper		0.67098 mils		1	0
Dielectric 5	prepreg	FR4	8.6 mils	FR4 natural	4.5	0.02
In5.Cu	copper		1.37 mils		1	0
Dielectric 6	core	FR4	8 mils	FR4 natural	4.5	0.02
In6.Cu	copper		1.37 mils		1	0
Dielectric 7	prepreg	FR4	4.4 mils	FR4 natural	4.5	0.02
B.Cu	copper		0.67098 mils		1	0
B.Mask	Bottom Solder Mask	Not specified	0.3937 mils	Not specified	3.3	0
B.Paste	Bottom Solder Paste		0 mils		1	0
B.Silkscreen	Bottom Silk Screen	Not specified	0 mils	Green	1	0