



1. FABRICATE PCB FROM GERBER DATA CONTAINED IN ZIP FILE
2. CLASS 3 PCB PER IPC-6011
3. TYPE 3 PCB PER IPC-6012A WITH AMENDMENT 1
4. TYPE 1C ASSEMBLY PER IPC-2222
5. MATERIAL REQUIREMENTS
  - HIGH TEMP. FR4
  - SEE STACK-UP DETAIL FOR AREA WEIGHT PER SQUARE FOOT
6. PINK RING IS NOT PERMITTED
7. PLATING IN THROUGH HOLES SHALL BE 0.001 INCH MINIMUM
8. PREPREG LAYERS SHALL BE 2 PLIES MINIMUM
9. SOLDER MASK -GREEN PHOTO- IMAGEABLE SOLDER MASK PER IPC-SM-840C CLASS H  
SHALL BE APPLIED TO BOTH SIDES OF THE PCB (SMOBC)
10. FINISH - ALL EXPOSED COPPER AREAS NOT COVERED WITH SOLDER MASK  
SHALL BE GOLD PLATED
11. TOLERANCES:
  - BOW AND TWIST SHALL NOT EXCEED 0.5%
  - CONDUCTOR WIDTH AND SPACING SHALL BE WITHIN 0.001 INCH OF GERBER FILE DATA
  - FINAL PWB THICKNESS SHALL BE AS SHOWN IN STACK-UP DETAIL
  - SURFACE MOUNT PADS SHALL BE FLAT AND SHALL NOT EXTEND MORE THAN 0.003 INCH ABOVE THE PCB SURFACE
12. PLATED THROUGH HOLES:
  - HOLE SIZES IN DRILL CHART ARE IN MILS AND SPECIFY FINISHED DIAMETERS
  - LAYER TO LAYER REGISTRATION SHALL BE WITHIN 0.003 INCH
  - HOLE LOCATION SHALL BE WITHIN 0.004 RADIUS OF TRUE POSITION (RTP)
  - ALL HOLES SHALL BE ON FIRST DRILL. SECOND DRILL IS NOT PERMITTED
  - TOLERANCE FOR COMPONENT LEAD HOLES IS +/- 0.003 INCH
  - TOLERANCE FOR VIA HOLES IS +0.002 / -0.010 INCH
13. CONTROLLED IMPEDANCE OF 100 OHMS +/- 10% TO BE MATCHED ON ALL LAYERS(5/5/5 FOR INNER AND 7/5/7 FOR TOP)
14. FILL ALL VIAS
15. CROSS SECTION CUT REQUIRED

## BOARD CHARACTERISTICS

Copper Layer Count: 8 Board Thickness: 62.99 mils

Board overall dimensions: 4330.70 mils x 7155.91 mils

Min track/spacing: 5.00 mils / 5.00 mils Min hole diameter: 8.00 mils

Copper Finish: ENIG Impedance Control: Yes

Castellated pads: No Plated Board Edge: No

Edge card connectors: No

| Layer Name   | Type                | Material      | Thickness (mils) | Color         | Epsilon R | Loss Tangent |
|--------------|---------------------|---------------|------------------|---------------|-----------|--------------|
| F.Silkscreen | Top Silk Screen     | Not specified | 0 mils           | Green         | 1         | 0            |
| F.Paste      | Top Solder Paste    |               | 0 mils           |               | 1         | 0            |
| F.Mask       | Top Solder Mask     | Not specified | 0.3937 mils      | Not specified | 3.3       | 0            |
| F.Cu         | copper              |               | 0.67098 mils     |               | 1         | 0            |
| Dielectric 1 | prepreg             | FR4           | 4.4 mils         | FR4 natural   | 4.5       | 0.02         |
| In1.Cu       | copper              |               | 1.37 mils        |               | 1         | 0            |
| Dielectric 2 | core                | FR4           | 8 mils           | FR4 natural   | 4.5       | 0.02         |
| In2.Cu       | copper              |               | 0.67098 mils     |               | 1         | 0            |
| Dielectric 3 | prepreg             | FR4           | 8.6 mils         | FR4 natural   | 4.5       | 0.02         |
| In3.Cu       | copper              |               | 1.37 mils        |               | 1         | 0            |
| Dielectric 4 | core                | FR4           | 8 mils           | FR4 natural   | 4.5       | 0.02         |
| In4.Cu       | copper              |               | 0.67098 mils     |               | 1         | 0            |
| Dielectric 5 | prepreg             | FR4           | 8.6 mils         | FR4 natural   | 4.5       | 0.02         |
| In5.Cu       | copper              |               | 1.37 mils        |               | 1         | 0            |
| Dielectric 6 | core                | FR4           | 8 mils           | FR4 natural   | 4.5       | 0.02         |
| In6.Cu       | copper              |               | 1.37 mils        |               | 1         | 0            |
| Dielectric 7 | prepreg             | FR4           | 4.4 mils         | FR4 natural   | 4.5       | 0.02         |
| B.Cu         | copper              |               | 0.67098 mils     |               | 1         | 0            |
| B.Mask       | Bottom Solder Mask  | Not specified | 0.3937 mils      | Not specified | 3.3       | 0            |
| B.Paste      | Bottom Solder Paste |               | 0 mils           |               | 1         | 0            |
| B.Silkscreen | Bottom Silk Screen  | Not specified | 0 mils           | Green         | 1         | 0            |