

Vendiqo Order Platform

Full manual test scenarios — Cloud admin, Pi PWA, Android app

This document covers functional manual tests for the entire platform: cloud ERP/admin, Raspberry Pi edge (waiter POS, cash register, kitchen, pickup), and the Android WebView app.

Record Pass / Fail / Blocked, build version, date, and tester name. Run TC-ENV-* first. Stripe Terminal cases are in section Cloud/Pi Android Stripe; see also [stripe-terminal-test-scenarios.pdf](#) for card-payment depth.

Legend: Cloud = browser admin UI; Pi = LAN PWA or Android shell; E2E = data visible in cloud after Pi sync.

Environment baseline

TC-ENV-001 Cloud stack reachable with bootstrap admin

Prerequisites

- Docker running; cloud compose up (API :8000, frontend :5173)
- cloud/.env from example with APP_ENV=development

Actions

1. Open cloud frontend login URL in browser
2. Sign in with ADMIN_EMAIL / ADMIN_PASSWORD from .env
3. Open API /docs when ENABLE_OPENAPI=true

Expected outcome

- Login succeeds; dashboard loads without console errors
- Bootstrap hire company and admin user exist if DB was fresh
- OpenAPI page lists auth and core resources

TC-ENV-002 Pi stack reachable unpaired and paired-ready

Prerequisites

- Pi compose up (API :8001, PWA :5174)
- Optional: cloud running for later pairing tests

Actions

1. Open Pi PWA in browser or on device
2. Confirm setup/pairing screen when unpaired
3. Call Pi GET /health or equivalent status endpoint

Expected outcome

- PWA loads; shows pairing UI when no appliance credential stored
- Pi API responds healthy
- No crash loop in Pi backend logs

Cloud — login, roles, org picker

TC-C-AUTH-001 Valid login and session persistence

Prerequisites

- Known org user credentials
- Cloud frontend on login route

Actions

- 1. Log in with email and password
- 2. Refresh the browser page
- 3. Navigate to Dashboard and Events

Expected outcome

- User lands on dashboard after login
- Session remains authenticated after refresh
- Sidebar shows org-scoped menu items for the user role

TC-C-AUTH-002 Invalid credentials rejected

Prerequisites

- Cloud login page open

Actions

- 1. Enter valid email with wrong password
- 2. Submit login
- 3. Retry with unknown email

Expected outcome

- Login fails with clear error message
- User stays on login page; no partial session
- No sensitive details leaked in error text

TC-C-AUTH-003 Organisation picker scopes data

Prerequisites

- User with access to two or more organisations
- Events or articles exist in each org

Actions

- 1. Log in and note active organisation in sidebar
- 2. Switch organisation via picker
- 3. Open Events list and verify rows

Expected outcome

- List updates to selected organisation only
- Active org persists on navigation within session
- URL/state does not show other org's records

TC-C-AUTH-004 Platform admin hire-company picker

Prerequisites

- Platform admin account
- At least two hire companies in cloud

Actions

- 1. Log in as platform admin
- 2. Use hire-company picker in sidebar
- 3. Open Verleiher and tenant-admin areas

Expected outcome

- Hire-company picker visible

- Switching hire company changes platform-scoped lists
- Non-platform users do not see hire-company picker

TC-C-AUTH-005 Non-admin blocked from tenant-admin routes

Prerequisites

- Org user without tenant admin flag

Actions

- 1. Log in as standard org user
- 2. Attempt direct navigation to /users and /organisations
- 3. Attempt /appliances

Expected outcome

- Redirects or no-access placeholder for restricted sections
- Users menu hidden or disabled in nav
- No CRUD API calls succeed for forbidden resources (403)

Cloud — hire companies (platform admin)

TC-C-HC-001 List and create hire company

Prerequisites

- Platform admin logged in
- Unique hire company name prepared

Actions

- 1. Open Verleiher (hire companies)
- 2. Create hire company with name and contact fields
- 3. Save and find row in list

Expected outcome

- New hire company appears in table
- Detail view opens with saved values
- Hire company selectable in platform picker

TC-C-HC-002 Edit hire company details

Prerequisites

- Existing hire company
- Platform admin session

Actions

- 1. Open hire company detail
- 2. Change display name or contact email
- 3. Save and reload detail page

Expected outcome

- Changes persist after reload
- Linked organisations still associated
- No validation error on required fields

TC-C-HC-003 Hire company context filters platform view

Prerequisites

- Two hire companies with distinct organisations
- Platform admin

Actions

- 1. Select hire company A in picker
- 2. Note visible organisations/events
- 3. Switch to hire company B

Expected outcome

- Data sets differ per active hire company
- Switch does not leak records across companies
- Picker label matches active hire company

Cloud — organisations

TC-C-ORG-001 Create organisation under hire company

Prerequisites

- Tenant admin or platform admin
- Active hire company selected

Actions

- 1. Open Organisations
- 2. Create organisation with name and currency
- 3. Save

Expected outcome

- Organisation listed and openable in detail
- Organisation appears in org picker for permitted users
- Defaults applied (e.g. currency) as configured

TC-C-ORG-002 Edit organisation settings

Prerequisites

- Existing organisation
- Tenant admin

Actions

- 1. Open organisation detail
- 2. Update address or receipt-related org fields
- 3. Save

Expected outcome

- Saved fields shown on reload
- Org-scoped cloud pages use updated organisation

TC-C-ORG-003 Assign cloud user to organisation

Prerequisites

- Organisation and spare user email
- Tenant admin

Actions

- 1. Open organisation users/members section
- 2. Add or link user with role
- 3. Log in as that user and pick organisation

Expected outcome

- User sees organisation in picker after login
- Role limits visible menu items appropriately

TC-C-ORG-004 Organisation receipt template

Prerequisites

- Organisation with receipt template editor
- Sample logo optional

Actions

- 1. Open receipt template settings for organisation
- 2. Edit header/footer lines
- 3. Save template

Expected outcome

- Template saves without error
- Pi sync later can apply template on printed receipts (see E2E)

TC-C-ORG-005 Organisation appliance lending record**Prerequisites**

- Registered appliance
- Organisation and tenant admin

Actions

- 1. Open organisation lendings or appliance lendings view
- 2. Create lending linking appliance to organisation
- 3. Verify lending visible in dashboard/lendings list

Expected outcome

- Lending row shows appliance, org, and dates
- Appliance available for pairing in Pi when lent to org

Cloud — appliances & lendings

TC-C-APP-001 Register new appliance

Prerequisites

- Tenant admin
- Unique appliance name/identifier

Actions

- 1. Open Appliances
- 2. Create appliance record
- 3. Generate or reveal pairing credential

Expected outcome

- Appliance listed with ID
- Pairing secret/token shown once or retrievable per UI flow
- Credential usable on Pi setup screen

TC-C-APP-002 Pair Pi edge device to appliance

Prerequisites

- Appliance credential from TC-C-APP-001
- Pi unpaired on same network

Actions

- 1. On Pi setup, enter cloud URL and pairing code
- 2. Complete pairing
- 3. Confirm cloud appliance shows last-seen or paired state

Expected outcome

- Pi shows paired status and admin menu
- Cloud appliance record reflects edge connection
- Sync enabled when SYNC_ENABLED=1

TC-C-APP-003 Lend appliance to organisation

Prerequisites

- Paired or unpaired appliance
- Target organisation

Actions

- 1. Create appliance lending to organisation with date range
- 2. Open Appliance lendings list as org user

Expected outcome

- Lending visible in cloud lendings view
- Org users see appliance in scope for events/sync

TC-C-APP-004 Return appliance lending

Prerequisites

- Active lending on appliance

Actions

- 1. End or return lending in cloud UI
- 2. Refresh lendings list

Expected outcome

- Lending marked returned/ended
- Appliance no longer active for that org period

TC-C-APP-005 Revoke pairing and re-pair

Prerequisites

- Paired Pi appliance
- New pairing credential if rotation supported

Actions

- 1. Unpair from Pi admin or cloud revoke action
- 2. Confirm Pi returns to setup screen
- 3. Re-pair with valid credential

Expected outcome

- Old token rejected after revoke
- Re-pair restores sync and event bundle access

Cloud — users

TC-C-USR-001 Create cloud user with role

Prerequisites

- Tenant admin
- Unique email

Actions

- 1. Open Users
- 2. Create user with password and role (admin vs user)
- 3. Save

Expected outcome

- User appears in list
- New user can log in with assigned role behavior

TC-C-USR-002 Edit user role and org access

Prerequisites

- Existing non-platform user

Actions

- 1. Open user detail
- 2. Change role or organisation memberships
- 3. Save; log in as user in incognito

Expected outcome

- Permissions match updated role
- Restricted routes blocked after downgrade

TC-C-USR-003 Deactivate or delete user

Prerequisites

- Disposable test user

Actions

- 1. Disable or delete user in Users UI
- 2. Attempt login with that account

Expected outcome

- Login fails for removed/disabled user
- User removed from pickers and assignment lists

TC-C-USR-004 Set Pi admin PIN/code for user

Prerequisites

- User with Pi admin permission
- Paired Pi

Actions

- 1. Set Pi admin code on user in cloud
- 2. On Pi, open admin area and enter code

Expected outcome

- Pi admin menu unlocks
- Wrong code rejected

Cloud — articles & categories

TC-C-CAT-001 Create article category

Prerequisites

- Active organisation selected
- Admin or catalog editor role

Actions

- 1. Open Article categories
- 2. Create category with name and sort order
- 3. Save

Expected outcome

- Category listed for organisation
- Available when creating articles

TC-C-CAT-002 Create article with price and category

Prerequisites

- At least one category

Actions

- 1. Open Articles
- 2. Create article with name, price, category, tax flags as applicable
- 3. Save

Expected outcome

- Article appears in org catalog
- Price stored in minor units correctly in UI

TC-C-CAT-003 Configure article additions

Prerequisites

- Base article and addition articles exist

Actions

- 1. Edit base article
- 2. Link addition articles with optional/min rules
- 3. Save

Expected outcome

- Additions saved on article
- Pi order flow prompts additions picker when article ordered

TC-C-CAT-004 Archive or disable article

Prerequisites

- Article used in past event optional

Actions

- 1. Mark article inactive/archived per UI
- 2. Check article list filter

Expected outcome

- Article hidden from default active list
- Not offered on new event menus after bundle refresh

TC-C-CAT-005 Bulk import or duplicate article

Prerequisites

- Source article with additions

Actions

- 1. Duplicate article or use copy action if available
- 2. Rename duplicate and save

Expected outcome

- Duplicate has independent ID
- Addition links copied or empty per product rules

Cloud — waiters

TC-C-WAI-001 Create waiter with PIN

Prerequisites

- Active organisation

Actions

- 1. Open Waiters
- 2. Create waiter display name and PIN
- 3. Save

Expected outcome

- Waiter listed for organisation
- PIN usable on Pi waiter login after sync

TC-C-WAI-002 Edit waiter and deactivate

Prerequisites

- Existing waiter

Actions

- 1. Change name or PIN
- 2. Deactivate waiter
- 3. Pull sync on Pi and attempt login

Expected outcome

- Updated PIN works when active
- Deactivated waiter cannot open shift on Pi

TC-C-WAI-003 Waiter visible only in active org

Prerequisites

- Two organisations with distinct waiters

Actions

- 1. Select org A; note waiters
- 2. Switch to org B

Expected outcome

- Each org list shows only its waiters
- No cross-org waiter IDs in API responses

Cloud — dashboard

TC-C-DASH-001 Dashboard shows org summary

Prerequisites

- Org with events and lendings
- Org user logged in

Actions

1. Open Dashboard
2. Review widgets/cards for events and appliances

Expected outcome

- Counts or lists reflect active organisation only
- Links navigate to Events and Appliance lendings

TC-C-DASH-002 Appliance lendings read-only view

Prerequisites

- At least one active lending

Actions

1. Open Appliance lendings from dashboard or menu
2. Filter/search if available

Expected outcome

- Lending rows show appliance name, org, status
- Org user cannot perform platform-only actions

TC-C-DASH-003 Dashboard empty state for new org

Prerequisites

- Fresh organisation without events

Actions

1. Select new organisation
2. Open Dashboard

Expected outcome

- Empty states readable; no errors
- CTA or hints point to create event/catalog

Cloud — event configuration tabs

TC-C-EVTC-001 Configure kitchen/bar stations

Prerequisites

- Event detail configuration tab Stations

Actions

- 1. Add station with name and printer target
- 2. Map articles to station routes
- 3. Save event config

Expected outcome

- Stations listed on event
- Pi routes order lines to station print jobs

TC-C-EVTC-002 Assign event waiters

Prerequisites

- Org waiters exist
- Event configuration tab event waiters

Actions

- 1. Attach waiters to event
- 2. Save
- 3. Sync; verify only assigned waiters on Pi

Expected outcome

- Assigned waiters can log in on Pi for event
- Unassigned waiter rejected or hidden

TC-C-EVTC-003 Configure cash registers and layouts

Prerequisites

- Event tab Registers and Layouts

Actions

- 1. Create register with layout UUID
- 2. Place articles and vouchers on layout grid
- 3. Save

Expected outcome

- Register appears in Pi register mode picker
- Layout cells match cloud preview

TC-C-EVTC-004 Voucher definitions for event

Prerequisites

- Event vouchers tab

Actions

- 1. Create voucher definition with value rules
- 2. Save and sync

Expected outcome

- Voucher sale tile on register layout if configured
- Redemption available on pay flow

TC-C-EVTC-005 App layouts for waiter ordering

Prerequisites

- Event layouts for waiter mode

Actions

- 1. Edit waiter layout cells and categories
- 2. Save
- 3. Open table order on Pi

Expected outcome

- Pi order grid mirrors cloud layout
- Stock-limited articles show availability

TC-C-EVTC-006 Receipt profiles per station

Prerequisites

- Event receipts tab
- Stations configured

Actions

- 1. Assign receipt templates per station or register
- 2. Save

Expected outcome

- Guest and kitchen receipts use correct template after print

TC-C-EVTC-007 Event stock quantities

Prerequisites

- Event stock tab
- Articles with limited stock

Actions

- 1. Set stock counts per article
- 2. Save and sync
- 3. Order until depleted on Pi

Expected outcome

- Pi blocks or warns when stock exhausted
- Cloud stock tab shows consumption if updated

Cloud — events (stammdaten & workflow)

TC-C-EVT-001 Create event in draft/test status

Prerequisites

- Organisation with catalog
- Admin on cloud

Actions

- 1. Open Events and create event
- 2. Set name, dates, currency, status draft or test
- 3. Save stammdaten

Expected outcome

- Event appears in list with correct status chip
- Detail opens with stammdaten tabs

TC-C-EVT-002 Copy event configuration

Prerequisites

- Source event with stations and layout

Actions

- 1. Use copy/duplicate event action
- 2. Name new event and save

Expected outcome

- New event ID created
- Stations, layouts, and catalog references copied per rules

TC-C-EVT-003 Delete event with confirmation

Prerequisites

- Disposable test event without production orders

Actions

- 1. Delete event from list or detail
- 2. Confirm dialog

Expected outcome

- Event removed from list
- Pi bundle no longer offers event after sync

TC-C-EVT-004 Status workflow draft → test → prod

Prerequisites

- Event in draft
- Validation rules for prod met (dates, config)

Actions

- 1. Advance status to test
- 2. Fix any blocking validation messages
- 3. Advance to prod when allowed

Expected outcome

- Status label updates in list
- Illegal transitions blocked with message
- Prod event eligible for Pi prod selection

TC-C-EVT-005 Stammdaten payment mode for waiters**Prerequisites**

- Event detail open

Actions

- 1. Set payment mode to pay later, pay now, or instant paid
- 2. Save stammdaten
- 3. Sync event to Pi and create table order

Expected outcome

- Pi enforces pay-later vs pay-now vs instant behavior on submit
- Mode persisted after reload

TC-C-EVT-006 Payment types cash and card toggles**Prerequisites**

- Event stammdaten Zahlungsarten
- Stripe configured if testing card

Actions

- 1. Enable cash and card payment types
- 2. Save and sync to Pi
- 3. Open pay screen on Pi

Expected outcome

- Only enabled types offered on Pi pay UI
- Disabling card removes terminal/card path

TC-C-EVT-007 TWINT and QR display toggles**Prerequisites**

- Event with TWINT enabled in cloud
- Pi payment flow

Actions

- 1. Enable TWINT in event payment settings
- 2. Save; admin sync on Pi
- 3. Start TWINT payment on open order

Expected outcome

- TWINT QR or deep link shown when enabled
- TWINT hidden when disabled in stammdaten

TC-C-EVT-008 Archive event status**Prerequisites**

- Completed event eligible for archive

Actions

- 1. Set status to archive
- 2. Filter events list by archive

Expected outcome

- Archived event hidden from default filters
- Historical reports still accessible if supported

Cloud — event reporting

TC-C-RPT-001 Event Umsatz report

Prerequisites

- Prod event with payments on Pi
- Cloud event reporting Umsatz

Actions

- 1. Open event reports Umsatz
- 2. Select date range covering test sales

Expected outcome

- Totals match sum of payments within tolerance
- Payment method breakdown shown

TC-C-RPT-002 Transaktionen list and export

Prerequisites

- Multiple payments and refunds if any

Actions

- 1. Open Transaktionen tab
- 2. Filter by waiter or register if available
- 3. Export CSV if offered

Expected outcome

- Each payment row shows time, amount, method, reference
- Export contains same rows as on-screen filter

TC-C-RPT-003 Sammelrechnungen (collective invoices)

Prerequisites

- Collective bills created on Pi

Actions

- 1. Open Sammelrechnungen report
- 2. Open detail for one collective bill

Expected outcome

- Collective bill totals align with Pi settlement
- Linked tables or orders listed

TC-C-RPT-004 Schichten (shifts) report

Prerequisites

- Closed shift on Pi with sales

Actions

- 1. Open Schichten report for event
- 2. Compare opening/closing cash totals

Expected outcome

- Shift row shows waiter, open/close times
- Revenue matches payments during shift window

Cloud — Stripe Connect & card payments

TC-C-STR-001 Start Stripe Connect onboarding

Prerequisites

- Tenant admin
- Stripe test mode keys in cloud .env

Actions

- 1. Open account settings Stripe section
- 2. Start Connect onboarding
- 3. Complete Stripe test onboarding flow

Expected outcome

- Return URL lands on stripe-connect-return route
- Connected account id stored; status shown connected

TC-C-STR-002 Refresh expired Connect link

Prerequisites

- Connect account incomplete or link expired

Actions

- 1. Open Stripe refresh URL or click refresh in settings
- 2. Complete Stripe prompt

Expected outcome

- User can continue onboarding without error
- Settings show updated capability status

TC-C-STR-003 Enable card payment type on event

Prerequisites

- Stripe connected for organisation
- Event stammdaten

Actions

- 1. Enable Karte/card in event payment types
- 2. Save and sync to Pi

Expected outcome

- Pi pay flow offers card/terminal
- Missing Connect blocks card with clear message

TC-C-STR-004 Card-present payment on Pi terminal

Prerequisites

- Paired Stripe Terminal or Tap to Pay on Android
- Event with card enabled

Actions

- 1. Create order and open pay
- 2. Choose card and complete on terminal

Expected outcome

- Payment succeeds; receipt offered
- Cloud Transaktionen shows card payment

TC-C-STR-005 Disconnect or rotate Stripe keys handling

Prerequisites

- Stripe test dashboard access

Actions

1. Remove or invalidate secret in .env (staging only)
2. Restart cloud backend
3. Attempt card payment

Expected outcome

- Cloud logs configuration error; card disabled gracefully
- No partial charges without valid Stripe config

Cloud — account settings

TC-C-SET-001 Change account password

Prerequisites

- Logged-in user
- New password meets policy

Actions

- 1. Open Account settings
- 2. Change password with current password confirmation
- 3. Log out and log in with new password

Expected outcome

- Password change succeeds
- Old password rejected after change

TC-C-SET-002 Account settings profile fields

Prerequisites

- User with editable profile

Actions

- 1. Update display name or locale if available
- 2. Save settings

Expected outcome

- Fields persist on reload
- Header shows updated email/name

Pi — pairing & setup

TC-P-SETUP-001 First-time pairing flow

Prerequisites

- Appliance credential from cloud
- Pi on setup screen

Actions

- 1. Enter cloud base URL
- 2. Enter pairing code
- 3. Submit

Expected outcome

- Pi shows paired state
- Admin sync menu available

TC-P-SETUP-002 Invalid pairing code rejected

Prerequisites

- Pi setup screen

Actions

- 1. Enter wrong pairing code
- 2. Submit

Expected outcome

- Error toast or message; remains on setup
- No partial bundle downloaded

TC-P-SETUP-003 Unpair and return to setup

Prerequisites

- Paired Pi
- Pi admin code

Actions

- 1. Open Pi admin
- 2. Unpair device
- 3. Confirm setup screen

Expected outcome

- Local credentials cleared
- Cloud still shows appliance; re-pair possible

Pi — admin sync & bundle

TC-P-SYNC-001 Admin pull sync from cloud

Prerequisites

- Paired Pi; cloud event in test/prod
- Network reachable

Actions

- 1. Open Pi admin sync
- 2. Run Pull
- 3. Open event picker

Expected outcome

- Pull completes without error
- New/updated event and catalog visible

TC-P-SYNC-002 Push local orders to cloud

Prerequisites

- Offline or queued orders on Pi
- Sync enabled

Actions

- 1. Create order while cloud reachable
- 2. Run Push from admin sync

Expected outcome

- Push reports success count
- Cloud Transaktionen shows order/payment

TC-P-SYNC-003 Sync status and last error display

Prerequisites

- Paired Pi

Actions

- 1. Open sync status panel
- 2. Induce benign error (wrong cloud URL) then fix

Expected outcome

- Status shows last sync time
- Error message human-readable; recovers after fix

TC-P-SYNC-004 Bundle refresh after cloud config change

Prerequisites

- Cloud event layout changed

Actions

- 1. Change layout in cloud
- 2. Pull on Pi
- 3. Open order UI

Expected outcome

- Pi layout matches cloud without re-pair
- Old cached layout not shown

Pi — event selection & mode

TC-P-EVT-001 Select prod event in waiter mode

Prerequisites

- Paired Pi; prod event synced
- Waiter assigned to event

Actions

- 1. Choose event from Pi event list
- 2. Select waiter mode (not register)
- 3. Log in with waiter PIN

Expected outcome

- Hub shows tables and open orders entry points
- Event name shown in header

TC-P-EVT-002 Select event in register mode

Prerequisites

- Register configured on event

Actions

- 1. Choose same event in register mode
- 2. Pick register from list

Expected outcome

- Register order layout loads
- No waiter PIN required for register flow

Pi — waiter hub & shift

TC-P-WAI-001 Waiter PIN login

Prerequisites

- Synced waiter with known PIN
- Event selected

Actions

- 1. Enter waiter PIN on login screen
- 2. Confirm hub loads

Expected outcome

- Correct PIN opens hub
- Wrong PIN shows error without lockout excess

TC-P-WAI-002 Open shift with float

Prerequisites

- Waiter logged in
- No open shift

Actions

- 1. Tap open shift
- 2. Enter opening cash float
- 3. Confirm

Expected outcome

- Shift open indicator visible
- Orders allowed

TC-P-WAI-003 Hub navigation to tables and orders

Prerequisites

- Open shift

Actions

- 1. Open tables list
- 2. Select table with open order
- 3. Return to hub

Expected outcome

- Navigation works without losing shift
- Active table highlighted

TC-P-WAI-004 Waiter logout returns to PIN screen

Prerequisites

- Active waiter session

Actions

- 1. Log out waiter from hub menu

Expected outcome

- PIN entry screen shown
- Another waiter can log in

Pi — ordering

TC-P-ORD-001 Create table order from layout

Prerequisites

- Open shift; pay-later event
- Empty table

Actions

- 1. Select table
- 2. Add articles from layout cells
- 3. Submit order

Expected outcome

- Order appears on table summary
- Kitchen tickets print or queue per station

TC-P-ORD-002 Article with additions picker

Prerequisites

- Article with mandatory additions configured

Actions

- 1. Tap article on order screen
- 2. Select additions and confirm
- 3. Submit line

Expected outcome

- Line shows addition labels and price delta
- Cannot submit without required additions

TC-P-ORD-003 Stock-limited article blocked

Prerequisites

- Event stock zero for article

Actions

- 1. Attempt to add depleted article

Expected outcome

- Toast or disabled state prevents add
- Other articles still orderable

TC-P-ORD-004 Sell voucher from layout

Prerequisites

- Voucher definition on event
- Register or waiter layout includes voucher cell

Actions

- 1. Add voucher line to cart
- 2. Submit/pay per mode

Expected outcome

- Voucher line in basket with correct amount
- Voucher code or balance created per backend rules

TC-P-ORD-005 Order-level discount**Prerequisites**

- Event allows order discount

Actions

- 1. Add items
- 2. Apply order discount percent or amount
- 3. Submit

Expected outcome

- Total reduced correctly
- Cloud report shows discounted total

TC-P-ORD-006 Line notes and quantity edit**Prerequisites**

- Open order on table

Actions

- 1. Add line with note
- 2. Change quantity via modal
- 3. Submit update

Expected outcome

- Note prints on kitchen chit if configured
- Quantity reflected in table total

TC-P-ORD-007 Pay-now submit opens payment immediately**Prerequisites**

- Event payment mode pay now

Actions

- 1. Build cart on table
- 2. Submit order

Expected outcome

- Pay screen opens with correct total
- Unpaid order not left without payment prompt

Pi — open tables

TC-P-TBL-001 Open tables list shows active orders

Prerequisites

- Multiple tables with orders

Actions

- 1. Open tables overview
- 2. Compare totals with table detail

Expected outcome

- Only tables with activity highlighted
- Totals match sum of open lines

TC-P-TBL-002 Split pay by line groups

Prerequisites

- Table with several line groups
- Pay-later mode

Actions

- 1. Open table pay / split pay
- 2. Move lines to basket
- 3. Settle partial amount

Expected outcome

- Partial payment reduces remaining balance
- Remaining lines stay open on table

TC-P-TBL-003 Transfer table to another number

Prerequisites

- Order on table A
- Empty table B

Actions

- 1. Open transfer table action
- 2. Select destination table B
- 3. Confirm

Expected outcome

- Order appears on table B
- Table A cleared

TC-P-TBL-004 Assign waiter to table

Prerequisites

- Two waiters with open shifts

Actions

- 1. Assign table to waiter B
- 2. Log in as waiter B

Expected outcome

- Table visible in waiter B hub
- Reporting attributes sales to correct waiter if configured

TC-P-TBL-005 Collective assign tables to bill**Prerequisites**

- Collective billing enabled
- Multiple tables with orders

Actions

- 1. Start collective bill
- 2. Add tables
- 3. Review collective total

Expected outcome

- Combined total equals sum of tables
- Collective bill id stable until paid

TC-P-TBL-006 Close empty table after pay**Prerequisites**

- Table fully paid

Actions

- 1. Pay remaining balance
- 2. Return to tables list

Expected outcome

- Table no longer shows open balance
- Table available for new order

Pi — payments

TC-P-PAY-001 Cash payment exact amount

Prerequisites

- Open order with known total
- Cash enabled

Actions

- 1. Open pay screen
- 2. Enter exact cash amount
- 3. Confirm pay

Expected outcome

- Payment succeeds toast
- Receipt prompt if configured
- Table cleared or order closed

TC-P-PAY-002 Cash change calculation

Prerequisites

- Cash payment with amount tendered greater than total

Actions

- 1. Enter tendered cash above total
- 2. Complete payment

Expected outcome

- Change amount shown correctly
- Payment recorded for total due only

TC-P-PAY-003 TWINT payment flow

Prerequisites

- TWINT enabled on event
- TWINT test environment

Actions

- 1. Choose TWINT on pay screen
- 2. Complete TWINT QR flow

Expected outcome

- Payment marked paid on success
- TWINT QR hidden after completion

TC-P-PAY-004 Pay open order from order list

Prerequisites

- Pay-later table order unsubmitted payment

Actions

- 1. Open order from hub
- 2. Tap pay order
- 3. Complete cash pay

Expected outcome

- Order pay route shows line breakdown
- Returns to hub after pay

TC-P-PAY-005 Instant paid mode marks lines paid on send**Prerequisites**

- Event payment mode instant paid

Actions

- 1. Submit new items to table

Expected outcome

- No separate pay step for submitted lines
- Table total reflects paid lines

TC-P-PAY-006 Payment receipt print and skip**Prerequisites**

- Printer configured
- Successful payment

Actions

- 1. Complete payment
- 2. Accept receipt print
- 3. Repeat and decline receipt

Expected outcome

- Receipt prints on accept
- Skip does not block payment completion

Pi — collective bills

TC-P-COL-001 Create collective bill

Prerequisites

- Several tables with open orders

Actions

- 1. Open collective bills
- 2. Create new bill and add tables

Expected outcome

- Collective bill list shows new entry with total

TC-P-COL-002 Pay collective bill cash

Prerequisites

- Open collective bill

Actions

- 1. Open collective pay
- 2. Pay full amount cash

Expected outcome

- All included tables closed
- Cloud Sammelrechnung updated after sync

TC-P-COL-003 Remove table from collective before pay

Prerequisites

- Collective with 2+ tables

Actions

- 1. Remove one table from collective
- 2. Verify total recalculates

Expected outcome

- Removed table stands alone again
- Collective total reduced accordingly

Pi — voucher redeem

TC-P-VCH-001 Redeem voucher on table pay

Prerequisites

- Valid voucher with balance
- Table pay-later order

Actions

- 1. Open split/table pay
- 2. Redeem voucher against basket
- 3. Pay remainder cash

Expected outcome

- Voucher credit subtracted from total
- Remainder charged correctly

TC-P-VCH-002 Voucher redeem on register pay

Prerequisites

- Register cart with articles
- Voucher definition allows redeem

Actions

- 1. Build register cart
- 2. Apply voucher redemption
- 3. Pay payable balance

Expected outcome

- Register total shows voucher deduction
- Cannot redeem against voucher-only sale if restricted

Pi — cash register

TC-P-REG-001 Register mode order from layout

Prerequisites

- Register selected on prod/test event

Actions

- 1. Add items via register layout
- 2. Pay at register

Expected outcome

- Order completes without table number
- Pickup code generated if enabled

TC-P-REG-002 Customer display shows ordering state

Prerequisites

- Second display or customer display route

Actions

- 1. Add items on register
- 2. Observe customer display

Expected outcome

- Lines and total mirror register cart
- TWINT QR shown on display when applicable

TC-P-REG-003 Pickup code printed and called

Prerequisites

- Event with pickup codes enabled

Actions

- 1. Complete register order
- 2. Note pickup code
- 3. Open pickup screen and mark ready

Expected outcome

- Code appears in pickup queue
- Customer display updates when called

TC-P-REG-004 Register hold and resume pickup

Prerequisites

- Register order in progress

Actions

- 1. Hold order on customer display flow
- 2. Resume and pay

Expected outcome

- Cart restored on resume
- No duplicate payment on resume pay

TC-P-REG-005 Register voucher sale line

Prerequisites

- Voucher cell on register layout

Actions

- 1. Sell voucher from register
- 2. Pay by card or cash

Expected outcome

- Voucher sale line separated from food lines
- Receipt shows voucher item

TC-P-REG-006 Register display idle screen

Prerequisites

- No active cart

Actions

- 1. Leave register idle for timeout period

Expected outcome

- Customer display shows idle/branding state
- New order clears idle

Pi — kitchen & pickup

TC-P-KIT-001 Kitchen monitor shows new tickets

Prerequisites

- Station printer or KDS route configured
- Submitted order with kitchen items

Actions

- 1. Open kitchen monitor view
- 2. Submit order from waiter

Expected outcome

- Ticket appears with table, items, notes
- Bump/complete removes or dims ticket

TC-P-KIT-002 Pickup screen marks order ready

Prerequisites

- Register order with pickup code

Actions

- 1. Open pickup screen
- 2. Mark order ready

Expected outcome

- Status changes visible to staff
- Customer display shows ready state if linked

TC-P-KIT-003 Station filter on kitchen monitor

Prerequisites

- Multiple stations with orders

Actions

- 1. Filter kitchen view by station

Expected outcome

- Only matching station lines shown
- Switching filter updates list immediately

Pi — stock view

TC-P-STK-001 Stock view reflects cloud limits

Prerequisites

- Event with stock counts synced

Actions

- 1. Open stock view on Pi
- 2. Sell one unit of limited article
- 3. Refresh stock view

Expected outcome

- Counts decrement locally
- Sold-out articles marked unavailable

Pi — printing

TC-P-PRT-001 Station print on order submit

Prerequisites

- Printer IP configured in bundle or override
- Order with station-routed items

Actions

- 1. Submit order
- 2. Verify kitchen printer output

Expected outcome

- Chit prints with station name, table, items
- Failures queued in print status UI

TC-P-PRT-002 Retry failed print job

Prerequisites

- Simulate printer offline or wrong IP

Actions

- 1. Submit order to trigger failure
- 2. Open print failures in admin
- 3. Fix printer and retry

Expected outcome

- Failure listed with error hint
- Retry succeeds after printer reachable

TC-P-PRT-003 Admin test print

Prerequisites

- Pi admin access
- Printer on network

Actions

- 1. Open admin printer test
- 2. Send test print

Expected outcome

- Test page prints
- Success toast in admin

TC-P-PRT-004 Guest receipt after payment

Prerequisites

- Payment completed
- Receipt printer configured

Actions

- 1. Accept payment receipt
- 2. Verify receipt content

Expected outcome

- Receipt shows items, VAT, payments, org header
- QR or TWINT info only if applicable

Pi — shifts

TC-P-SHF-001 Close shift with cash reconciliation

Prerequisites

- Open shift with cash sales

Actions

- 1. Open close shift
- 2. Enter counted cash
- 3. Confirm close

Expected outcome

- Shift closed; hub requires new open shift
- Variance shown if counted vs expected differs

TC-P-SHF-002 Switch waiter closes previous session

Prerequisites

- Waiter A logged in with open shift

Actions

- 1. Log out waiter A
- 2. Log in waiter B and open shift

Expected outcome

- Waiter B shift independent
- Waiter A cannot add orders without re-login

TC-P-SHF-003 Cannot order without open shift

Prerequisites

- Waiter logged in, shift closed

Actions

- 1. Attempt to open table order

Expected outcome

- Prompt to open shift first
- After opening shift, ordering enabled

Pi — Android printer & terminal

TC-P-AND-001 Android app pairs like PWA

Prerequisites

- Android build installed
- Pairing credential

Actions

- 1. Open Android app setup
- 2. Pair to cloud appliance

Expected outcome

- Same bundle and events as browser PWA after sync

TC-P-AND-002 Android Bluetooth receipt printer

Prerequisites

- BT printer paired in Android settings
- Printer driver enabled in app

Actions

- 1. Configure printer in app settings
- 2. Run test print
- 3. Pay order and print receipt

Expected outcome

- BT print succeeds
- Receipt matches ESC/POS layout

TC-P-AND-003 Android Stripe Terminal Tap to Pay

Prerequisites

- Stripe Terminal configured
- Event card payments enabled

Actions

- 1. Take card payment on Android
- 2. Complete on-device reader

Expected outcome

- Payment success on Pi
- Cloud shows card transaction after push

TC-P-AND-004 Android offline queue and sync

Prerequisites

- Network disabled briefly

Actions

- 1. Create cash order offline
- 2. Restore network
- 3. Push sync

Expected outcome

- Order retained locally
- Push uploads without duplicate charge

TC-P-AND-005 Android kiosk/fullscreen register

Prerequisites

- Tablet in register mode

Actions

- 1. Lock to register display route
- 2. Run full sale cycle

Expected outcome

- No accidental navigation out of register
- Customer display works on second screen if connected

End-to-end cross-system

TC-E2E-001 Cloud config to Pi sale to cloud report

Prerequisites

- Full stack running
- Prod or test event end-to-end

Actions

- 1. Create article and event in cloud
- 2. Pull on Pi; sell item for cash
- 3. Push sync
- 4. Open cloud Transaktionen

Expected outcome

- Sale appears in cloud within expected delay
- Amounts and article names match

TC-E2E-002 Multi-appliance same event

Prerequisites

- Two paired Pis on same event

Actions

- 1. Sell on Pi A table 1
- 2. Sell on Pi B table 2
- 3. Push both; view Umsatz

Expected outcome

- Both sales aggregated in cloud report
- No order id collision

TC-E2E-003 Org receipt template on printed receipt

Prerequisites

- Custom org receipt header in cloud
- Pi printed guest receipt

Actions

- 1. Update org receipt template
- 2. Pull bundle
- 3. Complete payment with receipt print

Expected outcome

- Printed header/footer matches template

TC-E2E-004 Archive event removes from Pi picker

Prerequisites

- Event used on Pi

Actions

- 1. Archive event in cloud
- 2. Pull on Pi
- 3. Open event list

Expected outcome

- Archived event not selectable for new sessions
- Existing local data handled per retention rules