

Introduction to R, version 2

Contents

Introduction	3
1 Starting out in R	5
1.1 Variables	6
1.2 Saving code in an R script	7
1.3 Vectors	8
1.4 Types of vector	8
1.5 Indexing vectors	9
1.6 Sequences	10
1.7 Functions	10
2 Data frames	13
2.1 Setting up	13
2.2 Loading data	14
2.3 Exploring	16
2.4 Indexing data frames	17
2.5 Columns are vectors	18
2.6 Logical indexing	19
2.7 Factors	22
2.8 Readability vs tidyness	24
2.9 Sorting	25
2.10 Joining data frames	25
2.11 Further reading	27
3 Plotting with ggplot2	28
3.1 Elements of a ggplot	28
3.2 Further geoms	30
3.3 Highlighting subsets	32
3.4 Fine-tuning a plot	32
3.5 Faceting	34
3.6 Saving ggplots	35
4 Summarizing data	36
4.1 Summary functions	36
4.2 Missing values	37
4.3 Grouped summaries	38
4.4 t-test	40

5	Thinking in R	42
5.1	Lists	43
5.2	Other types not covered here	43
5.3	Programming	44
6	Next steps	45
6.1	Deepen your understanding	45
6.2	Expand your vocabulary	45
6.3	Join the community	46

Introduction



These are course notes for the “Introduction to R” course given by the Monash Bioinformatics Platform¹ for the Monash Data Fluency² initiative. Our teaching style is based on the style of The Carpentries³. This is a new version of the course focussing on the modern Tidyverse⁴ set of packages. We believe this is currently the quickest route to being productive in R.

- PDF version for printing⁵
- ZIP of data files used in this workshop⁶

During the workshop we will be using the RStudio Cloud to use R over the web:

- RStudio Cloud⁷

You can also install R on your own computer. There are two things to download and install:

- Download R⁸
- Download RStudio⁹

R is the language itself. RStudio provides a convenient environment in which to use R, either on your local computer or on a server.

Source code

This book was created in R using the `rmarkdown` and `bookdown` packages!

¹<https://www.monash.edu/researchinfrastructure/bioinformatics>

²<https://monashdatafluency.github.io/>

³<https://carpentries.org/>

⁴<https://www.tidyverse.org/>

⁵<https://monashdatafluency.github.io/r-intro-2/r-intro-2.pdf>

⁶<https://monashdatafluency.github.io/r-intro-2/r-intro-2-files.zip>

⁷<https://rstudio.cloud/>

⁸<https://cran.rstudio.com/>

⁹<https://www.rstudio.com/products/rstudio/download/>

- GitHub page¹⁰

Authors and copyright

This course is developed for the Monash Bioinformatics Platform by Paul Harrison.



This work is licensed under a CC BY-4: Creative Commons Attribution 4.0 International License¹¹. The attribution is “Monash Bioinformatics Platform” if copying or modifying these notes.

Data files are derived from Gapminder, which has a CC BY-4 license. The attribution is “Free data from www.gapminder.org”. The data is given here in a form designed to teach various points about the R language. Refer to the Gapminder site¹² for the original form of the data if using it for other uses.

¹⁰<https://github.com/MonashDataFluency/r-intro-2>

¹¹<http://creativecommons.org/licenses/by/4.0/>

¹²<https://www.gapminder.org>

Chapter 1

Starting out in R

R is both a programming language and an interactive environment for data exploration and statistics. Today we will be concentrating on R as an *interactive environment*.

Working with R is primarily text-based. The basic mode of use for R is that the user types in a command in the R language and presses enter, and then R computes and displays the result.


We will be working in RStudio¹. The easiest way to get started is to go to RStudio Cloud² and create a new project. Monash staff and students can log in using their Monash Google account.

The main way of working with R is the *console*, where you enter commands and view results. RStudio surrounds this with various conveniences. In addition to the console panel, RStudio provides panels containing:

- A text editor, where R commands can be recorded for future reference.
- A history of commands that have been typed on the console.
- An “environment” pane with a list of *variables*, which contain values that R has been told to save from previous commands.
- A file manager.
- Help on the functions available in R.
- A panel to show plots.

¹<https://www.rstudio.com/products/rstudio/download/>

²<https://rstudio.cloud/>



Open RStudio, click on the “Console” pane, type `1+1` and press enter. R displays the result of the calculation. In this document, we will show such an interaction with R as below.

```
1+1
```

```
## [1] 2
```

`+` is called an operator. R has the operators you would expect for basic mathematics: `+` `-` `*` `/` `^`. It also has operators that do more obscure things.

`*` has higher precedence than `+`. We can use brackets if necessary `()`. Try `1+2*3` and `(1+2)*3`.

Spaces can be used to make code easier to read.

We can compare with `==` `<` `>` `<=` `>=` `!=`. This produces a *logical* value, `TRUE` or `FALSE`. Note the double equals, `==`, for equality comparison.

```
2 * 2 == 4
```

```
## [1] TRUE
```

There are also character strings such as `"string"`. A character string must be surrounded by either single or double quotes.

1.1 Variables

A variable is a name for a value. We can create a new variable by assigning a value to it using `<-`.

```
width <- 5
```

RStudio helpfully shows us the variable in the “Environment” pane. We can also print it by typing the name of the variable and hitting enter. In general, R will print to the console any object returned by a function or operation *unless* we assign it to a variable.

```
width
```

```
## [1] 5
```

Examples of valid variables names: `hello`, `subject_id`, `subject.ID`, `x42`. Spaces aren't ok *inside* variable names. Dots (`.`) are ok in R, unlike in many other languages. Numbers are ok, except as the first character. Punctuation is not allowed, with two exceptions: `_` and `..`.

We can do arithmetic with the variable:

```
# Area of a square
width * width
```

```
## [1] 25
```

and even save the result in another variable:

```
# Save area in "area" variable
area <- width * width
```

We can also change a variable's value by assigning it a new value:

```
width <- 10
width
```

```
## [1] 10
```

```
area
```

```
## [1] 25
```

Notice that the value of `area` we calculated earlier hasn't been updated. Assigning a new value to one variable does not change the values of other variables. This is different to a spreadsheet, but usual for programming languages.

1.2 Saving code in an R script

Once we've created a few variables, it becomes important to record how they were calculated so we can reproduce them later.

The usual workflow is to save your code in an R script (".R file"). Go to "File/New File/R Script" to create a new R script. Code in your R script can be sent to the console by selecting it or placing the cursor on the correct line, and then pressing **Control-Enter** (**Command-Enter** on a Mac).

Tip

Add comments to code, using lines starting with the `#` character. This makes it easier for others to follow what the code is doing (and also for us the next time we come back to it).

Challenge: using variables

1. Re-write this calculation so that it *doesn't* use variables:


```
a <- 4*20
b <- 7
a+b
```

2. Re-write this calculation over multiple lines, using a variable:

```
2*2+2*2+2*2
```

1.3 Vectors

A *vector* of numbers is a collection of numbers. “Vector” means different things in different fields (mathematics, geometry, biology), but in R it is a fancy name for a collection of numbers. We call the individual numbers *elements* of the vector.

We can make vectors with `c()`, for example `c(1,2,3)`. `c` means “combine”. R is obsessed with vectors, in R even single numbers are vectors of length one. Many things that can be done with a single number can also be done with a vector. For example arithmetic can be done on vectors as it can be on single numbers.

```
myvec <- c(10,20,30,40,50)
myvec
```

```
## [1] 10 20 30 40 50
```

```
myvec + 1
```

```
## [1] 11 21 31 41 51
```

```
myvec + myvec
```

```
## [1] 20 40 60 80 100
```

```
length(myvec)
```

```
## [1] 5
```

```
c(60, myvec)
```

```
## [1] 60 10 20 30 40 50
```

```
c(myvec, myvec)
```

```
## [1] 10 20 30 40 50 10 20 30 40 50
```

When we talk about the length of a vector, we are talking about the number of numbers in the vector.

1.4 Types of vector

We will also encounter vectors of character strings, for example `"hello"` or `c("hello","world")`. Also we will encounter “logical” vectors, which contain `TRUE` and `FALSE` values. R also has “factors”, which are categorical vectors, and behave much like character vectors (think the factors in an experiment).

Challenge: mixing types

Sometimes the best way to understand R is to try some examples and see what it does.

What happens when you try to make a vector containing different types, using `c()`? Make a vector with some numbers, and some words (eg. character strings like `"test"`, or `"hello"`).

Why does the output show the numbers surrounded by quotes " " like character strings are?

Because vectors can only contain one type of thing, R chooses a lowest common denominator type of vector, a type that can contain everything we are trying to put in it. A different language might stop with an error, but R tries to soldier on as best it can. A number can be represented as a character string, but a character string can not be represented as a number, so when we try to put both in the same vector R converts everything to a character string.

1.5 Indexing vectors

Access elements of a vector with `[]`, for example `myvec[1]` to get the first element. You can also assign to a specific element of a vector.

```
myvec[1]
```

```
## [1] 10
```

```
myvec[2]
```

```
## [1] 20
```

```
myvec[2] <- 5
```

```
myvec
```

```
## [1] 10 5 30 40 50
```

Can we use a vector to index another vector? Yes!

```
myind <- c(4,3,2)
```

```
myvec[myind]
```

```
## [1] 40 30 5
```

We could equivalently have written:

```
myvec[c(4,3,2)]
```

```
## [1] 40 30 5
```

Challenge: indexing

We can create and index character vectors as well. A cafe is using R to create their menu.

```
items <- c("spam", "eggs", "beans", "bacon", "sausage")
```

1. What does `items[-3]` produce? Based on what you find, use indexing to create a version of `items` without "spam".
2. Use indexing to create a vector containing spam, eggs, sausage, spam, and spam.
3. Add a new item, "lobster", to `items`.

1.6 Sequences

Another way to create a vector is with `::`:

```
1:10
```

```
## [1] 1 2 3 4 5 6 7 8 9 10
```

This can be useful when combined with indexing:

```
items[1:4]
```


```
## [1] "spam" "eggs" "beans" "bacon"
```

Sequences are useful for other things, such as a starting point for calculations:

```
x <- 1:10
x*x
```

```
## [1] 1 4 9 16 25 36 49 64 81 100
```

```
plot(x, x*x)
```



1.7 Functions

Functions are the things that do all the work for us in R: calculate, manipulate data, read and write to files, produce plots. R has many built in functions and we will also be loading more specialized functions from “packages”.

```
sum(myvec)
## [1] 135
```

?sum

```
rep(42, 10)
```

```
## [1] 42 42 42 42 42 42 42 42 42 42
```

```
rep(c(1,2,3), 10)
```

```
## [1] 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2
```

```
rep(c(1,2,3), times=10)
```

```
## [1] 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2
```

```
## [1] 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2 3 1 2
rep(times=10, x=c(1,2,3))
```

Arguments can have default values, and a function may have many different possible arguments that make it do obscure things. For example, `rep` can also take an argument `each=`. It's typical for a function to be invoked with some number of positional arguments, which are always given, plus some less commonly used arguments, typically given by name.

```
## [1] 1 1 1 2 2 2 3 3 3
rep(c(1,2,3), each=3, times=5)
```

11

Challenge: using functions

1. Use `sum` to sum from 1 to 10,000.
2. Look at the documentation for the `seq` function. What does `seq` do? Give an example of using `seq` with either the `by` or `length.out` argument.

Chapter 2

Data frames

Data frame is R's name for tabular data. We generally want each row in a data frame to represent a unit of observation, and each column to contain a different type of information about the units of observation. Tabular data in this form is called “tidy data”¹.

Today we will be using a collection of modern packages collectively known as the Tidyverse². R and its predecessor S have a history dating back to 1976. The Tidyverse fixes some dubious design decisions baked into “base R”, including having its own slightly improved form of data frame, which is called a *tibble*. Sticking to the Tidyverse where possible is generally safer, Tidyverse packages are more willing to generate errors rather than ignore problems.

2.1 Setting up

Our first step is to download the files we need and to install the Tidyverse. This is the one step where we ask you to copy and paste some code:

```
# Download files for this workshop
download.file(
  "https://monashdatafluency.github.io/r-intro-2/r-intro-2-files.zip",
  destfile="r-intro-2-files.zip")
unzip("r-intro-2-files.zip")

# Install Tidyverse
install.packages("tidyverse")
```

If using RStudio Cloud, you might need to switch to R version 3.5.3 to successfully install Tidyverse. Use the drop-down in the top right corner of the page.

People also sometimes have problems installing all the packages in Tidyverse on Windows machines. If you run into problems you may have more success installing individual packages.

¹<http://vita.had.co.nz/papers/tidy-data.html>

²<https://www.tidyverse.org/>

```
install.packages(c("dplyr", "readr", "tidyr", "ggplot2"))
```

We need to load the `tidyverse` package in order to use it.

```
library(tidyverse)

# OR
library(dplyr)
library(readr)
library(tidyr)
library(ggplot2)
```

The `tidyverse` package loads various other packages, setting up a modern R environment. In this section we will be using functions from the `dplyr`, `readr` and `tidyr` packages.

R is a language with mini-languages within it that solve specific problem domains. `dplyr` is such a mini-language, a set of “verbs” (functions) that work well together. `dplyr`, with the help of `tidyr` for some more complex operations, provides a way to perform most manipulations on a data frame that you might need.

2.2 Loading data

We will use the `read_csv` function from `readr` to load a data set. (See also `read.csv` in base R.) CSV stands for Comma Separated Values, and is a text format used to store tabular data. The first few lines of the file we are loading are shown below. Conventionally the first line contains column headings.

```
name,region,oecd,g77,lat,long,income2017
Afghanistan,asia,FALSE,TRUE,33,66,low
Albania,europe,FALSE,FALSE,41,20,upper_mid
Algeria,africa,FALSE,TRUE,28,3,upper_mid
Andorra,europe,FALSE,FALSE,42.50779,1.52109,high
Angola,africa,FALSE,TRUE,-12.5,18.5,lower_mid
```

```
geo <- read_csv("r-intro-2-files/geo.csv")
```

```
## Rows: 196 Columns: 7
```

```
## -- Column specification -----
```

```
## Delimiter: ","
```

```
## chr (3): name, region, income2017
```

```
## dbl (2): lat, long
```

```
## lgl (2): oecd, g77
```

```
##
```

```
## i Use `spec()` to retrieve the full column specification for this data.
```

```
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
geo
```

```
## # A tibble: 196 x 7
```

```
##   name          region  oecd  g77    lat    long income2017
```

```
##      <chr>                <chr>    <lgl> <lgl> <dbl>  <dbl> <chr>
##  1 Afghanistan          asia      FALSE TRUE   33    66   low
##  2 Albania               europe    FALSE FALSE  41    20  upper_mid
##  3 Algeria               africa    FALSE TRUE   28     3  upper_mid
##  4 Andorra               europe    FALSE FALSE  42.5  1.52 high
##  5 Angola                africa    FALSE TRUE  -12.5  18.5 lower_mid
##  6 Antigua and Barbuda  americas FALSE TRUE   17.0 -61.8 high
##  7 Argentina            americas FALSE TRUE  -34   -64  upper_mid
##  8 Armenia              europe    FALSE FALSE  40.2  45   lower_mid
##  9 Australia            asia      TRUE  FALSE  -25   135  high
## 10 Austria              europe    TRUE  FALSE  47.3  13.3 high
## # ... with 186 more rows
```

`read_csv` has guessed the type of data each column holds:

- `<chr>` - character strings
- `<dbl>` - numerical values. Technically these are “doubles”, which is a way of storing numbers with 15 digits precision.
- `<lgl>` - logical values, `TRUE` or `FALSE`.

We will also encounter:

- `<int>` - integers, a fancy name for whole numbers.
- `<fct>` - factors, categorical data. We will get to this shortly.

You can also see this data frame referring to itself as “a tibble”. This is the Tidyverse’s improved form of data frame. Tibbles present themselves more conveniently than base R data frames. Base R data frames don’t show the type of each column, and output every row when you try to view them.

Tip

A data frame can also be created from vectors, with the `tibble` function. (See also `data.frame` in base R.) For example:

```
tibble(foo=c(10,20,30), bar=c("a","b","c"))
```


```
## # A tibble: 3 x 2
##   foo bar
##   <dbl> <chr>
## 1   10 a
## 2   20 b
## 3   30 c
```

The argument names become column names in the data frame.

Tip

The *path* to the file on our server is `"r-intro-2-files/geo.csv"`. This says, starting from your working directory, look in the directory `r-intro-2-files` for the file `geo.csv`. The steps in the path are separated by `/`. Your working directory is shown at the top of the console pane. The path needed might be different on your own computer, depending where you downloaded the file.

One way to work out the correct path is to find the file in the file browser pane, click on it and select “Import Dataset...”.



2.3 Exploring

The `View` function gives us a spreadsheet-like view of the data frame.

```
View(geo)
```

`print` with the `n` argument can be used to show more than the first 10 rows on the console.

```
print(geo, n=200)
```

We can extract details of the data frame with further functions:

```
nrow(geo)
```

```
## [1] 196
```

```
ncol(geo)
```

```
## [1] 7
```

```
colnames(geo)
```

```
## [1] "name"      "region"    "oecd"      "g77"      "lat"
## [6] "long"      "income2017"
```

```
summary(geo)
```

```
##      name      region      oecd      g77
## Length:196   Length:196   Mode :logical Mode :logical
## Class :character Class :character FALSE:165  FALSE:65
## Mode :character Mode :character  TRUE :31   TRUE :131
##
##
##      lat      long      income2017
## Min.   :-42.00 Min.   :-175.000 Length:196
## 1st Qu.:  4.00 1st Qu.: -5.625 Class :character
## Median : 17.42 Median :  21.875 Mode :character
## Mean   : 19.03 Mean   :  23.004
## 3rd Qu.: 39.82 3rd Qu.:  51.892
```

```
## Max. : 65.00 Max. : 179.145
```

2.4 Indexing data frames

Data frames can be subset using `[row,column]` syntax.

```
geo[4,2]
```

```
## # A tibble: 1 x 1
##   region
##   <chr>
## 1 europe
```

Note that while this is a single value, it is still wrapped in a data frame. (This is a behaviour specific to Tidyverse data frames.) More on this in a moment.

Columns can be given by name.

```
geo[4,"region"]
```

```
## # A tibble: 1 x 1
##   region
##   <chr>
## 1 europe
```

The column or row may be omitted, thereby retrieving the entire row or column.

```
geo[4,]
```

```
## # A tibble: 1 x 7
##   name      region oecd  g77    lat  long income2017
##   <chr>    <chr> <lgl> <lgl> <dbl> <dbl> <chr>
## 1 Andorra europe FALSE FALSE  42.5  1.52 high
```

```
geo[, "region"]
```

```
## # A tibble: 196 x 1
##   region
##   <chr>
## 1 asia
## 2 europe
## 3 africa
## 4 europe
## 5 africa
## 6 americas
## 7 americas
## 8 europe
## 9 asia
## 10 europe
## # ... with 186 more rows
```

Multiple rows or columns may be retrieved using a vector.

```
rows_wanted <- c(1,3,5)
geo[rows_wanted,]
```

```
## # A tibble: 3 x 7
##   name      region oecd g77    lat  long income2017
##   <chr>      <chr> <lgl> <lgl> <dbl> <dbl> <chr>
## 1 Afghanistan asia  FALSE TRUE   33    66 low
## 2 Algeria    africa FALSE TRUE   28     3 upper_mid
## 3 Angola     africa FALSE TRUE  -12.5 18.5 lower_mid
```

Vector indexing can also be written on a single line.

```
geo[c(1,3,5),]
```

```
## # A tibble: 3 x 7
##   name      region oecd g77    lat  long income2017
##   <chr>      <chr> <lgl> <lgl> <dbl> <dbl> <chr>
## 1 Afghanistan asia  FALSE TRUE   33    66 low
## 2 Algeria    africa FALSE TRUE   28     3 upper_mid
## 3 Angola     africa FALSE TRUE  -12.5 18.5 lower_mid
```

```
geo[1:7,]
```

```
## # A tibble: 7 x 7
##   name      region oecd g77    lat  long income2017
##   <chr>      <chr> <lgl> <lgl> <dbl> <dbl> <chr>
## 1 Afghanistan asia  FALSE TRUE   33    66 low
## 2 Albania    europe FALSE FALSE  41    20 upper_mid
## 3 Algeria    africa FALSE TRUE   28     3 upper_mid
## 4 Andorra    europe FALSE FALSE 42.5  1.52 high
## 5 Angola     africa FALSE TRUE  -12.5 18.5 lower_mid
## 6 Antigua and Barbuda americas FALSE TRUE   17.0 -61.8 high
## 7 Argentina  americas FALSE TRUE  -34   -64 upper_mid
```

2.5 Columns are vectors

Ok, so how do we actually get data out of a data frame?

Under the hood, a data frame is a list of column vectors. We can use `$` to retrieve columns. Occasionally it is also useful to use `[[]]` to retrieve columns, for example if the column name we want is stored in a variable.

```
head( geo$region )
```

```
## [1] "asia"      "europe"    "africa"    "europe"    "africa"    "americas"
```

```
head( geo[["region"]] )
```

```
## [1] "asia"      "europe"    "africa"    "europe"    "africa"    "americas"
```


To get the “region” value of the 4th row as above, but unwrapped, we can use:

```
geo$region[4]
```

```
## [1] "europe"
```

For example, to plot the longitudes and latitudes we could use:

```
plot(geo$long, geo$lat)
```



Quiz: reading R code

You encounter some wild R code, and aren't sure what it does. Based on R syntax you've encountered so far, what roles are the different names in this code playing?

```
highest <- geo$name[ head(order(geo$lat, decreasing=TRUE), n=10) ]
```

Find all examples of:

- A. The name of a variable to store a value to.
- B. The name of a variable to retrieve the value from.
- C. The name of a column to get from a data frame.
- D. The name of a function to call.
- E. The name of an argument to a function call.

See here³ for answers.

2.6 Logical indexing

A method of indexing that we haven't discussed yet is logical indexing. Instead of specifying the row number or numbers that we want, we can give a logical vector which is **TRUE** for the rows we want and **FALSE** otherwise. This can also be used with vectors.

We will first do this in a slightly verbose way in order to understand it, then learn a more concise way to do this using the **dplyr** package.

Southern countries have latitude less than zero.

³<https://monashdatafluency.github.io/r-intro-2/answers-reading-r-code.html>

```
is_southern <- geo$lat < 0
```

```
head(is_southern)
```

```
## [1] FALSE FALSE FALSE FALSE TRUE FALSE
```

```
sum(is_southern)
```

```
## [1] 40
```

sum treats TRUE as 1 and FALSE as 0, so it tells us the number of TRUE elements in the vector.

We can use this logical vector to get the southern countries from geo:

```
geo[is_southern,]
```

```
## # A tibble: 40 x 7
```

	name	region	oecd	g77	lat	long	income2017
	<chr>	<chr>	<lgl>	<lgl>	<dbl>	<dbl>	<chr>
## 1	Angola	africa	FALSE	TRUE	-12.5	18.5	lower_mid
## 2	Argentina	americas	FALSE	TRUE	-34	-64	upper_mid
## 3	Australia	asia	TRUE	FALSE	-25	135	high
## 4	Bolivia	americas	FALSE	TRUE	-17	-65	lower_mid
## 5	Botswana	africa	FALSE	TRUE	-22	24	upper_mid
## 6	Brazil	americas	FALSE	TRUE	-10	-55	upper_mid
## 7	Burundi	africa	FALSE	TRUE	-3.5	30	low
## 8	Chile	americas	TRUE	TRUE	-33.5	-70.6	high
## 9	Comoros	africa	FALSE	TRUE	-12.2	44.4	low
## 10	Congo, Dem. Rep.	africa	FALSE	TRUE	-2.5	23.5	low

```
## # ... with 30 more rows
```

Comparison operators available are:

- `x == y` – “equal to”
- `x != y` – “not equal to”
- `x < y` – “less than”
- `x > y` – “greater than”
- `x <= y` – “less than or equal to”
- `x >= y` – “greater than or equal to”

More complicated conditions can be constructed using logical operators:

- `a & b` – “and”, TRUE only if both `a` and `b` are TRUE.
- `a | b` – “or”, TRUE if either `a` or `b` or both are TRUE.
- `! a` – “not”, TRUE if `a` is FALSE, and FALSE if `a` is TRUE.

The `oecd` column of `geo` tells which countries are in the Organisation for Economic Co-operation and Development, and the `g77` column tells which countries are in the Group of 77 (an alliance of developing nations). We could see which OECD countries are in the southern hemisphere with:

```
southern_oecd <- is_southern & geo$oecd
```

```
geo[southern_oecd,]
```

```
## # A tibble: 3 x 7
##   name      region  oecd  g77    lat  long income2017
##   <chr>    <chr>   <lgl> <lgl> <dbl> <dbl> <chr>
## 1 Australia  asia    TRUE  FALSE -25   135   high
## 2 Chile      americas TRUE   TRUE -33.5 -70.6 high
## 3 New Zealand asia    TRUE  FALSE -42   174   high
```

`is_southern` seems like it should be kept within our `geo` data frame for future use. We can add it as a new column of the data frame with:

```
geo$southern <- is_southern
```

```
geo
```

```
## # A tibble: 196 x 8
##   name      region  oecd  g77    lat  long income2017 southern
##   <chr>    <chr>   <lgl> <lgl> <dbl> <dbl> <chr>   <lgl>
## 1 Afghanistan  asia    FALSE TRUE   33    66   low    FALSE
## 2 Albania        europe FALSE FALSE  41    20  upper_mid FALSE
## 3 Algeria        africa FALSE TRUE   28     3  upper_mid FALSE
## 4 Andorra        europe FALSE FALSE 42.5  1.52 high    FALSE
## 5 Angola         africa FALSE TRUE -12.5 18.5 lower_mid TRUE
## 6 Antigua and Barbuda americas FALSE TRUE  17.0 -61.8 high    FALSE
## 7 Argentina      americas FALSE TRUE  -34   -64  upper_mid TRUE
## 8 Armenia        europe FALSE FALSE 40.2  45   lower_mid FALSE
## 9 Australia      asia    TRUE  FALSE -25   135   high    TRUE
## 10 Austria        europe TRUE  FALSE 47.3 13.3 high    FALSE
## # ... with 186 more rows
```

Challenge: logical indexing

1. Which country is in both the OECD and the G77?
2. Which countries are in neither the OECD nor the G77?
3. Which countries are in the Americas? These have longitudes between -150 and -40.

2.6.1 A dplyr shorthand

The above method is a little laborious. We have to keep mentioning the name of the data frame, and there is a lot of punctuation to keep track of. `dplyr` provides a slightly magical function called `filter` which lets us write more concisely. For example:

```
filter(geo, lat < 0 & oecd)
```

```
## # A tibble: 3 x 8
##   name      region  oecd  g77    lat  long income2017 southern
##   <chr>    <chr>   <lgl> <lgl> <dbl> <dbl> <chr>   <lgl>
## 1 Australia  asia    TRUE  FALSE -25   135   high    TRUE
## 2 Chile      americas TRUE   TRUE -33.5 -70.6 high    TRUE
## 3 New Zealand asia    TRUE  FALSE -42   174   high    TRUE
```

In the second argument, we are able to refer to columns of the data frame as though they were variables. The code is beautiful, but also opaque. It's important to understand that under the hood we are creating and combining logical vectors.

2.7 Factors

The `count` function from `dplyr` can help us understand the contents of some of the columns in `geo`. `count` is also *magical*, we can refer to columns of the data frame directly in the arguments to `count`.

```
count(geo, region)
```

```
## # A tibble: 4 x 2
##   region      n
##   <chr>    <int>
## 1 africa     54
## 2 americas   35
## 3 asia       59
## 4 europe     48
```

```
count(geo, income2017)
```

```
## # A tibble: 4 x 2
##   income2017      n
##   <chr>        <int>
## 1 high          58
## 2 low           31
## 3 lower_mid     52
## 4 upper_mid     55
```

One annoyance here is that the different categories in `income2017` aren't in a sensible order. This comes up quite often, for example when sorting or plotting categorical data. R's solution is a further type of vector called a *factor* (think a factor of an experimental design). A factor holds categorical data, and has an associated ordered set of *levels*. It is otherwise quite similar to a character vector.

Any sort of vector can be converted to a factor using the `factor` function. This function defaults to placing the levels in alphabetical order, but takes a `levels` argument that can override this.

```
head( factor(geo$income2017, levels=c("low","lower_mid","upper_mid","high")) )
```

```
## [1] low      upper_mid upper_mid high      lower_mid high
## Levels: low lower_mid upper_mid high
```

We should modify the `income2017` column of the `geo` table in order to use this:

```
geo$income2017 <- factor(geo$income2017, levels=c("low","lower_mid","upper_mid","high"))
```


`count` now produces the desired order of output:

```
count(geo, income2017)
```

```
## # A tibble: 4 x 2
##   income2017     n
##   <fct>       <int>
## 1 low         31
## 2 lower_mid   52
## 3 upper_mid   55
## 4 high        58
```


When plot is given a factor, it shows a bar plot:

```
plot(geo$income2017)
```



When given two factors, it shows a mosaic plot:

```
plot(geo$income2017, factor(geo$oeed))
```



Similarly we can count two categorical columns at once.

```
count(geo, income2017, oeed)
```

```
## # A tibble: 6 x 3
##   income2017 oeed     n
##   <fct>       <lgl> <int>
## 1 low         FALSE    31
## 2 low         TRUE     1
## 3 lower_mid   FALSE    52
## 4 lower_mid   TRUE     1
## 5 upper_mid   FALSE    55
## 6 upper_mid   TRUE     1
## 7 high        FALSE    58
## 8 high        TRUE    10
```



```
## 1 low      FALSE 31
## 2 lower_mid FALSE 52
## 3 upper_mid FALSE 53
## 4 upper_mid TRUE  2
## 5 high     FALSE 29
## 6 high     TRUE  29
```

2.8 Readability vs tidyness

The counts we obtained counting `income2017` vs `oecd` were properly tidy in the sense of containing a single unit of observation per row. However to view the data, it would be more convenient to have income as columns and OECD membership as rows. We can use the `pivot_wider` function from `tidyr` to achieve this. (This is also sometimes also called a “cast” or a “spread”.)

```
counts <- count(geo, income2017, oecd)
pivot_wider(counts, names_from=income2017, values_from=n)
```

```
## # A tibble: 2 x 5
##   oecd    low lower_mid upper_mid  high
##   <lgl> <int>    <int>    <int> <int>
## 1 FALSE   31      52      53    29
## 2 TRUE    NA      NA      2    29
```

We could further specify `values_fill=list(n=0)` to fill in the NA values with 0.

Tip

Tidying is often the first step when exploring a data-set. The `tidyr`⁴ package contains a number of useful functions that help tidy (or un-tidy!) data. We’ve just seen `pivot_wider` which spreads two columns into multiple columns. The inverse of `pivot_wider` is `pivot_longer`, which gathers multiple columns into two columns: a column of column names, and a column of values. `pivot_longer` is often the first step when tidying a dataset you have received from the wild. (This is sometimes also called a “melt” or a “gather”.)

Challenge: counting

Investigate how many OECD and non-OECD nations come from the northern and southern hemispheres.

1. Using `count`.
2. By making a mosaic plot.

Remember you may need to convert columns to factors for `plot` to work, and that a `southern` column could be added to `geo` with:

```
geo$southern <- geo$lat < 0
```

⁴<http://tidyr.tidyverse.org/>

2.9 Sorting

Data frames can be sorted using the `arrange` function in `dplyr`.

```
arrange(gео, lat)
```

```
## # A tibble: 196 x 8
##   name      region  оecd  g77    lat  long income2017 southern
##   <chr>    <chr>   <lgl> <lgl> <dbl> <dbl> <fct>      <lgl>
## 1 New Zealand asia    TRUE FALSE -42   174   high      TRUE
## 2 Argentina  americas FALSE TRUE  -34   -64   upper_mid TRUE
## 3 Chile      americas TRUE  TRUE -33.5 -70.6 high      TRUE
## 4 Uruguay    americas FALSE TRUE  -33   -56   high      TRUE
## 5 Lesotho    africa  FALSE TRUE  -29.5 28.2 lower_mid TRUE
## 6 South Africa africa  FALSE TRUE  -29    24   upper_mid TRUE
## 7 Swaziland  africa  FALSE TRUE  -26.5 31.5 lower_mid TRUE
## 8 Australia  asia    TRUE FALSE -25   135   high      TRUE
## 9 Paraguay   americas FALSE TRUE -23.3 -58   upper_mid TRUE
## 10 Botswana  africa  FALSE TRUE  -22    24   upper_mid TRUE
## # ... with 186 more rows
```

Numeric columns are sorted in numeric order. Character columns will be sorted in alphabetical order. Factor columns are sorted in order of their levels. The `desc` helper function can be used to sort in descending order.

```
arrange(geo, desc(name))
```

```
## # A tibble: 196 x 8
##   name      region  оecd  g77    lat  long income2017 southern
##   <chr>    <chr>   <lgl> <lgl> <dbl> <dbl> <fct>      <lgl>
## 1 Zimbabwe  africa  FALSE TRUE  -19   29.8 low      TRUE
## 2 Zambia    africa  FALSE TRUE -14.3 28.5 lower_mid TRUE
## 3 Yemen     asia    FALSE TRUE  15.5 47.5 lower_mid FALSE
## 4 Vietnam   asia    FALSE TRUE  16.2 108. lower_mid FALSE
## 5 Venezuela americas FALSE TRUE   8   -66   upper_mid FALSE
## 6 Vanuatu    asia    FALSE TRUE  -16  167   lower_mid TRUE
## 7 Uzbekistan asia    FALSE FALSE 41.7 63.8 lower_mid FALSE
## 8 Uruguay    americas FALSE TRUE  -33   -56   high      TRUE
## 9 United States americas TRUE  FALSE 39.8 -98.5 high      FALSE
## 10 United Kingdom europe  TRUE  FALSE 54.8 -2.70 high      FALSE
## # ... with 186 more rows
```

2.10 Joining data frames

Let's move on to a larger data set. This is from the Gapminder⁵ project and contains information about countries over time.

```
gap <- read_csv("r-intro-2-files/gap-minder.csv")
gap
```

⁵<https://www.gapminder.org>

```
## # A tibble: 4,312 x 5
##   name          year population gdp_percap life_exp
##   <chr>         <dbl>     <dbl>     <dbl>     <dbl>
## 1 Afghanistan  1800     3280000      603      28.2
## 2 Albania      1800     410445      667      35.4
## 3 Algeria      1800    2503218      715      28.8
## 4 Andorra      1800       2654     1197      NA
## 5 Angola       1800    1567028      618      27.0
## 6 Antigua and Barbuda 1800      37000      757      33.5
## 7 Argentina    1800    534000     1507      33.2
## 8 Armenia      1800    413326      514       34
## 9 Australia    1800    351014      814      34.0
## 10 Austria     1800    3205587     1847      34.4
## # ... with 4,302 more rows
```

Quiz

What is the unit of observation in this new data frame?

It would be useful to have general information about countries from `geo` available as columns when we use this data frame. `gap` and `geo` share a column called `name` which can be used to match rows from one to the other.

```
gap_geo <- left_join(gap, geo, by="name")
gap_geo
```

```
## # A tibble: 4,312 x 12
##   name          year population gdp_percap life_exp region oecd g77    lat    long
##   <chr>         <dbl>     <dbl>     <dbl>     <dbl> <chr> <lgl> <lgl> <dbl> <dbl>
## 1 Afghani~  1800     3280000      603      28.2 asia  FALSE TRUE    33     66
## 2 Albania  1800     410445      667      35.4 europe FALSE FALSE   41     20
## 3 Algeria  1800    2503218      715      28.8 africa FALSE TRUE    28      3
## 4 Andorra  1800       2654     1197      NA europe FALSE FALSE  42.5    1.52
## 5 Angola   1800    1567028      618      27.0 africa FALSE TRUE  -12.5   18.5
## 6 Antigua~ 1800      37000      757      33.5 ameri~ FALSE TRUE   17.0  -61.8
## 7 Argenti~ 1800    534000     1507      33.2 ameri~ FALSE TRUE  -34    -64
## 8 Armenia  1800    413326      514       34 europe FALSE FALSE  40.2    45
## 9 Austral~ 1800    351014      814      34.0 asia  TRUE  FALSE  -25    135
## 10 Austria 1800    3205587     1847      34.4 europe TRUE   FALSE  47.3   13.3
## # ... with 4,302 more rows, and 2 more variables: income2017 <fct>,
## #   southern <lgl>
```

The output contains all ways of pairing up rows by `name`. In this case each row of `geo` pairs up with multiple rows of `gap`.

The “left” in “left join” refers to how rows that can’t be paired up are handled. `left_join` keeps all rows from the first data frame but not the second. This is a good default when the intent is to attaching some extra information to a data frame. `inner_join` discards all rows that can’t be paired up. `full_join` keeps all rows from both data frames.

2.11 Further reading

We’ve covered the fundamentals of `dplyr` and data frames, but there is much more to learn. Notably, we haven’t covered the use of the pipe `%>%` to chain `dplyr` verbs together. The “R for Data Science” book⁶ is an excellent source to learn more. The Monash Data Fluency “Programming and Tidy data analysis in R” course⁷ also covers this.

⁶<http://r4ds.had.co.nz/>

⁷<https://monashdatafluency.github.io/r-progtidy/>

Chapter 3

Plotting with ggplot2

We already saw some of R’s built in plotting facilities with the function `plot`. A more recent and much more powerful plotting library is `ggplot2`. `ggplot2` is another mini-language within R, a language for creating plots. It implements ideas from a book called “The Grammar of Graphics”¹. The syntax can be a little strange, but there are plenty of examples in the online documentation².

`ggplot2` is part of the Tidyverse, so loading the `tidyverse` package will load `ggplot2`.

```
library(tidyverse)
```

We continue with the Gapminder dataset, which we loaded with:

```
geo <- read_csv("r-intro-2-files/geo.csv")
gap <- read_csv("r-intro-2-files/gap-minder.csv")
gap_geo <- left_join(gap, geo, by="name")
```

3.1 Elements of a ggplot

Producing a plot with `ggplot2`, we must give three things:


1. A data frame containing our data.
2. How the columns of the data frame can be translated into positions, colors, sizes, and shapes of graphical elements (“aesthetics”).
3. The actual graphical elements to display (“geometric objects”).

Let’s make our first `ggplot`.

```
ggplot(gap_geo, aes(x=year, y=life_exp)) +
  geom_point()
```

¹<https://www.amazon.com/Grammar-Graphics-Statistics-Computing/dp/0387245448>


²<http://ggplot2.tidyverse.org/reference/>



The call to `ggplot` and `aes` sets up the basics of how we are going to represent the various columns of the data frame. `aes` defines the “aesthetics”, which is how columns of the data frame map to graphical attributes such as x and y position, color, size, etc. `aes` is another example of magic “non-standard evaluation”, arguments to `aes` may refer to columns of the data frame directly. We then literally add layers of graphics (“geoms”) to this.

Further aesthetics can be used. Any aesthetic can be either numeric or categorical, an appropriate scale will be used.

```
ggplot(gap_geo, aes(x=year, y=life_exp, color=region, size=population)) +  
  geom_point()
```



3.1.1 Challenge: make a ggplot

This R code will get the data from the year 2010:

```
gap2010 <- filter(gap_geo, year == 2010)
```


Create a ggplot of this with:

- `gdp_percap` as x.
- `life_exp` as y.
- `population` as the size.
- `region` as the color.

3.2 Further geoms


To draw lines, we need to use a “group” aesthetic.

```
ggplot(gap_geo, aes(x=year, y=life_exp, group=name, color=region)) +  
  geom_line()
```



A wide variety of geoms are available. Here we show Tukey box-plots. Note again the use of the “group” aesthetic, without this ggplot will just show one big box-plot.


```
ggplot(gap_geo, aes(x=year, y=life_exp, group=year)) +  
  geom_boxplot()
```



`geom_smooth` can be used to show trends.

```
ggplot(gap_geo, aes(x=year, y=life_exp)) +
  geom_point() +
  geom_smooth()
```


```
## `geom_smooth()` using method = 'gam' and formula 'y ~ s(x, bs = "cs")'
```



Aesthetics can be specified globally in `ggplot`, or as the first argument to individual geoms. Here, the “group” is applied only to draw the lines, and “color” is used to produce multiple trend lines:

```
ggplot(gap_geo, aes(x=year, y=life_exp)) +
  geom_line(aes(group=name)) +
  geom_smooth(aes(color=oe.cd))
```

```
## `geom_smooth()` using method = 'gam' and formula 'y ~ s(x, bs = "cs")'
```




3.3 Highlighting subsets

Geoms can be added that use a different data frame, using the `data=` argument.

```
gap_australia <- filter(gap_geo, name == "Australia")

ggplot(gap_geo, aes(x=year, y=life_exp, group=name)) +
  geom_line() +
  geom_line(data=gap_australia, color="red", size=2)
```




Notice also that the second `geom_line` has some further arguments controlling its appearance. These are **not** aesthetics, they are not a mapping of data to appearance, but rather a direct specification of the appearance. There isn't an associated scale as when color was an aesthetic.

3.4 Fine-tuning a plot


Adding `labs` to a `ggplot` adjusts the labels given to the axes and legends. A plot title can also be specified.

```
ggplot(gap_geo, aes(x=year, y=life_exp)) +
  geom_point() +
  labs(x="Year", y="Life expectancy", title="Gapminder")
```



Now, the figure has proper labels and titles. However, the title is not at the center of the figure. We can further customize it using `theme()` function (for more detail please see the docs `?theme`).


```
ggplot(gap_geo, aes(x=year, y=life_exp)) +
  geom_point() +
  labs(x="Year", y="Life expectancy", title="Gapminder") +
  theme(plot.title = element_text(hjust = 0.5))
```



Now figure looks better.

`coord_cartesian` can be used to set the limits of the x and y axes. Suppose we want our y-axis to start at zero.

```
ggplot(gap_geo, aes(x=year, y=life_exp)) +
  geom_point() +
  coord_cartesian(ylim=c(0,90))
```



Type `scale_` and press the tab key. You will see functions giving fine-grained controls over various scales (x, y, color, etc). These allow transformations (eg `log10`), and manually specified breaks (labelled values). Very fine grained control is possible over the appearance of ggplots, see the `ggplot2` documentation for details and further examples.


3.4.1 Challenge: refine your ggplot

Continuing with your scatter-plot of the 2010 data, add axis labels to your plot. Give your x axis a log scale by adding `scale_x_log10()`.

3.5 Faceting

Faceting lets us quickly produce a collection of small plots. The plots all have the same scales and the eye can easily compare them.

```
ggplot(gap_geo, aes(x=year, y=life_exp, group=name)) +  
  geom_line() +  
  facet_wrap(~ region)
```



Note the use of `~`, which we've not seen before. `~` syntax is used in R to specify dependence on some set of variables, for example when specifying a linear model. Here the information in each plot is dependent on the continent.

3.5.1 Challenge: facet your ggplot

Let's return again to your scatter-plot of the 2010 data.

Adjust your plot to now show data from all years, with each year shown in a separate facet, using `facet_wrap(~ year)`.

Advanced: Highlight Australia in your plot.

3.6 Saving ggplots

The act of plotting a ggplot is actually triggered when it is printed. In an interactive session we are automatically printing each value we calculate, but if you are using it with a programming construct such as a for loop or function you might need to explicitly `print()` the plot.

Ggplots can be saved using `ggsave`.

```
# Plot created but not shown.
p <- ggplot(gap_geo, aes(x=year, y=life_exp)) + geom_point()

# Only when we try to look at the value p is it shown
p

# Alternatively, we can explicitly print it
print(p)

# To save to a file
ggsave("test.png", p)

# This is an alternative method that works with "base R" plots as well:
png("test.png")
print(p)
dev.off()
```

3.6.1 Tip about sizing

Figures in papers tend to be quite small. This means text must be proportionately larger than we usually show on screen. Dots should also be proportionately larger, and lines proportionately thicker. The way to achieve this using `ggsave` is to specify a small width and height, given in inches. To ensure the output also has good resolution, specify a high dots-per-inch, or use a vector-graphics format such as PDF or SVG.

```
ggsave("test2.png", p, width=3, height=3, dpi=600)
```

Chapter 4

Summarizing data

Having loaded and thoroughly explored a data set, we are ready to distill it down to concise conclusions. At its simplest, this involves calculating summary statistics like counts, means, and standard deviations. Beyond this is the fitting of models, and hypothesis testing and confidence interval calculation. R has a huge number of packages devoted to these tasks and this is a large part of its appeal, but is beyond the scope of today.

Loading the data as before, if you have not already done so:

```
library(tidyverse)

geo <- read_csv("r-intro-2-files/geo.csv")
gap <- read_csv("r-intro-2-files/gap-minder.csv")
gap_geo <- left_join(gap, geo, by="name")
```

4.1 Summary functions

R has a variety of functions for summarizing a vector, including: `sum`, `mean`, `min`, `max`, `median`, `sd`.

```
mean( c(1,2,3,4) )
```

```
## [1] 2.5
```

We can use these on the Gapminder data.

```
gap2010 <- filter(gap_geo, year == 2010)
sum(gap2010$population)
```

```
## [1] 6949495061
```

```
mean(gap2010$life_exp)
```

```
## [1] NA
```

4.2 Missing values

Why did `mean` fail? The reason is that `life_exp` contains missing values (`NA`).

```
gap2010$life_exp
```

```
## [1] 56.20 76.31 76.55 82.66 60.08 76.85 75.82 73.34 81.98 80.50 69.13 73.79
## [13] 76.03 70.39 76.68 70.43 79.98 71.38 61.82 72.13 71.64 76.75 57.06 74.19
## [25] 77.08 73.86 57.89 57.73 66.12 57.25 81.29 72.45 47.48 56.49 79.12 74.59
## [37] 76.44 65.93 57.53 60.43 80.40 56.34 76.33 78.39 79.88 77.47 79.49 63.69
## [49] 73.04 74.60 76.72 70.52 74.11 60.93 61.66 76.00 61.30 65.28 80.00 81.42
## [61] 62.86 65.55 72.82 80.09 62.16 80.41 71.34 71.25 57.99 55.65 65.49 32.11
## [73] 71.58 82.61 74.52 82.03 66.20 69.90 74.45 67.24 80.38 81.42 81.69 74.66
## [85] 82.85 75.78 68.37 62.76 60.73 70.10 80.13 78.20 68.45 63.80 73.06 79.85
## [97] 46.50 60.77 76.10 NA 73.17 81.35 74.01 60.84 53.07 74.46 77.91 59.46
## [109] 80.28 63.72 68.23 73.42 75.47 65.38 69.74 NA 66.18 76.36 73.55 54.48
## [121] 66.84 58.60 NA 68.26 80.73 80.90 77.36 58.78 60.53 81.04 76.09 65.33
## [133] NA 77.85 58.70 74.07 77.92 69.03 76.30 79.84 79.52 73.66 69.24 64.59
## [145] NA 75.48 71.64 71.46 NA 68.91 75.13 64.01 74.65 73.38 55.05 82.69
## [157] 75.52 79.45 61.71 53.13 54.27 81.94 74.42 66.29 70.32 46.98 81.52 82.21
## [169] 76.15 79.19 69.61 59.30 76.57 71.10 58.74 69.86 72.56 76.89 78.21 67.94
## [181] NA 56.81 70.41 76.51 80.34 78.74 76.36 68.77 63.02 75.41 72.27 73.07
## [193] 67.51 52.02 49.57 58.13
```

R will not ignore these unless we explicitly tell it to with `na.rm=TRUE`.

```
mean(gap2010$life_exp, na.rm=TRUE)
```

```
## [1] 70.34005
```

Ideally we should also use `weighted.mean` here, to take population into account.

```
weighted.mean(gap2010$life_exp, gap2010$population, na.rm=TRUE)
```

```
## [1] 70.96192
```

`NA` is a special value. If we try to calculate with `NA`, the result is `NA`

```
NA + 1
```

```
## [1] NA
```

`is.na` can be used to detect `NA` values, or `na.omit` can be used to directly remove rows of a data frame containing them.

```
is.na( c(1,2,NA,3) )
```

```
## [1] FALSE FALSE TRUE FALSE
```

```
cleaned <- filter(gap2010, !is.na(life_exp))
weighted.mean(cleaned$life_exp, cleaned$population)
```

```
## [1] 70.96192
```

4.3 Grouped summaries

The `summarize` function in `dplyr` allows summary functions to be applied to data frames.

```
summarize(gap2010, mean_life_exp=weighted.mean(life_exp, population, na.rm=TRUE))

## # A tibble: 1 x 1
##   mean_life_exp
##           <dbl>
## 1           71.0
```

So far unremarkable, but `summarize` comes into its own when the `group_by` “adjective” is used.

```
summarize(
  group_by(gap_geo, year),
  mean_life_exp=weighted.mean(life_exp, population, na.rm=TRUE))

## # A tibble: 22 x 2
##   year mean_life_exp
##   <dbl>         <dbl>
## 1  1800          30.9
## 2  1810          31.1
## 3  1820          31.2
## 4  1830          31.4
## 5  1840          31.4
## 6  1850          31.6
## 7  1860          30.3
## 8  1870          31.5
## 9  1880          32.0
## 10 1890          32.5
## # ... with 12 more rows
```

Challenge: summarizing

What is the total population for each year? Plot the result.

Advanced: What is the total GDP for each year? For this you will first need to calculate GDP per capita times the population of each country.


`group_by` can be used to group by multiple columns, much like `count`. We can use this to see how the rest of the world is catching up to OECD nations in terms of life expectancy.

```
result <- summarize(
  group_by(gap_geo, year, oecd),
  mean_life_exp=weighted.mean(life_exp, population, na.rm=TRUE))
```

`## `summarise()` has grouped output by 'year'. You can override using the ``.groups` argument`

```
result
```

```
## # A tibble: 44 x 3
## # Groups:   year [22]
##   year oecd mean_life_exp
##   <dbl> <lgl>      <dbl>
## 1  1800 FALSE        29.9
## 2  1800 TRUE         34.7
## 3  1810 FALSE        29.9
## 4  1810 TRUE         35.2
## 5  1820 FALSE        30.0
## 6  1820 TRUE         35.9
## 7  1830 FALSE        30.0
## 8  1830 TRUE         36.2
## 9  1840 FALSE        30.0
## 10 1840 TRUE         36.2
## # ... with 34 more rows
ggplot(result, aes(x=year, y=mean_life_exp, color=oecd)) + geom_line()
```



A similar plot could be produced using `geom_smooth`. Differences here are that we have full control over the summarization process so we were able to use the exact summarization method we want (`weighted.mean` for each year), and we have access to the resulting numeric data as well as the plot. We have reduced a large data set down to a smaller one that distills out one of the stories present in this data. However the earlier visualization and exploration activity using `ggplot2` was essential. It gave us an idea of what sort of variability was present in the data, and any unexpected issues the data might have.

4.4 t-test

We will finish this section by demonstrating a t-test. The main point of this section is to give a flavour of how statistical tests work in R, rather than the details of what a t-test does.

Has life expectancy increased from 2000 to 2010?

```
gap2000 <- filter(gap_geo, year == 2000)
gap2010 <- filter(gap_geo, year == 2010)

t.test(gap2010$life_exp, gap2000$life_exp)

##
## Welch Two Sample t-test
##
## data: gap2010$life_exp and gap2000$life_exp
## t = 3.0341, df = 374.98, p-value = 0.002581
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
##  1.023455 4.792947
## sample estimates:
## mean of x mean of y
##  70.34005  67.43185
```

Statistical routines often have many ways to tweak the details of their operation. These are specified by further arguments to the function call, to override the default behaviour. By default, `t.test` performs an unpaired t-test, but these are repeated observations of the same countries. We can specify `paired=TRUE` to `t.test` to perform a paired sample t-test and gain some statistical power. Check this by looking at the help page with `?t.test`.

It's important to first check that both data frames are in the same order.

```
all(gap2000$name == gap2010$name)


## [1] TRUE

t.test(gap2010$life_exp, gap2000$life_exp, paired=TRUE)

##
## Paired t-test
##
## data: gap2010$life_exp and gap2000$life_exp
## t = 13.371, df = 188, p-value < 2.2e-16
## alternative hypothesis: true difference in means is not equal to 0
## 95 percent confidence interval:
##  2.479153 3.337249
## sample estimates:
## mean of the differences
##                2.908201
```

When performing a statistical test, it's good practice to visualize the data to make sure there is nothing funny going on.

```
plot(gap2000$life_exp, gap2010$life_exp)  
abline(0,1)
```



This is a visual confirmation of the t-test result. If there were no difference between the years then points would lie approximately evenly above and below the diagonal line, which is clearly not the case. However the outlier may warrant investigation.

Chapter 5

Thinking in R

The result of a t-test is actually a value we can manipulate further. Two functions help us here. `class` gives the “public face” of a value, and `typeof` gives its underlying type, the way R thinks of it internally. For example numbers are “numeric” and have some representation in computer memory, either “integer” for whole numbers only, or “double” which can hold fractional numbers (stored in memory in a base-2 version of scientific notation).

```
class(42)
```

```
## [1] "numeric"
```

```
typeof(42)
```

```
## [1] "double"
```

Let’s look at the result of a t-test:

```
result <- t.test(gap2010$life_exp, gap2000$life_exp, paired=TRUE)
```

```
class(result)
```

```
## [1] "htest"
```

```
typeof(result)
```

```
## [1] "list"
```

```
names(result)
```

```
## [1] "statistic" "parameter" "p.value" "conf.int" "estimate"
## [6] "null.value" "stderr" "alternative" "method" "data.name"
```

```
result$p.value
```

```
## [1] 4.301261e-29
```

In R, a t-test is just another function returning just another type of data, so it can also be a building block. The value it returns is a special type of vector called a “list”, but with a public face that presents itself nicely. This is a common

pattern in R. Besides printing to the console nicely, this public face may alter the behaviour of generic functions such as `plot` and `summary`.

Similarly a data frame is a list of vectors that is able to present itself nicely.

5.1 Lists

Lists are vectors that can hold anything as elements (even other lists!). It's possible to create lists with the `list` function. This becomes especially useful once you get into the programming side of R. For example writing your own function that needs to return multiple values, it could do so in the form of a list.

```
mylist <- list(hello=c("Hello","world"), numbers=c(1,2,3,4))
mylist
```

```
## $hello
## [1] "Hello" "world"
##
## $numbers
## [1] 1 2 3 4
```

```
class(mylist)
```

```
## [1] "list"
```

```
typeof(mylist)
```

```
## [1] "list"
```

```
names(mylist)
```

```
## [1] "hello" "numbers"
```

Accessing lists can be done by name with `$` or by position with `[[]]`.

```
mylist$hello
```

```
## [1] "Hello" "world"
```

```
mylist[[2]]
```

```
## [1] 1 2 3 4
```

5.2 Other types not covered here

Matrices are another tabular data type. These come up when doing more mathematical tasks in R. They are also commonly used in bioinformatics, for example to represent RNA-Seq count data. A matrix, as compared to a data frame:

- contains only one type of data, usually numeric (rather than different types in different columns).

- commonly has `rownames` as well as `colnames`. (Base R data frames can have `rownames` too, but it is easier to have any unique identifier as a normal column instead.)
- has individual cells as the unit of observation (rather than rows).

Matrices can be created using `as.matrix` from a data frame, `matrix` from a single vector, or using `rbind` or `cbind` with several vectors.

You may also encounter “S4 objects”, especially if you use Bioconductor¹ packages. The syntax for using these is different again, and uses `@` to access elements.

5.3 Programming

Once you have a useful data analysis, you may want to do it again with different data. You may have some task that needs to be done many times over. This is where programming comes in:

- Writing your own functions².
- For-loops³ to do things multiple times.
- If-statements⁴ to make decisions.

The “R for Data Science” book⁵ is an excellent source to learn more. Monash Data Fluency “Programming and Tidy data analysis in R” course⁶ also covers this.

¹<http://bioconductor.org/>

²<http://r4ds.had.co.nz/functions.html>

³<http://r4ds.had.co.nz/iteration.html>

⁴<http://r4ds.had.co.nz/functions.html#conditional-execution>

⁵<http://r4ds.had.co.nz/>

⁶<https://monashdatafluency.github.io/r-progtidy/>

Chapter 6

Next steps

6.1 Deepen your understanding

Our number one recommendation is to read the book “R for Data Science”¹ by Garrett Golemund and Hadley Wickham.

Statistical tasks such as model fitting, hypothesis testing, confidence interval calculation, and prediction are a large part of R, and one we haven’t demonstrated fully today. Linear models, and the linear model formula syntax `~`, are core to much of what R has to offer statistically. Many statistical techniques take linear models as their starting point, including `limma`² for differential gene expression, `glm` for logistic regression (etc), survival analysis with `coxph`, and mixed models to characterize variation within populations.

- “Statistical Models in S” by J.M. Chambers and T.J. Hastie is the primary reference for this, although there are some small differences between R and its predecessor S.
- “An Introduction to Statistical Learning”³ by G. James, D. Witten, T. Hastie and R. Tibshirani can be seen as further development of the ideas in “Statistical Models in S”, and is available online. It has more of a machine learning than a statistics flavour to it (the distinction is fuzzy!).
- “Modern Applied Statistics with S” by W.N. Venable and B.D. Ripley is a well respected reference covering R and S.
- “Linear Models with R” and “Extending the Linear Model with R” by J. Faraway⁴ cover linear models, with many practical examples.

6.2 Expand your vocabulary

Have a look at these cheat sheets to see what is possible with R.

¹<http://r4ds.had.co.nz/>

²<https://bioconductor.org/packages/release/bioc/html/limma.html>

³<http://www-bcf.usc.edu/~gareth/ISL/>

⁴<http://www.maths.bath.ac.uk/~jjf23/>

- RStudio’s collection of cheat sheets⁵ cover newer packages in R.
- An old-school cheat sheet⁶ for dinosaurs and people wishing to go deeper.
- A Bioconductor cheat sheet⁷ for biological data.

The R Manuals⁸ are the place to look if you need a precise definition of how R behaves.

6.3 Join the community

Join the Data Fluency community at Monash⁹.

- Mailing list for workshop and event announcements.
- Slack for discussion.
- Drop-in sessions on Friday afternoon.

Attend further Data Fluency R workshops.¹⁰ The material for our workshops is also available at this link for self-study.

Meetups in Melbourne:

- MelbURN¹¹
- R-Ladies¹²

The Carpentries¹³ run intensive two day workshops on scientific computing and data science topics worldwide. The style of this present workshop is very much based on theirs.

For bioinformatics, the Monash Bioinformatics Platform¹⁴ runs bioinformatics-specific workshops. Also COMBINE¹⁵ is an Australian bioinformatics student and early career researcher organization, and runs Carpentries workshops and similar.

⁵<https://www.rstudio.com/resources/cheatsheets/>

⁶<https://cran.r-project.org/doc/contrib/Short-refcard.pdf>

⁷<https://github.com/mikelove/bioc-refcard/blob/master/README.Rmd>

⁸<https://cran.r-project.org/manuals.html>

⁹<https://www.monash.edu/data-fluency>

¹⁰<https://www.monash.edu/data-fluency/toolkit/r>

¹¹<https://www.meetup.com/en-AU/MelbURN-Melbourne-Users-of-R-Network/>

¹²<https://www.meetup.com/en-AU/R-Ladies-Melbourne/>

¹³<https://carpentries.org/>

¹⁴<https://www.monash.edu/researchinfrastructure/bioinformatics/training>

¹⁵<https://combine.org.au/>