

ENERGY EFFICIENCY CENTER INDUSTRIAL WALKTHROUGH CHECKLIST & REFERENCE API

SEPTEMBER 8, 2020

PREPARED BY

ZACHARY THOMAS

CONTENTS

1	Introduction	2
2	API Endpoints	2
2.1	Card Endpoints	2
2.2	Category Endpoints	7
2.3	Header Endpoints	10
2.4	Home Endpoints	13
2.5	Icon Endpoints	16
2.6	Link Endpoints	18
2.7	Page Endpoints	19
2.8	Request Endpoints	31
2.9	Source Endpoints	36
2.10	User Endpoints	37
2.11	View Endpoints	41
3	Contact Information	43

1 INTRODUCTION

This document describes all of the API endpoints for the EEC Walkthrough application. The document is organized by route name and each API endpoint includes a general description, the expected input, and the expected output.

This API uses cookies to keep track of the user who is making requests. This means that each of these endpoints will have access to all user information for the current user even if it is not requested in the body. This includes ID, username, first name, last name, email, and role. All endpoints also have the option to return an error code. This will have a status code between 400 and 500. In the case of a validation error an object with the property "errors" will be returned, which is an array of objects that describe what was wrong with the request body. All other errors will return an object with the property "error", which is a string that describes the error.

To make handling responses from the API easier, all responses return a JSON object. To make it easier to tell what requests are being made to the API (as apposed to requests to get files), each API request starts with "api".

2 API ENDPOINTS

2.1 Card Endpoints

POST api/cards

Creates a new card. Only editors and admins can use this endpoint.

- HeaderId: The ID of the header that this card belongs to.
- cardType: The type of card to create. Examples include: default card, internal card, thumbnail gallery, internal thumbnail gallery, and more.
- title: The title of the card.
- items: The items that will be included in the card.
 - cardId: The ID of the card that this item belongs to.
 - indentation: The level of indentation (0 is none, 3 is max).
 - iconType: The ID of the icon that is displayed at the start of the item.
 - contentText: The main body of text for the item.
 - contentUrl: The URL of the item. For graphic items this will be the URL of the image to display, for link items this will be the URL to direct the user to.
 - contentLabel: The bold title of the item, this is shown before the content text.
 - contentMode: A special setting that depends on the item in particular. For links this will be used to describe the type of link (internal, external, internal download, external download).
 - internal: Determines if the item should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
 - sourceId: The ID of the source that this item is referencing.

```

1 {
2   headerId: 2,
3   cardType: 0,
4   title: "Best Practices",
5   items: [
6     {

```

```

7     cardId: 1,
8     indentation: 0,
9     iconType: 16,
10    contentText: "An informational page with analysis tools",
11    contentUrl: "https://www.bpa.gov/EE/Sectors/Industrial/Pages/Co",
12    contentLabel: "Bonneville Power Administration",
13    contentMode: 0,
14    internal: 0,
15    sourceId: 2
16  }
17 ]
18 }

```

Listing 1. Example Request Body

- insertId: The ID of the newly created card.

```

1 {
2   insertId: 10
3 }

```

Listing 2. Example Response

DELETE `api/cards/:cardId/changes`

Deletes an unpublished card / suggested changes to a card. Only editors and admins can use this endpoint.

- cardId: The ID of the card to delete.
- affectedRows: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 3. Example Response

DELETE `api/cards/:cardId`

Deletes a card (including published cards). Only admins can use this endpoint.

- cardId: The ID of the card to delete.
- affectedRows: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 4. Example Response

PATCH api/cards/:cardId

Updates a card. If the card is unpublished this will simply change the card. If the card is published then this will add a suggested edit to the card that will need to be published before it will replace the original. If the card is both published and has an edited version, then this will replace the edited version. Only an editor or an admin can use this endpoint.

- cardId: The ID of the card to update.
- cardType: The type of card to create. Examples include: default card, internal card, thumbnail gallery, internal thumbnail gallery, and more.
- title: The title of the card.
- items: The items that will be included in the card.
 - cardId: The ID of the card that this item belongs to.
 - indentation: The level of indentation (0 is none, 3 is max).
 - iconType: The ID of the icon that is displayed at the start of the item.
 - contentText: The main body of text for the item.
 - contentUrl: The URL of the item. For graphic items this will be the URL of the image to display, for link items this will be the URL to direct the user to.
 - contentLabel: The bold title of the item, this is shown before the content text.
 - contentMode: A special setting that depends on the item in particular. For links this will be used to describe the type of link (internal, external, internal download, external download).
 - internal: Determines if the item should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
 - sourceId: The ID of the source that this item is referencing.

```

1 {
2   cardType: 0,
3   title: "Best Practices",
4   items: [
5     {
6       cardId: 1,
7       indentation: 0,
8       iconType: 16,
9       contentText: "An informational page with analysis tools",
10      contentUrl: "https://www.bpa.gov/EE/Sectors/Industrial/Pages/Co",
11      contentLabel: "Bonneville Power Administration",
12      contentMode: 0,
13      internal: 0,
14      sourceId: 2
15    }
16  ]
17 }
```

Listing 5. Example Request Body

- cardId: The ID of the current card.

```

1 {
2   cardId: 1
3 }

```

Listing 6. Example Response

POST `api/cards/:cardId/publish`

Publishes a card. If the card is unpublished this will simply approve the card and show it publicly. If the card has a published version and an edit then the edit will replace the current published version while becoming approved. Only an admin can use this endpoint.

- `cardId`: The ID of the card to publish.

```

1 {
2   cardId: 1
3 }

```

Listing 7. Example Response

POST `api/cards/:cardId/unpublish`

Unpublishes a card. If the card is published this will simply make the card unapproved and unviewable by the public. If the card has a published version and an edit then the edit will be replaced by the current published version while becoming unapproved. Only an admin can use this endpoint.

- `cardId`: The ID of the card to unpublish.

```

1 {
2   cardId: 1
3 }

```

Listing 8. Example Response

PATCH `api/cards/:cardId/move/:direction/:mode`

Changes the selected card's position relative to other cards when displayed. If we are moving an unpublished card, it will move the card relative to all cards (excluding its published version). If we are moving a published card it will move relative to published cards (skipping over unpublished cards). Only editors or admins can move an unpublished card. Only admins can move a published card.

- `cardId`: The ID of the card to move.
- `direction`: A value of 1 moves the card up one row. A value of 0 moves the card down one row.
- `mode`: States what type of card we want to move. A value of 0 represents an unpublished card. A value of 1 represents a published card.

```

1 {
2   cardId: 1
3 }

```

Listing 9. Example Response

GET `api/cards/titles`

Returns a list of suggested titles for cards. Editors can use these suggested titles to quickly name cards that are similar across pages. Any user can use this endpoint.

- `titles`: An array of strings that will be used as the suggested titles.

```

1 {
2   titles: [
3     "General Off Site Resource Links",
4     "Best Practices",
5     "Caveats"
6   ]
7 }

```

Listing 10. Example Response

POST `api/cards/titles`

Replaces the current list of suggested card titles. Only admins can use this endpoint.

- `titles`: An array of strings that will be used as the new suggested titles.

```

1 {
2   titles: [
3     "Data Collection Guides",
4     "Rules of Thumb",
5     "Caveats"
6   ]
7 }

```

Listing 11. Example Request Body

```

1 {
2   titleCount: 3
3 }

```

Listing 12. Example Response

2.2 Category Endpoints

GET `api/categories/all`

Returns all of the categories and their respective pages. Users without an account, or external users will get all published categories and pages that are not internal. Internal users, editors, and admins will get all categories and pages.

- `categoryId`: The ID of the category.
- `created`: The date that the category was created.
- `description`: A general description of the category.
- `internal`: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- `pluralName`: The plural name of the category.
- `singleName`: The singular name of the category.
- `userId`: The ID of the user who created the category.
- `pages`: The list of pages that belong to the category.
 - `approved`: Whether this page is published and viewable in view mode.
 - `description`: The description of the page.
 - `internal`: Whether the page is viewable by the public (value of 0) or just by internal users (value of 1).
 - `name`: The name of the page.
 - `pageId`: The ID of the page.
 - `pageType`: The category ID that the page belongs to.

```

1 {
2   categories: [
3     {
4       categoryId: 5,
5       created: "2020-07-18T03:11:32.000Z",
6       description: "Standard recommended approaches for performing...",
7       internal: 0,
8       pluralName: "Assessments",
9       singleName: "Assessment",
10      userId: 51,
11      pages: [
12        approved: 1,
13        description: "Cybersecurity is...",
14        internal: 1,
15        name: "Cybersecurity",
16        pageId: 62,
17        pageType: 5
18      ]
19    }
20  ]
21 }
```

Listing 13. Example Response

GET api/categories/names

Returns the names and IDs of all categories. Users without an account, or external users will only have access to published categories that are not internal. Internal users, editors, and admins will have access to all categories.

- categoryId: The ID of the category.
- singleName: The singular name of the category.

```

1 {
2   categories: [
3     {
4       categoryId: 5,
5       singleName: "Assessment"
6     }
7   ]
8 }
```

Listing 14. Example Response

GET api/categories/:categoryId

Returns a single category and all of its pages. Users without an account, or external users will only have access to published categories and published pages that are not internal. Internal users, editors, and admins will have access to all categories and all pages.

- categoryId: The ID of the category.
- created: The date that the category was created.
- description: A general description of the category.
- internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- pluralName: The plural name of the category.
- singleName: The singular name of the category.
- userId: The ID of the user who created the category.
- pages: The list of pages that belong to the category.
 - approved: Whether this page is published and viewable in view mode.
 - description: The description of the page.
 - internal: Whether the page is viewable by the public (value of 0) or just by internal users (value of 1).
 - name: The name of the page.
 - pageId: The ID of the page.
 - pageType: The category ID that the page belongs to.

```

1 {
2   categoryId: 5,
3   created: "2020-07-18T03:11:32.000Z",
4   description: "Standard recommended approaches for performing...",
5   internal: 0,
6   pluralName: "Assessments",
```

```

7   singleName: "Assessment",
8   userId: 51,
9   pages: [
10    approved: 1,
11    description: "Cybersecurity is...",
12    internal: 1,
13    name: "Cybersecurity",
14    pageId: 62,
15    pageType: 5
16  ]
17 }

```

Listing 15. Example Response

POST api/categories

Creates a new category. This endpoint can only be used by admins.

- description: A general description of the category.
- internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- pluralName: The plural name of the category.
- singleName: The singular name of the category.

```

1 {
2   description: "Standard recommended approaches for performing...",
3   internal: 0,
4   pluralName: "Assessments",
5   singleName: "Assessment",
6 }

```

Listing 16. Example Request Body

- insertId: The ID of the newly created category.

```

1 {
2   insertId: 10
3 }

```

Listing 17. Example Response

PATCH api/categories/:categoryId

Updates a category. This endpoint can only be used by admins.

- categoryId: The ID of the category to be updated.
- description: A general description of the category.
- internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- pluralName: The plural name of the category.
- singleName: The singular name of the category.

```

1 {
2   description: "Standard recommended approaches for performing...",
3   internal: 0,
4   pluralName: "Assessments",
5   singleName: "Assessment",
6 }

```

Listing 18. Example Request Body

- categoryId: The ID of the category.

```

1 {
2   categoryId: 10
3 }

```

Listing 19. Example Response

2.3 Header Endpoints

POST api/headers

Creates a new header. Only editors and admins can use this endpoint.

- PageId: The ID of the page that this header belongs to.
- title: The title of the header.
- internal: Determines if the header should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.

```

1 {
2   pageId: 15,
3   title: "Wastewater Overview",
4   internal: 0
5 }

```

Listing 20. Example Request Body

- insertId: The ID of the newly created header.

```

1 {
2   insertId: 5
3 }

```

Listing 21. Example Response

DELETE api/headers/:headerId/changes

Deletes an unpublished header / suggested changes to a header. Only editors and admins can use this endpoint.

- headerId: The ID of the header to delete.
- affectedRows: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 22. Example Response

DELETE `api/headers/:headerId`

Deletes a header (including published headers). Only admins can use this endpoint.

- `headerId`: The ID of the header to delete.
- `affectedRows`: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 23. Example Response

PATCH `api/headers/:headerId`

Updates a header. If the header is unpublished this will simply change the header. If the header is published then this will add a suggested edit to the header that will need to be published before it will replace the original. If the header is both published and has an edited version, then this will replace the edited version. Only an editor or an admins can use this endpoint.

- `headerId`: The ID of the header to update.
- `title`: The title of the header.
- `internal`: Determines if the header should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.

```

1 {
2   title: "Compressed Air Overview",
3   internal: 0
4 }

```

Listing 24. Example Request Body

- `headerId`: The ID of the current header.

```

1 {
2   headerId: 1
3 }

```

Listing 25. Example Response

POST `api/headers/:headerId/publish`

Publishes a header. If the header is unpublished this will simply approve the header and show it publicly. If the header has a published version and an edit then the edit will replace the current published version while becoming approved. Only an admins can use this endpoint.

- `headerId`: The ID of the header to publish.

```

1 {
2   headerId: 1
3 }
```

Listing 26. Example Response

POST `api/headers/:headerId/unpublish`

Unpublishes a header. If the header is published this will simply make the header unapproved and unviewable by the public. If the header has a published version and an edit then the edit will be replaced by the current published version while becoming unapproved. Only an admins can use this endpoint.

- `headerId`: The ID of the header to unpublish.

```

1 {
2   headerId: 1
3 }
```

Listing 27. Example Response

PATCH `api/headers/:headerId/move/:direction/:mode`

Changes the selected header's position relative to other headers when displayed. If we are moving an unpublished header, it will move the card relative to all cards (excluding its published version). If we are moving a published header it will move relative to published header (skipping over unpublished headers). Only editors or admins can move an unpublished header. Only admins can move a published header.

- `headerId`: The ID of the header to move.
- `direction`: A value of 1 moves the header up one row. A value of 0 moves the header down one row.
- `mode`: States what type of header we want to move. A value of 0 represents an unpublished header. A value of 1 represents a published header.

```

1 {
2   headerId: 1
3 }
```

Listing 28. Example Response

2.4 Home Endpoints

GET api/home

Returns all of the data displayed on the homepage, with the exception of the sponsors. Any user can use this endpoint.

- mainHeader: The main header text for the homepage.
- secondaryHeader: The header for the card that describes the categories.
- sectionTitle: The title on the card that describes the categories.
- sectionFooter: The footer on the card that describes the categories.
- tidbitsHeader: The header for the card describing tidbits.
- tidbitsTitle: The title on the card that describes the tidbits.
- tidbitsFooter: The footer on the card that describes the tidbits.
- linksHeader: The header for the card describing links.
- linksTitlePrefix: The title on the card that is shown before the standard link icons are listed.
- linksTitlePostfixInternal: The title on the card that is shown before the link internal and external icons.
- linksTitlePostfixDownload: The title on the card that is shown before the link download icon.
- linksFooter: The footer on the card that describes the links.
- disclaimerHeader: The header of the disclaimer card.
- disclaimerText: The text on the disclaimer card.
- categories: The categories viewable by the current user.
 - categoryId: The ID of the category.
 - description: A general description of the category.
 - internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
 - pluralName: The plural name of the category.
 - singularName: The singular name of the category.

```

1 {
2   mainHeader: "Welcome",
3   secondaryHeader: "The purpose of this guide...",
4   sectionTitle: "This guide is broken down into sections:",
5   sectionFooter: "",
6   tidbitsHeader: "Each section...",
7   tidbitsTitle: "These include...",
8   tidbitsFooter: "Note: tidbit types can be...",
9   linksHeader: "Each section also references...",
10  linksTitlePrefix: "A preceding icon identifies...",
11  linksTitlePostfixInternal: "A trailing icon...",
12  linksTitlePostfixDownload: "A second trailing icon...",
13  linksFooter: "",
14  disclaimerHeader: "Disclaimer",
15  disclaimerText: "The primary objective...",
16  categories: [
17    {
18      categoryId: 5,
19      description: "Standard recommended...",
20      internal: 0,
```

```

21     pluralName: "Assessments",
22     singleName: "Assessment"
23   }
24 ]
25 }

```

Listing 29. Example Response

PATCH api/home

Updates the text that is displayed on the homepage. Only admins can use this endpoint.

- **mainHeader**: The main header text for the homepage.
- **secondaryHeader**: The header for the card that describes the categories.
- **sectionTitle**: The title on the card that describes the categories.
- **sectionFooter**: The footer on the card that describes the categories.
- **tidbitsHeader**: The header for the card describing tidbits.
- **tidbitsTitle**: The title on the card that describes the tidbits.
- **tidbitsFooter**: The footer on the card that describes the tidbits.
- **linksHeader**: The header for the card describing links.
- **linksTitlePrefix**: The title on the card that is shown before the standard link icons are listed.
- **linksTitlePostfixInternal**: The title on the card that is shown before the link internal and external icons.
- **linksTitlePostfixDownload**: The title on the card that is shown before the link download icon.
- **linksFooter**: The footer on the card that describes the links.
- **disclaimerHeader**: The header of the disclaimer card.
- **disclaimerText**: The text on the disclaimer card.

```

1 {
2   mainHeader: "Welcome",
3   secondaryHeader: "The purpose of this guide...",
4   sectionTitle: "This guide is broken down into sections:",
5   sectionFooter: "",
6   tidbitsHeader: "Each section...",
7   tidbitsTitle: "These include...",
8   tidbitsFooter: "Note: tidbit types can be...",
9   linksHeader: "Each section also references...",
10  linksTitlePrefix: "A preceding icon identifies...",
11  linksTitlePostfixInternal: "A trailing icon...",
12  linksTitlePostfixDownload: "A second trailing icon...",
13  linksFooter: "",
14  disclaimerHeader: "Disclaimer",
15  disclaimerText: "The primary objective..."
16 }

```

Listing 30. Example Request Body

- `homePageUpdated`: Generic value. Should always have a value of 1, showing that the home page was updated correctly.

```

1 {
2   homePageUpdated: 1
3 }
```

Listing 31. Example Response

GET `api/home/sponsors`

Returns all of the sponsors that should be listed on the homepage. Any user can use this endpoint.

- `sponsors`: The sponsors for this application.
 - `sponsorId`: The ID of the sponsor.
 - `name`: The name of the sponsor.
 - `title`: A short description of the sponsor that doubles as a link.
 - `websiteUrl`: The URL for the sponsors website.
 - `imageUrl`: The URL for the sponsors image.
 - `orderIndex`: A value that determines the order that the sponsors are listed in. A lower value will appear before a larger value.

```

1 {
2   sponsors: [
3     {
4       sponsorId: 5,
5       name: "Industrial Assessment Center",
6       title: "U.S. Department of Energy...",
7       websiteUrl: "https://www.energy.gov/eere/amo/industrial-assessment-centers-iacs",
8       imageUrl: "/images/IAC.png",
9       orderIndex: 0
10    }
11  ]
12 }
```

Listing 32. Example Response

PATCH `api/home/sponsors`

Updates the list of sponsors that is displayed on the homepage. Only admins can use this endpoint.

- `sponsors`: The sponsors for this application.
 - `sponsorId`: The ID of the sponsor.
 - `name`: The name of the sponsor.
 - `title`: A short description of the sponsor that doubles as a link.

- `websiteUrl`: The URL for the sponsors website.
- `imageUrl`: The URL for the sponsors image.
- `orderIndex`: A value that determines the order that the sponsors are listed in. A lower value will appear before a larger value.

```

1 {
2   sponsors: [
3     {
4       sponsorId: 5,
5       name: "Industrial Assessment Center",
6       title: "U.S. Department of Energy...",
7       websiteUrl: "https://www.energy.gov/eere/amo/industrial-assessment-centers-iacs",
8       imageUrl: "/images/IAC.png",
9       orderIndex: 0
10    }
11  ]
12 }
```

Listing 33. Example Request Body

- `sponsorsUpdated`: Generic value. Should always have a value of 1, showing that the sponsors were updated correctly.

```

1 {
2   sponsorsUpdated: 1
3 }
```

Listing 34. Example Response

2.5 Icon Endpoints

GET `api/icons/all`

Returns a list of all icons that can be appended to items. Any user can use this endpoint.

- `icons`: All possible icons.
 - `iconType`: The ID of the icon.
 - `groupIndex`: The type of item this icon represents (disabled = 0, default item = 1, graphics item = 2, link item = 3).
 - `typeKeyword`: The name of the icon when it is being hovered over or selected in a menu.
 - `typeName`: The name of the actual Font Awesome icon.
 - `color`: The color of the icon. Represented by a hexadecimal color code.

```

1 {
2   icons: [
3     {
4       iconType: 21,
```

```

5     groupIndex: 3,
6     typeKeyword: "Analysis Tool",
7     typeName: "list",
8     color: "#000000"
9   }
10 ]
11 }

```

Listing 35. Example Response

POST api/icons

Creates a new icon. Only an admin can use this endpoint.

- **groupIndex:** The type of item this icon represents (disabled = 0, default item = 1, graphics item = 2, link item = 3).
- **typeKeyword:** The name of the icon when it is being hovered over or selected in a menu.
- **typeName:** The name of the actual Font Awesome icon.
- **color:** The color of the icon. Represented by a hexadecimal color code.

```

1 {
2   groupIndex: 3,
3   typeKeyword: "Analysis Tool",
4   typeName: "list",
5   color: "#000000"
6 }

```

Listing 36. Example Request Body

- **insertId:** The ID of the newly created icon.

```

1 {
2   insertId: 10
3 }

```

Listing 37. Example Response

PATCH api/icons/:iconId

Updates an icon. Only an admin can use this endpoint.

- **iconId:** The ID of the icon.
- **groupIndex:** The type of item this icon represents (disabled = 0, default item = 1, graphics item = 2, link item = 3).
- **typeKeyword:** The name of the icon when it is being hovered over or selected in a menu.
- **typeName:** The name of the actual Font Awesome icon.
- **color:** The color of the icon. Represented by a hexadecimal color code.

```

1 {
2   groupIndex: 3,
3   typeKeyword: "Analysis Tool",
4   typeName: "list",
5   color: "#000000"
6 }

```

Listing 38. Example Request Body

- `iconId`: The ID of the icon.

```

1 {
2   iconId: 10
3 }

```

Listing 39. Example Response

2.6 Link Endpoints

GET `api/links/all/:onlyDead`

Returns a list of all of the published link items. If `onlyDead` is set to 1, then it only returns invalid links. Only admins can use this endpoint.

- `links`: All links.
 - `itemId`: The ID of the link item.
 - `time`: The time the link was last confirmed valid. This value is null if the link is currently invalid.
 - `title`: The text that the link is embedded in.
 - `url`: The URL for the link.

```

1 {
2   links: [
3     {
4       itemId: 384,
5       time: "2020-06-29T20:55:45.00Z",
6       title: "U.S. Department of Energy analysis tool",
7       url: "https://www.energy.gov/eere/amo/measur"
8     }
9   ]
10 }

```

Listing 40. Example Response

PATCH `api/links/:linkId`

Changes the URL of a link item, and updates the last confirmed valid date to the current time. Only admins can use this endpoint.

- `linkId`: The ID of the link item.
- `url`: The new URL for the link item.

```

1 {
2   url: "https://www.bpa.gov/EE/Sectors/Industrial/Pages/Compressed-Air.aspx"
3 }

```

Listing 41. Example Request Body

- `linkId`: The ID of the link item.

```

1 {
2   linkId: 10
3 }

```

Listing 42. Example Response

PATCH `api/links/:linkId/timestamp`

Updates a link item's confirmed valid date to the current time. Only editors or admins can use this endpoint.

- `linkId`: The ID of the link item.
- `timestamp`: The time that the link was confirmed valid.

```

1 {
2   timestamp: "2020-06-29T20:55:45.00Z"
3 }

```

Listing 43. Example Response

2.7 Page Endpoints

GET `api/pages/:pageId/all`

Returns all of the page, header, card, and item data for a single page. Any user can use this endpoint. Only internal users will be allowed to get info about private or unpublished pages, headers, cards, and items.

- `pageId`: The ID of the page.
- `pageType`: The ID of the category that this page belongs to.
- `name`: The name of the page.
- `title`: The title of the initial card that shows at the top of the page.
- `description`: Text that describes the general subject of the page.
- `imageUrl`: The URL for the image shown at the top of the page.
- `created`: The time that the page was created, last updated, or last published (whichever was most recent).
- `userId`: The ID of the user who created or last updated the page (whichever was most recent).
- `approved`: Lets us know if the page is published (1) or unpublished (0).

- internal: Determines if the page should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
- tempPageId: If the page is published and there is an edited version the page, then this is the same as the pageId, otherwise null.
- tempPageType: If the page is published and there is an edited version the page, then this is the same as the pageType, except in relation to the unpublished version, otherwise null.
- tempTitle: If the page is published and there is an edited version the page, then this is the same as the title, except in relation to the unpublished version, otherwise null.
- tempUserId: If the page is published and there is an edited version the page, then this is the same as the userId, except in relation to the unpublished version, otherwise null.
- tempImageUrl: If the page is published and there is an edited version of the page, then this is similar to imageUrl, except in relation to the unpublished version, otherwise null.
- sources: All of the sources that are referenced on this page.
 - pageId: The page ID of the page that this source belongs to.
 - sourceId: The ID of this source.
 - text: The citation text that describes this source (IEEE style).
 - url: An optional URL that links to a web page related to the source.
- headers: All of the headers that are on this page.
 - headerId: The ID of the header.
 - pageId: The ID of the page that this header belongs to.
 - orderIndex: The order that the headers should be displayed in. A lower value means the header is displayed before a header with a higher value.
 - title: The title of the header.
 - internal: Determines if the header should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
 - created: The time that the header was created, last updated, or last published (whichever was most recent).
 - userId: The ID of the user who created or last updated the header (whichever was most recent).
 - approved: Lets us know if the page is published (1) or unpublished (0).
 - tempHeaderId: If the header is published and there is an edited version of the header, then this is the same as headerId, otherwise null.
 - tempCreated: If the header is published and there is an edited version of the header, then this is the time that the edited version was created or last updated, otherwise null.
 - tempInternal: If the header is published and there is an edited version of the header, then this is similar to internal, except in relation to the unpublished version, otherwise null.
 - tempOrderIndex: If the header is published and there is an edited version of the header, then this is similar to orderIndex, except in relation to the unpublished version, otherwise null.
 - tempTitle: If the header is published and there is an edited version of the header, then this is similar to title, except in relation to the unpublished version, otherwise null.

- tempUserId: If the header is published and there is an edited version of the header, then this is similar to userId, except in relation to the unpublished version, otherwise null.
- cards: The cards that belong to this header.
 - * cardId: The ID of the card.
 - * HeaderId: The ID of the header that this card belongs to.
 - * cardType: The type of card to create. Examples include: default card, internal card, thumbnail gallery, internal thumbnail gallery, and more.
 - * title: The title of the card.
 - * created: The time that the card was created, last updated, or last published (whichever was most recent).
 - * userId: The ID of the user who created or last updated the card (whichever was most recent).
 - * approved: Lets us know if the card is published (1) or unpublished (0).
 - * orderIndex: The order that the cards should be displayed in. A lower value means the card is displayed before a card with a higher value.
 - * tempCardId: If the card is published and there is an edited version of the card, then this is the same as cardId, otherwise null.
 - * tempCardType: If the card is published and there is an edited version of the card, then this is similar to cardType, except in relation to the unpublished version, otherwise null.
 - * tempCreated: If the card is published and there is an edited version of the card, then this is the time that the edited version was created or last updated, otherwise null.
 - * tempOrderIndex: If the card is published and there is an edited version of the card, then this is the similar to orderIndex, except in relation to the unpublished version, otherwise null.
 - * tempTitle: If the card is published and there is an edited version of the card, then this is the similar to title, except in relation to the unpublished version, otherwise null.
 - * tempUserId: If the card is published and there is an edited version of the card, then this is the similar to userId, except in relation to the unpublished version, otherwise null.
 - * cards: The cards that belong to this header.
 - * items / tempItems: The items that belong to this card. "items" are always approved (1), tempItems are always unapproved (0).
 - itemId: The ID of the item.
 - cardId: The ID of the card that this item belongs to.
 - indentation: The level of indentation (0 is none, 3 is max).
 - iconType: The ID of the icon that is displayed at the start of the item.
 - contentText: The main body of text for the item.
 - contentUrl: The URL of the item. For graphic items this will be the URL of the image to display, for link items this will be the URL to direct the user to.
 - contentLabel: The bold title of the item, this is shown before the content text.
 - contentMode: A special setting that depends on the item in particular. For links this will be used to describe the type of link (internal, external, internal download, external download).

- internal: Determines if the item belongs to a published (1) or unpublished (0) version of the card.
- iconType: The ID of the icon to use with this item.
- typeName: The Font Awesome name of the icon that is used with this item.
- typeKeyword: The name displayed when a user hovers over the icon.
- color: The hex color code to use for the icon.
- sourceId: The ID of the source that this item is referencing.

```

1 {
2   pageId: 2,
3   pageType: 2,
4   name: "Compressed Air",
5   title: "Compressed air is a common utility...",
6   description: "Compressed air has been a key...",
7   imageUrl: "/images/air.png",
8   created: "2020-07-23T10:01:49.000Z",
9   userId: 42,
10  approved: 1,
11  internal: 0,
12  tempCreated: null,
13  tempDescription: null,
14  tempImageUrl: null,
15  tempInternal: null,
16  tempImageUrl: null,
17  tempName: null,
18  tempPageId: null
19  sources: [
20    {
21      sourceId: 1,
22      pageId: 2,
23      text: "S. Cottrell, the study skills handbook...",
24      url: ""
25    }
26  ],
27  headers: [
28    {
29      headerId: 1,
30      pageId: 2,
31      approved: 1,
32      internal: 0,
33      orderIndex: 1,
34      created: "2020-07-01T18:19:56.000Z",
35      title: "Compressed Air Overview",
36      userId: 51,
37      tempCreated: null,
38      tempHeaderId: null,
39      tempInternal: null,
40      tempOrderIndex: null,
41      tempTitle: null,
42      tempUserId: null

```

```

43 cards: [
44   {
45     cardId: 9,
46     cardType: 0,
47     approved: 1,
48     created: "2020-06-02T20:58:31.000Z",
49     headerId: 1,
50     orderIndex: 3,
51     title: "Pros",
52     userId: 42,
53     tempCardId: 9,
54     tempCardType: 0,
55     tempCreated: "2020-09-03T23:15:22.000Z",
56     tempOrderIndex: 3,
57     tempTitle: "Pros",
58     tempUserId: 58
59     items [
60       {
61         approved: 1,
62         itemId: 25,
63         cardId: 9,
64         color: "#000000",
65         contentLabel: "",
66         contentMode: 0,
67         contentText: "Versatile. Offers compact energy density.",
68         contentUrl: "",
69         created: "2020-06-02T22:38:04.000Z",
70         internal: 0
71         indentation: 0,
72         iconType: 1,
73         typeName: "plus",
74         typeKeyword: "Pros",
75         sourceId: 0
76       }
77     ],
78     tempItems: [
79       {
80         approved: 0,
81         itemId: 25,
82         cardId: 9,
83         color: "#000000",
84         contentLabel: "",
85         contentMode: 0,
86         contentText: "Versatile. Energy can be stored in a compact way.",
87         contentUrl: "",
88         created: "2020-09-03T23:15:49.000Z",
89         internal: 0
90         indentation: 0,
91         iconType: 1,
92         typeName: "plus",

```



```

93         typeKeyword: "Pros",
94         sourceId: 0
95     }
96 ]
97 }
98 ]
99 }
100 ]
101 }

```

Listing 44. Example Response

GET `api/pages/search/:text/:cursorPrimary/:cursorSecondary`

Returns a limited list of pages that match the search text and that only includes pages that are at or beyond the cursor. Any user can use this endpoint, however internal or unpublished pages will only be returned for internal users.

- **text:** The partial or full text that is used to find a match. Partial matches are allowed. For example: searching for "press" would be able to return "Compressed Air" since "press" is contained within "Compressed Air".
- **cursorPrimary:** This cursor should contain the name of the page you want to start your search at (alphabetical order). This cursor is used to allow infinite scrolling, while only loading a small number of page results at a time. If this is a new search then this value should be null.
- **cursorSecondary:** This cursor should contain the page ID of the page you want to start your search at. This cursor is used in instances where the primary cursor value is ambiguous. If this is a new search then this value should be null.
- **nextCursor:** An object that contains the information needed to continue searching the rest of the pages (the primary and secondary cursor).
- **pages:** The pages returned from the search.
 - * **pageId:** The ID of the page.
 - * **created:** The time that the page was created, last updated, or last published (whichever was most recent).
 - * **description:** Text that describes the general subject of the page.
 - * **imageUrl:** The URL for the image shown at the top of the page.
 - * **internal:** Determines if the page should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
 - * **approved:** Lets us know if the page is published (1) or unpublished (0).
 - * **name:** The name of the page.
 - * **pageType:** The ID of the category that this page belongs to.
 - * **title:** The title of the initial card that shows at the top of the page.
 - * **url:** The URL needed to access the page.
 - * **userId:** The ID of the user who created or last updated the page (whichever was most recent).

```

1 {
2   nextCursor: {
3     primary: null,
4     secondary: null
5   },
6   pages: [
7     {
8       pageId: 46,
9       created: "2020-07-02T19:39:56.000Z",
10      description: "Steam energy offered a great...",
11      imageUrl: "https://live.staticflickr.com/65535/...",
12      internal: 0,
13      approved: 1,
14      name: "Boilders and Steam",
15      pageType: 2,
16      title: "Boilers and Steam Systems are found in a large...",
17      url: "/wiki/search-results/46",
18      userId: 51
19    }
20  ]
21 }

```

Listing 45. Example Response

POST api/pages

Creates a new page. Only editors and admins can use this endpoint.

- **pageType**: The ID of the category that this page belongs to.
- **name**: The name of the page.
- **title**: The title of the initial card that shows at the top of the page.
- **description**: Text that describes the general subject of the page.
- **imageUrl**: The URL for the image shown at the top of the page.
- **internal**: Determines if the page should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.

```

1 {
2   pageType: 1,
3   name: "Wastewater Treatment",
4   title: "Municipalities and industry need...",
5   description: "Wastewater treatment systems can...",
6   imageUrl: "https://live.staticflickr.com/65535/...",
7   internal: 0
8 }

```

Listing 46. Example Request Body

- **insertId**: The ID of the newly created page.

```

1 {
2   insertId: 50
3 }

```

```
3 }
```

Listing 47. Example Response

DELETE `api/pages/:pageId/changes`

Deletes an unpublished page / suggested changes to a page. Only editors and admins can use this endpoint.

- `pageId`: The ID of the page to delete.
- `affectedRows`: The number of table rows affected by this action.

```
1 {
2   affectedRows: 1
3 }
```

Listing 48. Example Response

DELETE `api/pages/:pageId`

Deletes a page (including published pages). Only admins can use this endpoint.

- `pageId`: The ID of the page to delete.
- `affectedRows`: The number of table rows affected by this action.

```
1 {
2   affectedRows: 1
3 }
```

Listing 49. Example Response

PATCH `api/pages/:pageId`

Updates a page. If the page is unpublished this will simply change the page. If the page is published then this will add a suggested edit to the page that will need to be published before it will replace the original. If the page is both published and has an edited version, then this will replace the edited version. Only an editor or an admins can use this endpoint.

- `pageId`: The ID of the page to update.
- `pageType`: The ID of the category that this page belongs to.
- `name`: The name of the page.
- `title`: The title of the initial card that shows at the top of the page.
- `description`: Text that describes the general subject of the page.
- `imageUrl`: The URL for the image shown at the top of the page.
- `internal`: Determines if the page should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.

```

1 {
2   pageType: 1,
3   name: "Wastewater Treatment",
4   title: "Municipalities and industry need...",
5   description: "Wastewater treatment systems can...",
6   imageUrl: "https://live.staticflickr.com/65535/...",
7   internal: 0
8 }

```

Listing 50. Example Request Body

- `pageId`: The ID of the current page.

```

1 {
2   pageId: 1
3 }

```

Listing 51. Example Response

POST `api/pages/:pageId/publish`

Publishes a page. If the page is unpublished this will simply approve the page and show it publicly. If the page has a published version and an edit then the edit will replace the current published version while becoming approved. Only an admins can use this endpoint.

- `pageId`: The ID of the page to publish.

```

1 {
2   pageId: 1
3 }

```

Listing 52. Example Response

POST `api/pages/:pageId/unpublish`

Unpublishes a page. If the page is published this will simply make the page unapproved and unviewable by the public. If the page has a published version and an edit then the edit will be replaced by the current published version while becoming unapproved. Only an admins can use this endpoint.

- `pageId`: The ID of the page to unpublish.

```

1 {
2   pageId: 1
3 }

```

Listing 53. Example Response

GET `api/pages/report/:start/:end/:offset/:condense`

Returns a report of all of the published content within the date range. Only editors and admins can use this endpoint.

- **start:** The start date of the report (ex: 2020-09-01).
- **end:** The end date of the report (ex: 2020-09-06).
- **offset:** The minute offset of the time zone that the request is being made for, in relation to UTC (ex: 420 for PDT).
- **condense:** Whether to condense changes for an individual object into a single entry in the report, or to include every change as its own entry in the report.
- **pages:** Pages that were published or deleted within the date range.
 - **historyId:** The ID of this history record.
 - **removed:** If this history record is noting the removal of the page, then this value will be 1. If this history record is signifying that the page was published, then the value will be 0.
 - **oldVersion:** The previous version of this page. It has the following properties: created, description, historyId, imageUrl, internal, name, pageId, pageType, removed, and title.
 - **pageId:** The ID of the page.
 - **pageType:** The ID of the category that this page belongs to.
 - **name:** The name of the page.
 - **title:** The title of the initial card that shows at the top of the page.
 - **description:** Text that describes the general subject of the page.
 - **imageUrl:** The URL for the image shown at the top of the page.
 - **created:** The time that the page was created, last updated, or last published (whichever was most recent).
 - **userId:** The ID of the user who created or last updated the page (whichever was most recent).
 - **approved:** Lets us know if the page is published (1) or unpublished (0).
 - **internal:** Determines if the page should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
- **headers:** Headers that were published or deleted within the date range.
 - **historyId:** The ID of this history record.
 - **removed:** If this history record is noting the removal of the header, then this value will be 1. If this history record is signifying that the header was published, then the value will be 0.
 - **oldVersion:** The previous version of this header. It has the following properties: created, headerId, historyId, internal, pageId, removed, and title.
 - **headerId:** The ID of the header.
 - **pageId:** The ID of the page that this header belongs to.
 - **orderIndex:** The order that the headers should be displayed in. A lower value means the header is displayed before a header with a higher value.
 - **title:** The title of the header.
 - **internal:** Determines if the header should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
 - **created:** The time that the header was created, last updated, or last published (whichever was most recent).

- userId: The ID of the user who created or last updated the header (whichever was most recent).
- approved: Lets us know if the page is published (1) or unpublished (0).
- cards: Cards that were published or deleted within the date range.
 - historyId: The ID of this history record.
 - removed: If this history record is noting the removal of the page, then this value will be 1. If this history record is signifying that the page was published, then the value will be 0.
 - oldVersion: The previous version of this card. It has the following properties: cardId, cardType, created, headerId, historyId, items, removed, and title.
 - cardId: The ID of the card.
 - HeaderId: The ID of the header that this card belongs to.
 - cardType: The type of card to create. Examples include: default card, internal card, thumbnail gallery, internal thumbnail gallery, and more.
 - title: The title of the card.
 - created: The time that the card was created, last updated, or last published (whichever was most recent).
 - userId: The ID of the user who created or last updated the card (whichever was most recent).
 - approved: Lets us know if the card is published (1) or unpublished (0).
 - orderIndex: The order that the cards should be displayed in. A lower value means the card is displayed before a card with a higher value.
 - items: The items that belong to this card.
 - * itemId: The ID of the item.
 - * cardId: The ID of the card that this item belongs to.
 - * indentation: The level of indentation (0 is none, 3 is max).
 - * iconType: The ID of the icon that is displayed at the start of the item.
 - * contentText: The main body of text for the item.
 - * contentUrl: The URL of the item. For graphic items this will be the URL of the image to display, for link items this will be the URL to direct the user to.
 - * contentLabel: The bold title of the item, this is shown before the content text.
 - * contentMode: A special setting that depends on the item in particular. For links this will be used to describe the type of link (internal, external, internal download, external download).
 - * internal: Determines if the item belongs to a published (1) or unpublished (0) version of the card.
 - * iconType: The ID of the icon to use with this item.
 - * typeName: The Font Awesome name of the icon that is used with this item.
 - * typeKeyword: The name displayed when a user hovers over the icon.
 - * color: The hex color code to use for the icon.
 - * sourceId: The ID of the source that this item is referencing.

```

1 {
2   pages: [
3     {
4       categoryName: "Technologies",

```

```

5     created: "2020-09-03T10:12:55.000Z",
6     description: "Lorem ipsum...",
7     historyId: 12,
8     imageUrl: "https://placekitten.com/600/500",
9     internal: 1,
10    name: "New Page",
11    pageId: 59,
12    pageType: 2,
13    removed: 0,
14    sortType: 0,
15    title: "A page for testing",
16    oldVersion: {...}
17  }
18 ],
19 headers: [
20   {
21     categoryName: "Industries",
22     created: "2020-08-20T00:22:00.000Z",
23     description: "Wastewater treatment systems can address a multitude...",
24     historyId: 14,
25     imageUrl: "https://live.satsicflickr...",
26     internal: 0,
27     name: "Wastewater Treatment",
28     pageId: 50,
29     pageType: 1,
30     removed: 0,
31     sortType: 0,
32     title: "Municipalities and industry...",
33     oldVersion: {...}
34   }
35 ],
36 cards: [
37   {
38     cardId: 13,
39     cardType: 0,
40     categoryName: "Technologies",
41     created: "2020-05-23T22:20:20.000Z",
42     headerId: 1,
43     headerName: "Compressed Air Overview",
44     historyId: 4,
45     pageId: 2,
46     pageName: "Compressed Air",
47     pageType: 2,
48     removed: 0,
49     sortType: 2,
50     title: "Cons",
51     oldVersion: {...},
52     items: [
53       {
54         itemId: 32,

```

```

55     cardId: 13,
56     color: "#000000",
57     contentLabel: "",
58     contentMode: 0,
59     contentText: "Extremely energy...",
60     contentUrl: "",
61     created: "2020-05-23T22:52:18.000Z",
62     iconType: 2,
63     indentation: 0,
64     internal: 0,
65     itemId: 32,
66     orderIndex: 1,
67     typeKeyword: "Cons",
68     typeName: "minus"
69   }
70 ]
71 }
72 ]
73 }

```

Listing 54. Example Response

2.8 Request Endpoints

GET api/requests/all

Returns a list of all publish requests that are awaiting approval. Only editors and admins can use this endpoint.

- requests: All publish requests that are awaiting approval.
 - requestId: The ID of the publish request.
 - status: The status of the publish request.
 - title: The title of the publish request.
 - description: The description of the request. This will often include more information about the request and why it is needed.
 - userId: The ID of the user who has opened the publish request.
 - userName: The username of the user who has opened the publish request.
 - created: The date that the publish request was created.

```

1 {
2   requests: [
3     {
4       requestId: 2,
5       status: 1,
6       title: "New Request",
7       description: "This request includes a few pages that I want approved",
8       userId: 58,
9       userName: "testUser",

```



```

10     created: "2020-09-04T20:55:06.000Z",
11   }
12 ]
13 }

```

Listing 55. Example Response

GET api/requests/:requestId

Returns all the data related to a publish request. Only editors and admins can use this endpoint.

- requestId: The ID of the publish request.
- status: The status of the publish request.
- title: The title of the publish request.
- description: The description of the request. This will often include more information about the request and why it is needed.
- userId: The ID of the user who has opened the publish request.
- userName: The username of the user who has opened the publish request.
- created: The date that the publish request was created.
- comments: Comments left on the request by users.
 - commentId: The ID of the comment.
 - requestId: The ID of the publish request that this comment is on.
 - comment: The actual text of the comment.
 - review: The type of comment (0 = comment, 1 = suggest change, 2 = approval).
 - userId: The ID of the user who made the comment.
 - userName: The name of the user who made the comment.
- objects: The objects (pages, headers, and/or cards) that are being selected as part of the publish request.
 - objectType: The type of object that this is (1 = page, 2 = header, 3 = card).
 - The properties that the object will have is based on the object type. Pages will have the following additional properties: approved, categoryName, created, description, imageUrl, internal, name, pageId, pageType, title, and userId. Headers will have the following additional properties: approved, categoryName, created, headerId, internal, orderIndex, pageId, pageName, pageType, title, and userId. Cards will have the following additional properties: approved, cardId, cardType, categoryName, created, headerId, headerName, items, objectType, orderIndex, pageId, pageName, title, and userId.

```

1 {
2   requestId: 2,
3   status: 1,
4   title: "New Request",
5   description: "This request includes a few pages that I want approved",
6   userId: 58,
7   userName: "testUser",
8   created: "2020-09-04T20:55:06.000Z",

```

```

9  comments: [
10    {
11      commentId: 2,
12      requestId: 2,
13      comment: "Looks good.",
14      review: 2,
15      userId: 42,
16      username: "Silverware"
17    }
18  ],
19  objects: [
20    {
21      objectType: 1,
22      pageId: 48,
23      pageType: 2,
24      approved: 0,
25      categoryName: "Technologies",
26      created: "2020-07-02T22:10:36.000Z",
27      description: "Vapor compression is...",
28      imageUrl: "https://live.staticflickr.com/65535/...",
29      internal: 0,
30      name: "Refrigeration",
31      objectType: 1,
32      pageId: 48,
33      pageType: 2,
34      title: "Refrigeration technology...",
35      userId: 51
36    }
37  ]
38 }

```

Listing 56. Example Response

POST api/requests/selections

Allows a user to use any number of object's type and ID to get more detailed information about them. Only editors and admins can use this endpoint.

- objects: The objects that the user wants more information about.
 - objectType: The type of the object (1 = page, 2 = header, 3 = card).
 - objectId: The ID of the object.

```

1  {
2    objects: [
3      {
4        objectType: 1,
5        objectId: 50
6      }
7    ]

```

```
8 }
```

Listing 57. Example Request Body

- objects: The objects that the user requested more information about.
 - objectType: The name of the object type.
 - key: A key that is the objects ID with the first letter of its object type appended to it.
 - objectName: The name or title of the object.

```
1 {
2   objects: [
3     {
4       objectType: "Header",
5       key: "32H",
6       objectName: "Boilers and Steam Opportunities to Consider"
7     }
8   ]
9 }
```

Listing 58. Example Response

POST api/requests/

Creates a new publish request. Only editors and admins can use this endpoint.

- description: The description of the request. This will often include more information about the request and why it is needed.
- title: The title of the publish request.
- objects: The objects that are part of the publish request.
 - objectType: The type of the object (1 = page, 2 = header, 3 = card).
 - objectId: The ID of the object.

```
1 {
2   description: "This new request will add 3 pages, and 2 headers that are ready",
3   title: "Tim's Request",
4   objects: [
5     {
6       objectType: 3,
7       objectId: 168
8     }
9   ]
10 }
```

Listing 59. Example Request Body

- insertId: The ID of the new publish request.

```

1 {
2   insertId: 4
3 }

```

Listing 60. Example Response

POST `api/requests/comment/:requestId`

Creates a new comment on a publish request. Only editors and admins can use this endpoint.

- `requestId`: The ID of the publish request to add a comment to.
- `comment`: The actual text of the comment.
- `status`: The type of comment (0 = comment, 1 = suggest change, 2 = approval).

```

1 {
2   comment: "Did you want to do anything else with the 5th card?",
3   status: "0"
4 }

```

Listing 61. Example Request Body

- `insertId`: The ID of the new comment.

```

1 {
2   insertId: 4
3 }

```

Listing 62. Example Response

DELETE `api/requests/:requestId`

Deletes a publish request. Only the creator of the request and admins can use this endpoint.

- `requestId`: The ID of the publish request to delete.
- `affectedRows`: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 63. Example Response

POST `api/requests/accept/:requestId`

Accepts the publish request. This causes all of the objects that are part of the publish request to become published. Only an admins can use this endpoint.

- `requestId`: The ID of the publish request to accept.
- `objectsApproved`: The number of objects that were published by the request.

```

1 {
2   objectsApproved: 5
3 }

```

Listing 64. Example Response

2.9 Source Endpoints

GET `api/sources/page/:pageId`

Returns all of the sources on a page (even the ones not being used by an item). Only editors and admins can use this endpoint.

- `pageId`: The ID of the page to get the sources from.
- `sources`: All of the sources that belong to the page.
 - `pageId`: The page ID of the page that this source belongs to.
 - `sourceId`: The ID of this source.
 - `text`: The citation text that describes this source (IEEE style).
 - `url`: An optional URL that links to a web page related to the source.

```

1 {
2   sources: [
3     {
4       pageId: 2,
5       sourceId: 1,
6       text: "S. Cottrell, The study skills handbook...",
7       url: ""
8     }
9   ]
10 }

```

Listing 65. Example Response

POST `api/sources/all/page/:pageId`

Creates a list of sources for a page. Since this new list of sources replaces the previous one, it can be used as a way to create, edit, and delete sources. Only admins can use this endpoint.

- `pageId`: The ID of the page to post the source list to.
- `sources`: All of the sources to add to the page.
 - `text`: The citation text that describes this source (IEEE style).
 - `url`: An optional URL that links to a web page related to the source.

```

1 {
2   sources: [

```

```

3  {
4      text: "S. Cottrell, The study skills handbook...",
5      url: ""
6  }
7  ]
8  }

```

Listing 66. Example Request Body

- sourcesApproved: The number of sources that were successfully added from the new source list.

```

1  {
2      sourcesApproved: 1
3  }

```

Listing 67. Example Response

POST api/sources/page/:pageId

Adds a single source to a page. Only editors and admins can use this endpoint.

- pageId: The ID of the page to add the source to.
- text: The citation text that describes this source (IEEE style).
- url: An optional URL that links to a web page related to the source.

```

1  {
2      text: "S. Cottrell, The study skills handbook...",
3      url: ""
4  }

```

Listing 68. Example Request Body

- insertId: The ID of the new source.

```

1  {
2      insertId: 1
3  }

```

Listing 69. Example Response

2.10 User Endpoints

GET api/users/:userId

Returns basic information about a user. Any logged in user can use this endpoint.

- userId: The ID of the user to get information about.
- created: The date that the user account was created.
- email: The user's email address.

- firstName: The user's first name.
- lastName: The user's last name.
- role: The user's role (0 = not logged in, 1 = external user, 2 = internal user, 3 = editor, 4 = admin).
- userId: The ID of the user.
- username: The username of the user.

```

1 {
2   created: "2020-05-14T20:39:15.000Z",
3   email: "thomasza@oregonstate.edu",
4   firstName: "Zachary",
5   lastName: "Thomas",
6   role: 4,
7   userId: 42,
8   username: "Silverware"
9 }

```

Listing 70. Example Response

POST api/users/login

Attempts to login the user. If the user's username and password are correct, then they will be given cookies that will confirm their identity for use with the other endpoints. Any user can use this endpoint.

- username: The username of the account that the user wants to login to.
- password: A password that should match the username's password.

```

1 {
2   username: "newUser",
3   password: "hunter2"
4 }

```

Listing 71. Example Request Body

- email: The user's email address.
- firstName: The user's first name.
- lastName: The user's last name.
- role: The user's role (0 = not logged in, 1 = external user, 2 = internal user, 3 = editor, 4 = admin).
- userId: The ID of the user account.
- username: The username of the user.

```

1 {
2   email: "johnDoe@gmail.com",
3   firstName: "John",
4   lastName: "Doe",
5   role: 2,
6   userId: 42,
7   username: "newUser"

```

```
8 }
```

Listing 72. Example Response

POST `api/users/`

Creates a new user account. The new user must not have the same username or email as an existing user. The new user will always start with the "external user" role. Passwords are salted and hashed before being stored in the database. Any user can use this endpoint.

- email: The user's email address.
- firstName: The user's first name.
- lastName: The user's last name.
- password: The user's password.
- username: The user's username.

```
1 {
2   email: "johnDoe@gmail.com",
3   firstName: "John",
4   lastName: "Doe",
5   password: "hunter2",
6   username: "newUser"
7 }
```

Listing 73. Example Request Body

- insertId: The ID of the new user.

```
1 {
2   insertId: 42
3 }
```

Listing 74. Example Response

GET `api/users/search/:text/:role/:sort/:order/:cursorPrimary/:cursorSecondary`

Returns a limited list of users that match the search text and that only includes users that are at or beyond the cursor. The search text can find matches for first name, last name, username, email, or user ID. Only admins can use this endpoint.

- text: The partial or full text that is used to find a match. Partial matches are allowed. For example: searching for "oh" would be able to return "John123" since "oh" is contained within "John123".
- cursorPrimary: This cursor should contain the username of the user you want to start your search at (alphabetical order). This cursor is used to allow infinite scrolling, while only loading a small number of page results at a time. If this is a new search then this value should be null.
- cursorSecondary: This cursor should contain the user ID of the user you want to start your search at. This cursor is used in instances where the primary cursor value is ambiguous. If this is a new search then this value should be null.

- **nextCursor:** An object that contains the information needed to continue searching the rest of the users (the primary and secondary cursor).
- **users:** The users returned from the search.
 - **created:** The date that the user account was created.
 - **createdUnix:** Seconds since January 1st, 1970 (UTC).
 - **email:** The user's email address.
 - **firstName:** The user's first name.
 - **lastName:** The user's last name.
 - **role:** The user's role (0 = not logged in, 1 = external user, 2 = internal user, 3 = editor, 4 = admin).
 - **username:** The user's username.

```

1 {
2   nextCursor: {
3     primary: null,
4     secondary: null
5   },
6   created: "2020-09-01T02:00:00.000Z",
7   createdUnix: 1598925600,
8   email: "testeditor@gmail.com",
9   firstName: "John",
10  lastName: "Doe",
11  role: 3,
12  userId: 67,
13  username: "testEditor"
14 }

```

Listing 75. Example Response

PATCH `api/users/:userId`

Updates a user's information. Only the user being updated or an admin can use this endpoint. Only admins can change a user's role.

- **userId:** The ID of the user to update.
- **email:** The user's new email address.
- **firstName:** The user's new first name.
- **lastName:** The user's new last name.
- **role:** The user's new role which can only be set by admins (0 = not logged in, 1 = external user, 2 = internal user, 3 = editor, 4 = admin).
- **username:** The user's username.
- **oldPassword:** The user's current password.
- **newPassword:** The user's new password.

```

1 {
2   email: "johnDoe@gmail.com",

```

```

3  firstName: "John",
4  lastName: "Doe",
5  role: 3,
6  username: "newUser",
7  oldPassword: "hunter2",
8  newPassword: "hunter3"
9  }

```

Listing 76. Example Request Body

- `affectedRows`: The number of table rows affected by this action.

```

1  {
2    affectedRows: 1
3  }

```

Listing 77. Example Response

POST `api/users/:userId/newPassword`

Generates a new random password for a user. This endpoint is ideal for when an admin wants to give a user access to an account that they forgot the password to. Only admins can use this endpoint.

- `userId`: The ID of user account to generate a new password for.
- `password`: The new randomly generated password.

```

1  {
2    password: "9RBahxx47qiKcny"
3  }

```

Listing 78. Example Response

2.11 View Endpoints

GET `api/views/page/:pageId`

Returns all of the views available to the current user for the specific page. Any user can use this endpoint.

- `pageId`: The ID of the page to get the views for.
- `views`: The views that can be accessed on this page.
 - `pageId`: The page that this view belongs to.
 - `public`: Whether this view is viewable by all users (1) or only viewable by the current user (0).
 - `userId`: The user ID of the user who created this view.
 - `viewId`: The ID of the view.
 - `viewName`: The name of the view.
 - `headers`: The headers and their filter settings for the current view.

- * **headerId**: The ID of the current header.
- * **filters**: An array of filter icon IDs. Each value represents a specific filter that is disabled on the current header while in this view.

```

1 {
2   views: [
3     {
4       pageId: 2,
5       public: 1,
6       userId: 51,
7       viewId: 11,
8       viewName: "Opportunities",
9       headers: [
10        {
11          headerId: 1,
12          filters: [1, 2, 3, 4, 5]
13        }
14      ]
15    }
16  ]
17 }

```

Listing 79. Example Response

POST **api/views/page/:pageId**

Creates a new view for the specific page. Any logged in user can use this endpoint.

- **pageId**: The ID of the page where the new view is created.
- **publicView**: Whether this view is viewable by all users (1) or only viewable by the current user (0).
- **viewName**: The name of the new view.
- **headers**: The headers and their filter settings for the current view.
 - **headerId**: The ID of the current header.
 - **filters**: An array of filter icon IDs. Each value represents a specific filter that is disabled on the current header while in this view.

```

1 {
2   publicView: 0,
3   viewName: "No pros or cons",
4   headers: [
5     {
6       headerId: 1,
7       filters: [1, 2]
8     }
9   ]
10 }

```

Listing 80. Example Request Body

- insertId: The ID of the new view.

```
1 {  
2   insertId: 5  
3 }
```

Listing 81. Example Response

DELETE `api/views/:viewId`

Deletes a view. Only the user who created the view or an admin can use this endpoint.

- viewId: The ID of the view to delete.
- affectedRows: The number of table rows affected by this action.

```
1 {  
2   affectedRows: 1  
3 }
```

Listing 82. Example Response

3 CONTACT INFORMATION

If you have any questions about this API that are not answered in this document feel free to reach out to me by email at silverware13@gmail.com.