

ENERGY EFFICIENCY CENTER INDUSTRIAL WALKTHROUGH CHECKLIST & REFERENCE API

SEPTEMBER 5, 2020

PREPARED BY

ZACHARY THOMAS

CONTENTS

1	Introduction	2
2	API Endpoints	2
2.1	Card Endpoints	2
2.2	Category Endpoints	7
2.3	Header Endpoints	10
2.4	Home Endpoints	13
2.5	Icon Endpoints	16
3	Contact Information	18

1 INTRODUCTION

This document describes all of the API endpoints for the EEC Walkthrough application. The document is organized by route name and each API endpoint includes a general description, the expected input, and the expected output.

This API uses cookies to keep track of the user who is making requests. This means that each of these endpoints will have access to all user information for the current user even if it is not requested in the body. This includes ID, username, first name, last name, email, and their role. All endpoints also have the option to return an error code. This will have a status code between 400 and 500. In the case of a validation error an object with the property "errors" will be returned, which is an array of objects that describe what was wrong with the request body. All other errors will return an object with the property "error", which is a string that describes the error.

To make handling responses from the API easier, all responses return a JSON object. To make it easier to tell what requests are being made to the API (as apposed to requests to get files), each API request starts with "api".

2 API ENDPOINTS

2.1 Card Endpoints

POST api/cards

Creates a new card. Only editors and admins can use this endpoint.

- HeaderId: The ID of the header that this card belongs to.
- cardType: The type of card to create. Examples include: default card, internal card, thumbnail gallery, internal thumbnail gallery, and more.
- title: The title of the card.
- items: The items that will be included in the card.
 - cardId: The ID of the card that this item belongs to.
 - indentation: The level of indentation (0 is none, 3 is max).
 - iconType: The ID of the icon that is displayed at the start of the item.
 - contentText: The main body of text for the item.
 - contentUrl: The URL of the item. For graphic items this will be the URL of the image to display, for link items this will be the URL to direct the user to.
 - contentLabel: The bold title of the item, this is shown before the content text.
 - contentMode: A special setting that depends on the item in particular. For links this will be used to describe the type of link (internal, external, internal download, external download).
 - internal: Determines if the item should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
 - sourceId: The ID of the source that this item is referencing.

```

1 {
2   headerId: 2,
3   cardType: 0,
4   title: "Best Practices",
5   items: [
6     {

```

```

7     cardId: 1,
8     indentation: 0,
9     iconType: 16,
10    contentText: "An informational page with analysis tools",
11    contentUrl: "https://www.bpa.gov/EE/Sectors/Industrial/Pages/Co",
12    contentLabel: "Bonneville Power Administration",
13    contentMode: 0,
14    internal: 0,
15    sourceId: 2
16  }
17 ]
18 }

```

Listing 1. Example Request Body

- insertId: The ID of the newly created card.

```

1 {
2   insertId: 10
3 }

```

Listing 2. Example Response

DELETE `api/cards/:cardId/changes`

Delete an unpublished card / suggested changes to a card. Only editors and admins can use this endpoint.

- cardId: The ID of the card to delete.
- affectedRows: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 3. Example Response

DELETE `api/cards/:cardId`

Delete a specific card (including published cards). Only admins can use this endpoint.

- cardId: The ID of the card to delete.
- affectedRows: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 4. Example Response

PATCH api/cards/:cardId

Updates a card. If the card is unpublished this will simply change the card. If the card is published then this will add a suggested edit to the card that will need to be published before it will replace the original. If the card is both published and has an edited version, then this will replace the edited version. Only an editor or an admin can use this endpoint.

- cardId: The ID of the card to update.
- cardType: The type of card to create. Examples include: default card, internal card, thumbnail gallery, internal thumbnail gallery, and more.
- title: The title of the card.
- items: The items that will be included in the card.
 - cardId: The ID of the card that this item belongs to.
 - indentation: The level of indentation (0 is none, 3 is max).
 - iconType: The ID of the icon that is displayed at the start of the item.
 - contentText: The main body of text for the item.
 - contentUrl: The URL of the item. For graphic items this will be the URL of the image to display, for link items this will be the URL to direct the user to.
 - contentLabel: The bold title of the item, this is shown before the content text.
 - contentMode: A special setting that depends on the item in particular. For links this will be used to describe the type of link (internal, external, internal download, external download).
 - internal: Determines if the item should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.
 - sourceId: The ID of the source that this item is referencing.

```

1 {
2   cardType: 0,
3   title: "Best Practices",
4   items: [
5     {
6       cardId: 1,
7       indentation: 0,
8       iconType: 16,
9       contentText: "An informational page with analysis tools",
10      contentUrl: "https://www.bpa.gov/EE/Sectors/Industrial/Pages/Co",
11      contentLabel: "Bonneville Power Administration",
12      contentMode: 0,
13      internal: 0,
14      sourceId: 2
15    }
16  ]
17 }
```

Listing 5. Example Request Body

- cardId: The ID of the current card.

```

1 {
2   cardId: 1
3 }

```

Listing 6. Example Response

POST `api/cards/:cardId/publish`

Publishes a card. If the card is unpublished this will simply approve the card and show it publicly. If the card has a published version and an edit then the edit will replace the current published version while becoming approved. Only an admin can use this endpoint.

- `cardId`: The ID of the card to publish.

```

1 {
2   cardId: 1
3 }

```

Listing 7. Example Response

POST `api/cards/:cardId/unpublish`

Unpublishes a card. If the card is published this will simply make the card unapproved and unviewable by the public. If the card has a published version and an edit then the edit will be replaced by the current published version while becoming unapproved. Only an admin can use this endpoint.

- `cardId`: The ID of the card to unpublish.

```

1 {
2   cardId: 1
3 }

```

Listing 8. Example Response

PATCH `api/cards/:cardId/move/:direction/:mode`

Changes the selected card's position relative to other cards when displayed. If we are moving an unpublished card, it will move the card relative to all cards (excluding its published version). If we are moving a published card it will move relative to published cards (skipping over unpublished cards). Only editors or admins can move an unpublished card. Only admins can move a published card.

- `cardId`: The ID of the card to move.
- `direction`: A value of 1 moves the card up one row. A value of 0 moves the card down one row.
- `mode`: States what type of card we want to move. A value of 0 represents an unpublished card. A value of 1 represents a published card.

```

1 {
2   cardId: 1
3 }

```

Listing 9. Example Response

GET `api/cards/titles`

Gets a list of suggested titles for cards. Editors can use these suggested titles to quickly name cards that are similar across pages. Any user can use this endpoint.

- `titles`: An array of strings that will be used as the suggested titles.

```

1 {
2   titles: [
3     "General Off Site Resource Links",
4     "Best Practices",
5     "Caveats"
6   ]
7 }

```

Listing 10. Example Response

POST `api/cards/titles`

Replaces the current list of suggested card titles. Only admins can use this endpoint.

- `titles`: An array of strings that will be used as the new suggested titles.

```

1 {
2   titles: [
3     "Data Collection Guides",
4     "Rules of Thumb",
5     "Caveats"
6   ]
7 }

```

Listing 11. Example Request Body

```

1 {
2   titleCount: 3
3 }

```

Listing 12. Example Response

2.2 Category Endpoints

GET `api/categories/all`

Gets all of the categories and their respective pages. Users without an account, or external users will get all published categories and pages that are not internal. Internal users, editors, and admins will get all categories and pages.

- `categoryId`: The ID of the category.
- `created`: The date that the category was created.
- `description`: A general description of the category.
- `internal`: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- `pluralName`: The plural name of the category.
- `singleName`: The singular name of the category.
- `userId`: The ID of the user who created the category.
- `pages`: The list of pages that belong to the category.
 - `approved`: Whether this page is published and viewable in view mode.
 - `description`: The description of the page.
 - `internal`: Whether the page is viewable by the public (value of 0) or just by internal users (value of 1).
 - `name`: The name of the page.
 - `pageId`: The ID of the page.
 - `pageType`: The category ID that the page belongs to.

```

1 {
2   categories: [
3     {
4       categoryId: 5,
5       created: "2020-07-18T03:11:32.000Z",
6       description: "Standard recommended approaches for performing...",
7       internal: 0,
8       pluralName: "Assessments",
9       singleName: "Assessment",
10      userId: 51,
11      pages: [
12        approved: 1,
13        description: "Cybersecurity is...",
14        internal: 1,
15        name: "Cybersecurity",
16        pageId: 62,
17        pageType: 5
18      ]
19    }
20  ]
21 }
```

Listing 13. Example Response

GET api/categories/names

Gets the names and IDs of all categories. Users without an account, or external users will get all published categories that are not internal. Internal users, editors, and admins will get all categories.

- categoryId: The ID of the category.
- singleName: The singular name of the category.

```

1 {
2   categories: [
3     {
4       categoryId: 5,
5       singleName: "Assessment"
6     }
7   ]
8 }
```

Listing 14. Example Response

GET api/categories/:categoryId

Gets a single category and all of its pages. Users without an account, or external users will get a published category and the pages that are not internal. Internal users, editors, and admins will get the category and all of the pages.

- categoryId: The ID of the category.
- created: The date that the category was created.
- description: A general description of the category.
- internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- pluralName: The plural name of the category.
- singleName: The singular name of the category.
- userId: The ID of the user who created the category.
- pages: The list of pages that belong to the category.
 - approved: Whether this page is published and viewable in view mode.
 - description: The description of the page.
 - internal: Whether the page is viewable by the public (value of 0) or just by internal users (value of 1).
 - name: The name of the page.
 - pageId: The ID of the page.
 - pageType: The category ID that the page belongs to.

```

1 {
2   categoryId: 5,
3   created: "2020-07-18T03:11:32.000Z",
4   description: "Standard recommended approaches for performing...",
5   internal: 0,
6   pluralName: "Assessments",
7   singleName: "Assessment",
```

```

8   userId: 51,
9   pages: [
10    approved: 1,
11    description: "Cybersecurity is...",
12    internal: 1,
13    name: "Cybersecurity",
14    pageId: 62,
15    pageType: 5
16  ]
17 }

```

Listing 15. Example Response

POST api/categories

Creates a new category. This endpoint can only be used by admins.

- description: A general description of the category.
- internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- pluralName: The plural name of the category.
- singleName: The singular name of the category.

```

1 {
2   description: "Standard recommended approaches for performing...",
3   internal: 0,
4   pluralName: "Assessments",
5   singleName: "Assessment",
6 }

```

Listing 16. Example Request Body

- insertId: The ID of the newly created category.

```

1 {
2   insertId: 10
3 }

```

Listing 17. Example Response

PATCH api/categories/:categoryId

Updates a category. This endpoint can only be used by admins.

- categoryId: The ID of the category to be updated.
- description: A general description of the category.
- internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
- pluralName: The plural name of the category.
- singleName: The singular name of the category.

```

1 {
2   description: "Standard recommended approaches for performing...",
3   internal: 0,
4   pluralName: "Assessments",
5   singleName: "Assessment",
6 }

```

Listing 18. Example Request Body

- categoryId: The ID of the category.

```

1 {
2   categoryId: 10
3 }

```

Listing 19. Example Response

2.3 Header Endpoints

POST api/headers

Creates a new header. Only editors and admins can use this endpoint.

- PageId: The ID of the page that this header belongs to.
- title: The title of the header.
- internal: Determines if the header should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.

```

1 {
2   pageId: 15,
3   title: "Wastewater Overview",
4   internal: 0
5 }

```

Listing 20. Example Request Body

- insertId: The ID of the newly created header.

```

1 {
2   insertId: 5
3 }

```

Listing 21. Example Response

DELETE api/headers/:headerId/changes

Delete an unpublished header / suggested changes to a header. Only editors and admins can use this endpoint.

- headerId: The ID of the header to delete.
- affectedRows: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 22. Example Response

DELETE `api/headers/:headerId`

Delete a specific header (including published headers). Only admins can use this endpoint.

- `headerId`: The ID of the header to delete.
- `affectedRows`: The number of table rows affected by this action.

```

1 {
2   affectedRows: 1
3 }

```

Listing 23. Example Response

PATCH `api/headers/:headerId`

Updates a header. If the header is unpublished this will simply change the header. If the header is published then this will add a suggested edit to the header that will need to be published before it will replace the original. If the header is both published and has an edited version, then this will replace the edited version. Only an editor or an admins can use this endpoint.

- `headerId`: The ID of the header to update.
- `title`: The title of the header.
- `internal`: Determines if the header should be viewable by the public, or just internal users. A value of 1 is only viewable by internal users, while a value of 0 is viewable by everyone.

```

1 {
2   title: "Compressed Air Overview",
3   internal: 0
4 }

```

Listing 24. Example Request Body

- `headerId`: The ID of the current header.

```

1 {
2   headerId: 1
3 }

```

Listing 25. Example Response

POST `api/headers/:headerId/publish`

Publishes a header. If the header is unpublished this will simply approve the header and show it publicly. If the header has a published version and an edit then the edit will replace the current published version while becoming approved. Only an admins can use this endpoint.

- `headerId`: The ID of the header to publish.

```

1 {
2   headerId: 1
3 }
```

Listing 26. Example Response

POST `api/headers/:headerId/unpublish`

Unpublishes a header. If the header is published this will simply make the header unapproved and unviewable by the public. If the header has a published version and an edit then the edit will be replaced by the current published version while becoming unapproved. Only an admins can use this endpoint.

- `headerId`: The ID of the header to unpublish.

```

1 {
2   headerId: 1
3 }
```

Listing 27. Example Response

PATCH `api/headers/:headerId/move/:direction/:mode`

Changes the selected header's position relative to other headers when displayed. If we are moving an unpublished header, it will move the card relative to all cards (excluding its published version). If we are moving a published header it will move relative to published header (skipping over unpublished headers). Only editors or admins can move an unpublished header. Only admins can move a published header.

- `headerId`: The ID of the header to move.
- `direction`: A value of 1 moves the header up one row. A value of 0 moves the header down one row.
- `mode`: States what type of header we want to move. A value of 0 represents an unpublished header. A value of 1 represents a published header.

```

1 {
2   headerId: 1
3 }
```

Listing 28. Example Response

2.4 Home Endpoints

GET api/home

Gets all of the data displayed on the homepage, with the exception of the sponsors. Any user can use this endpoint.

- mainHeader: The main header text for the homepage.
- secondaryHeader: The header for the card that describes the categories.
- sectionTitle: The title on the card that describes the categories.
- sectionFooter: The footer on the card that describes the categories.
- tidbitsHeader: The header for the card describing tidbits.
- tidbitsTitle: The title on the card that describes the tidbits.
- tidbitsFooter: The footer on the card that describes the tidbits.
- linksHeader: The header for the card describing links.
- linksTitlePrefix: The title on the card that is shown before the standard link icons are listed.
- linksTitlePostfixInternal: The title on the card that is shown before the link internal and external icons.
- linksTitlePostfixDownload: The title on the card that is shown before the link download icon.
- linksFooter: The footer on the card that describes the links.
- disclaimerHeader: The header of the disclaimer card.
- disclaimerText: The text on the disclaimer card.
- categories: The categories viewable by the current user.
 - categoryId: The ID of the category.
 - description: A general description of the category.
 - internal: Whether the category is viewable by the public (value of 0) or just by internal users (value of 1).
 - pluralName: The plural name of the category.
 - singularName: The singular name of the category.

```

1 {
2   mainHeader: "Welcome",
3   secondaryHeader: "The purpose of this guide...",
4   sectionTitle: "This guide is broken down into sections:",
5   sectionFooter: "",
6   tidbitsHeader: "Each section...",
7   tidbitsTitle: "These include...",
8   tidbitsFooter: "Note: tidbit types can be...",
9   linksHeader: "Each section also references...",
10  linksTitlePrefix: "A preceding icon identifies...",
11  linksTitlePostfixInternal: "A trailing icon...",
12  linksTitlePostfixDownload: "A second trailing icon...",
13  linksFooter: "",
14  disclaimerHeader: "Disclaimer",
15  disclaimerText: "The primary objective...",
16  categories: [
17    {
18      categoryId: 5,
19      description: "Standard recommended...",
20      internal: 0,
```

```

21     pluralName: "Assessments",
22     singleName: "Assessment"
23   }
24 ]
25 }

```

Listing 29. Example Response

PATCH api/home

Updates the text that is displayed on the homepage. Only admins can use this endpoint.

- mainHeader: The main header text for the homepage.
- secondaryHeader: The header for the card that describes the categories.
- sectionTitle: The title on the card that describes the categories.
- sectionFooter: The footer on the card that describes the categories.
- tidbitsHeader: The header for the card describing tidbits.
- tidbitsTitle: The title on the card that describes the tidbits.
- tidbitsFooter: The footer on the card that describes the tidbits.
- linksHeader: The header for the card describing links.
- linksTitlePrefix: The title on the card that is shown before the standard link icons are listed.
- linksTitlePostfixInternal: The title on the card that is shown before the link internal and external icons.
- linksTitlePostfixDownload: The title on the card that is shown before the link download icon.
- linksFooter: The footer on the card that describes the links.
- disclaimerHeader: The header of the disclaimer card.
- disclaimerText: The text on the disclaimer card.

```

1 {
2   mainHeader: "Welcome",
3   secondaryHeader: "The purpose of this guide...",
4   sectionTitle: "This guide is broken down into sections:",
5   sectionFooter: "",
6   tidbitsHeader: "Each section...",
7   tidbitsTitle: "These include...",
8   tidbitsFooter: "Note: tidbit types can be...",
9   linksHeader: "Each section also references...",
10  linksTitlePrefix: "A preceding icon identifies...",
11  linksTitlePostfixInternal: "A trailing icon...",
12  linksTitlePostfixDownload: "A second trailing icon...",
13  linksFooter: "",
14  disclaimerHeader: "Disclaimer",
15  disclaimerText: "The primary objective..."
16 }

```

Listing 30. Example Request Body

- `homePageUpdated`: Generic value. Should always have a value of 1, showing that the home page was updated correctly.

```

1 {
2   homePageUpdated: 1
3 }
```

Listing 31. Example Response

GET `api/home/sponsors`

Gets all of the sponsors that should be listed on the homepage. Any user can use this endpoint.

- `sponsors`: The sponsors for this application.
 - `sponsorId`: The ID of the sponsor.
 - `name`: The name of the sponsor.
 - `title`: A short description of the sponsor that doubles as a link.
 - `websiteUrl`: The URL for the sponsors website.
 - `imageUrl`: The URL for the sponsors image.
 - `orderIndex`: A value that determines the order that the sponsors are listed in. A lower value will appear before a larger value.

```

1 {
2   sponsors: [
3     {
4       sponsorId: 5,
5       name: "Industrial Assessment Center",
6       title: "U.S. Department of Energy...",
7       websiteUrl: "https://www.energy.gov/eere/amo/industrial-assessment-centers-iacs",
8       imageUrl: "/images/IAC.png",
9       orderIndex: 0
10    }
11  ]
12 }
```

Listing 32. Example Response

PATCH `api/home/sponsors`

Updates the list of sponsors that is displayed on the homepage. Only admins can use this endpoint.

- `sponsors`: The sponsors for this application.
 - `sponsorId`: The ID of the sponsor.
 - `name`: The name of the sponsor.
 - `title`: A short description of the sponsor that doubles as a link.

- `websiteUrl`: The URL for the sponsors website.
- `imageUrl`: The URL for the sponsors image.
- `orderIndex`: A value that determines the order that the sponsors are listed in. A lower value will appear before a larger value.

```

1 {
2   sponsors: [
3     {
4       sponsorId: 5,
5       name: "Industrial Assessment Center",
6       title: "U.S. Department of Energy...",
7       websiteUrl: "https://www.energy.gov/eere/amo/industrial-assessment-centers-iacs",
8       imageUrl: "/images/IAC.png",
9       orderIndex: 0
10    }
11  ]
12 }
```

Listing 33. Example Request Body

- `sponsorsUpdated`: Generic value. Should always have a value of 1, showing that the sponsors were updated correctly.

```

1 {
2   sponsorsUpdated: 1
3 }
```

Listing 34. Example Response

2.5 Icon Endpoints

GET `api/icons/all`

Gets a list of all icons that can be appended to items. Any user can use this endpoint.

- `icons`: All possible icons.
 - `iconType`: The ID of the icon.
 - `groupIndex`: The type of item this icon represents (disabled = 0, default item = 1, graphics item = 2, link item = 3).
 - `typeKeyword`: The name of the icon when it is being hovered over or selected in a menu.
 - `typeName`: The name of the actual Font Awesome icon.
 - `color`: The color of the icon. Represented by a hexadecimal color code.

```

1 {
2   icons: [
3     {
4       iconType: 21,
```

```

5     groupIndex: 3,
6     typeKeyword: "Analysis Tool",
7     typeName: "list",
8     color: "#000000"
9   }
10 ]
11 }

```

Listing 35. Example Response

POST api/icons

Creates a new icon. Only an admin can use this endpoint.

- **groupIndex:** The type of item this icon represents (disabled = 0, default item = 1, graphics item = 2, link item = 3).
- **typeKeyword:** The name of the icon when it is being hovered over or selected in a menu.
- **typeName:** The name of the actual Font Awesome icon.
- **color:** The color of the icon. Represented by a hexadecimal color code.

```

1 {
2   groupIndex: 3,
3   typeKeyword: "Analysis Tool",
4   typeName: "list",
5   color: "#000000"
6 }

```

Listing 36. Example Request Body

- **insertId:** The ID of the newly created icon.

```

1 {
2   insertId: 10
3 }

```

Listing 37. Example Response

PATCH api/icons/:iconId

Updates an icon. Only an admin can use this endpoint.

- **iconId:** The ID of the icon.
- **groupIndex:** The type of item this icon represents (disabled = 0, default item = 1, graphics item = 2, link item = 3).
- **typeKeyword:** The name of the icon when it is being hovered over or selected in a menu.
- **typeName:** The name of the actual Font Awesome icon.
- **color:** The color of the icon. Represented by a hexadecimal color code.

```
1 {  
2   groupIndex: 3,  
3   typeKeyword: "Analysis Tool",  
4   typeName: "list",  
5   color: "#000000"  
6 }
```

Listing 38. Example Request Body

- `iconId`: The ID of the icon.

```
1 {  
2   iconId: 10  
3 }
```

Listing 39. Example Response

3 CONTACT INFORMATION

If you have any questions about this API that are not answered in this document feel free to reach out to me by email at silverware13@gmail.com.