Report - Adversarial Testing of WebAgents

Student: Oszkár Urbán
Supervisors: Robin Staab, Max Baader, Mislav Balunović, Martin Vechev

Task overview & key checkpoints:

- Environment: Investigated the robustness of various web agents [1-5]
- PGD algorithm: Implemented adversarial attacks using the Projected Gradient Descent (PGD) algorithm, increasing the length of enforceable image descriptions from 4 to 19 tokens [GitHub]
- E2E Adversarial attack pipeline: Developed a Proof of Concept pipeline that effectively fooled the VisualWebArena (VWA) setting [GitHub]

Environment

- Pivoted from WebArena to VisualWebArena (VWA)
  - VWA introduces tasks that emphasize visual understanding with language processing
  - VWA proposes a new VLM agent inspired by Set-of-Marks (SOM) prompting, which partitions images into regions marked with alphanumerics, masks, or boxes, simplifying the model's action space.
- technical detail: Due to the large size of docker images for mock websites (~60-90GB), the focus was limited to the Classifieds (Amazon) mock website.

PGD algorithm

- Initially implemented the “original” epsilon add/subtract method, which could enforce only 4-5 tokens.

```
#perfrom either targeted or untargeted attack
   if targeted:
       out = input_ - eps * input_.grad.sign()
   else:
       out = input_ + eps * input_.grad.sign()
```

- Improved the length of enforceable tokens from 4 to 19 by incorporating the Adam optimizer

```
optimizer = torch.optim.Adam([input_], lr=0.0095)
[…]
loss.backward(retain_graph=True)
optimizer.step()
input_.data = input_.data.clamp_(min=x_min, max=x_max)
```

- technical details & findings:
  - The “original” epsilon add/subtract approach gradually altered the image description toward a target by enforcing one token at a time

- The "PGD with Adam" method exhibited a binary behavior, where the target description appeared only when all tokens were correctly enforced.
- The captioning model (Salesforce/blip2-flan-t5-xl) demonstrated strong descriptive behavior, with the initial “a” in the description being particularly challenging to change due to the model’s tendency to adhere to the pattern “a {quality} {item}”.

Image preprocessing issues

- blip2 preprocessing method was unsuitable as it converts images to numpy arrays before applying transformations, causing a loss of gradients
- implemented own preprocess to address this issue by applying the corresponding transformations directly on Torch tensors

Issue

- PGD-altered images, when processed by Blip2, returned incorrect descriptions due to preprocessing discrepancies, particularly in the resize operation

Solution

- set the anti-alias option to True to match Pillow's downsampling operation.

- After switching to the Adam optimizer & fixing the preprocessing issues, the behavior of the loss curve no longer exhibited periodic 'jumps.' (default lr)





E2E Adversarial attack pipeline

Observation Handler

- before each action [Observation Handler retrieves environment observation]

TextObservationProcessor

- update default alt description of each image by running blip2 inference



- **attack**: load the PGD-altered image and run blip2 inference, producing the desired target description



ImageObservationProcessor

- draw bounding boxes around images and interactive elements (buttons, text fields, etc.) on the webpage screenshot



  - **attack**: replace images in the screenshot with their PGD-altered equivalent



- technical details & findings:
  - Successfully fooled VWA agent, even when targeting only the TextObservationProcessor, indicating that the model's reasoning relies heavily on the image description rather than the actual image content
- future work: Investigate how many and which specific "target" images need to be altered to deceive the agent effectively "Where does the agent actually look?"

POC Demo recordings

- Fool navigation starting from the Home Page
  - intent: Find the most expensive boat from Middle River that is longer than 10 meters
- Fool navigation starting from the Cars gallery view
  - intent: Find the most expensive truck from Ohio that is white.
- Fool reasoning starting from the HomePage
  - intent: What is the size of the musical instrument on this page?
- finding: Attacks had a higher success rate on tasks that were challenging for the agent from the outset. For example, 'Navigate to the boat that is white' was solved, but 'Navigate to the boat that is longer than 10m' successfully fooled the agent because the answer wasn't as obvious, requiring more reasoning—where the attack could exploit the inherent uncertainty of the model.

Github Resources

- PGD algorithm code
- Demo results
- Modified VisualWebArena pipeline that utilizes PGD-altered images

Other notes

- After reviewing a recent publication from CMU and following internal discussions, we decided not to pursue a publication for ICLR. They use llava-hf/llava-1.5-7b-hf, while we utilize the more powerful Salesforce/blip2-flan-t5-xl captioning model, which is arguably harder to manipulate to produce longer sequences of target text. However, this wouldn't be enough of a selling point
- for more detailed, unedited (daily) updates of my work see
  Adversarial Testing of Web Agents - Progress

References

[1] https://arxiv.org/pdf/2401.13649
[2] https://arxiv.org/pdf/2307.13854
[3] https://miniwob.farama.org/index.html
[4] https://arxiv.org/pdf/2404.06474
[5] https://arxiv.org/pdf/2310.03720