

Setup Guide for Everyone

Step-by-step installation and handover

A practical guide for version 1.0.0-rc.6

Prepared from the supplied RC5 project and roadmap. Updated 5 September 2026.

Review build - synthetic data only.

The full roadmap is not complete. All-data client encryption remains unmet; formal ISO assurance and real-environment acceptance are outstanding. Read the scope and release assessment before deployment.

Inside this guide

Read this one page before doing anything

Parts list: collect these before Step 1

Part A - prepare the cloud parts (Cloud/Edge owners)

Part B - place and verify the RC6 package

Part C - connect the Terminal to the correct AWS account

Part D - answer the RC6 setup questions

Part E - run the read-only check

Part F - create and approve the production plan

Part G - apply the approved plan

Part H - if the Terminal closes or a stage fails

Part I - verify the assembled system before client data

Part J - error finder

RC6 privacy and upgrade additions to acceptance

Final assembly checklist

Official pages used for screen locations

Tiny glossary

After installation - school and family handover

Review build - use a separate evaluation environment and synthetic records only. The full roadmap is unfinished. In particular, encryption of every stored value in the browser is not implemented; selected restricted fields are encrypted. Formal ISO assurance, complete finance and integration workflows, and real-cloud/device/security acceptance remain outstanding. The impossible guarantee that no person can capture a visible medical record is not claimed. Read the technical guide and `docs/RC6_ROADMAP_COVERAGE.md` before choosing an environment. This guide does not authorise a live school upgrade or turn a passed local test into production acceptance.

This edition retains the familiar 45-step installation sequence and adds the RC6 changes. The new-school path is for an isolated trial. The existing-school path is provided for rehearsals and a later approved release; preserve RC5 until the documented release blockers are closed.

The supplied revision-4 PDF referred to a companion CDK policy JSON that was absent from the source archive. Step 17A now explains the real prerequisite and uses explicitly approved policy identifiers; it does not invent a reviewed policy file or checksum. RC6 already includes the repository-root repair, so the old Step 15A source patch must not be applied again.

Read this one page before doing anything

This manual explains **Edutex 1.0.0-rc.6 assembly for one school**. It is written like furniture assembly: collect the labelled parts, complete one numbered action, compare the result, and stop if it does not match.

There is **no paper deployment worksheet and no hidden website form**. When this guide says “answer the setup questions”, you type each answer into the **Terminal panel at the bottom of Visual Studio Code**. RC6 creates the file for you. Do not create or edit `rc6.json` by hand.

The four commands that do the deployment

Command	Plain-English job	Can change production?
<code>npm run setup -- configure</code>	Asks one setup question at a time and saves non-secret answers	No
<code>npm run setup -- check-cloud</code>	Checks your computer and approved AWS prerequisites	No; read-only
<code>npm run setup -- plan</code>	Tests/builds RC6 and creates Cloudflare/AWS plans for approval	No production apply
<code>npm run deploy:apply</code>	Applies the approved plan, migrates, creates the school, then starts Edutex	Yes

What “Terminal” means in this manual

The Terminal is a text panel inside Visual Studio Code - not an AWS page and not a Cloudflare page. To open it at any time:

1. Look at the very top of the Visual Studio Code window.
2. Click the menu named **Terminal**.
3. Click **New Terminal**.
4. Look at the bottom of the Visual Studio Code window. A panel with a blinking cursor appears.
5. Click once next to the blinking cursor. That is where commands in grey boxes are typed.
6. Type or paste **one complete command**, then press the keyboard **Enter/Return** key once.
7. Never type the decorative \$ used by some other manuals; this manual does not show one.

Opening files and copying commands

If a code PATH command is unavailable, choose **File > Open File** in VS Code and select that same file in Finder/Files. On macOS, open -a "Visual Studio Code" PATH is another option. A missing optional code shortcut is not an AWS connection failure. Do not edit evidence just to open it.

Commands target Bash, macOS zsh or WSL Bash. Native PowerShell has different variable/continuation syntax. Use the specified shell for this walkthrough; native Windows and real devices still need acceptance testing. Read the command in the Markdown file if a PDF viewer copies visual wrapping. A backslash at the physical end of a command line is intentional. Never copy ↵ or add a \$ prompt.

Stop rules

Stop immediately - do not “try something” - if:

- anyone asks you to paste a password, API token, Tunnel token, private key, recovery code or AWS access key into rc6.json, source code, a ticket, chat, screenshot or ordinary text file;
- a command says failed, error, NOT ACCEPTED, access denied, wrong account, invalid, destroy, or exits without the exact success line shown in its step;
- the AWS account ID, region, school hostname or change ID is not exactly the approved value;
- a plan shows a public AWS load balancer/IP, public database access, an unexpected deletion, a second school/hostname, or weaker WAF/MFA/RLS/TLS/IAM controls;
- source/configuration/plan bytes change after approval;
- the current time is outside the approved maintenance window; or
- migration/bootstrap does not report container exit code zero.

Call the named Cloud/Security or Release owner. Preserve the terminal output and work folder. Do not delete evidence, open network access, disable a security check or manually start another ECS task.

Parts list: collect these before Step 1

Do not start assembly with a missing part.

Assurance boundary: The inherited control documents provide a baseline mapping of technical controls and evidence to OWASP ASVS/Top 10 and supports ISO/IEC 27001 and ISO 9001 management systems. Source alone is not “100% compliant” or certified; approval also requires live controls, retained evidence, audit, management review, independent penetration testing and any claimed accredited certification.

People

Label	Person you need	What that person must provide/approve
P1	Release Manager	RC6 ZIP/checksum, release approval and exact change ID/window
P2	AWS Cloud Owner	Dedicated account, SSO role, CDK bootstrap, state bucket/KMS, SES and permissions
P3	Cloudflare/Edge Owner	Zone, Tunnel, plan entitlement, restricted temporary API token and edge approval
P4	Security Approver	Reviews plan, IAM/network/WAF, stop rules and evidence
P5	School Data/Identity Owner	School details, initial admin, login methods, directory claims/roles and acceptance
P6	Deployment Operator	Follows this manual on the managed workstation
P7	Independent Tester	Tests the deployed target and reports vulnerabilities independently

P2/P3/P4 are skilled roles even though this manual uses plain language. “Easy to follow” does not mean an unapproved person should receive production administrator access.

Accounts and cloud parts

- Dedicated evaluation AWS account ID (12 digits); an existing-school rehearsal must use isolated resources.
- Approved AWS region, such as ap-southeast-2.

- IAM Identity Center start URL, Identity Center region, account permission-set/role and approved CLI profile name.
- Stable modern CDK bootstrap stack named `CDKToolkit` in that account/region.
- Customer-managed symmetric KMS key for Terraform state; key enabled and automatic rotation on.
- General-purpose S3 state bucket in the same region, versioning on, `BucketOwnerEnforced`, all four public-access blocks on, bucket-wide TLS-only deny policy, default SSE-KMS using that exact key and S3 Bucket Key on.
- Verified Amazon SES domain/email identity in the same region/account, an approved From address, and the configuration-set name if one is used.
- Cloudflare account ID, DNS zone ID, school zone and plan with the WAF/rate features in RC6.
- Remotely managed Cloudflare Tunnel name/UUID and its token stored as `AWSCURRENT` in AWS Secrets Manager.
- A short-lived, resource-scoped Cloudflare API token available from the approved password manager only for plan/apply.

School and approval parts

- Permanent lower-case school slug, for example `northview-college`.
- Exact school legal/display name and exact HTTPS hostname (without `https://` or `/`).
- First campus name; academic year label/start/end; IANA time zone; two-letter country code.
- Named initial administrator's individual email and full name.
- Approved whole-site IP CIDRs/countries and administration IP CIDRs - or a documented decision that a list is intentionally empty.
- Release Manager name, Security Approver name, approved change ID and window start/end in ISO date format with numeric UTC offset.

Workstation

Use one organisation-managed, encrypted, patched workstation with EDR, screen lock and no unapproved browser extensions. It must already have:

- Visual Studio Code;
- Bash terminal (macOS/Linux, or Ubuntu 24.04 under WSL 2 on Windows);
- Node.js 24 or later and npm 11 or later;
- AWS CLI v2;
- Terraform 1.10 or later;
- Docker Engine/Desktop 24 or later with buildx; and
- `unzip`, `shasum` OR `sha256sum`.

If a tool is missing, stop and ask workstation support to install it from the official vendor package. Do not copy an installer/script from a forum, file-sharing site or random search result.

Part A - prepare the cloud parts (Cloud/Edge owners)

The Deployment Operator may observe these steps and copy **identifiers**, but P2/P3 must make the security decisions. If the organisation already has an approved equivalent, inspect it instead of creating a duplicate.

Step 1 - confirm the dedicated AWS account and region

Where you are: a web browser on the managed workstation.

1. Open a new browser tab.
2. Go to <https://console.aws.amazon.com/>.
3. Sign in through the organisation's AWS access portal with MFA. Do not sign in as the AWS root user.
4. In the AWS console, look at the top-right corner. Click the current **Region** name.
5. Click the approved region. All AWS resource steps below stay in this region.
6. Click the account/user menu at the top-right and record the displayed 12-digit **Account ID** in the approved change record. An account ID is an identifier, not a password.

Expected result: the top bar shows the approved role/account and region.

Stop if: this is a development/test/shared account, the account ID differs, or you used root/static credentials.

Step 2 - inspect or create the Terraform-state KMS key

Where you are: AWS Console in the approved account/region.

1. Click the search box at the top of AWS Console.
2. Type Key Management Service, then click **Key Management Service**.
3. In the left menu, click **Customer managed keys**.
4. If the approved state key already exists, click its alias and continue at action 10.
5. Otherwise click **Create key**.
6. Select **Symmetric**, then **Encrypt and decrypt**. Keep key material origin **KMS** and choose the organisation-approved regional/multi-region setting. Click **Next**.
7. Enter an alias that identifies purpose/environment, for example alias/edutex-production-terraform-state. Do not put a school secret in the description.
8. Select only the approved key administrators and usage roles. Apply the organisation's reviewed key policy/permissions boundary; do not grant everyone, wildcard principals or public access.
9. Review the account ID, principals and policy, then click **Finish**.
10. On the key detail page, confirm **Key state** is Enabled, **Key spec** is SYMMETRIC_DEFAULT, and origin is AWS_KMS.
11. Open the **Key rotation** or **Key material and rotations** tab.

12. In **Automatic key rotation**, click **Edit**, select **Enable**, keep the approved period, then click **Save**.
13. Return to the key detail/overview page and copy the full **ARN** beginning `arn:aws:kms:` into the approved non-secret change record.

Expected result: enabled customer-managed key, automatic rotation enabled, ARN account/region matching Step 1. AWS's current console rotation procedure is documented at [Official reference](#).

Stop if: the key is AWS-managed, disabled, pending deletion, asymmetric/imported, in another account/region, has rotation off, or its policy is not approved.

Step 3 - inspect or create the encrypted Terraform-state S3 bucket

Where you are: AWS Console, same account/region.

1. Use the top search box, type `s3`, then click **S3**.
2. In the left menu, click **General purpose buckets** (or **Buckets** if that is the label shown).
3. If an approved dedicated state bucket exists, click its name and continue at action 10.
4. Otherwise click **Create bucket**.
5. Choose **General purpose**. Enter a globally unique lower-case name approved by P2, for example `edutex-production-terraform-state-<account-id>` with the real account ID in place of the words.
6. Choose the same AWS Region as Step 1.
7. Under **Object Ownership**, select **ACLs disabled (recommended)** / **Bucket owner enforced**.
8. Under **Block Public Access settings**, tick **Block all public access** and leave all four individual boxes selected.
9. Under **Bucket Versioning**, select **Enable**.
10. Under **Default encryption**, choose **Server-side encryption with AWS Key Management Service keys (SSE-KMS)**.
11. Choose **Enter AWS KMS key ARN** and paste the exact customer-key ARN from Step 2. Do not choose `aws/s3`.
12. Set **Bucket Key** to **Enable**.
13. Add only approved non-secret tags. Click **Create bucket**.
14. Click the bucket name, then click **Properties**. Confirm **Bucket Versioning: Enabled** and default encryption names the exact KMS key with Bucket Key enabled.
15. Click **Permissions**. Confirm **Object Ownership: Bucket owner enforced** and all four **Block public access** values are on.
16. Still on **Permissions**, scroll to **Bucket policy** and click **Edit**. Paste the exact block below into the editor. Before saving, replace both occurrences of `REPLACE_WITH_YOUR_EXACT_BUCKET_NAME` with the bucket name shown at the top of this AWS page. Remove no quotes, commas or braces.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "DenyInsecureTransport",
      "Effect": "Deny",
      "Principal": "*",
      "Action": "s3:*",
      "Resource": [
        "arn:aws:s3::REPLACE_WITH_YOUR_EXACT_BUCKET_NAME",
        "arn:aws:s3::REPLACE_WITH_YOUR_EXACT_BUCKET_NAME/*"
      ],
      "Condition": {
        "Bool": {
          "aws:SecureTransport": "false"
        }
      }
    }
  ]
}
```

17. Ask P4 to compare the two resource names with the bucket name and confirm the statement is a **Deny**, the principal is exactly `"*"`, the action is `s3:*`, and the condition is exactly `aws:SecureTransport = false`. This statement does not make the bucket public; it denies every non-TLS request. Click **Save changes** only after that comparison.

18. Reopen **Bucket policy**, confirm the deny covers the bucket and `/*`, then copy only the bucket **name** into the approved change record.

Expected result: the bucket has encryption, key, bucket-key, versioning, ownership, public-block and TLS-only safeguards. The RC6 check re-reads them through AWS APIs. AWS's current console instructions are at [Official reference](#) and [Official reference](#).

Stop if: any control differs, the key ARN is wrong, or existing objects/state belong to another school/environment without an approved separate key prefix.

Step 4 - confirm the CDK bootstrap stack

Where you are: AWS Console.

1. Use the search box, type `CloudFormation`, then click **CloudFormation**.
2. In the left menu click **Stacks**.
3. Search for the exact stack name `CDKToolkit`.
4. Click it. Confirm the status is `CREATE_COMPLETE`, `UPDATE_COMPLETE` or `UPDATE_ROLLBACK_COMPLETE` and that P2 has reviewed its execution policy/trust/asset encryption.
5. If it does not exist, stop. P2 must bootstrap the account/region using the organisation's approved modern CDK bootstrap pipeline, permissions boundaries and execution policies. The beginner operator must not improvise an `AdministratorAccess` bootstrap.

Expected result: one stable `CDKToolkit` stack in the exact account/region.

Stop if: absent, in progress/failed, unreviewed, or a custom bootstrap name/qualifier is expected; RC6 currently checks the default stable stack name.

Step 5 - confirm Amazon SES is ready

Where you are: AWS Console.

1. Search for Amazon Simple Email Service, then click **Amazon Simple Email Service**.
2. Confirm the top-right region is still the approved region.
3. In the left menu under **Configuration**, click **Verified identities**.
4. Find the approved school domain or From email. Click it.
5. Confirm **Verification status** is Verified/Successful, and DKIM/domain DNS checks are green.
6. Copy the identity **ARN** beginning `arn:aws:ses:` into the approved change record.
7. Record the exact From address, for example `no-reply@school-domain.edu`.
8. In SES, open **Account dashboard** and confirm the account has production sending access if real invitations will be sent; record the sending decision/limits.
9. Under **Configuration sets**, confirm the approved configuration set exists, or record that the organisation deliberately uses none.

Expected result: same account/region, identity successful, approved From address/configuration. The current AWS identity-status location is documented at [Official reference](#).

Stop if: status is pending/failed, SES is in the wrong region/account, sending is sandboxed when production delivery is required, or the From address is not covered.

Step 6 - create the Cloudflare Tunnel shell (do not publish a route manually)

Current Cloudflare navigation is **Networks > Connectors > Cloudflare Tunnels** (older accounts may show **Networks > Tunnels**). Select a remotely managed cloudflared tunnel. In this architecture the connector runs inside the AWS deployment. A new shell can therefore show pending/disconnected before that task starts. Do not install a production connector on your laptop just to change that status. Copy only the needed token securely into Secrets Manager in Step 7; do not run the displayed install command on your computer. See the [official tunnel procedure](#).

Where you are: Cloudflare dashboard in a browser, signed in with MFA.

1. Open `https://dash.cloudflare.com/` and select the approved Cloudflare account.
2. In the left navigation, click **Networking**, then **Tunnels**.
3. Click **Create a tunnel**.
4. Choose **Cloudflared** if asked for the connector type.
5. Enter an unambiguous name such as `edutex-production-northview-college` using the real school slug. Click **Create Tunnel**.
6. Do **not** install cloudflared on the workstation and do not manually add a public route. RC6 configures the route and the AWS Fargate sidecar runs the connector.
7. On the Tunnel detail page, copy the **Tunnel ID** (UUID such as `12345678-abcd-4abc-8abc-123456789abc`) into the approved change record.

8. Also record the exact Tunnel name/account, but not its token.

Expected result: one named, remotely managed Tunnel; it can be inactive before AWS exists. Cloudflare's current dashboard path is documented at [Official reference](#).

Stop if: a duplicate/production route exists unexpectedly, the account is wrong, or someone proposes exposing an AWS IP/load balancer.

Step 7 - move the Tunnel token directly into AWS Secrets Manager

Where you are: two browser tabs - Cloudflare Tunnel and AWS Secrets Manager. P2/P3 perform this together. The token must not be typed in the VS Code Terminal.

1. In Cloudflare, open **Networking → Tunnels**, click the Tunnel, open **Overview**, then click **Add a replica**.
2. The page shows an install command containing `--token eyJ...`. Treat the entire `eyJ...` value as a password. Copy only that token using the approved secure clipboard/password-manager process.
3. Immediately switch to the AWS tab. Go to <https://console.aws.amazon.com/secretsmanager/>, in the same account/region as Step 1.
4. Click **Store a new secret**.
5. Select **Other type of secret**.
6. Select the **Plaintext** tab. Paste only the Tunnel token. Do not add quotes, `--token`, the Docker command or explanatory text.
7. Choose the approved encryption key. If using a customer key, confirm the future ECS execution role is explicitly permitted to decrypt it; otherwise use the approved Secrets Manager key decision.
8. Click **Next**. For **Secret name**, enter `edutex/production/cloudflare/tunnel-token` unless the approved naming standard specifies a stricter name compatible with RC6.
9. Add a non-secret description and approved tags. Do not place token fragments in tags.
10. Click **Next**. Configure the approved rotation process; a Tunnel-token rotation normally requires coordination with the running connector.
11. Click **Next**, review account/region/name, then click **Store**.
12. Open the new secret's detail page. Copy only its **Secret ARN** into the approved change record.
13. Do not click **Retrieve secret value**. Clear the secure clipboard and close the Add-replica screen.

Expected result: the secret detail page exists; its ARN matches the account/region; current version has stage `AWSCURRENT`. AWS's console flow is documented at [Official reference](#).

Stop if: the token appeared in a terminal, normal file, screenshot, chat, ticket, browser history field or logs. Revoke/rotate it and treat the exposure under the incident process.

Step 8 - record Cloudflare account ID, zone ID and policy inputs

Where you are: Cloudflare dashboard.

1. Select the school's DNS zone/domain.
2. On the zone **Overview** page, find the 32-character **Zone ID** and copy it into the approved change record.
3. Find the 32-character **Account ID** and copy it too.
4. Confirm the exact intended hostname, for example `portal.northview.edu.au`. Do not include `https://`, a path or trailing slash.
5. P3 records approved whole-site IP CIDRs, country codes and administration IP CIDRs. A single address must include `/32` for IPv4 or `/128` for IPv6.
6. P3 confirms whether the purchased plan exposes Bot Management score fields. Record no unless this is explicitly confirmed.
7. Confirm the plan permits Cloudflare Managed WAF, OWASP managed WAF, custom rules and the rate limits in `infra/cloudflare/main.tf`. Do not plan to weaken RC6 to fit a smaller plan.

Expected result: two 32-character IDs, one Tunnel UUID and approved policy lists.

Stop if: zone/account/tunnel belong to different customers, or plan entitlements are unknown.

Step 9 - create the short-lived Cloudflare plan/apply API token

Where you are: Cloudflare dashboard. Do this near the approved deployment window.

1. For a user token, click the profile icon → **My Profile** → **API Tokens**. For an organisation-approved account token, use **Manage Account** → **API Tokens**.
2. Click **Create Token**, then **Create Custom Token**.
3. Name it with school/change/expiry, for example `Edutex northview CHG-8451 temporary deploy`.
4. Add only the permissions required by the reviewed Terraform resources: exact account Tunnel edit, exact zone DNS edit and exact zone WAF/Rulesets/rate-limit edit/read permissions exposed by the current Cloudflare token builder.
5. Under resource scope, include only the approved account and school zone - not all accounts/zones.
6. Add the shortest practical TTL covering plan review/apply. If the organisation has fixed egress IPs, restrict client source IP too.
7. Click **Continue to summary**. P3/P4 compare permissions/resources/TTL, then click **Create Token**.
8. Cloudflare shows the token once. Copy it directly into the approved enterprise password manager entry. Do not place it in this guide, change record, JSON, tfvars, source or terminal history.
9. Close the one-time token page.

Expected result: one short-lived least-privilege token in the password manager. Current Cloudflare steps are at [Official reference](#).

Stop if: it is a Global API Key, has all-account/all-zone resources, excessive TTL, or cannot be stored by the approved secret process.

Part B - place and verify the RC6 package

The example school slug in command boxes is `northview-college`. Before typing a command, replace that exact example with the real permanent slug. Do not replace other punctuation, quotes or spaces.

Step 10 - create separate private working folders

Where you are: Visual Studio Code, **Terminal** > **New Terminal**, using Bash, macOS zsh or WSL Bash. The following examples use `northview-college`; substitute the approved school slug consistently.

```
umask 077
export EDUTEX_BASE="$HOME/Edutex-Deployments"
export EDUTEX_SCHOOL="$EDUTEX_BASE/schools/northview-college"
export EDUTEX_CONFIG="$EDUTEX_SCHOOL/rc6.json"
export EDUTEX_WORK="$EDUTEX_SCHOOL/work-rc6"
mkdir -p "$EDUTEX_BASE/download" "$EDUTEX_BASE/release/rc6" "$EDUTEX_WORK"
chmod 700 "$EDUTEX_BASE" "$EDUTEX_BASE/download" "$EDUTEX_BASE/release/rc6"
chmod 700 "$EDUTEX_SCHOOL" "$EDUTEX_WORK"
```

These variables contain paths, not passwords. Keep this Terminal open. A new Terminal needs these exports again, but not another extraction. The RC6 release and work folders are separate from RC5. Use `ls -ld "$EDUTEX_SCHOOL" "$EDUTEX_WORK"` to inspect their owner-only permissions. Do not repurpose a synchronised/shared folder for credentials or deployment evidence.

Step 11 - put the ZIP and checksum into Download

Where you are: the workstation's file manager - Finder on macOS or Files inside the Linux/WSL environment according to IT policy.

1. Download these two separate release files from the approved handover location:
`Edutex-production-1.0.0-rc.6.zip` and `Edutex-production-1.0.0-rc.6.zip.sha256`.
2. Do not open the ZIP yet.
3. Move both files into your private `Edutex-Deployments/download` folder.
4. Return to the VS Code Terminal and type:

```
cd "$HOME/Edutex-Deployments/download"
ls -l Edutex-production-1.0.0-rc.6.zip Edutex-production-1.0.0-rc.6.zip.sha256
```

Expected result: exactly two filenames and non-zero ZIP size.

Stop if: a filename contains (1), the checksum arrived inside the same ZIP only, or either file differs from the handed-over release.

Step 12 - verify the ZIP fingerprint

Where you are: Terminal in the private download folder. A matching hash detects changed bytes; obtain both the archive and its expected fingerprint through the approved release handover.

On macOS:

```
shasum -a 256 -c Edutex-production-1.0.0-rc.6.zip.sha256
```

On Linux or WSL:

```
sha256sum --check Edutex-production-1.0.0-rc.6.zip.sha256
```

Expected result: the exact ZIP filename followed by `OK`. On a mismatch, stop and retain both files for investigation. Do not substitute a hash calculated from an untrusted ZIP as its approval.

Step 13 - test and extract into the new RC6 directory

Where you are: same Terminal in the download folder.

```
unzip -t Edutex-production-1.0.0-rc.6.zip
unzip -q Edutex-production-1.0.0-rc.6.zip -d "$EDUTEX_BASE/release/rc6"
```

Run the second line only after the archive test reports no errors. If extraction asks to overwrite, stop: you are not in an empty release directory. Do not overwrite the RC5 installation.

```
cd "$EDUTEX_BASE/release/rc6/Edutex-production"
ls package.json README.md
```

Expected result: both files print. The project root is the folder containing `package.json`.

Step 14 - open the correct folder in Visual Studio Code

Where you are: Visual Studio Code.

1. At the top, click **File** → **Open Folder...**
2. Browse to `Edutex-Deployments` → `release` → `rc6` → `Edutex-production`.
3. Select the `Edutex-production` folder itself, then click **Open**.
4. If Visual Studio Code asks whether you trust the authors, compare the verified checksum and approved handover, then choose **Yes, I trust the authors** only if both passed.
5. In the left **Explorer**, confirm you see `apps`, `docs`, `infra`, `packages`, `scripts`, `package.json` and `README.md` at the top level.
6. Click **Terminal** → **New Terminal**.
7. Type:

```
pwd
```

Expected result: the path ends exactly `/Edutex-Deployments/release/rc6/Edutex-production`.

Stop if: it ends in `download`, `schools`, `apps`, `infra`, a previous RC, or the ZIP itself.

Step 15 - check the computer and install the locked dependencies

Where you are: Terminal at the RC6 project root.

```
node -p "require('./package.json').version"
npm run setup -- check
```

The version must be `1.0.0-rc.6`. The computer check reports missing tools and whether Docker is running. Install missing tools using the vendor's supported installer: Node 24+, npm 11+, AWS CLI v2, Terraform 1.10 to below 2.0, Docker 24+ with Buildx, and VS Code. Reopen the Terminal after an installation and restore the path variables from Step 10. On macOS, launch

Docker from Applications and wait until its engine is running. Do not create or change Docker socket permissions manually.

```
npm run setup -- install
npm run quality
```

`install` runs locked installation with general install scripts disabled, then the required Sharp rebuild. `quality` checks documented source, types, tests, lint, formatting, builds and artifacts. Do not continue while it reports an error. The precise file/test counts are in the release report; a printed count alone is not the success signal.

Step 15A from the old guide is retired. The RC6 source and compiled tools already resolve the repository root correctly. Applying the old patch again would change the reviewed source.

Part C - connect the Terminal to the correct AWS account

Step 16 - open the AWS CLI SSO setup wizard

First run `aws --version`. If the shell says `command not found: aws`, install AWS CLI v2 and reopen the Terminal before proceeding. `aws configure list-profiles` being empty means no local named profile exists yet; an AWS web-console login does not automatically create one.

The start URL comes from IAM Identity Center or the AWS access portal, not from the ordinary AWS console home page. The Identity Center region can differ from the Edutex workload region. If the portal stays on an access-request page, P2 must verify the user's account/permission-set assignment. The official [AWS SSO setup procedure](#) explains the wizard and named profiles. Never paste AWS access keys from an unrelated login method.

Where you are: VS Code Terminal. P2 supplies the SSO Start URL, Identity Center region, 12-digit account and exact permission-set/role name.

1. Type:

```
aws configure sso
```

2. At `SSO session name`, type a descriptive non-secret name such as `edutex-production` and press Enter.

3. At `SSO start URL`, paste the P2-approved `https://...awsapps.com/start` URL and press Enter.

4. At `SSO region`, type the region that hosts **IAM Identity Center**. This may differ from the Edutex workload region; use P2's value.

5. At `SSO registration scopes`, press Enter to accept `sso:account:access` unless P2 specifies an approved alternative.

6. The browser opens. Confirm the organisation, sign in and complete MFA. Approve only the expected AWS CLI/botocore access request, then return to the Terminal.

7. Select/type the exact 12-digit production account.

8. Select/type the exact approved deployment permission set/role.

9. At CLI default `client Region`, type the Edutex workload region from Step 1.

10. At CLI default `output format`, type `json`.

11. At CLI profile name, type the approved profile name, for example `edutex-production-deployer`. Record this exact spelling; RC6 will ask for it.

Expected result: AWS CLI says the profile was configured and shows an example command. Current AWS instructions are at [Official reference](#).

Stop if: a prompt asks for AWS Access Key ID/Secret Access Key. That is not the SSO wizard.

Step 17 - sign in and compare the account ID

Where you are: same Terminal.

1. Replace the sample profile name if yours differs, then type:

```
aws sso login --profile edutex-production-deployer
```

2. Complete the browser MFA/authorization and return to the Terminal.

3. Type:

```
aws sts get-caller-identity --profile edutex-production-deployer --output json
```

4. Compare the "Account" value character-for-character with Step 1.
5. Confirm the "Arn" names the approved role/session, not root or an unexpected user.

Expected result: exact account/role. Do not screenshot or paste the response into public chat.

Stop if: any mismatch or `AccessDenied`; ask P2 to fix the SSO assignment/profile.

Step 17A - P2 prepares a missing CDKToolkit stack

Skip only if Step 4 found a reviewed, stable stack in the exact account and region. P2 is the AWS cloud owner; P4 reviews the execution policy and its maximum permissions boundary.

1. Open AWS **IAM > Policies** and locate the approved customer-managed CloudFormation execution policy and approved permissions-boundary policy. Record the execution policy ARN and boundary name. An execution policy grants permitted actions; a boundary limits the maximum and grants nothing alone.
2. If either is absent, P2/P4 must prepare and review the organisation-specific JSON first. In IAM, choose **Policies > Create policy > JSON**, paste that approved policy, review validation warnings, then give it the approved name. Retain its version and review evidence. The uploaded archive did not contain the companion policy claimed by the old PDF, so there is no valid bundled policy hash to copy. Do not substitute `AdministratorAccess` or remove the boundary to clear a deployment error.
3. At the RC6 project root, set these non-secret values using the approved account/profile/region:

```
export EDUTEX_PROFILE='YOUR_APPROVED_PROFILE'
export EDUTEX_ACCOUNT='YOUR_12_DIGIT_ACCOUNT_ID'
export EDUTEX_REGION='YOUR_APPROVED_REGION'
export EDUTEX_CDK_EXECUTION_POLICY='YOUR_APPROVED_POLICY_ARN'
export EDUTEX_CDK_BOUNDARY='YOUR_APPROVED_BOUNDARY_NAME'
npm run build --workspace @edutex/infra-aws
```


4. In VS Code, open `infra/aws/cdk.context.json`. Preserve existing keys. Have P2/P4 set the `@aws-cdk/core:permissionsBoundary` object with name equal to the approved boundary name, then save. Do this before creating a deployment plan; it changes source hashes. The boundary must cover the current RC6 service roles, including any approved alert-delivery permissions.
5. After the bootstrap change is reviewed, P2 runs this entire Bash/zsh command block. The final backslash on each continued line is part of the command; it joins the next line.

```
npm exec --workspace @edutex/infra-aws -- cdk bootstrap \
  "aws://$EDUTEX_ACCOUNT/$EDUTEX_REGION" \
  --profile "$EDUTEX_PROFILE" \
  --cloudformation-execution-policies "$EDUTEX_CDK_EXECUTION_POLICY" \
  --custom-permissions-boundary "$EDUTEX_CDK_BOUNDARY" \
  --bootstrap-customer-key \
  --public-access-block-configuration \
  --termination-protection \
  --no-version-reporting
```

6. In **CloudFormation > Stacks**, select `CDKToolkit` in the same region. Wait for `CREATE_COMPLETE` or stable `UPDATE_COMPLETE`; inspect Events if it fails. Verify termination protection, trusted accounts, policies and asset encryption. Do not add `--trust`, a different qualifier or `--force` to work around an error. The bootstrap key and resources incur AWS charges.

AWS documents the bootstrap options and its broad default execution policy in the [CDK bootstrap reference](#). A missing approved policy is a cloud prerequisite, not a reason to silently widen access.

Part D - answer the RC6 setup questions

Step 18 - understand exactly where the answers go

You fill the deployment answers in **the same VS Code Terminal panel** used in Steps 15-17.

- Do not open AWS/Cloudflare and type answers into a “worksheet”.
- Do not create a JSON file.
- Do not paste all answers at once.
- RC6 prints one question, you type one answer, then press Enter.
- Some prompts show a default in square brackets. Pressing Enter without typing selects that default.
- NOT ACCEPTED means the answer format is wrong. Read the message, obtain/correct the approved value and answer that same question again.
- `Ctrl+C` cancels safely before deployment. You can rerun the interview later.

Step 19 - choose new-school configuration or the RC5 upgrade path

Where you are: Terminal at the RC6 root, with the Step 10 variables restored if necessary.

For a new, isolated school trial:

```
npm run setup -- configure --output "$EDUTEX_CONFIG"
```


Answer one displayed question, then press Enter. The interview creates the JSON; there is no separate worksheet or web form. It must never ask for a password, API token or Tunnel token value.

For an existing RC5 school, use the upgrade interview instead:

```
npm run setup -- upgrade \
  --from "$EDUTEX_SCHOOL/production.json" \
  --output "$EDUTEX_CONFIG"
```

Use the actual old configuration path if it differs. The output must be new; do not overwrite the old file. This copies approved school/cloud identifiers, marks the purpose `existing-school-upgrade`, and asks for a new change ID, named reviewers and maintenance dates. It does not deploy anything. Step 20's full interview applies only to a new school. A copied live configuration still points to live resources: never use it as an isolated test simply by renaming it. P2 must arrange the restored rehearsal and its isolated resources first. Actual live use remains blocked by RC6's release gaps.

Before any future live upgrade, rehearse a populated restore, preserve tenant/identity/key IDs, resolve duplicate person-account links, verify guardian rights and fee allocations, and keep the RC5 archive/receipt. The new workflow skips another school bootstrap. Forward database migrations are not undone by reinstalling the old ZIP. Follow technical guide section 7 for the full review.

Step 20 - answer every interview prompt in order

All typing happens at the blinking Terminal cursor. Samples show format only; use approved real values. Never use the sample/example values in production.

Terminal question	Where the real answer comes from	Format/example	Stop if
AWS region	AWS top-right region / P2	ap-southeast-2	It differs from KMS/S3/SES
AWS account ID	Step 1 / STS result	exactly 12 digits	Shared/wrong account
School slug	P5/change record	northview-college	Temporary, spaces/capitals
Edutex hostname	P3/P5 DNS approval	portal.northview.edu.au	Contains https://, /, capitals
SES configuration set	Step 5	edutex-transactional, or Enter only for approved none	Does not exist
Approved change ID	P1's change system	CHG-2026-8451	Draft/unapproved
Release manager	Approved change	full person name	Self/unidentified

Terminal question	Where the real answer comes from	Format/example	Stop if
Security/cloud approver	Approved change	different full person name	Not authorised
Maintenance window start	Approved change	2026-09-12T20:00:00+10:00	No numeric offset
Maintenance window end	Approved change	later ISO time	At/before start
AWS CLI profile	Step 16	edutex-production-deployer	Not configured/tested
Cloudflare Tunnel token secret ARN	Step 7 AWS secret detail	begins arn:aws:secretsmanager:	You have token value, not ARN
Terraform state bucket	Step 3	bucket name only	Includes s3:// or wrong account
Terraform state KMS key ARN	Step 2	begins arn:aws:kms:	Alias/wrong key/account/region
Cloudflare account ID	Step 8	32 hexadecimal characters	Wrong customer
Cloudflare zone ID	Step 8	32 hexadecimal characters	Wrong domain
Cloudflare Tunnel ID	Step 6	UUID with hyphens	Token/name instead of UUID
Whole-site allowed IP ranges	P3 network decision	comma list such as 203.0.113.0/24 or Enter	Plain IP without prefix
Whole-site allowed countries	P3 decision	comma list AU,NZ, or Enter	Lower-case/not approved
Administration IP ranges	P3 decision	comma CIDRs; /32 for one IPv4	Empty without accepted risk
Enable Cloudflare Bot Management rule?	P3 plan confirmation	yes or default no	“yes” guessed
School legal/display name	P5 approved name	Northview College	Nickname/typo
First campus name	P5	Main Campus or approved name	Temporary placeholder

Terminal question	Where the real answer comes from	Format/example	Stop if
Academic year name	P5	2027 School Year	Wrong calendar
Academic year start	P5	2027-01-27	Not YYYY-MM-DD
Academic year end	P5	2027-12-17	Before start
School time zone	P5	Australia/Melbourne	Abbreviation such as AEST
School country code	P5	AU	Not two upper-case letters
Initial administrator email	P5 named person	individual school address	Shared inbox unless approved
Initial administrator name	P5	full display name	Unknown person
Verified SES identity ARN	Step 5	begins arn:aws:ses:	Wrong region/account/pending
Invitation From address	Step 5	plain email only	Name <email> form
Production application task count	Capacity approval	default 3, maximum 30	Less than 3/unapproved higher value
Alert email sender (or none)	Approved verified SES identity	none for the isolated trial	Do not use a live recipient/sender accidentally
Enable SMS alert dispatch? (yes/no)	Approved SNS setup	no for the isolated trial	Do not enable untested external delivery

Expected result: after the final answer, RC6 prints `CREATED:` followed by the exact `.../rc6.json` path and a `NEXT: check` command.

Stop if: the interview exits with a validation stack/message. Photographing the screen is not needed; copy the non-secret error text into the controlled incident/change record if authorised.

Step 21 - review the created non-secret file without editing it

Where you are: VS Code.

1. In the Terminal type:

```
code "$EDUTEX_CONFIG"
```

2. A new editor tab opens. Do not type in it.

3. P1/P2/P3/P5 compare every displayed identifier/name/date/list with the approved record.
4. Confirm there is no property/value containing an actual password, API token, Tunnel token, client secret, private key, recovery code or session token. The Secrets Manager **ARN** is expected and is not the secret value.
5. Close the editor tab using its × without saving.
6. In Terminal, verify permissions:

```
ls -l "$EDUTEX_CONFIG"
```

Expected result: Linux/WSL/macOS permission text begins -rw-----.

Stop if: any answer is wrong. Do not edit the JSON. Obtain approval, then rerun Step 19 with --replace appended and complete every prompt again; a replacement requires a new plan.

Part E - run the read-only check

Step 22 - run the read-only cloud checks

Where you are: the RC6 project Terminal. Docker is running and the named AWS SSO login is current.

```
npm run setup -- check-cloud --config "$EDUTEX_CONFIG" --work-dir "$EDUTEX_WORK"
```

The check verifies tool versions/Buildx, caller account, bootstrap readiness, Tunnel secret metadata, state bucket controls, KMS, SES and other configured prerequisites. It does not read the Tunnel token value. A successful result ends with CHECK PASSED for and the exact approved hostname. If the AWS token expired, repeat `aws sso login --profile YOUR_APPROVED_PROFILE` and rerun this check. A missing CDK stack goes back to Step 17A. Fix reported resources; do not disable the checks.

Step 23 - save the check result

Where you are: organisation's controlled change/evidence system.

1. Select/copy only the non-secret Terminal output from the start of `deploy:check` through CHECK PASSED.
2. Attach/save it to the approved change record using the organisation's confidential evidence classification.
3. Record operator, timestamp, RC6 version, exact hostname/account/region.
4. Do not attach AWS SSO cache files or secret values.

Expected result: P1/P4 can independently see that preflight passed before planning.

Part F - create and approve the production plan

Step 24 - enter the Cloudflare token without displaying it

Where you are: the same Bash or macOS zsh Terminal. The scoped token comes from P3's approved secret manager. Type the first line and press Enter, then type the second line and press Enter:

```
printf '%s' 'Paste the temporary Cloudflare token, then press Enter: '
IFS= read -r -s CLOUDFLARE_API_TOKEN
```

The second line now waits for the token. Paste the token once and press Enter; nothing should be shown. Only after that, run:

```
printf '\n'
export CLOUDFLARE_API_TOKEN
```

Do not paste these instructions as one block while the hidden prompt is waiting. Do not use the old Bash-only `read -p` form in zsh. Do not print the variable or enter it into the interview JSON. If exposed, clear the variable and have P3 revoke and replace it.

Step 25 - create the plan

Where you are: same Terminal, source unchanged, Docker running, AWS SSO current and the temporary Cloudflare token in memory.

```
npm run setup -- plan --config "$EDUTEX_CONFIG" --work-dir "$EDUTEX_WORK"
```

Wait for the command to finish. It runs quality/build/audit gates, validates Terraform, saves the Cloudflare plan, and creates the AWS assembly/diff. A final `PLAN READY` means a plan exists; it is not approval. Save the printed evidence paths and plan-record SHA-256 for the reviewers. If it fails, clear the Cloudflare token as in Step 26 and fix the named problem before replanning. The RC5 repository-root repair is already present; do not copy a patch into RC6 to bypass a failure.

Step 26 - remove the Cloudflare token from this Terminal

Where you are: same Terminal after `PLAN READY` or after a failed plan.

1. Type:

```
unset CLOUDFLARE_API_TOKEN
```

2. Let the original token expire/revoke it according to P3's decision if plan review will be long.

Expected result: command prints nothing. This does not erase every theoretical process/memory copy; it removes the variable from future child commands in this Terminal.

Step 27 - open the two human-readable plans

Where you are: VS Code Terminal.

1. Open the Cloudflare plan:

```
code "$EDUTEX_WORK/cloudflare-plan.txt"
```

2. Open the AWS diff:

code "\$EDUTEX_WORK/aws-cdk-diff.txt"

3. In the left Explorer or top tabs, switch between the two files. Do not edit/save them.
4. P3/P4 review the Cloudflare plan for exact proxied CNAME/Tunnel/hostname, Cloudflare and OWASP managed WAF, custom rules, health/scanner/method blocks, rate limits and exact IP/country/admin semantics.
5. P2/P4 review AWS diff/template/IAM for no public ALB/IP/inbound app rule, database only through exact security groups, private tasks, encryption, backups/retention, narrow secret/KMS grants, immutable Node/Cloudflared image digests and ApplicationDesiredCount default zero.
6. Everyone reviews all deletes/replacements. A desired, explained create is not the same as an unexplained destroy.

Expected result: two independent reviewers approve the exact plan or reject it with reasons.

Stop if: a reviewer has not inspected actual files, permissions/plan features are unavailable, or a control is weakened to avoid a provider-plan error.

Step 28 - record the exact approval binding

Where you are: controlled change system and `plan-record.json` open in VS Code.

1. Open:

code "\$EDUTEX_WORK/plan-record.json"

2. Record the release, change ID, hostname and every SHA-256 field exactly:
configurationSha256, sourceSha256, terraformPlanSha256, terraformProviderLockSha256, terraformPlanTextSha256, cloudFormationTemplateSha256, cloudFormationAssemblySha256 and cloudFormationDiffSha256. The provider-lock hash binds the exact Cloudflare provider build selected by terraform init; the assembly hash binds the CDK asset manifest/deployment assembly; the source hash deliberately excludes Terraform's generated `.terraform.lock.hcl`. Also copy the 64-character PLAN RECORD SHA-256 printed by the plan command into the change record.
3. P1 and P4 independently approve those values and the two plan files. Record names/timestamps and the approved maintenance/rollback decision.
4. Close files without saving.
5. From now until apply, do not run formatter, update dependencies, edit source/config, replace the plan or move pieces into the source tree.

Expected result: the change record names exact hashes and two approvals, not "latest plan".

Stop if: anything changes. Repeat plan and approval; never edit `plan-record.json`.

Part G - apply the approved plan

Step 29 - perform the final four checks at the start of the window

Where you are: VS Code Terminal and controlled change record.

1. Confirm wall clock is between the exact ISO start/end values in `rc6.json`.
2. Confirm incident/on-call, P1/P2/P3/P4 and rollback contacts are available.
3. Confirm the approved hostname/change ID/hashes still match Step 28.
4. Refresh AWS SSO:

```
aws sso login --profile edutex-production-deployer
```

5. Repeat Step 24 with a fresh approved Cloudflare token and keep it hidden.

Expected result: active short-lived AWS and Cloudflare credentials, exact approved window.

Stop if: outside window, an approver withdrew approval, plan/config/source changed or incident coverage is unavailable.

Step 30 - apply the exact approved plan

Where you are: same Terminal at the RC6 root, during the agreed window. Only a synthetic trial is eligible for this review build; a future live upgrade requires closure of the release blockers first.

Set the three non-secret values from the approved change record. Replace every placeholder before running either block. The hash is the approved **plan-record** SHA-256, not the ZIP checksum.

```
export EDUTEX_CHANGE_ID='APPROVED_CHANGE_ID'
export EDUTEX_HOSTNAME='APPROVED_EXACT_HOSTNAME'
export EDUTEX_PLAN_HASH='APPROVED_64_CHARACTER_PLAN_RECORD_SHA256'
```

Then paste the entire following block. There are no wrap arrows. Each line ending in `\` continues the same command; the final line has no backslash. Each option is followed by its value.

```
npm run deploy:apply -- \
  --config "$EDUTEX_CONFIG" \
  --work-dir "$EDUTEX_WORK" \
  --execute \
  --approval-id "$EDUTEX_CHANGE_ID" \
  --confirm-hostname "$EDUTEX_HOSTNAME" \
  --confirm-record-sha256 "$EDUTEX_PLAN_HASH"
```

Read the config/work paths, change ID, hostname and approved hash together with the reviewer before pressing Enter. A `dquote>` or continuation prompt after a incomplete paste means the shell is waiting; press Control-C and copy the complete block from the Markdown guide. Never type a decorative arrow. Preflight and hashes must pass again. On mismatch, stop and regenerate/review the changed plan.

Step 31 - watch the fixed apply sequence

Where you are: same Terminal. Do not run a second apply in another terminal.

The labels must appear in this order:

1. **Approved Cloudflare plan apply** - applies the exact binary plan.
2. **AWS private foundation deployment (application stopped)** - creates/updates infrastructure with application task count zero.
3. **migration ECS task start/completion/result** - private one-shot PostgreSQL migrations.
4. **school-bootstrap ECS task start/completion/result** - for a new school only, creates the tenant, school-isolated Cognito pool, confidential OAuth client, backend-only client secret in tenant-scoped AWS Secrets Manager, first administrator and relational defaults.
5. **AWS application activation** - changes desired count to the approved value (at least three).
6. **Edutex service stabilization** - waits for ECS service stability.
7. **DEPLOYMENT COMPLETE: <exact hostname>** - writes the receipt.

For existing-school-upgrade, bootstrap is skipped and the existing tenant, identity pool and keys are retained. An upgrade has a planned outage while tasks are at zero.

Expected result: exact completion line, no failed container, no public-origin workaround.

Stop if: any stage fails. Do not infer the application state from a failed terminal command; check the recorded ECS progress. Preserve the screen and follow Part H; do not manually create a school or rerun ECS.

Step 32 - remove temporary credentials and inspect the receipt

Where you are: Terminal after completion.

1. Remove the Cloudflare variable:

```
unset CLOUDFLARE_API_TOKEN
```

2. Open the receipt:

```
code "$EDUTEX_WORK/deployment-receipt.json"
```

3. Compare release/change/hostname/hashes and confirm migration task ARN, new-school bootstrap ARN where applicable, stack ID, cluster and service names are present. Do not edit.
4. Save the entire owner-only work folder to the approved encrypted evidence repository according to retention policy - not email/chat.
5. On this dedicated workstation, end cached AWS SSO sessions when operational follow-up is done:

```
aws sso logout
```

6. P3 revokes the temporary Cloudflare token or confirms automatic expiry.

Expected result: one immutable evidence set and no longer-needed active deployment token.

Part H - if the Terminal closes or a stage fails

Step 33 - do not start over

If power/network/Terminal fails, RC6 has already recorded completed stages and one-shot task ARNs.

1. Do not delete work.
2. Do not delete/recreate the CloudFormation stack/Tunnel/state.
3. Do not run `aws ecs run-task` manually.
4. Do not edit `deployment-progress.json`.
5. Reopen the exact verified RC6 folder in Visual Studio Code.
6. Open a new Terminal and sign into the same approved AWS profile.

Step 34 - display local progress

```
npm run deploy:status -- --config "$EDUTEX_CONFIG" --work-dir "$EDUTEX_WORK"
```

Expected result: it lists `plan-record.json`, `deployment-progress.json` and receipt as present or not present, then names completed stages such as `cloudflare`, `foundation`, `migration`.

Stop if: progress says it belongs to different inputs or files are malformed/missing after a stage was known to complete. Preserve evidence and escalate.

Step 35 - resume only after correction and renewed approval

Where you are: first, the organisation's AWS log viewer/change record with P2/P4; only return to the VS Code Terminal after they approve the exact recovery.

1. Read the final red error line in the Terminal. Copy the text to the approved confidential incident/change record. Do not include tokens, passwords, cookies or secret values.
2. P2 opens **AWS Console → Elastic Container Service → Clusters**, opens the cluster named in `aws-stack-outputs.json`, chooses **Tasks**, selects the exact failed task ARN recorded in `deployment-progress.json`, and reads that task's **Logs** tab/linked CloudWatch log stream.
3. P2/P3/P4 identify and fix the cause without opening public access, disabling RLS/WAF/MFA/TLS or editing a plan/progress file.
4. If source, configuration or either plan must change, do **not** resume. Repeat Steps 19-28 with a new change/plan, then obtain approval for those new bytes.
5. If the failure happened before a migration/bootstrap task was started - or the existing recorded task is still running - do not request a retry. Wait for the exact task result. After a temporary external fault is corrected, obtain continuation approval and rerun the ordinary Step 30 command.
6. If the error explicitly says `migration failed:` or `school-bootstrap failed:`, locate the full ARN printed after `--confirm-failed-task-arn`. Two operators compare that ARN, character for character, with the matching `migrationTaskArn` or `bootstrapTaskArn` in `deployment-progress.json`.
7. P4 records approval for **one replacement attempt of that exact stopped task ARN**. Do not use an ARN from the AWS list, memory, a different school or an older change.

8. Return to the VS Code Terminal. Sign into the same approved AWS profile and perform Step 24 again with a fresh hidden Cloudflare token.
9. Start with the exact Step 30 apply command. If the migration task failed, append these two items to the end, replacing the sample ARN by the exact ARN from the error/progress file:

```
--retry-failed-task migration \  
--confirm-failed-task-arn arn:aws:ecs:REGION:ACCOUNT_ID:task/CLUSTER/FAILED_TASK_ID
```

10. If the school-bootstrap task failed, append these two items instead:

```
--retry-failed-task bootstrap \  
--confirm-failed-task-arn arn:aws:ecs:REGION:ACCOUNT_ID:task/CLUSTER/FAILED_TASK_ID
```

11. Before Enter, the second operator confirms: original Step 30 path/change/hostname/hash values are unchanged; task kind matches the failed stage; ARN exactly matches progress; current time is inside the approved window. Press Enter once.
12. RC6 rechecks approved hashes, proves the exact recorded predecessor failed, records its ARN in `failedTaskArns`, creates only one replacement with a new idempotency token and resumes.
13. If the replacement also fails, stop. Its ARN is now the current task ARN. A further attempt requires a new diagnosis and new exact-ARN approval. RC6 hard-stops after ten recorded failures and requires a formal deployment incident.

Expected result: interrupted successful work resumes without duplication, or exactly one approved failed task is replaced; the process eventually prints `DEPLOYMENT COMPLETE`.

Stop if: ARN/kind does not match, the task actually succeeded/is still running, approved bytes changed, the window closed, or anyone proposes deleting/editing the progress file.

Part I - verify the assembled system before client data

Completion means infrastructure exists; it does not mean production acceptance.

Step 36 - verify Cloudflare Tunnel and DNS

Where you are: Cloudflare dashboard.

1. Go to **Networking → Tunnels** and click the named Tunnel.
2. Confirm status is **Healthy** and connectors correspond to expected Fargate tasks/locations.
3. Open the school zone → **DNS Records**. Find the exact hostname.
4. Confirm type `CNAME`, target ends `.cfargotunnel.com`, and proxy cloud is orange/**Proxied**.
5. Confirm no `A/AAAA/CNAME` record reveals an AWS load balancer/public IP.

Expected result: healthy outbound Tunnel and Cloudflare-only DNS target.

Stop if: degraded/down, unexpected connector, grey-cloud DNS or exposed origin.

Step 37 - verify WAF and network restrictions

Where you are: Cloudflare school zone.

1. Open **Security → WAF → Managed rules** (or current **Security Settings** view).
2. Confirm the Cloudflare Managed Ruleset and Cloudflare OWASP Core Ruleset execute only for the exact Edutex hostname; RC6 sets OWASP paranoia level 3 by disabling only level 4.
3. Open custom/security rules and confirm Edutex site geography/IP, admin network (when configured), method, scanner and private health-path rules are enabled.
4. Open rate limiting and confirm authentication and API rules are enabled.
5. From approved and denied test networks/countries, run documented synthetic requests. Confirm expected allow/block/challenge and inspect Security Events.
6. Test `/health/live` from the internet; Cloudflare should block it even though ECS internal health remains healthy.

Expected result: plan and live Cloudflare policy match; security events contain tests.

Stop if: a required ruleset is unavailable/disabled, exclusions appeared, or a deny case reaches the app. Current Cloudflare managed-rule navigation is documented at [Official reference](#).

Step 38 - perform the first administrator sign-in safely

Where you are: managed browser/device assigned to the named initial administrator.

1. The administrator opens the SES/Cognito invitation in their school mailbox. Support never asks them to send the temporary password.
2. In a browser, type `https://` followed by the exact Edutex hostname.
3. Choose **Username and password** if shown, enter their exact email and temporary password.
4. When prompted, create a unique organisation-policy password in their password manager. Do not reuse/share it.
5. Enrol TOTP: open the organisation-approved authenticator, scan the displayed QR, type the current code and securely store recovery information under policy.
6. When the portal loads, open the account/user menu and click **Register a passkey**.
7. Complete Cognito managed-login WebAuthn using an organisation-approved hardware/platform authenticator with user verification. Do not enrol a passkey on a shared/unmanaged device.
8. Sign out, then test both password+TOTP and passkey according to policy. Keep a permitted recovery path; do not remove TOTP merely because passkey works.

Expected result: independent device-bound session, required TOTP for password and verified passkey sign-in; logout invalidates the current session. The callback succeeds only while Cognito's live MFA/TOTP/passkey configuration still matches the policy in Edutex.

Stop if: email is wrong/unverified, temporary credential is shared, TOTP can be skipped for password, tokens appear in browser storage/URL, or sessions appear on another client.

Step 39 - choose login methods and modules in Edutex Administration

Where you are: authenticated Edutex portal as an authorised administrator.

1. In the portal navigation, open **Administration**.
2. In **Authentication** → **Allowed sign-in methods**, select only methods approved by P5/P4.
3. If **Username and password** is enabled, confirm **Authenticator policy** is locked to **Required for password sign-in**.
4. In **Sessions** → **Device security**, enter approved idle/absolute/step-up limits; never lengthen them merely to avoid user complaints without risk approval.
5. Click the page's **Save authentication policy** action. Wait for the success message saying new sign-ins use the policy immediately.
6. In the module/home visibility section, enable only school-approved modules and save. Hidden UI is not authorization; server permissions still apply.
7. Open a private/incognito sign-in window and confirm only selected methods/buttons appear and protected /app assets are unavailable before authentication.

Expected result: school controls the home/login choices, and password always has TOTP.

Stop if: no success message, stale-row conflict, an unselected method appears, or hidden module data remains accessible without permission.

Step 40 - add an external identity provider (Microsoft, Google, OIDC or SAML)

Where you are: Edutex **Administration** with P5 identity engineer present. First create the approved enterprise application in Microsoft Entra/Google/IdP using the exact callback/logout URLs from the school's Cognito/technical identity plan. Never guess redirect URLs or claims.

1. In **Connected identity providers**, click **Add provider**.
2. Select **Provider type**: Microsoft Entra ID, Google Workspace, OpenID Connect or SAML 2.0.
3. Enter a permanent lower-case **Provider key**, reviewed display name and button label.
4. For Microsoft/OIDC, enter the exact HTTPS issuer URL. For SAML, enter the approved HTTPS metadata URL. For Google/Microsoft/OIDC, enter exact client ID and one-time client secret.
5. Enter the minimal approved scopes and exact attribute mapping. Map verified email/subject and the dedicated group/role/assurance claims required by policy; do not map an untrusted display name to privilege.
6. Click **Configure provider** once.
7. Wait for Identity provider staged as disabled.... The provider list must show **Disabled**.
8. Confirm the client secret field is cleared/not returned. Edutex stores it in tenant-scoped AWS Secrets Manager.

Expected result: provider exists but is disabled; it cannot be published accidentally.

Stop if: it appears Enabled immediately, secret is returned/displayed, metadata/issuer is not HTTPS/approved, or IdP signature/claim design is unresolved.

Step 41 - add exact claim-to-role mappings before enabling SSO

Where you are: same Administration page, **Directory authorisation** → **Claim-to-role mappings**.

1. Click **Add mapping**.
2. Select the exact identity provider.
3. Enter the approved **Claim name** and **Exact claim value**. Copy case/spacing/identifier exactly from the verified IdP token/assertion design; no wildcard/substring guess.
4. Select the least-privileged Edutex role.
5. Select the matching category: Student, Teacher, Corporate staff, IT staff, Executive staff, Parent/guardian or Contractor.
6. Enter the approved priority according to the reviewed mapping design; avoid conflicting matches.
7. Click **Add mapping** and confirm it appears in the list.
8. Repeat for each approved group/category. Explicitly include negative/no-match/conflicting-group test cases in the plan.

Expected result: at least one exact provider-scoped mapping exists. A provider cannot be enabled without one.

Stop if: the claim source is not signed/verified, nested/dynamic/group-overage behavior is not tested, or a broad group would grant administrator privilege.

Step 42 - test then publish SSO

1. During an approved identity test window, click **Enable** on the staged provider. RC6 checks its current row version and exact mapping.
2. Enable the corresponding Microsoft/Google/SAML family switch in **Allowed sign-in methods** and save. Generic OIDC uses the provider's own status.
3. In a separate private window, test one synthetic user for each mapped category, plus no-match, disabled user, conflicting groups, absent MFA assurance and removed-group cases.
4. Confirm every user receives only the intended Edutex role/category and a separate device session.
5. Remove a directory group, sign in again and confirm stale directory-managed permission is removed.
6. On any failure, immediately return to Administration, click **Disable** for the provider and turn off its sign-in-method switch; preserve evidence.
7. Only after all positive/negative tests pass may P5/P4 record publication acceptance.

Expected result: exact claims map to exact least privilege; no match fails closed; stale grants are removed on subsequent federation.

Step 43 - execute the security/quality acceptance pack

P4/P7 must run and retain evidence for every applicable item - not simply tick this list:

- direct AWS origin discovery/connection fails;
- Cloudflare/TLS/header/cache/request-smuggling/host-header tests pass;

- unauthenticated users cannot download protected portal JavaScript/assets;
- password+TOTP, passkey, OAuth state/nonce/PKCE/browser binding, logout, expiry, recovery, disabled user, step-up and per-device revoke behavior pass;
- two live synthetic tenants/users cannot read, link or mutate one another at API and PostgreSQL RLS layers;
- parameterized SQL/mass-assignment/IDOR/injection/upload/SSRF/XSS/CSRF/rate-limit negative tests pass;
- selected sensitive fields are AES-GCM ciphertext in browser-to-database flow, keys require recent assurance and KMS tenant context, and plaintext/keys do not appear in logs/database;
- S3 is private and upload content/type/size/pixel/re-encoding controls work;
- audit chain verifies, security logs/alerts reach on-call, clocks correlate and incident exercise completes;
- isolated restore meets approved RPO/RTO without overwriting production;
- mobile, desktop, keyboard, screen reader, zoom and supported-browser tests pass;
- SAST, DAST, dependency, secret, container, IaC and live cloud-configuration scans pass or have an authorised time-bound treatment permitted by policy; and
- independent penetration-test findings are remediated/retested before client data/go-live.

Expected result: P1/P4/P5 sign target acceptance with objective evidence and residual-risk owner.

Stop if: any cross-tenant, auth bypass, public origin, secret leak, integrity failure or mandatory high/critical issue exists. Those are release blockers, not waivable convenience defects.

Step 44 - complete ISO/quality governance and handover

1. ISMS owner maps actual evidence to the licensed ISO/IEC 27001:2022+Amd 1:2024 requirements, completes risk assessment/treatment and final Statement of Applicability.
2. QMS owner records requirements, competence, verification, nonconformity/CAPA, supplier controls, release acceptance, quality objectives and customer feedback under ISO 9001:2015+Amd 1:2024.
3. Conduct objective internal audits and management reviews; close findings with effectiveness evidence.
4. Retain approved ZIP/hash, source/lock/SBOM/image digest/signature, plans/hashes/receipt, tests, restore, monitoring, SSO, privacy/legal, penetration-test and approvals under records policy.
5. Provide school support/on-call contacts, incident/privacy notification route, backup/restore owner, identity owner and planned review/patch dates.
6. Claim certification only when a current accredited certificate's organisation/scope/validity actually covers the service. Otherwise say "designed to support an ISO-aligned ISMS/QMS".

Expected result: accountable operational service with controlled evidence - not merely running code.

Part J - error finder

Step 45 - match the exact message before asking for help

What you see	Most likely meaning	Exact safe action
output file already exists	Interview already ran	Review it; use --replace only after approved changed input
NOT ACCEPTED	Current answer format invalid	Read reason; obtain correct approved value; answer same prompt
Secret-like property/value	Credential or unsafe name entered	Remove it from workflow; store secret in approved manager; rerun interview
placeholder value	Example/sample still used	Replace by rerunning interview with real approved data
AWS profile resolved account ... not approved	Wrong SSO profile/account	Stop; aws sso logout; P2 fixes assignment/profile; sign in again
CDK bootstrap stack readiness fails	CDKToolkit missing/unstable	P2 performs approved bootstrap/remediation; rerun read-only check
Tunnel secret has no AWSCURRENT	Secret created without current value/stage	P2/P3 correct Secrets Manager version; never paste token in Terminal
State bucket region/encryption/public/ownership/versioning failure	One mandatory state protection differs	P2 corrects bucket/KMS policy/config, then reruns check
KMS rotation failure	Customer key rotation off/unsupported	P2 selects suitable symmetric AWS-origin key and enables rotation
SES verification failure	Identity not SUCCESS in exact region	Finish DNS verification/production sending; do not bypass invitations
Cloudflare token missing	Hidden environment variable not set	Repeat Step 24 with a fresh scoped token
Terraform 403/permission error	Token scope/resource/TTL wrong	P3 revokes/fixes token; never broaden without review
WAF/rate resource unsupported	Purchased plan lacks feature	Stop and upgrade/approve architecture; do not delete security rule

What you see	Most likely meaning	Exact safe action
quality/source-doc/test/audit failure	Release/source/dependency not releasable	Engineering fixes in a new reviewed RC; new plan/approval
plan hash mismatch	Source/config/plan changed	Generate and approve a completely new plan
outside maintenance window	Current time not approved	Stop; schedule/approve new window; regenerate config/plan as required
migration/bootstrap container exit non-zero	Data/provisioning failed	Preserve ARN/logs/progress; follow exact-ARN retry in Step 35
ECS service not stable	Runtime/tunnel/health/config problem	Keep evidence; use CloudWatch/ECS incident process; do not open origin
SSO provider cannot enable	No exact mapping/stale row	Refresh, create approved mapping, retest; do not bypass gate
stale row-version conflict	Another admin changed config	Refresh, compare both changes, reapply only the intended reviewed change

Additional RC6 checks:

What you see	Meaning and next action
command not found: aws	Install AWS CLI v2, reopen Terminal, then Step 16.
aws configure list-profiles prints nothing	Configure the named SSO profile in Step 16.
Expired SSO token or unavailable cached credentials	Sign in again with the same named profile.
AWS portal stuck loading an access request	P2 checks IAM Identity Center account and permission-set assignment.
No CDK boundary/execution policy	Use Step 17A; the missing companion JSON is not assumed to exist.
Cloudflare Tunnel pending before apply	Expected until the AWS connector starts; do not install it on the laptop.

What you see	Meaning and next action
dquote> or pasted wrap arrows	Control-C; copy the complete Step 30 block from Markdown.
Missing code command	Use VS Code File > Open File.
Duplicate person-account link on upgrade	Correct verified links in the restored rehearsal; never delete people automatically.
Medical view locked	Reopen online and verify access; do not create an offline copy.
Parent cannot see old unallocated invoice	Finance must review guardian fee allocations; household membership alone is insufficient.
Alert blocked or uncertain	Check saved rule scope, recipient rights and provider evidence before any resend.

When reporting an error, provide release, school slug, timestamp, failed [RC6] label, sanitized message, account/region/hostname identifiers and evidence path. Never provide secrets, cookies, authorization headers, temporary passwords, full student data or decrypted values.

RC6 privacy and upgrade additions to acceptance

Before a complete-roadmap or live-data claim, close every development blocker in `docs/RC6_ROADMAP_COVERAGE.md`. All-data client encryption is specifically unmet. The browser medical view is online-only and locks after 60 seconds, on hiding, on logout and on record teardown. A late response cannot re-open the view or restore cleared keys. Restricted student notes and clinical record dialogs also lock on hiding and after five minutes; save work before their deadlines. These controls do not guarantee prevention of screenshots or photography.

Test two guardians with different rights and fee shares, a student account, a restricted teacher, finance creator/approver separation, nurse/wellbeing case access, internal forms and revoked accounts. Rehearse both a fresh install and an upgrade from populated RC5 data. Actual AWS/Cloudflare, MFA, backup/restore, external message delivery, physical devices and independent security checks remain. The final repeat browser pass was blocked by the review browser's URL policy; earlier synthetic phone/tablet/desktop inspection is useful evidence, not a completed device certification.

ISO 9001, ISO 27001, ISO 21001, ISO/IEC 19788 and ISO/IEC 29187-1 requirements must be scoped and assessed using the actual standards and organisational evidence. No certificate is provided by this source build, and adding a document title is not a control implementation.

Final assembly checklist

Do not mark an item complete from memory.

- [] Correct RC6 ZIP and separately delivered SHA-256 verified before extraction.
- [] Correct Edutex-production folder open; release prints 1.0.0-rc.6.
- [] Source documentation gate covers every maintained file and implemented function.
- [] One school/hostname/account/region/Cloudflare zone/tunnel/evidence set only.
- [] AWS SSO short-lived role/account compared through STS; no static access key/root use.
- [] CDKToolkit stable and reviewed.
- [] State bucket region/versioning/ownership/public block/TLS-only policy/exact KMS/Bucket Key verified.
- [] KMS key enabled/rotating; SES identity and production sending/configuration set successful; Tunnel token only in Secrets Manager.
- [] rc6.json created by Terminal interview, reviewed, owner-only and secret-free.
- [] deploy:check ended CHECK PASSED.
- [] Hidden short-lived Cloudflare token used only for plan/apply and removed/revoked.
- [] deploy:plan ended PLAN READY; two plan files, provider lock and exact hashes independently approved.
- [] Source/config/plan unchanged and apply ran inside exact approved window.
- [] Foundation ran at zero app tasks; migration and, for a new school, bootstrap succeeded before activation.
- [] DEPLOYMENT COMPLETE and receipt preserved in encrypted controlled evidence.
- [] Cloudflare Tunnel/DNS/WAF/rates/IP/country/admin policy verified live; no public AWS origin.
- [] Initial admin changed temporary password, enrolled required TOTP and approved passkey.
- [] Cognito OAuth client is confidential; its client secret exists only at the tenant-scoped Secrets Manager name and backend IAM can read only that exact suffix.
- [] Login methods/session limits/modules configured and negative-tested.
- [] Every external provider staged disabled, exact mappings approved, positive/negative tests passed and failed providers disabled.
- [] Cross-tenant/RLS, encryption, logs/alerts, restore, accessibility, resilience and independent penetration tests passed or release remains blocked.
- [] Privacy/legal/records, ISO 27001 ISMS and ISO 9001 QMS evidence/audits/reviews completed.
- [] Development blockers remain visible; trial results are recorded and no live data is admitted until later production acceptance.

Official pages used for screen locations

Console labels can change after this guide. At each release, P2/P3 verifies the current official page before changing a security decision:

- AWS CLI IAM Identity Center: [Official reference](#)
- AWS KMS automatic rotation: [Official reference](#)
- S3 default SSE-KMS/Bucket Key: [Official reference](#)
- S3 versioning: [Official reference](#)
- SES verified identities: [Official reference](#)
- Secrets Manager create secret: [Official reference](#)
- Cloudflare create remote Tunnel: [Official reference](#)
- Cloudflare Tunnel tokens: [Official reference](#)
- Cloudflare API tokens: [Official reference](#)
- Cloudflare managed WAF dashboard: [Official reference](#)

Tiny glossary

Word	Meaning in this manual
Browser	Chrome/Edge/Safari/approved app used for AWS, Cloudflare and Edutex websites
Visual Studio Code	Desktop code/file application containing Explorer, editor tabs and Terminal
Terminal	Bottom text panel where one command or interview answer is typed
Repository root	Open folder ending release/Edutex-production, containing package.json
Identifier/ARN	Non-secret name/ID pointing to a cloud resource; still treat as internal metadata
Secret/token	Credential that grants access; never belongs in JSON/source/chat/evidence
Plan	Proposed changes, reviewed before apply
Apply	The mutating action that creates/changes production
Hash/SHA-256	Fingerprint proving bytes are unchanged
State	Terraform's confidential record of managed Cloudflare resources
RLS	PostgreSQL row-level security independently restricting rows by tenant
CIDR	IP address/range plus prefix, such as /32 for one IPv4 address
Slug	Permanent lower-case hyphenated school identifier
ARN	AWS resource identifier beginning arn:aws:; not the secret value behind it

After installation - school and family handover

Sign in for the first time

Use the exact address provided by the school. Check the school name and web address before entering information. Follow the school's invitation and set up the required extra sign-in protection.

An authenticator app produces a short-lived TOTP code. A supported passkey uses a device or security key and user verification. Your school decides which methods are enabled and tests them with the actual devices people use. Do not share codes or approve an unexpected sign-in request.

If Microsoft or Google sign-in is enabled, choose the school's approved option and the correct school account. Seeing a Microsoft or Google button does not mean any account is allowed. Google sign-in also does not automatically import Google Classroom work into Edutex.

If you lose a phone or authenticator, contact the school's recovery team. They must verify your identity. Creating a second unrelated account or borrowing someone else's account can break the links that protect student and family information.

Make the workspace comfortable

Open the account menu using your initials. Choose the device setting, Light or Dark appearance and select **Save appearance**. Your preference is saved to your account so another signed-in device can use it too.

On a phone, **More** opens navigation. Close it with its close button or Escape on a keyboard. Wide record tables scroll within their own area. Forms use larger controls on small screens. The main staff dashboard has filters and personal display choices; saving them changes your own view.

To add the site to an iPhone or iPad home screen, open the approved HTTPS address in Safari, use Share and choose Add to Home Screen if available on your device. Other browsers may offer an Install or Add to Home Screen option. The icon opens the web app; it does not make medical records available offline. The school must test its supported device versions before rollout.

Use a managed device where school policy requires one. Sign out when finished on a shared device. Tell ICT if text is clipped, focus disappears, a control is difficult to tap or a screen reader cannot identify it; include the screen name and device/browser version.

Set up the school in this order

Administrators should create the basic records before asking staff to enter linked work:

1. Campus, school year, terms, rooms and daily session times.
2. Staff, students, guardians and verified account links.
3. Classes, memberships, student/staff groups and group managers.
4. Important dates and the year levels affected by no-class arrangements.
5. Published school contacts, learning material and forms.
6. Finance accounts, budgets, approval responsibilities and guardian fee allocations.
7. Event venues, templates, risk arrangements and consent processes.
8. A small set of trial dashboards and disabled alert rules.

Choose linked records by name in the search controls. If a person or record is missing, ask the administrator to check that it exists and that you have access. Do not create duplicates simply to make a dropdown work.

An account link identifies a real person's portal account. A family relationship describes what that person may see or do for a child. Check both. Separated parents may need different contact, consent, medical and fee rights.

Everyday staff tasks

Dashboard and attendance

Choose the relevant year levels and other available filters. Multiple filters can narrow the dashboard together. Change the offered follow-up column, such as Movement to Room, and save your view. School-wide records remain controlled by the relevant module permissions.

Important dates can mark no classes for the school or selected year levels. Check the date and scope before adding attendance. The database rejects attendance rolls that conflict with a no-class date.

Events and consent

Start with a suitable event template, then check every copied detail. Enter the venue, dates, activities, student/staff participation, emergency arrangements, supervision and relevant risks. Include return-to-work restrictions where appropriate. A template is a starting point; someone must still think through the actual event.

Submit the proposal through the configured approval stream. The record shows decision history. Complete required planning and approval before publishing parent invitations.

Parents can give, decline or withdraw consent through their portal. For paper consent, authorised staff can print the event form, retain the signed evidence through the school's records process, and record the decision with its paper reference. The visible history distinguishes paper entries from portal actions. Never mark an unsigned form as signed to clear a reminder.

Finance

Use the appropriate purchase order, approval, received-goods, supplier bill, invoice and payment steps. Some decisions need a different authorised person from the creator. A conflict message means the record changed or the requested action does not meet the workflow rules; reload and check it.

Before issuing an invoice with split fees, allocate its full amount to the correct guardians. Each parent sees their own allocation and its payments. Do not assume a shared family record means permission to see another adult's debts.

Purchase orders, supplier bills, budgets and payroll use AUD. Invoices, receipts and bank accounts can name a currency, but FX conversion and international payroll are not implemented.

Edutex records reviewed receipts; it does not collect card details in RC6. Follow the school's verified payment instructions. Payroll figures, GST working papers and financial reports need finance-owner review. Automatic sibling discounts, timetable payroll, direct debit and government lodgement are not complete in this build.

Care, risk, maintenance and alumni

Nurse and wellbeing access depends on the user's care permissions and, where relevant, assignment to the case. Enter clinical narratives only in the designated encrypted fields.

Risk records can link incidents and hazards to relevant people or places. Maintenance records track work categories, status, cost and history. Alumni records support profiles, donations, events and links to current families. These modules supply record management and selected insights; they do not yet implement every automation or specialised report in the roadmap.

Build a dashboard or alert carefully

Insights lets permitted staff create KPI, bar or table tiles. Choose a supported dataset, field, date scope, title and colour. Monetary tiles have a currency. Use the shared timeline option if you want several tiles to move together. A group manager can share a dashboard with their group, but colleagues still need permission for its underlying data.

For a Smart Alert, start from a template such as absent days, outstanding fees, departure without approval or pending event consent. Check the conditions, time window and recipients. Save it while disabled and choose **Preview saved rule**. The preview does not send notifications.

Only enable a rule after the preview and recipients make sense. Email and text messages require ICT to configure approved delivery services. A disabled or failed service does not mean the message was delivered. Ask ICT to inspect blocked or uncertain deliveries before resending anything.

The builder offers a defined list of sources and conditions. It cannot express every possible school rule. Date windows matter: an old unpaid invoice outside the selected window will not appear in that alert. Use the finance report as well when checking debtors.

Parent portal

Sign in with your own linked account and choose the child. If a child is missing or incorrect, stop and ask the school to check the relationship. Do not try another family's account.

Use the tabs to view the child's timetable, published grades, events, your allocated fees, medical information, important dates, contacts, forms and messages. Availability depends on school publication and your verified rights.

Choose **Update my contact details** to change your contact email, phone or address. The contact email is separate from your sign-in email; ask the school if your sign-in identity also needs changing.

Choose **Submit an absence**, select all-day absence, late arrival or leave early, enter the date/time and reason, then submit. The form labels the device timezone. Check it especially while travelling. Submission is a request to the school, not proof a departure has been approved; follow the school's duty-of-care process.

For event consent, read the invitation before choosing a decision. For a published school form, complete the required questions and submit. Contact the school if an answer needs correction.

Fees show your allocated share, recorded payments and balance. Use verified school payment instructions or contact finance. Edutex does not ask for card details in this build.

Student portal

Students can see their own timetable, published grades, materials, assignments, forms, dates, contacts and messages. A student account cannot switch into another student's records.

Open an assignment, read the instructions, choose **Submit assignment**, write the response and check it before submitting. RC6 supports a text response. File uploads, automatic Classroom submission and a full revision workflow are not supplied by this screen. Contact the teacher if a submitted answer needs correction.

Subject or sport selections can be collected through forms the school explicitly publishes for students. An internal staff form should not appear in the student portal; report it if one does.

Medical information on a phone

The medical view works online and asks the server to check access before revealing a record. It clears when hidden and after its short access deadline, currently 60 seconds. Save changes promptly. Reopen the record to reauthorise if it locks.

It does not download a private offline medical file. There is no promise that a visible web page is impossible to capture or photograph. Do not take screenshots or copy care information into personal notes or ordinary messages. Use the school's approved clinical and emergency procedures.

If you cannot connect during an event, follow the school's pre-agreed emergency arrangements. Do not rely on this release as an offline medical system. Tell the event leader about connection problems before leaving.

When something goes wrong

What you see	What to do
Access denied or a missing module	Ask the school to verify your role and account category.
Another sign-in/MFA request	Sign in again through the approved address; sensitive tasks need recent verification.
Missing child, fees or class	Ask the administrator to check links, permissions and publication.
Record changed/conflict	Reload, compare the latest record and retry the intended change.
Medical record locked	Reopen online; do not look for an offline copy.
No alert arrived	Ask ICT to check the saved rule, window, recipient and delivery evidence.
Blank screen	Reload once; record the screen name and visible error for ICT.
Unexpected personal information	Stop using that record and report it through the school's privacy process.

Report the screen, action, approximate time, browser/device and any request/reference ID. Use synthetic examples during the trial. Avoid sending medical details, passwords, tokens or screenshots containing student information in an ordinary support message.

Trial sign-off and first-week handover

Ask one representative of each role to test the tasks they actually perform. Include two guardians with different fee shares, a student, a teacher with limited permissions, a finance approver, a care worker and the technician owner. Test denied access as well as successful actions.

Have ICT demonstrate recovery from a backup and account access revocation. Record supported devices, training needs and a named support contact. The release assessment must list unfinished work plainly; a visually improved screen is not evidence that a privacy or accounting requirement is complete.

Before a later production rollout, the school must close the development and security acceptance blockers and record its release decision. Until then, keep the trial isolated and use made-up information.