



SMART COVER TILES

PAINT FOR TILES

SMART COVER TILES is a high performance water-based paint for tiles. It is ideal for easy renovation of interior spaces as it does not require prior priming.

Ideal for application on porcelain tiles such as stoneware, tiles, gresite, etc. It offers good condensation resistance and is suitable for use in bathrooms.

It offers good resistance to condensation and is suitable for use in bathrooms.

Available in 11 colours with a low satin finish.

PROPERTIES

- Especially recommended for the renovation of interior spaces (tiles).
- Good resistance to water and condensation.
- Adheres without prior priming.
- Ready-to-use product, quick-drying and easy to apply.

APPLICATIONS / FIELDS OF APPLICATION

Product developed for the renovation of tiles with a decorative finish.

Tile paint designed for interiors. Maintenance: clean with a non-abrasive cloth dampened with water and pH neutral soap.

TECHNICAL DATA

PROPERTIES	SPECIFICATION	UNIT	METHOD
Features	Acrylic Resin		
Non-volatile content	52-54	%	UNE-EN ISO 3251:2020
Rotational Viscosity	2500-3500	cp	UNE-EN ISO 2555
Density	1,2±0,1	g/cm ³	UNE-EN ISO 2811-1
Brightness	<12	GU	UNE-EN ISO 2813 (60°)
Adhesion Cutting and Grating	class 1		UNE-EN ISO ISO 2409
Fineness	>7	(Hegman/μ)	UNE-EN ISO 1524
Hardness Persoz	150	s	UNE-EN ISO 1522
Drying time to touch	1	Hours	
Drying time between layers	8	Hours	

PERFORMANCES

SMARTCOVER TILES : In general 0,15 L/m² (two layers)

PREPARATION OF THE SUBSTRATE

New surfaces: Before painting, the substrate must be properly prepared. It must be dry, clean and free of dust, grease or dirt. For deep cleaning, we recommend using our Ecoclean Basic detergent cleaner.

Previously painted surfaces: If the surface has been previously varnished or painted, check if it is in good condition and well adhered. If not, it is recommended to remove the previous coating. This can be done by sanding or stripping, ensuring that the surface is left in good condition. If joint sealing is required, it is recommended to proceed before Primacem Joint is applied. For its application, consult the product data sheet.

If the original coating is in good condition, a compatibility test with the substrate can be carried out beforehand in an inconspicuous area.

MAINTENANCE

After 7 days after painting, it can be washed with water and a mild detergent. Do not use abrasive products, scouring pads or brushes that could scratch the surface.

PRESENTATION

It comes in 2.5L containers.

STORAGE CONDITIONS

The product must be stored in its original closed and unopened packaging sheltered from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if properly stored.

The product must not be used for purposes other than those specified, without first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legislative requirements.

The Safety Data Sheets of the product are available to the professional.

APPLICATION

- Before applying **SMART COVER TILES**, check that the surface is dry and free of grease and dust.
- Stir the contents until the product is homogenised.
- Apply with a short pile velourex roller or microfibre roller.
- Application should be carried out at ambient temperatures between 10°C and 30°C.
- Apply two to three layers respecting the drying time between layers.
- Allow to dry for at least 7 days before use to achieve its performance.
- After use, cover the container; be careful to leave little air space if it is to be used again for a long period of time.

SPECIAL PRECAUTIONS

It is essential to follow the instructions on the label of the container. For further information, please refer to the safety data sheet of the product.

TOOL CLEANING

Tools should be washed with water immediately after use.



last edition: April 2024