

Code Reference: builder-rich-future-sections.js

A source-level explanation with function details, file communication, variables, endpoints, and debugging notes.

Item	Explanation
File	builder-rich-future-sections.js
Purpose	Builder-side helper code for richer future portfolio sections and section defaults.
Lines	410
Size	21,340 bytes
Talks to	Mostly local to its own feature area.
Functions	13
Variables/constants	42
API mentions	0
Signals	17

How this file participates in the system

This generated section reads the actual file and points out line numbers, declarations, endpoints, events, source excerpts, and debugging cues.

Important implementation signals

Item	Explanation
Rich text at line 82	Rich editor behavior, formatting, paste handling, or content sanitization. Evidence: <button type="button" data-rich-action="font-small">Small</button>
Rich text at line 83	Rich editor behavior, formatting, paste handling, or content sanitization. Evidence: <button type="button" data-rich-action="font-normal">Normal</button>
Rich text at line 84	Rich editor behavior, formatting, paste handling, or content sanitization. Evidence: <button type="button" data-rich-action="font-large">Large</button>
Rich text at line 97	Rich editor behavior, formatting, paste handling, or content sanitization. Evidence: data-placeholder="Write the overview here. You can paste images directly into this area."
Browser DOM at line 125	Builder or website interface behavior in the browser/Electron renderer. Evidence: if (editor.dataset.richEditor === "pending-description") {
Browser DOM at line 139	Builder or website interface behavior in the browser/Electron renderer. Evidence: if (editor.dataset.richEditor === "pending-description") {
Browser DOM at line 193	Builder or website interface behavior in the browser/Electron renderer. Evidence: document.querySelector("#pending-editor")?.scrollIntoView({ behavior: "smooth", block: "nearest" });
Browser DOM at line 204	Builder or website interface behavior in the browser/Electron renderer. Evidence: const type = button.dataset.openEditor;
Browser DOM at line 205	Builder or website interface behavior in the browser/Electron renderer. Evidence: const mode = button.dataset.mode "add";
Browser DOM at line 206	Builder or website interface behavior in the browser/Electron renderer. Evidence: const index = button.dataset.index;
Browser DOM at line 208	Builder or website interface behavior in the browser/Electron renderer. Evidence: const section = (project.sections []).find((item) => item.id === button.dataset.sectionId);
Browser DOM at line 213	Builder or website interface behavior in the browser/Electron renderer. Evidence: sectionId: button.dataset.sectionId,
Browser DOM at line 222	Builder or website interface behavior in the browser/Electron renderer. Evidence: const section = (project.sections []).find((item) => item.id === button.dataset.sectionId);
Browser DOM at line 226	Builder or website interface behavior in the browser/Electron renderer. Evidence: sectionId: button.dataset.sectionId,
Cloudflare or AI at line 238	Public AI assistant, Worker deployment, or model-provider fallback behavior. Evidence: // their richDescription field back to the project model. Fallback to

Item	Explanation
Browser DOM at line 245	Builder or website interface behavior in the browser/Electron renderer. Evidence: <code>const richEditor = form.querySelector("[data-rich-editor='pending-description']");</code>
Browser DOM at line 393	Builder or website interface behavior in the browser/Electron renderer. Evidence: <code>document.addEventListener("contextmenu", (event) => {</code>

Important constants and variables

Item	Explanation
text	Line 34: <code>const text = plainTextFromRich(rich).trim();</code>
label	Line 73: <code>const label = editor?.type === "custom-section" ? "Section overview" : "Subsection overview";</code>
folder	Line 74: <code>const folder = pendingEditorFolder(editor);</code>
originalPopulateRichEditor	Line 108: <code>const originalPopulateRichEditor = typeof populateRichEditor === "function" ? populateRichEditor : null;</code>
originalSaveRichEditorToProject	Line 109: <code>const originalSaveRichEditorToProject = typeof saveRichEditorToProject === "function" ? saveRichEditorToProject : null;</code>
originalOpenPendingEditor	Line 110: <code>const originalOpenPendingEditor = typeof openPendingEditor === "function" ? openPendingEditor : null;</code>
originalOpenEditorFromButton	Line 111: <code>const originalOpenEditorFromButton = typeof openEditorFromButton === "function" ? openEditorFromButton : null;</code>
originalRenderPendingEditor	Line 112: <code>const originalRenderPendingEditor = typeof renderPendingEditor === "function" ? renderPendingEditor : null;</code>
originalRenderSectionContent	Line 113: <code>const originalRenderSectionContent = typeof renderSectionContent === "function" ? renderSectionContent : null;</code>
originalSavePendingEditor	Line 114: <code>const originalSavePendingEditor = typeof savePendingEditor === "function" ? savePendingEditor : null;</code>
originalRenderCustomSection	Line 115: <code>const originalRenderCustomSection = typeof renderCustomSection === "function" ? renderCustomSection : null;</code>
originalParseProjectForPortfolio	Line 116: <code>const originalParseProjectForPortfolio = typeof parseProjectForPortfolio === "function" ? parseProjectForPortfolio : null;</code>
originalParsedSectionHasContent	Line 117: <code>const originalParsedSectionHasContent = typeof parsedSectionHasContent === "function" ? parsedSectionHasContent : null;</code>
originalPreviewSectionHasRenderableContent	Line 118: <code>const originalPreviewSectionHasRenderableContent = typeof previewSectionHasRenderableContent === "function" ? previewSectionHasRenderableContent : null;</code>
rich	Line 140: <code>const rich = extractRichSummary(editor);</code>
title	Line 154: <code>const title = pendingEditor.title "";</code>
description	Line 155: <code>const description = pendingEditor.description "";</code>
isTool	Line 156: <code>const isTool = pendingEditor.type === "tool";</code>
isSimpleText	Line 157: <code>const isSimpleText = pendingEditor.type === "text-array";</code>
isSectionDetails	Line 158: <code>const isSectionDetails = pendingEditor.type === "custom-section";</code>
usesRich	Line 159: <code>const usesRich = pendingEditorUsesRichDescription();</code>
project	Line 202: <code>const project = selectedProject();</code>
type	Line 204: <code>const type = button.dataset.openEditor;</code>
mode	Line 205: <code>const mode = button.dataset.mode "add";</code>
index	Line 206: <code>const index = button.dataset.index;</code>
section	Line 208: <code>const section = (project.sections []).find((item) => item.id === button.dataset.sectionId);</code>
item	Line 209: <code>const item = mode === "edit" ? section?.items?.[Number(index)] : {};</code>
section	Line 222: <code>const section = (project.sections []).find((item) => item.id === button.dataset.sectionId);</code>
project	Line 242: <code>const project = selectedProject();</code>
title	Line 244: <code>const title = form.elements.title.value.trim();</code>
richEditor	Line 245: <code>const richEditor = form.querySelector("[data-rich-editor='pending-description']");</code>

Item	Explanation
richDescription	Line 246: const richDescription = richEditor ? extractRichSummary(richEditor) : null;
description	Line 247: const description = richEditor ? richPlainTextOrSpacer(richDescription) : form.elements.description?.value.trim() "";
section	Line 253: const section = (project.sections []).find((item) => item.id === pendingEditor.sectionId);
nextItem	Line 256: const nextItem = {
section	Line 278: const section = (project.sections []).find((item) => item.id === pendingEditor.sectionId);
section	Line 297: const section = (project.sections []).find((item) => item.id === sectionId);
parsed	Line 352: const parsed = originalParseProjectForPortfolio(project);
sectionId	Line 355: const sectionId = parsedSection.id.replace("custom:", "");
sourceSection	Line 356: const sourceSection = (project.sections []).find((section) => section.id === sectionId);
editor	Line 394: const editor = event.target.closest("[data-rich-editor]");
block	Line 395: const block = event.target.closest(".rich-block");

Event handlers and user interactions

Item	Explanation
Line 393	document.addEventListener("contextmenu", (event) => {

Function-by-function detail

hasRichContent - lines 23-31

Item	Explanation
Source location	Lines 23-31 (9 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	function hasRichContent(rich) {
Touches	filesystem
Calls detected	some
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 1 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

23:     function hasRichContent(rich) {
24:         return Boolean(rich?.blocks?.some((block) =>
25:             (block.type === "image" && block.url) ||
26:             (block.type === "formula" && block.formula) ||
27:             block.text ||
28:             block.title ||
29:             block.caption
30:         ));
31:     }

```

richPlainTextOrSpacer - lines 33-36

Item	Explanation
Source location	Lines 33-36 (4 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	function richPlainTextOrSpacer(rich) {

Item	Explanation
Touches	Mostly local calculations or local UI state.
Calls detected	plainTextFromRich, trim, hasRichContent
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 1 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

33:     function richPlainTextOrSpacer(rich) {
34:         const text = plainTextFromRich(rich).trim();
35:         return text || (hasRichContent(rich) ? "\u200B" : "");
36:     }

```

pendingEditorUsesRichDescription - lines 41-43

Item	Explanation
Source location	Lines 41-43 (3 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	function pendingEditorUsesRichDescription(editor = pendingEditor) {
Touches	Mostly local calculations or local UI state.
Calls detected	includes
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 1 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

41:     function pendingEditorUsesRichDescription(editor = pendingEditor) {
42:         return Boolean(editor && ["custom", "custom-section"].includes(editor.type));
43:     }

```

pendingEditorFolder - lines 48-57

Item	Explanation
Source location	Lines 48-57 (10 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	function pendingEditorFolder(editor = pendingEditor) {
Touches	Mostly local calculations or local UI state.
Calls detected	slugify
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 4 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

48:     function pendingEditorFolder(editor = pendingEditor) {
49:         if (!editor) return "custom-overview";
50:         if (editor.type === "custom-section") {
51:             return `custom-${slugify(editor.sectionId || "section")}-overview`;
52:         }
53:         if (editor.type === "custom") {

```

```

54:         return `custom- $\{slugify(editor.sectionId || "section")\}$ -subsection`;
55:     }
56:     return "custom-overview";
57: }

```

pendingEditorRichBlocks - lines 62-65

Item	Explanation
Source location	Lines 62-65 (4 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	function pendingEditorRichBlocks(editor = pendingEditor) {
Touches	Mostly local calculations or local UI state.
Calls detected	textBlocksFromPlainText, richBlocksFromValue
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 2 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

62:     function pendingEditorRichBlocks(editor = pendingEditor) {
63:         if (!editor) return textBlocksFromPlainText("");
64:         return richBlocksFromValue(editor.richDescription, editor.description || "");
65:     }

```

renderPendingRichDescriptionEditor - lines 72-103

Item	Explanation
Source location	Lines 72-103 (32 source lines).
Purpose	Renders UI, markup, or display output.
Declaration	function renderPendingRichDescriptionEditor(editor = pendingEditor) {
Touches	filesystem
Calls detected	pendingEditorFolder, escapeHtml
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 1 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

72:     function renderPendingRichDescriptionEditor(editor = pendingEditor) {
73:         const label = editor?.type === "custom-section" ? "Section overview" : "Subsection overview";
74:         const folder = pendingEditorFolder(editor);
75:         return `
76: <div class="pending-rich-description rich-design-summary-field">
77:   <div class="summary-builder-heading">
78:     <span> $\{label\}$ </span>
79:   </div>
80:   <div class="rich-summary-panel">
81:     <div class="rich-summary-toolbar" aria-label=" $\{escapeHtml(label)\}$  tools">
82:       <button type="button" data-rich-action="font-small">Small</button>
83:       <button type="button" data-rich-action="font-normal">Normal</button>
84:       <button type="button" data-rich-action="font-large">Large</button>
85:       <button type="button" data-rich-action="align-left">Left</button>
86:       <button type="button" data-rich-action="align-center">Center</button>
87:       <button type="button" data-rich-action="align-right">Right</button>
88:       <button type="button" data-rich-action="add-image">Add image</button>
89:       <button type="button" data-rich-action="add-formula">Add formula</button>
90:       <button type="button" data-rich-action="edit-block">Edit selected</button>
91:       <button class="danger-icon" type="button" data-rich-action="delete-block">Delete
selected</button>
92:     </div>
93:   <div
94:     class="rich-summary-editor"

```

```

95:         data-rich-editor="pending-description"
96:         data-rich-folder="${escapeHtml(folder)}"
97:         data-placeholder="Write the overview here. You can paste images directly into this area."
98:         aria-label="${escapeHtml(label)} rich editor"
99:     ></div>
100: </div>
101: </div>
102: `;
103: }

```

section - lines 208-209

Item	Explanation
Source location	Lines 208-209 (2 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	const section = (project.sections []).find((item) => item.id === button.dataset.sectionId);
Touches	browser/Electron DOM
Calls detected	find
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 0 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

208:         const section = (project.sections || []).find((item) => item.id ===
button.dataset.sectionId);
209:         const item = mode === "edit" ? section?.items?.[Number(index)] : {};

```

section - lines 222-230

Item	Explanation
Source location	Lines 222-230 (9 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	const section = (project.sections []).find((item) => item.id === button.dataset.sectionId);
Touches	browser/Electron DOM
Calls detected	find, openPendingEditor
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 0 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

222:         const section = (project.sections || []).find((item) => item.id ===
button.dataset.sectionId);
223:         openPendingEditor({
224:             type,
225:             mode: "edit",
226:             sectionId: button.dataset.sectionId,
227:             title: section?.title || "",
228:             description: section?.description || "",
229:             richDescription: section?.richDescription || null
230:         });

```

section - lines 253-262

Item	Explanation
Source location	Lines 253-262 (10 source lines).

Item	Explanation
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	<code>const section = (project.sections []).find((item) => item.id === pendingEditor.sectionId);</code>
Touches	Mostly local calculations or local UI state.
Calls detected	find
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 1 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

253:         const section = (project.sections || []).find((item) => item.id ===
pendingEditor.sectionId);
254:         if (!section) return;
255:         section.items = section.items || [];
256:         const nextItem = {
257:             title,
258:             description,
259:             richDescription,
260:             type: "Text",
261:             status: "draft"
262:         };

```

section - lines 278-291

Item	Explanation
Source location	Lines 278-291 (14 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	<code>const section = (project.sections []).find((item) => item.id === pendingEditor.sectionId);</code>
Touches	filesystem
Calls detected	find, setStatus, scheduleAutosave, renderAll, originalSavePendingEditor
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 3 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

278:         const section = (project.sections || []).find((item) => item.id ===
pendingEditor.sectionId);
279:         if (!section) return;
280:         section.title = title;
281:         section.description = description;
282:         section.richDescription = richDescription;
283:         pendingEditor = null;
284:         setStatus("Saved in the project editor. Click Save project to include this version in the
portfolio preview.");
285:         scheduleAutosave();
286:         renderAll();
287:         return;
288:     }
289:     return originalSavePendingEditor(form);
290: };
291: }

```

section - lines 297-301

Item	Explanation
Source location	Lines 297-301 (5 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.

Item	Explanation
Declaration	const section = (project.sections []).find((item) => item.id === sectionId);
Touches	Mostly local calculations or local UI state.
Calls detected	find, escapeHtml
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 2 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

297:         const section = (project.sections || []).find((item) => item.id === sectionId);
298:         if (!section) return `<p class="evidence-empty">Section not found.</p>`;
299:         return `
300:         <div class="section-window-heading">
301:         <h3>${escapeHtml(section.title || "Custom section")}</h3>

```

sourceSection - lines 356-360

Item	Explanation
Source location	Lines 356-360 (5 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	const sourceSection = (project.sections []).find((section) => section.id === sectionId);
Touches	Mostly local calculations or local UI state.
Calls detected	find, hasRichContent, clone, richPlainTextOrSpacer
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 0 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```

356:         const sourceSection = (project.sections || []).find((section) => section.id ===
sectionId);
357:         if (hasRichContent(sourceSection?.richDescription)) {
358:             parsedSection.rich = clone(sourceSection.richDescription);
359:             parsedSection.description = sourceSection.description ||
richPlainTextOrSpacer(sourceSection.richDescription);
360:         }

```

improveRichContextMenu - lines 392-405

Item	Explanation
Source location	Lines 392-405 (14 source lines).
Purpose	Named function in the repository. Inspect the surrounding lines to learn its exact inputs and outputs.
Declaration	function improveRichContextMenu() {
Touches	browser/Electron DOM
Calls detected	addEventListener, closest, preventDefault, selectRichBlock, currentRichBlock, syncRichContextMenuControls
API endpoints	None detected inside this function body.
Storage keys	No local/session storage keys detected.
Async/return clues	0 await expression(s), 1 return statement(s).
Debug approach	Trigger the user action that reaches this function, inspect inputs/state before the function, then inspect the returned value, DOM update, file write, process output, or API response after it runs.

Source excerpt:

```
392:     function improveRichContextMenu() {
393:         document.addEventListener("contextmenu", (event) => {
394:             const editor = event.target.closest("[data-rich-editor]");
395:             const block = event.target.closest(".rich-block");
396:             if (!editor && !block) return;
397:             event.preventDefault();
398:             activeSummaryEditor = editor || block.closest("[data-rich-editor]");
399:             selectRichBlock(block || currentRichBlock(activeSummaryEditor));
400:             syncRichContextMenuControls(activeSummaryBlock);
401:             summaryContextMenu.style.left = `${event.clientX}px`;
402:             summaryContextMenu.style.top = `${event.clientY}px`;
403:             summaryContextMenu.hidden = false;
404:             }, true);
405:     }
```

Representative opening snippet

```
1: // JavaScript source code
2: (() => {
3:     "use strict";
4:
5:     /**
6:      * Extend the portfolio builder with rich description editors for custom
7:      * sections and subsections. This patch adds a new rich editor to the
8:      * pending editor for custom items so that images, formulas and other
9:      * formatted content can be used in overviews of future sections. It
10:     * hooks into existing helper functions such as `populateRichEditor`
11:     * and `saveRichEditorToProject` by overriding them at runtime. To
12:     * avoid interfering with built-in behaviour, everything is wrapped
13:     * inside an IIFE and existing functions are stored before being
14:     * redefined. If a function is not present in the current context
15:     * (because the builder script changed), the patch simply does
16:     * nothing.
17:     */
18:
19:     // Guard against applying the patch multiple times.
20:     if (window.builderRichFutureSectionsPatchLoaded) return;
21:
22:     // Helpers to detect whether an object has meaningful rich content.
23:     function hasRichContent(rich) {
24:         return Boolean(rich?.blocks?.some((block) =>
25:             (block.type === "image" && block.url) ||
26:             (block.type === "formula" && block.formula) ||
27:             block.text ||
28:             block.title ||
29:             block.caption
30:         ));
31:     }
32:
33:     function richPlainTextOrSpacer(rich) {
34:         const text = plainTextFromRich(rich).trim();
35:         return text || (hasRichContent(rich) ? "\u200B" : "");
36:     }
37:
38:     // Determine whether the pending editor should use a rich editor. All
39:     // custom sections and subsections use rich editors. Tools, design
40:     // objects and other built-in forms continue to use plain text areas.
41:     function pendingEditorUsesRichDescription(editor = pendingEditor) {
42:         return Boolean(editor && ["custom", "custom-section"].includes(editor.type));
43:     }
44:
45:     // Build a folder name for images uploaded via the pending editor. For
46:     // custom sections and subsections, use a prefix based on the section
47:     // id so that uploaded images are organised under docs/<project>/<folder>/.
48:     function pendingEditorFolder(editor = pendingEditor) {
49:         if (!editor) return "custom-overview";
50:         if (editor.type === "custom-section") {
51:             return `custom-${slugify(editor.sectionId || "section")}-overview`;
52:         }
53:         if (editor.type === "custom") {
54:             return `custom-${slugify(editor.sectionId || "section")}-subsection`;
55:         }
56:         return "custom-overview";
57:     }
58:
59:     // Derive blocks from a rich value or fallback plain text. When the
60:     // editor is empty, provide a single text block so that the content
61:     // area is editable.
62:     function pendingEditorRichBlocks(editor = pendingEditor) {
63:         if (!editor) return textBlocksFromPlainText("");
64:         return richBlocksFromValue(editor.richDescription, editor.description || "");
65:     }
66:
67:     // Render the rich description field for the pending editor. This
68:     // function builds a UI similar to other rich editors in the builder,
69:     // including a toolbar and editable area with appropriate data
70:     // attributes. The label varies depending on whether we're editing
71:     // a section or a subsection.
```

```
72:     function renderPendingRichDescriptionEditor(editor = pendingEditor) {
```