

NAME

sys/types.h – data types

SYNOPSIS

#include <sys/types.h>

DESCRIPTION

The <sys/types.h> header shall include definitions for at least the following types:

blkcnt_t

Used for file block counts.

blksize_t

Used for block sizes.

clock_t

Used for system times in clock ticks or CLOCKS_PER_SEC; see <time.h> .

clockid_t

Used for clock ID type in the clock and timer functions.

dev_t Used for device IDs.

fsblkcnt_t

Used for file system block counts.

fsfilcnt_t

Used for file system file counts.

gid_t Used for group IDs.

id_t Used as a general identifier; can be used to contain at least a **pid_t**, **uid_t**, or **gid_t**.

ino_t Used for file serial numbers.

key_t Used for XSI interprocess communication.

mode_t

Used for some file attributes.

nlink_t

Used for link counts.

off_t Used for file sizes.

pid_t Used for process IDs and process group IDs.

pthread_attr_t

Used to identify a thread attribute object.

pthread_barrier_t

Used to identify a barrier.

pthread_barrierattr_t

Used to define a barrier attributes object.

pthread_cond_t

Used for condition variables.

pthread_condattr_t

Used to identify a condition attribute object.

pthread_key_t

Used for thread-specific data keys.

pthread_mutex_t

Used for mutexes.

pthread_mutexattr_t
Used to identify a mutex attribute object.

pthread_once_t
Used for dynamic package initialization.

pthread_rwlock_t
Used for read-write locks.

pthread_rwlockattr_t
Used for read-write lock attributes.

pthread_spinlock_t
Used to identify a spin lock.

pthread_t
Used to identify a thread.

size_t Used for sizes of objects.

ssize_t Used for a count of bytes or an error indication.

suseconds_t
Used for time in microseconds.

time_t Used for time in seconds.

timer_t
Used for timer ID returned by *timer_create()*.

trace_attr_t
Used to identify a trace stream attributes object.

trace_event_id_t
Used to identify a trace event type.

trace_event_set_t
Used to identify a trace event type set.

trace_id_t
Used to identify a trace stream.

uid_t Used for user IDs.

useconds_t
Used for time in microseconds.

All of the types shall be defined as arithmetic types of an appropriate length, with the following exceptions:

key_t

pthread_attr_t

pthread_barrier_t
pthread_barrierattr_t

pthread_cond_t
pthread_condattr_t
pthread_key_t
pthread_mutex_t
pthread_mutexattr_t

pthread_once_t
pthread_rwlock_t
pthread_rwlockattr_t

pthread_spinlock_t

trace_attr_t
trace_event_id_t

trace_event_set_t

trace_id_t

Additionally:

- * **mode_t** shall be an integer type.
- * **nlink_t**, **uid_t**, **gid_t**, and **id_t** shall be integer types.
- * **blkcnt_t** and **off_t** shall be signed integer types.
- * **fsblkcnt_t**, **fsfilcnt_t**, and **ino_t** shall be defined as unsigned integer types.
- * **size_t** shall be an unsigned integer type.
- * **blksize_t**, **pid_t**, and **ssize_t** shall be signed integer types.
- * **time_t** and **clock_t** shall be integer or real-floating types.

The type **ssize_t** shall be capable of storing values at least in the range [-1, {SSIZE_MAX}]. The type **useconds_t** shall be an unsigned integer type capable of storing values at least in the range [0, 1000000]. The type **suseconds_t** shall be a signed integer type capable of storing values at least in the range [-1, 1000000].

The implementation shall support one or more programming environments in which the widths of **blksize_t**, **pid_t**, **size_t**, **ssize_t**, **suseconds_t**, and **useconds_t** are no greater than the width of type **long**. The names of these programming environments can be obtained using the *confstr()* function or the *getconf* utility.

There are no defined comparison or assignment operators for the following types:

pthread_attr_t

pthread_barrier_t
pthread_barrierattr_t

pthread_cond_t
pthread_condattr_t
pthread_mutex_t
pthread_mutexattr_t
pthread_rwlock_t
pthread_rwlockattr_t

pthread_spinlock_t

trace_attr_t

The following sections are informative.

APPLICATION USAGE

None.

RATIONALE

None.

FUTURE DIRECTIONS

None.

SEE ALSO

<time.h>, the System Interfaces volume of IEEE Std 1003.1-2001, *confstr()*, the Shell and Utilities volume of IEEE Std 1003.1-2001, *getconf*

COPYRIGHT

Portions of this text are reprinted and reproduced in electronic form from IEEE Std 1003.1, 2003 Edition, Standard for Information Technology -- Portable Operating System Interface (POSIX), The Open Group Base Specifications Issue 6, Copyright (C) 2001-2003 by the Institute of Electrical and Electronics Engineers, Inc and The Open Group. In the event of any discrepancy between this version and the original IEEE and The Open Group Standard, the original IEEE and The Open Group Standard is the referee document. The original Standard can be obtained online at <http://www.opengroup.org/unix/online.html> .