PA1401

pa1401 > JS PA1401.JS > ...

```
// 1. Variable declaration and log
let name = "otlotleg";
console.log(name); // Outputs: otlotleg

// 2. Regular Function
function getname(name) {
    return name;
}

// 3. Arrow Function
const getSurname = (Surname) => {
    return Surname;
};

// 4. Template Literals
name = "zandi"; // Reassigned
let Surname = "sepamo";

let fullname = name + " " + Surname;
console.log(name); // Outputs: zandi

let vollname = `${name} ${Surname}`;
console.log(vollname); // Outputs: zandi sepamo

// 5. Defining the object
const person = {
    gender: 12,
    name: "kaybe",
    Surname: "monday",
    venue: "cape town"
};
```

```
// 6. Destructuring the object (Fixed the spelling of Surname)
const { gender, name: personName, Surname: personSurname, venue } = person;


// Testing the output
console.log(personName);
console.log(venue);

// Spread operator
const topics = ['html', 'css', 'javaScript']; // Fixed to square brackets

// Spreads 'topics' elements into the new array and adds 'python'
const language = [...topics, "python"];

console.log(language);
// Outputs: ['html', 'css', 'javaScript', 'python']

// 1. Defining a Class
class Person {
    // The constructor sets up the properties when a new object is created
    constructor(name, surname, gender, venue) {
        this.name = name;
        this.surname = surname;
        this.gender = gender;
        this.venue = venue;
    }

    // A method (function inside a class) to get the full name
    getFullName() {
        return `${this.name} ${this.surname}`;
    }
```

```
    // Another method
    introduce() {
        return `Hi, I am ${this.name} from ${this.venue}.`;
    }
}

// 2. Creating an Instance (Object) from the Class
const person1 = new Person("Kaybe", "Monday", 12, "Cape Town");
const person2 = new Person("Zandi", "Zulu", "Female", "Johannesburg");

// 3. Testing the class methods
console.log(person1.getFullName()); // Outputs: Kaybe Monday
console.log(person2.introduce());   // Outputs: Hi, I am Zandi from Johannesburg.


// person.js

// Use 'export' before the class to allow other files to use it
export class Person {
    constructor(name, surname, venue) {
        this.name = name;
        this.surname = surname;
        this.venue = venue;
    }

    introduce() {
        return `Hi, I am ${this.name} from ${this.venue}.`;
    }
}
```

```
    // You can also export standalone functions or variables
    export function greet(user) {
        return `Hello, ${user}!`;
    }
```

1 > JS maths.js > subtraction

```
// 1. Math Functions (Fixed subtraction logic)
export function add(num1, num2) {
    return num1 + num2;
}

export function subtraction(num1, num2) {
    return num1 - num2;
}

// 2. Exporting Variables (Gave them unique names)
export const thankYouMessage = "thank you";
export const morningGreeting = "morning";
```

```
// main.js
import { add, subtraction, thankYouMessage, morningGreeting } from './maths.js';

console.log(subtraction(10, 4));
console.log(morningGreeting);
```