

VMRDH-Jobs

Srirama Bhamidipati

2025-10-13

Job index

VMRDH 3.0	5
I Standard Uitvoer	6
1 Matrix Compressies	7
1.1 Purpose	7
1.2 Inputs	7
1.3 Outputs	8
1.4 Code	9
2 Voertuigprestaties	13
2.1 Purpose	13
2.2 Inputs	14
2.3 Outputs	16
2.4 Code	16
3 Skim Matrix Exports	17
3.1 Purpose	17
3.2 Inputs	17
3.3 Outputs	17
3.4 Code	17
4 Bereikbaarheid	18
4.1 Purpose	18
4.2 Inputs	19
4.3 Outputs	19
4.4 Code	19
5 (Multiple) Selected Link Compress	20
5.1 Purpose	21
5.2 Inputs	21
5.3 Outputs	22

5.4	Code	23
5.4.1	Without compression or export to Excel	23
5.4.2	With compression or export to Excel	24
6	INEXDO	26
6.1	Purpose	27
6.2	Inputs	28
6.3	Outputs	28
6.4	Code	28
7	Uitsnednetwork	29
7.0.1	Purpose	29
7.0.2	Inputs	29
7.0.3	Outputs	30
7.0.4	Code	30
8	Milieu	31
8.1	Purpose	31
8.2	Inputs	31
8.3	Outputs	31
8.4	Code	31
II	Custom Jobs	32
9	Trip Length Distribution	33
9.1	Purpose	33
9.2	Inputs	34
9.2.1	Method 1 - Regular Ranges	34
9.2.2	Method 2 - Irregular Ranges	35
9.3	Outputs	36
9.4	Code	36
III	Others	38
10	Weekdagmodule	39
10.1	Fieldnames in Geomilieu Export	40
10.2	Dagdeel Calculation Periods	41

IV Prototype4	42
Why?	43
Process-Flowchart	43
11 Modules	44
11.1 CARMOD Module	44
11.1.1 Purpose	44
11.1.2 Inputs	44
11.1.3 .coeff File	44
11.1.4 .sum File	44
11.1.5 .log File	45
11.2 QUAD	45
11.2.1 Purpose	45
11.2.2 Inputs	45
11.2.3 Outputs	45
11.2.4 Code	45
11.3 IntraLOS	45
11.3.1 Purpose	45
11.3.2 Inputs	45
11.3.3 Outputs	45
11.3.4 Code	46

VMRDH 3.0

This pdf acts as a manual to understand the OmniTrans jobs, their purpose, inputs and outputs. It also allows you to download the jobs and input templates.

Part I


Standard Uitvoer

1 Matrix Compressies

1.1 Purpose

There are 4 types of matrix compression jobs. Each job has a different spatial aggregation level. The four aggregation levels are :

- Stedelijkheid
- Gemeenten
- MRDH groot / MRDH groot etm
- MRDH Studiegebied



1.2 Inputs

The inputs for the job are matrices listed under `$matrices`. Different jobs handle the different level of aggregation for you, so you do not have to change anything else in the job (see outputs if you want to change output formats). The input `$matrices` takes a list, each item in the list takes the form `["Output_Sheet_name", [P,M,T,U]]`.



! Important

Each spatial level is a different job. If you have changed only the list of matrices in the job, you can use it without caution. But if you have changed the `# definieer Gebieden` part of the code, that is, if you have changed the definition of each gebied, you have to be careful that each *Centroid Number* is exclusively in ONLY ONE *gebied*. If not, you will get an error.

1.3 Outputs

You also have to control the output format. The output can be in two formats: excel or openoffice. If you are working

on the MRDH servers, you must open/ uncomment the `Naar Open Office` and the the two lines below it. If you want to get an excel format output, you would comment the `Naar Open Office` and the the two lines below it and uncomment `Naar Excel` and the two lines below it.

1.4 Code

Download the code.[matrixcompress.rb](#)

```
# Variabelen:
#=====
# definieer matrices [naam,[pmtu]]
$matrices = [
  ["Fiets_as", [1,5,3,1]],
  ["Fiets_rd", [1,5,2,1]],
  ["Fiets_os", [1,5,1,1]],
  ["Fiets_etm",[1,5,4,1]],
  ["OV_as", [1,4,3,1]],
  ["OV_rd", [1,4,2,1]],
  ["OV_os", [1,4,1,1]],
  ["OV_etm",[1,4,4,1]],
  #~ ["VNT_FietsLopen_as",[1,4,3,83]],
  #~ ["VNT_FietsLopen_rd",[1,4,2,83]],
  #~ ["VNT_FietsLopen_os",[1,4,1,83]],
  #~ ["VNT_FietsLopen_etm",[1,4,4,83]],
  #~ ["VNT_LopenLopen_as",[1,4,3,84]],
  #~ ["VNT_LopenLopen_rd",[1,4,2,84]],
  #~ ["VNT_LopenLopen_os",[1,4,1,84]],
  #~ ["VNT_LopenLopen_etm",[1,4,4,84]],
  #~ ["VNT_LopenFiets_as",[1,4,3,85]],
  #~ ["VNT_LopenFiets_rd",[1,4,2,85]],
  #~ ["VNT_LopenFiets_os",[1,4,1,85]],
  #~ ["VNT_LopenFiets_etm",[1,4,4,85]],
  #~ ["VNT_FietsFiets_as",[1,4,3,86]],
  #~ ["VNT_FietsFiets_rd",[1,4,2,86]],
  #~ ["VNT_FietsFiets_os",[1,4,1,86]],
  #~ ["VNT_FietsFiets_etm",[1,4,4,86]],
  ["Vracht_as", [1,3,3,1]],
```



```

gebied17=[[6479, 6480, 6481, 6482, 6483, 6484, 6485, 6486, 6487, 6488, 6489, 6490, 6491, 6492, 6493, 6494, 6495, 6496, 6497, 6498, 6499]]
gebied18=[[6519, 6520, 6521, 6522, 6523, 6524, 6530, 6531, 6532, 6533, 6534, 6535, 6536, 6537, 6538, 6539, 6540, 6541, 6542, 6543, 6544]]
gebied19=[[6499, 6514, 6515, 6516, 6517, 6518, 6525, 6526, 6527, 6528, 6529, 6546, 6547, 6548, 6549, 6550, 6551, 6552, 6553, 6554, 6555]]

#Staddelen Den Haag (8)
gebied20=[[79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 157, 166, 167, 168, 169, 170, 171, 172, 173, 174]]
gebied21=[[214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234]]
gebied22=[[309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329]]
gebied23=[[420, 421, 422, 423, 451, 452, 453, 454, 698, 699, 700, 701, 702, 703, 704, 705, 706, 707, 708, 709]]
gebied24=[[611, 612, 613, 614, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637]]
gebied25=[[1, 2, 8, 23, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41]]
gebied26=[[3, 4, 5, 6, 7, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 91, 92]]
gebied27=[[941, 942, 943, 944, 945, 946, 947, 948, 949, 950, 951, 952, 953, 954, 955, 956, 957, 958, 959, 960]]

gebied28=[[3801..3900], "Albrandswaard"]
gebied29=[[3901..4050], "Barendrecht"]
gebied30=[[4751..4850], "Brielle"]
gebied31=[[4301..4450, 6668], "Capelle aan den IJssel"]
gebied32=[[2251..2500, 1082], "Delft"]
gebied33=[[5101..5250], "Hellevoetssluis"]
gebied34=[[4201..4300], "Krimpen aan den IJssel"]
gebied35=[[4451..4650, 5252, 5253], "Lansingerland"]
gebied36=[[1351..1550], "Leidschendam"]
gebied37=[[4651..4750], "Maassluis"]
gebied38=[[2651..2800], "Midden Delfland"]
gebied39=[[3501..3800], "Nissewaard"]
gebied40=[[2001..2250], "Pijnacker"]
gebied41=[[4051..4200], "Ridderkerk"]
gebied42=[[2501..2650, 1090], "Rijswijk"]
gebied43=[[3359, 3360, 3361, 3362, 3363, 3364, 3365, 3366, 3367, 3368, 3369, 3370, 3371, 3372, 3373, 3374, 3375, 3376, 3377, 3378, 3379]]
gebied44=[[3351, 3352, 3353, 3354, 3355, 3356, 3357, 3358, 3372, 3373, 3374, 3448, 3449, 3450, 3451, 3452, 3453, 3454, 3455, 3456, 3457]]
gebied45=[[4951..5100], "Vlaardingen"]
gebied46=[[1151..1350, 1086], "Wassenaar"]
gebied47=[[2801..3350], "Westland"]
gebied48=[[4851..4950], "Westvoorne"]
gebied49=[[1551..2000], "Zoetermeer"]


gebied50=[[6708, 7235, 7236, 7237, 7238, 7239, 7240, 7241, 7242, 7243, 7244, 7245, 7246, 7247, 7248, 7249, 7250, 7251, 7252, 7253]]
gebied51=[[6701, 6702, 6703, 6704, 6705, 6706, 6707, 6709, 6710, 6711, 6712, 6713, 6714, 6715, 6716, 6717, 6718, 6719, 6720, 6721]]
gebied52=[[6832, 6862, 6863, 6865, 6866, 6867, 6868, 6869, 6870, 6872, 6873, 6874, 6875, 6876, 6877, 6878, 6879, 6880, 6881, 6882]]

```


2 Voertuigprestaties

2.1 Purpose

The voertuigprestaties (or vehicle-km, vehicle-hours) is a performance indicator for the whole network (or selected-part of a network). This indicator shows how many km were travelled by all the vehicles collectively in the network or how many hours were spent by all the vehicles collectively in the network. More time spent by vehicles in the network could indicate congestion. Similarly more vehicle-km driven by vehicles indicate higher pollution/ fuel-usage levels for example.



2.2 Inputs

! Important

Be careful! Each line of this job is an input parameter. Read carefully and select the pmturi numbers very carefully.

- `vgtm.load`: In this parameter, you create a list `[]`. Each item in the list is a pmturi and enclosed inside `[]`. Each item is separated by a comma.
- `vgtm.network` : In this parameter, you create a list `[]`. Each item in the list is a p and m combination refereing

to a network. The number of items in this list should be same as the number of items in `vgtm.load`.

- `vgtm.loadNaam` : In this parameter you create a list []. Each item in this list is a string that defines the name of the load defined under `vgtm.load`. The number of items in this list should be same as the number of items in `vgtm.load`.
- `vtgkm.variant`: This parameter is also a list [] and contains items that are names of the variants in your model. It is not necessary that the number of items in this list is same as number of items in the `vgtm.load`.
- `vtgkm.selectie` : If you want to calculate these performance indicators only for a small part of the network, you must first define a selection in omnitrans, give it a name. In this job, you refer to that name in this parameter. Again, this parameters is a list and can take multiple `selection-names`.
- `vtgkm.wegtype` : You have this optional parameter to calculate this indicator only for certain wegtypes. This parameter is again a list of items indicating the wegtype.
- `vtgkm.filterWegtype`: You have this optional parameter that a list of wegtypes. For example you want to calculate the indicator for all links but not connectors. Then you must exclude the connector wegtype in this list.

```
## pmturi load
vtgkm.load          = [ [1,2,1,103,11,20],[1,2,3,103,11,20]]# verplicht!

## opties (pmturi afhankelijk)

# default = Dagdeel factor (1.0)
#~ vtgkm.factorren  = [ 1.0                1.0    1.0    1.0    ]

vtgkm.netwerk       = [ [2,1],                [2,3]]
vtgkm.loadNaam      = [ "Auto_os",            "Auto_as"]

## opties voor categoriën:
vtgkm.variant = ["2016","2020","2023","2030Laag","2030Hoog","2040Hoog"]
```

```
# default = current variant

vtgkm.selectie = ["VTGP_2016","VTGP_2020","VTGP_2023","VTGP_2030",
"VTGP_2030","VTGP_2040"]
# default = hele netwerk

vtgkm.wegtype = 1          # default = none
vtgkm.filterWegtype = [14,15,16,17,18,19,20,21,22,51,99]
```

2.3 Outputs

You also have to control the output format. The output can be in two formats: excel or openoffice. If you are working on the MRDH servers, you must open/ uncomment the `## extra opties voor excel` and the lines below it. On MRDH servers, you can set `vtgkm.openoffice = true`

2.4 Code

Download the code.[matrixcompress.rb](#)

3 Skim Matrix Exports

3.1 Purpose

Some text explaining what the code does.

3.2 Inputs

Following are the inputs to this job.

3.3 Outputs

Following are the outputs to this job.

3.4 Code

Download the code.[matrixcompress.rb](#)

4 Bereikbaarheid

4.1 Purpose



4.2 Inputs

Following are the inputs to this job.

4.3 Outputs

Following are the outputs to this job.

4.4 Code

Download the code.[matrixcompress.rb](#)

5 (Multiple) Selected Link Compress

This job has the advantage of doing multiple selected link compressions in one run. You can specify the links and directions you want to analyze in the code. The job will then loop through each specified link and direction, performing the selected link compression and generating the corresponding reports. Two forms are supported:


- Only store resulting select link matrices in OT database without exporting to Excel.
- Export to Excel after compression to 65x65 matrices or MRDH municipalities or another.



5.1 Purpose

This job calculates selected link compressions for specified links and generates reports in Excel. You can use this job to calculate selected link assignments for auto, vracht, OV and bicycles. You can use this job to calculate selected link assignments without generating reports in Excel.

The following image is a schematic and shows an example of the output and the matrix numbers. The output takes each possible combinations of time and LinkID.



5.2 Inputs

- **vracht:** Set to true or false to indicate if vracht should be included in the assignment.
- **auto:** Set to true or false to indicate if auto should be included in the assignment.
- **ov:** Set to true or false to indicate if OV should be included in the assignment.
- **fiets:** Set to true or false to indicate if bicycles should be included in the assignment.
- **dagdelen:** Array with the time periods to be included in the assignment. Possible values are T_Os, T_Rd, T_As.
- **totaal_toedeling_bestaat:** Set to true if the total assignment already exists in the OT database. This can save time if you have already run a full assignment and only want to do selected link assignments.

- **threads:** Number of threads to be used for the assignment. This can speed up the assignment process.
- **linknrs:** Array of arrays with the link numbers and directions to be analyzed. Each inner array should contain the link number and direction (1 for outbound, 2 for inbound, 3 for both).

```
# Variabelen:
#=====
$vracht = true
$auto = true
$ov = false
$fiets = false
$dagdelen = [T_Rd] # [T_Os,T_Rd,T_As]
$totaal_toedeling_bestaat = false
$threads = 11
# linknummers opgeven en daarna de richting [3 = beide, 1 = heen 2 = terug]
linknrs = [[16144,1],[16143,2]]
```

5.3 Outputs

The outputs of this job are the selected link matrices stored in the OT database. If you choose to export to Excel, the output will also include Excel files with the selected link assignment results. You can also export to other formats if from the GUI when you open the matrix.

Here is the output of an example run

Selected Link matrices (44)

1	2	1	1	400	20	Totaal, Auto, Os, Totaal, Result400, Iteratie20
1	2	1	1	401	20	Totaal, Auto, Os, Totaal, Result401, Iteratie20
1	2	1	1	402	20	Totaal, Auto, Os, Totaal, Result402, Iteratie20
1	2	1	1	403	20	Totaal, Auto, Os, Totaal, Result403, Iteratie20
1	2	1	1	404	20	Totaal, Auto, Os, Totaal, Result404, Iteratie20
1	2	1	1	405	20	Totaal, Auto, Os, Totaal, Result405, Iteratie20
1	2	1	1	406	20	Totaal, Auto, Os, Totaal, Result406, Iteratie20
1	2	1	1	407	20	Totaal, Auto, Os, Totaal, Result407, Iteratie20
1	2	2	1	421	20	Totaal, Auto, Rd, Totaal, Result421, Iteratie20
1	2	2	1	422	20	Totaal, Auto, Rd, Totaal, Result422, Iteratie20
1	2	2	1	423	20	Totaal, Auto, Rd, Totaal, Result423, Iteratie20
1	2	2	1	424	20	Totaal, Auto, Rd, Totaal, Result424, Iteratie20
1	2	2	1	425	20	Totaal, Auto, Rd, Totaal, Result425, Iteratie20
1	2	2	1	426	20	Totaal, Auto, Rd, Totaal, Result426, Iteratie20
1	2	2	1	427	20	Totaal, Auto, Rd, Totaal, Result427, Iteratie20
1	2	3	1	411	20	Totaal, Auto, As, Totaal, Result411, Iteratie20
1	2	3	1	412	20	Totaal, Auto, As, Totaal, Result412, Iteratie20
1	2	3	1	413	20	Totaal, Auto, As, Totaal, Result413, Iteratie20
1	2	3	1	414	20	Totaal, Auto, As, Totaal, Result414, Iteratie20
1	2	3	1	415	20	Totaal, Auto, As, Totaal, Result415, Iteratie20
1	2	3	1	416	20	Totaal, Auto, As, Totaal, Result416, Iteratie20
1	2	3	1	417	20	Totaal, Auto, As, Totaal, Result417, Iteratie20
1	3	1	1	400	1	Totaal, Vracht, Os, Totaal, Result400, Iteratie1
1	3	1	1	401	1	Totaal, Vracht, Os, Totaal, Result401, Iteratie1
1	3	1	1	402	1	Totaal, Vracht, Os, Totaal, Result402, Iteratie1
1	3	1	1	403	1	Totaal, Vracht, Os, Totaal, Result403, Iteratie1
1	3	1	1	404	1	Totaal, Vracht, Os, Totaal, Result404, Iteratie1
1	3	1	1	405	1	Totaal, Vracht, Os, Totaal, Result405, Iteratie1
1	3	1	1	406	1	Totaal, Vracht, Os, Totaal, Result406, Iteratie1
1	3	1	1	407	1	Totaal, Vracht, Os, Totaal, Result407, Iteratie1
1	3	2	1	421	1	Totaal, Vracht, Rd, Totaal, Result421, Iteratie1
1	3	2	1	422	1	Totaal, Vracht, Rd, Totaal, Result422, Iteratie1
1	3	2	1	423	1	Totaal, Vracht, Rd, Totaal, Result423, Iteratie1
1	3	2	1	424	1	Totaal, Vracht, Rd, Totaal, Result424, Iteratie1
1	3	2	1	425	1	Totaal, Vracht, Rd, Totaal, Result425, Iteratie1
1	3	2	1	426	1	Totaal, Vracht, Rd, Totaal, Result426, Iteratie1
1	3	2	1	427	1	Totaal, Vracht, Rd, Totaal, Result427, Iteratie1
1	3	3	1	411	1	Totaal, Vracht, As, Totaal, Result411, Iteratie1
1	3	3	1	412	1	Totaal, Vracht, As, Totaal, Result412, Iteratie1
1	3	3	1	413	1	Totaal, Vracht, As, Totaal, Result413, Iteratie1
1	3	3	1	414	1	Totaal, Vracht, As, Totaal, Result414, Iteratie1
1	3	3	1	415	1	Totaal, Vracht, As, Totaal, Result415, Iteratie1
1	3	3	1	416	1	Totaal, Vracht, As, Totaal, Result416, Iteratie1
1	3	3	1	417	1	Totaal, Vracht, As, Totaal, Result417, Iteratie1

5.4 Code

5.4.1 Without compression or export to Excel

/07_SelectedLinkCompress/Select-
edLinkCompress.rb

```
# Variabelen:
#=====
```

```

$vracht = true
$auto = true
$ov = false
$fiets = false
$dagdelen = [T_Rd] # [T_Os,T_Rd,T_As]
$totaal_toedeling_bestaat = false
$threads = 11
# linknummers opgeven en daarna de richting [3 = beide, 1 = heen 2 = terug]
linknrs = [[16144,1],[16143,2]]
for x in 0..linknrs.length-1
    $link = linknrs[x]
    $result = 421+x
    #$result = 400
    load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\01a Toedelen MVT (sellink).r
    load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\01b Toedelen OV (sellink).r
    load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\01c Toedelen Fiets (sellink).r
    load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\02 Aanmaken OD-matrices.rb'
end

```

5.4.2 With compression or export to Excel

The only difference is the last line in the job. The difference with the previous code is that after creating the OD matrices, a compression to 65x65 matrices or MRDH municipalities or another is done and exported to Excel.

```

# Variabelen:
#=====
$vracht = true
$auto = true
$ov = false
$fiets = false
$dagdelen = [T_Rd] # [T_Os,T_Rd,T_As]
$totaal_toedeling_bestaat = false
$threads = 11
# linknummers opgeven en daarna de richting [3 = beide, 1 = heen 2 = terug]

```

```

linknrs = [[16144,1],[16143,2]]
for x in 0..linknrs.length-1          # hier niks doen, loop
  $link = linknrs[x]                  # hier niks doen, loop
  $result = 421+x    # uniek getal opgeven die nog niet binnen deze variant gebruikt wordt(alles)

  load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\01a Toedelen MVT (sellink).r'
  load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\01b Toedelen OV (sellink).r'
  load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\01c Toedelen Fiets (sellink).r'
  load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\02 Aanmaken OD-matrices.rb'


  load $Ot.dirJob+'Standaard uitvoer\Routines\SelectedLinkCompress\03 matrixcompress sellink (I)
end

```

6 INEXDO


Sub area analysis of transport modeling is a method used to evaluate and understand the travel patterns and behaviors within a specific geographic area or zone. This type of analysis is crucial for urban planners, transportation engineers, and policymakers to make informed decisions about infrastructure development, traffic management, and public transportation services. A select-area analysis or a sub-area analysis typically involves the following steps:

1. **Data Collection:** Gather data on travel patterns, including origin-destination matrices, traffic counts, public transportation usage, and demographic information.
2. Cut a small portion of the model area, a sub-area, for detailed analysis. This can be done by selecting specific zones or regions within the larger model.
3. **Analysis:** Analyze the results of the model to identify key travel patterns, congestion points, and areas of high demand for transportation services. This involves internal-internal, internal-external and external-external trips.



6.1 Purpose

INEXDO is voor al het inkomend, uitgaand en doorgaand verkeer door een of meerdere zones.



	ZONE1	ZONE2	ZONE3	ZONE4	ZONE5	ZONE6	ZONE7	ZONE8	ZONE9	ZONE10
ZONE1	166	876	320	186	674	539	829	849	508	441
ZONE2	146	907	874	816	143	873	980	693	452	101
ZONE3	235	738	148	74	685	407	252	15	322	739
ZONE4	11	107	506	371	297	482	967	679	10	148
ZONE5	433	876	600	936	822	14	656	48	568	663
ZONE6	662	4	583	661	310	341	526	928	924	795
ZONE7	573	91	541	534	178	565	531	31	168	784
ZONE8	176	236	624	697	762	589	144	816	570	721
ZONE9	957	261	535	43	873	412	199	712	784	93
ZONE10	704	442	178	340	898	374	809	325	640	328

	ZONE1	ZONE2	ZONE3	ZONE4	ZONE5	ZONE6	ZONE7	ZONE8	ZONE9	ZONE10
ZONE1										
ZONE2	External External				External Internal				External External	
ZONE3										
ZONE4										
ZONE5	Internal External				Internal Internal				Internal External	
ZONE6										
ZONE7										
ZONE8	External External				External Internal				External External	
ZONE9										
ZONE10										

6.2 Inputs

- Zone number(s) : the zones you want to use
- Matrix location

6.3 Outputs

Following are the outputs to this job.

6.4 Code

```
Zone = [1,2,3,4]+[5,6,7,8]
```


7 Uitsnednetwork

This job allows you to cut a cordon from the larger network and create an OD matrix for this cordon. This is also known as **sub-area analysis**. This cut out network is useful for further analysis in other software, such as Vissim or Aimsun or other microscopic simulation software.



7.0.1 Purpose

Look inside each tab to understand what you will get from this job.

7.0.2 Inputs

Following are the inputs to this job.

```
fratarTest.source_cube = '2020_KAL' # Geef MatrixCube op (hier: 2016_SMC)
fratarTest.matrix = [1,2,1,103]      # Geef Matrix (1 PER AANROEP!) (Hier Auto OS)
```

7.0.3 Outputs

Following are the outputs to this job.

```
fratarTest.destination_cube = 'FratarDemo' # Resultaatcube
```

7.0.4 Code

Download the code.[matrixcompress.rb](#)

8 Milieu

8.1 Purpose

Some text explaining what the code does.

8.2 Inputs

Following are the inputs to this job.

8.3 Outputs

Following are the outputs to this job.

8.4 Code

Download the code.[matrixcompress.rb](#)


Part II

Custom Jobs

9 Trip Length Distribution

9.1 Purpose

This job can create trip length distribution for a normal matrix or for a select link matrix or any matrix. One of these matrices is then combined with a skim matrix of choice.



9.2 Inputs

This job can be run in two ways. The first method uses regular ranges for the x-axis and the second method uses irregular ranges. The regular ranges are specified using a min, max and interval. The irregular ranges are specified using an array of lower limits and an array of upper limits.

9.2.1 Method 1 - Regular Ranges

Following are the inputs to this job. You will also need a encrypted file `tld.rc` in your job folder.

The following parameters are used to select the matrices and create a table.

- The parameter `mode_matrix_number`: is the matrix number of the trip matrix.
- The parameter `skim_matrix_number`: is the matrix number of the skim matrix.
- The parameters used for the chart are also used for the table.

The following parameters are used for plotting a chart. These 3 values will come based on the skim matrix.

- The parameter `x_axis_max`: is the maximum distance you want to show on the x-axis.
- The parameter `x_axis_min`: is the minimum distance you want to show on the x-axis.
- The parameter `x_axis_interval`: is the interval on the x-axis.

! Important

To specify the x-axis min max, open your skim matrix in Omnitrans and check the min max values. Be sure to check that the *Total trips in the matrix* is same as *Total trips in the frequency table*. Both these values are shown in the output of this job. If they are not the same, your classes in the frequency table do not cover the entire range

of distances in the skim matrix.

```
$mode_matrix_number = [1,11,10,1] # trip matrix
$skim_matrix_number = [1,11,10,1,13,1] # skim matrix

$x_axis_max = 11 # max value on x-axis
$x_axis_min = 0 # min value on x-axis
$x_axis_interval = 1 # interval on x-axis
```

9.2.2 Method 2 - Irregular Ranges

Following are the inputs to this job. You will also need a encrypted file tld.rc in your job folder.

The following parameters are used to select the matrices and create a table.

- The parameter `mode_matrix_number`: is the matrix number of the trip matrix.
- The parameter `skim_matrix_number`: is the matrix number of the skim matrix.
- ~~The parameters used for the chart are also used for the table.~~

The following parameters are used for a generating a frequency table. These 2 values will come based on the skim matrix.

- The parameter `x_axis_min`: is an array of lower limits of the class on x-axis.
- The parameter `x_axis_max`: is an array of upper limits of the class on x-axis.
- The parameter `x_axis_interval`: is always set to zero.

! Important

To specify the x-axis min max, open your skim matrix in Omnitrans and check the min max values. Be sure to check that the *Total trips in the matrix* is same as *Total trips in the frequency table*. Both these values are shown in the output of this job. If they are not the same, your

classes in the frequency table do not cover the entire range of distances in the skim matrix.

```
$mode_matrix_number = [1,11,10,1] # trip matrix
$skim_matrix_number = [1,11,10,1,13,1] # skim matrix

$x_axis_min = [0,10,20,40] # lower limits
$x_axis_max = [10,20,40,100] # upper limits
$x_axis_interval = 0 # interval on x-axis
```

9.3 Outputs

Following are the outputs to this job:

- A tabular format that you can copy paste into excel.
- A chart that you can save as an image
- No chart is created for irregular ranges (Method 2).

9.4 Code

Download the encrypted file [tld.rc](#)

```
# OmniTRANS Job for 'Delft Tutorial Static'
# Created 2-9-2025 13:17:16
# Author 'Srirama'

=begin
This script creates a trip length distribution chart
based on trip and distance matrices. It uses the OtChart library
to visualize the distribution of trips by distance.
=end

require "OtChart"
```



```
# INPUTS

$mode_matrix_number = [1,11,10,1] # trip matrix
$skim_matrix_number = [1,11,10,1,13,1] # skim matrix

$x_axis_min = 0
$x_axis_max = 11
$x_axis_interval = 1

# Uncomment the following lines for irregular ranges
# $x_axis_min = [0,10,20,40] # lower limits
# $x_axis_max = [10,20,40,100] # upper limits
# $x_axis_interval = 0 # interval on x-axis

requireCrypted($0t.dirJob+"tld.rc")
```

Part III

Others

10 Weekdagmodule

In the weekdagmodule, there are options to generate shapefiles in GEOMILIEU and CIMLK formats. In these shapefiles, there are several fields. The definition of these fields are as follows:

10.1 Fieldnames in Geomilieu Export

ANODE	A-knoop		
BNODE	B-knoop		
LINKNR	Linknummer		
STAGPCT	Percentage Stagnerend verkeer		
	Wettelijke snelheden		
Motoren dag	V_MCDAY		
Personenauto dag	V_LVDAY		
MiddelZware vracht dag	V_LTDAY		
Zware vracht dag	V_HTDAY		
Motoren avond	V_MCEVE		
Personenauto avond	V_LVEVE		
MiddelZware vracht avond	V_LTEVE		
Zware vracht avond	V_HTEVE		
Motoren nacht	V_MCNl		
Personenauto nacht	V_LVNI		
MiddelZware vracht nacht	V_LTNI		
Zware vracht nacht	V_HTNI		
	Intensiteiten		
	richting A > B	richting B > A	doorsnede
MVT etmaal	LOADAB	LOADBA	TOTINTENS
MVT dag	-	-	-
MVT avond	-	-	-
MVT nacht	-	-	-
Motoren dag	INTMCDAYAB	INTMCDAYBA	FLOWMCDAY
Motoren avond	INTMCEVEAB	INTMCEVEBA	FLOWMCEVE
Motoren nacht	INTMCNIAB	INTMCNIBA	FLOWMCNI
Personenauto dag	INTLVDAYAB	INTLVDAYBA	FLOWLVDAY
Personenauto avond	INTLVEVEAB	INTLVEVEBA	FLOWLVEVE
Personenauto nacht	INTLVNIAB	INTLVNIBA	FLOWLVNI
MiddelZware vracht dag	INTLTDAYAB	INTLTDAYBA	FLOWLTDAY
MiddelZware vracht avond	INTLTEVEAB	INTLTEVEBA	FLOWLTEVE
MiddelZware vracht nacht	INTLTNIAB	INTLTNIBA	FLOWLTNI
Zware vracht dag	INTHTDAYAB	INTHTDAYBA	FLOWHTDAY
Zware vracht avond	INTHTEVEAB	INTHTEVEBA	FLOWHTEVE
Zware vracht nacht	INTHTNIAB	INTHTNIBA	FLOWHTNI
	percentages per uur		
	richting A > B	richting B > A	doorsnede
MVT etmaal	-	-	-
MVT dag	GPCTDAYAB	GPCTDAYBA	PFLOWDAY
MVT avond	GPCTEVEAB	GPCTEVEBA	PFLOWEVE
MVT nacht	GPCTNIAB	GPCTNIBA	PFLOWNI
Motoren dag	PCTMCDAYAB	PCTMCDAYBA	PFLOWMCDAY
Motoren avond	PCTMCEVEAB	PCTMCEVEBA	PFLOWMCEVE
Motoren nacht	PCTMCNIAB	PCTMCNIBA	PFLOWMCNI
Personenauto dag	PCTLVDAYAB	PCTLVDAYBA	PFLOWLVDAY
Personenauto avond	PCTLVEVEAB	PCTLVEVEBA	PFLOWLVEVE
Personenauto nacht	PCLTVNIAB	PCLTVNIBA	PFLOWLVNI
MiddelZware vracht dag	PCLTLDAYAB	PCLTLDAYBA	PFLOWLTDAY
MiddelZware vracht avond	PCLLTEVEAB	PCLLTEVEBA	PFLOWLTEVE
MiddelZware vracht nacht	PCLLTNIAB	PCLLTNIBA	PFLOWLTNI
Zware vracht dag	PCTHTDAYAB	PCTHTDAYBA	PFLOWHTDAY
Zware vracht avond	PCTHTEVEAB	PCTHTEVEBA	PFLOWHTEVE
Zware vracht nacht	PCTHTNIAB	PCTHTNIBA	PFLOWHTNI

10.2 Dagdeel Calculation Periods

```
DAY => dag = 12 uur  
EVE => avond = 4 uur  
NI => nacht = 8 uur
```

Rekenvoorbeeld

```
Dag LV * 12 + Avond LV * 4 + Nacht LV * 8 => LV Etmaal
```

Part IV

Prototype4

Why?

This model takes a shift from trip-based model to a tour based model.

Process-Flowchart

11 Modules

11.1 CARMOD Module

11.1.1 Purpose

Its primary function is to ensure that the car ownership (auto-bezit) within the Model is consistent with the car ownership totals provided by the DYNAMO model. Additionally, CARMOD is responsible for spatially distributing this car ownership.

11.1.2 Inputs

Following are the inputs to this job.

```
fratarTest.source_cube = '2020_KAL' # Geef MatrixCube op (hier: 2016_SMC)
fratarTest.matrix = [1,2,1,103]      # Geef Matrix (1 PER AANROEP!) (Hier Auto OS)
```

11.1.3 .coeff File

This file contains the updated Alternative Specific Constants (ASCs) and other coefficients for the autobezit model, which are used by the SES program

See Online Version for a sample .coeff file.

11.1.4 .sum File

Download the code.[matrixcompress.rb](#)

11.1.5 .log File

11.2 QUAD

11.2.1 Purpose

Some text explaining what the code does.

11.2.2 Inputs

Following are the inputs to this job.

11.2.3 Outputs

Following are the outputs to this job.

11.2.4 Code

Download the code.[matrixcompress.rb](#)

11.3 IntraLOS

11.3.1 Purpose

Some text explaining what the code does.

11.3.2 Inputs

Following are the inputs to this job.

11.3.3 Outputs

Following are the outputs to this job.

11.3.4 Code

Download the code [matrixcompress.rb](#)