

Dragan's live session 2

Dragan Doder



Methods in AI Research

Before we start...

- Next week: Wrap up session on Thursday
 - A mock exam (\approx twice shorter than the final exam) – available on Monday on BB
 - A quiz on BB

Before we start...

- Next week: Wrap up session on Thursday
 - A mock exam (\approx twice shorter than the final exam) – available on Monday on BB
 - A quiz on BB
- Today:
 - Quiz questions
 - Exercises from the slides
 - Your questions regarding Lecture 14
 - One to one questions (I will stay on Teams)

Before we start...

- Next week: Wrap up session on Thursday
 - A mock exam (\approx twice shorter than the final exam) – available on Monday on BB
 - A quiz on BB
- Today:
 - Quiz questions
 - Exercises from the slides
 - Your questions regarding Lecture 14
 - One to one questions (I will stay on Teams)
 - Your question regarding exercises - no time for all, please contact me for One to One questions (or later via Teams)


Quiz Questions

Before we start...

- S is a **complete** extension if it is an admissible set and every argument defended by S belongs to S
- S is a **preferred** extension if it is a maximal (for \subseteq) complete extension
- S is a **stable** extension if it is a complete set and attacks all the arguments that do not belong to S
- S is a **grounded** extension if it is the minimal (for \subseteq) complete extension (can be calculated as follows: (1) non-attacked are accepted, those attacked by accepted are rejected (2) ignore arguments that are already accepted/rejected and repeat the process)


Question 1

Consider the graph depicted above (note that a is a self-attacking argument). Find all grounded, preferred and stable extensions.



Question 1

Consider the graph depicted above (note that a is a self-attacking argument). Find all grounded, preferred and stable extensions.




Grounded & preferred: $\{b\}$; Stable: none

Typical mistakes:

- ❶ Grounded is \emptyset – False!
 - Non-attacked arguments are in every extension
 - Check the procedure from the slides

Question 1

Consider the graph depicted above (note that a is a self-attacking argument). Find all grounded, preferred and stable extensions.



Grounded & preferred: $\{b\}$; Stable: none

Typical mistakes:

1 Grounded is \emptyset – False!

- Non-attacked arguments are in every extension
- Check the procedure from the slides


2 Stable is \emptyset – False?

- \emptyset is a set of arguments (with 0 elements), which does not satisfy the definition of stable semantics
- $\emptyset \neq \{\emptyset\}$

Question 2

Consider the graph depicted above. Which of the following sentences is true?


- 1 there are 4 complete extensions, and 2 of them are preferred
- 2 there are 6 complete extensions, and 3 of them are preferred
- 3 there are 5 complete extensions, and they are all preferred
- 4 there are 3 complete extensions, and they are all preferred



Question 2

Consider the graph depicted above. Which of the following sentences is true?

- ① there are 4 complete extensions, and 2 of them are preferred
- ② there are 6 complete extensions, and 3 of them are preferred
- ③ there are 5 complete extensions, and they are all preferred
- ④ there are 3 complete extensions, and they are all preferred




- Complete = conflict free + defends its elements + contains everything it defends
- Preferred = maximal complete (wrt \subseteq , which means no proper superset is also complete)
- Complete: $\emptyset, \{a\},$

Question 2

Consider the graph depicted above. Which of the following sentences is true?

- ① there are 4 complete extensions, and 2 of them are preferred
- ② there are 6 complete extensions, and 3 of them are preferred
- ③ there are 5 complete extensions, and they are all preferred
- ④ there are 3 complete extensions, and they are all preferred




- Complete = conflict free + defends its elements + contains everything it defends
- Preferred = maximal complete (wrt \subseteq , which means no proper superset is also complete)
- Complete: \emptyset , $\{a\}$, $\{d\}$,

Question 2

Consider the graph depicted above. Which of the following sentences is true?

- ① there are 4 complete extensions, and 2 of them are preferred
- ② there are 6 complete extensions, and 3 of them are preferred
- ③ there are 5 complete extensions, and they are all preferred
- ④ there are 3 complete extensions, and they are all preferred




- Complete = conflict free + defends its elements + contains everything it defends
- Preferred = maximal complete (wrt \subseteq , which means no proper superset is also complete)
- Complete: \emptyset , $\{a\}$, $\{d\}$, $\{a, c\}$,

Question 2

Consider the graph depicted above. Which of the following sentences is true?

- ① there are 4 complete extensions, and 2 of them are preferred
- ② there are 6 complete extensions, and 3 of them are preferred
- ③ there are 5 complete extensions, and they are all preferred
- ④ there are 3 complete extensions, and they are all preferred




- Complete = conflict free + defends its elements + contains everything it defends
- Preferred = maximal complete (wrt \subseteq , which means no proper superset is also complete)
- Complete: \emptyset , $\{a\}$, $\{d\}$, $\{a, c\}$, $\{b, d\}$, $\{a, d\}$

Question 2

Consider the graph depicted above. Which of the following sentences is true?

- ① there are 4 complete extensions, and 2 of them are preferred
- ② there are 6 complete extensions, and 3 of them are preferred
- ③ there are 5 complete extensions, and they are all preferred
- ④ there are 3 complete extensions, and they are all preferred




- Complete = conflict free + defends its elements + contains everything it defends
- Preferred = maximal complete (wrt \subseteq , which means no proper superset is also complete)
- Complete: \emptyset , $\{a\}$, $\{d\}$, $\{a, c\}$, $\{b, d\}$, $\{a, d\}$
- Preferred: $\{a, c\}$, $\{b, d\}$, $\{a, d\}$

Question 3

Consider the graph depicted above. Under Preferred semantics, which of the following sentences is true:


- ❶ all three arguments are either credulously or sceptically justified
- ❷ all three arguments are indefensible
- ❸ either a or b is sceptically justified
- ❹ both a and b are credulously justified



Question 3

Consider the graph depicted above. Under Preferred semantics, which of the following sentences is true:

- 1 all three arguments are either credulously or sceptically justified
- 2 all three arguments are indefensible
- 3 either a or b is sceptically justified
- 4 both a and b are credulously justified




- Preferred: $\{a\}, \{b\}$

Question 3

Consider the graph depicted above. Under Preferred semantics, which of the following sentences is true:

- 1 all three arguments are either credulously or sceptically justified
- 2 all three arguments are indefensible
- 3 either a or b is sceptically justified
- 4 both a and b are credulously justified




- Preferred: $\{a\}, \{b\}$
- credulously justified = belong to some extension; sceptically justified = belong to all extensions

Question 3

Consider the graph depicted above. Under Preferred semantics, which of the following sentences is true:

- 1 all three arguments are either credulously or sceptically justified
- 2 all three arguments are indefensible
- 3 either a or b is sceptically justified
- 4 both a and b are credulously justified



- Preferred: $\{a\}, \{b\}$
- credulously justified = belong to some extension; sceptically justified = belong to all extensions
- Thus, both a and b are credulously justified

Question 4

Given the knowledge base $\mathcal{K} = \{p, q, r\}$ and the rule base $\mathcal{R} = \{r_1 : p \Rightarrow a; r_2 : q \Rightarrow b; r_3 : r \Rightarrow c; r_4 : \neg b \Rightarrow \neg c; r_5 : c \Rightarrow \neg a\}$, it is **not** possible to construct an argument whose conclusion is:

- 1 a
- 2 $\neg a$
- 3 c
- 4 $\neg c$

Each possible conclusion must be inferred by a rule (if it is not in \mathcal{K}).
In order to infer $\neg c$, we would need to apply r_4 . But we cannot infer $\neg b$.

Question 5

Given the knowledge base $\mathcal{K} = \{p, q, t\}$ and the rule base $\mathcal{R} = \{r_1 : p \Rightarrow s; r_2 : q \Rightarrow \neg s; r_3 : q, t \Rightarrow \neg n(r_1)\}$, we can construct the arguments:

$A_1 : p$

$A_2 : A_1 \Rightarrow s$

$B_1 : q$

$B_2 : B_1 \Rightarrow \neg s$

$C : t$

$D : B_1, C \Rightarrow \neg n(r_1)$

Find all the attacks between those arguments. For each attack determine its type (rebut/undercut/undermine).

Question 5

Given the knowledge base $\mathcal{K} = \{p, q, t\}$ and the rule base $\mathcal{R} = \{r_1 : p \Rightarrow s; r_2 : q \Rightarrow \neg s; r_3 : q, t \Rightarrow \neg n(r_1)\}$, we can construct the arguments:

$A_1 : p$

$A_2 : A_1 \Rightarrow s$

$B_1 : q$

$B_2 : B_1 \Rightarrow \neg s$

$C : t$

$D : B_1, C \Rightarrow \neg n(r_1)$

Find all the attacks between those arguments. For each attack determine its type (rebut/undercut/undermine).

- B_2 and A_2 attack each other

Question 5

Given the knowledge base $\mathcal{K} = \{p, q, t\}$ and the rule base $\mathcal{R} = \{r_1 : p \Rightarrow s; r_2 : q \Rightarrow \neg s; r_3 : q, t \Rightarrow \neg n(r_1)\}$, we can construct the arguments:

$A_1 : p$

$A_2 : A_1 \Rightarrow s$

$B_1 : q$

$B_2 : B_1 \Rightarrow \neg s$

$C : t$

$D : B_1, C \Rightarrow \neg n(r_1)$

Find all the attacks between those arguments. For each attack determine its type (rebut/undercut/undermine).

- B_2 and A_2 attack each other—rebut

Question 5

Given the knowledge base $\mathcal{K} = \{p, q, t\}$ and the rule base $\mathcal{R} = \{r_1 : p \Rightarrow s; r_2 : q \Rightarrow \neg s; r_3 : q, t \Rightarrow \neg n(r_1)\}$, we can construct the arguments:

$A_1 : p$

$A_2 : A_1 \Rightarrow s$

$B_1 : q$

$B_2 : B_1 \Rightarrow \neg s$

$C : t$

$D : B_1, C \Rightarrow \neg n(r_1)$

Find all the attacks between those arguments. For each attack determine its type (rebut/undercut/undermine).

- B_2 and A_2 attack each other—rebut
- D attacks A_2

Question 5

Given the knowledge base $\mathcal{K} = \{p, q, t\}$ and the rule base $\mathcal{R} = \{r_1 : p \Rightarrow s; r_2 : q \Rightarrow \neg s; r_3 : q, t \Rightarrow \neg n(r_1)\}$, we can construct the arguments:

$A_1 : p$

$A_2 : A_1 \Rightarrow s$

$B_1 : q$

$B_2 : B_1 \Rightarrow \neg s$

$C : t$

$D : B_1, C \Rightarrow \neg n(r_1)$

Find all the attacks between those arguments. For each attack determine its type (rebut/undercut/undermine).

- B_2 and A_2 attack each other – rebut
- D attacks A_2 – undercut

Question 6

Consider a FO language that contains the constant symbol UU (that stands for Utrecht University), the unary relation symbol Tea and binary relation symbols $StudiesAt$ ($At(x, y)$ means that x studies at y) and $Drinks$ ($Drinks(x, y)$ stands for x drinks y). Select the correct translation of the sentence "There is a student of Utrecht University which does not drink any tea." to FOL.

$$\exists x(StudiesAt(x, UU) \wedge \neg \exists y(Tea(y) \wedge Drinks(x, y)))$$

Question 6

Consider a FO language that contains the constant symbol UU (that stands for Utrecht University), the unary relation symbol Tea and binary relation symbols $StudiesAt$ ($At(x, y)$ means that x studies at y) and $Drinks$ ($Drinks(x, y)$ stands for x drinks y). Select the correct translation of the sentence
There is a student of Utrecht University which does not drink any tea.
to FOL.

$$\exists x (StudiesAt(x, UU) \wedge \neg \exists y (Tea(y) \wedge Drinks(x, y)))$$

- $\forall x At(x, UU) \rightarrow Smart(x)$

“Everyone at UU is smart”

- $\exists x At(x, UU) \wedge Tall(x)$

“Someone at UU is Tall”

Question 7

Is it following DL statement valid?

$$\exists r.C \sqsubseteq \forall r.C$$

Question 7

Is it following DL statement valid?

$$\exists r.C \sqsubseteq \forall r.C$$

Answer: Not true!

- $\exists r.C$ – individuals that are in relation r with some element in C
- $\forall r.C$ – individuals that are in relation r only with elements in C

And how about this?

Is it following DL statement valid?

$$\forall r.C \sqsubseteq \exists r.C$$

And how about this?

Is it following DL statement valid?

$$\forall r.C \sqsubseteq \exists r.C$$


Answer: It is not!

If I do not have any brother, then

- I belong to the class given by $\forall \textit{brother.Criminal}$
- but I do not belong to the class given by $\exists \textit{brother.Criminal}$


Exercises from the slides

Exercise 1




- 1 Calculate stable, preferred, complete and grounded extensions
- 2 For each semantics, determine which arguments are sceptically justified, and which are credulously justified.

Exercise 1




- 1 Complete:
 \emptyset (this set is a complete extension iff every argument is attacked)

Exercise 1




- 1 Complete:
- \emptyset (this set is a complete extension iff every argument is attacked)
 - $\{c, d\}$, $\{b, d\}$

Exercise 1




- 1 Complete:
 \emptyset (this set is a complete extension iff every argument is attacked)
 $\{c, d\}$, $\{b, d\}$
- 2 Preferred - those complete that are not subsets of some other complete extension.

Exercise 1




- 1 Complete:
 \emptyset (this set is a complete extension iff every argument is attacked)
 $\{c, d\}$, $\{b, d\}$
- 2 Preferred - those complete that are not subsets of some other complete extension.
- 3 Stable extensions - they must be preferred, just check if they attack every argument outside itself (and if they are conflict-free)

Exercise 1




- 1 Complete:
 \emptyset (this set is a complete extension iff every argument is attacked)
 $\{c, d\}$, $\{b, d\}$
- 2 Preferred - those complete that are not subsets of some other complete extension.
- 3 Stable extensions - they must be preferred, just check if they attack every argument outside itself (and if they are conflict-free)
- 4 Grounded - minimal complete, actually it is the intersection of all complete extensions.

Exercise 1



- 1 Complete:
 \emptyset (this set is a complete extension iff every argument is attacked)
 $\{c, d\}$, $\{b, d\}$
- 2 Preferred - those complete that are not subsets of some other complete extension.
- 3 Stable extensions - they must be preferred, just check if they attack every argument outside itself (and if they are conflict-free)
- 4 Grounded - minimal complete, actually it is the intersection of all complete extensions. We can also use the procedure to find it


Exercise 1



- 1 Complete:
 \emptyset (this set is a complete extension iff every argument is attacked)
 $\{c, d\}$, $\{b, d\}$
- 2 Preferred - those complete that are not subsets of some other complete extension.
- 3 Stable extensions - they must be preferred, just check if they attack every argument outside itself (and if they are conflict-free)
- 4 Grounded - minimal complete, actually it is the intersection of all complete extensions. We can also use the procedure to find it


Correction: all sceptically accepted are already credulously accepted.

Exercise 2



Calculate stable, preferred, complete and grounded extensions

Exercise 2




Calculate stable, preferred, complete and grounded extensions

Complete: \emptyset , $\{e\}$, $\{c, d\}$

Structured argumentation Exercise 1

$$\mathcal{K} = \{Bird, Penguin\}$$

$$\mathcal{R}_d = \{r_1: Bird \Rightarrow Flies, r_2: Penguin \Rightarrow \neg Flies, r_3: Penguin \Rightarrow \neg r_1\}.$$



Structured argumentation Exercise 2

Take the knowledge base

$$\mathcal{K} = \{Bat, Baby\}$$

and the rule-base

$$\mathcal{R}_d = \{r_1: Bat \Rightarrow Flies, r_2: Baby \Rightarrow \neg Flies, r_3: Bat \rightarrow Mammal, r_4: Mammal \Rightarrow \neg Flies, r_5: Baby \Rightarrow \neg r_1, r_6: Bat \Rightarrow \neg r_4\}$$

- A. Construct all the arguments which can be built using this knowledge and rule base.
- B. Indicate which of these arguments attack each other, and what the type of each attack is (rebut/undercut/undermine).

Structured argumentation Exercise 2

$\mathcal{K} = \{Bat, Baby\}$

$\mathcal{R}_d = \{r_1: Bat \Rightarrow Flies, r_2: Baby \Rightarrow \neg Flies, r_3: Bat \rightarrow$

$Mammal, r_4: Mammal \Rightarrow \neg Flies, r_5: Baby \Rightarrow \neg r_1, r_6: Bat \Rightarrow \neg r_4\}$

Baby



Bat

Structured argumentation Exercise 2

$\mathcal{K} = \{Bat, Baby\}$

$\mathcal{R}_d = \{r_1: Bat \Rightarrow Flies, r_2: Baby \Rightarrow \neg Flies, r_3: Bat \rightarrow$

$Mammal, r_4: Mammal \Rightarrow \neg Flies, r_5: Baby \Rightarrow \neg r_1, r_6: Bat \Rightarrow \neg r_4\}$




Structured argumentation Exercise 2

$\mathcal{K} = \{Bat, Baby\}$

$\mathcal{R}_d = \{r_1: Bat \Rightarrow Flies, r_2: Baby \Rightarrow \neg Flies, r_3: Bat \rightarrow$

$Mammal, r_4: Mammal \Rightarrow \neg Flies, r_5: Baby \Rightarrow \neg r_1, r_6: Bat \Rightarrow \neg r_4\}$





Structured argumentation Exercise 2

$\mathcal{K} = \{Bat, Baby\}$

$\mathcal{R}_d = \{r_1: Bat \Rightarrow Flies, r_2: Baby \Rightarrow \neg Flies, r_3: Bat \rightarrow$

$Mammal, r_4: Mammal \Rightarrow \neg Flies, r_5: Baby \Rightarrow \neg r_1, r_6: Bat \Rightarrow \neg r_4\}$




Structured argumentation Exercise 2

$\mathcal{K} = \{Bat, Baby\}$

$\mathcal{R}_d = \{r_1: Bat \Rightarrow Flies, r_2: Baby \Rightarrow \neg Flies, r_3: Bat \rightarrow$

$Mammal, r_4: Mammal \Rightarrow \neg Flies, r_5: Baby \Rightarrow \neg r_1, r_6: Bat \Rightarrow \neg r_4\}$




Structured argumentation Exercise 2

$\mathcal{K} = \{Bat, Baby\}$

$\mathcal{R}_d = \{r_1: Bat \Rightarrow Flies, r_2: Baby \Rightarrow \neg Flies, r_3: Bat \rightarrow$

$Mammal, r_4: Mammal \Rightarrow \neg Flies, r_5: Baby \Rightarrow \neg r_1, r_6: Bat \Rightarrow \neg r_4\}$



Your questions

Your questions 1

Question

I do not really know how to find all complete extensions. Is there an algorithm for that?

Your questions 1

Question

I do not really know how to find all complete extensions. Is there an algorithm for that?

No. Only for the grounded semantics there is an algorithm.

Your questions 1

Question

I do not really know how to find all complete extensions. Is there an algorithm for that?

No. Only for the grounded semantics there is an algorithm.

Question

1) I did not fully understand what is meant by a minimal or maximal extension. Does this mean the extension that has the least or most elements that is still complete?

2) Shouldn't all arguments that are sceptically justified also be credulously justified?

Your questions 1

Question

I do not really know how to find all complete extensions. Is there an algorithm for that?

No. Only for the grounded semantics there is an algorithm.

Question

1) I did not fully understand what is meant by a minimal or maximal extension. Does this mean the extension that has the least or most elements that is still complete?

2) Shouldn't all arguments that are sceptically justified also be credulously justified?

1) Maximal means maximal wrt \subseteq . For example, if we have 3 complete extensions: $\{a, b, c, d, e, f\}$, $\{a, g\}$ and $\{a, b, c, e, f\}$, the first two will be preferred.

Your questions 1

Question

I do not really know how to find all complete extensions. Is there an algorithm for that?

No. Only for the grounded semantics there is an algorithm.

Question

1) I did not fully understand what is meant by a minimal or maximal extension. Does this mean the extension that has the least or most elements that is still complete?

2) Shouldn't all arguments that are sceptically justified also be credulously justified?

1) Maximal means maximal wrt \subseteq . For example, if we have 3 complete extensions: $\{a, b, c, d, e, f\}$, $\{a, g\}$ and $\{a, b, c, e, f\}$, the first two will be preferred. Minimal is again minimal wrt \subseteq .

2) Yes! Sorry to all, I omitted sceptically accepted from the set of credulously accepted in the exercises, but they also belong there!

Your questions 2

Question

The semantic extensions lecture was hard for me to understand, perhaps because i do not directly see an application for this. If you could go through the exercises in this quiz regarding the extensions that would be great.

Your questions 2

Question

The semantic extensions lecture was hard for me to understand, perhaps because I do not directly see an application for this. If you could go through the exercises in this quiz regarding the extensions that would be great.

Question

Thank you for the lectures! I thought it was interesting, also the non-obligatory lecture.

However, I would like some more explanations or examples of the construction of arguments from a knowledge base with the following rules. I feel that part is discussed briefly, but it is a little complicated. Especially question 4 in the quiz; I do not feel I have the knowledge to answer this. I would like to practice a bit more with this. The bat-example in the lecture was really hard.

Can you also maybe explain the rebuttal, undermine and undercut with respect to the knowledge base and construction of arguments. In a graph I can see which attack is performed, but this is hard for me in a simple line of arguments.

Your questions 2

Question

The semantic extensions lecture was hard for me to understand, perhaps because I do not directly see an application for this. If you could go through the exercises in this quiz regarding the extensions that would be great.

Question

Thank you for the lectures! I thought it was interesting, also the non-obligatory lecture.

However, I would like some more explanations or examples of the construction of arguments from a knowledge base with the following rules. I feel that part is discussed briefly, but it is a little complicated. Especially question 4 in the quiz; I do not feel I have the knowledge to answer this. I would like to practice a bit more with this. The bat-example in the lecture was really hard.

Can you also maybe explain the rebuttal, undermine and undercut with respect to the knowledge base and construction of arguments. In a graph I can see which attack is performed, but this is hard for me in a simple line of arguments.

General comment: if this lecture didn't answer your question completely, please ask me later via Teams.

Your questions 3

Question

1. Notation for concepts related to attacks and undercutting is inconsistent. E.g. slides have " $\text{Conc}(A) = \neg n(r)$ for some B' with defeasible top rule r " where the notation $\neg n(r)$ is used but the exercises use $\neg n(r)$
2. Why justifications have are named sceptical and credulous? Both names seem to suggest that a the justification is not very strong or certain.
3. Is spelling sceptical as skeptical correct? Or is it a different word?
A. Could you explain the intuitive meaning of labelling arguments as "sceptically" and "credulously" justified? Why were these words chosen?

Your questions 3

Question

1. Notation for concepts related to attacks and undercutting is inconsistent. E.g. slides have " $\text{Conc}(A) = \neg n(r)$ for some B' with defeasible top rule r" where the notation $\neg n(r)$ is used but the exercises use $\neg n(r)$
2. Why justifications have are named sceptical and credulous? Both names seem to suggest that a the justification is not very strong or certain.
3. Is spelling sceptical as skeptical correct? Or is it a different word?
A. Could you explain the intuitive meaning of labelling arguments as "sceptically" and "credulously" justified? Why were these words chosen?

Question

The formal argumentation was not all clear to me. The construction of the arguments and linking them to attacks can be covered more extensively.
If we have a rule that is r1: $q \Rightarrow a$, is $\neg a \Rightarrow \neg q$ also a rule in formal argumentation? (because in propositional logic : $q \Rightarrow a \Leftrightarrow \neg a \Rightarrow \neg q$)

Your questions 3

Question

1. Notation for concepts related to attacks and undercutting is inconsistent. E.g. slides have " $\text{Conc}(A) = \neg n(r)$ for some B' with defeasible top rule r " where the notation $\neg n(r)$ is used but the exercises use $\neg n(r)$
2. Why justifications have are named sceptical and credulous? Both names seem to suggest that a the justification is not very strong or certain.
3. Is spelling sceptical as skeptical correct? Or is it a different word?
A. Could you explain the intuitive meaning of labelling arguments as "sceptically" and "credulously" justified? Why were these words chosen?

Question

The formal argumentation was not all clear to me. The construction of the arguments and linking them to attacks can be covered more extensively.
If we have a rule that is $r1: q \Rightarrow a$, is $\neg a \Rightarrow \neg q$ also a rule in formal argumentation? (because in propositional logic : $q \Rightarrow a \Leftrightarrow \neg a \Rightarrow \neg q$)

\Rightarrow is an inference rule (can be also $p, q, r \Rightarrow s$), converse does not hold in general

Your questions 3

Question

1. Notation for concepts related to attacks and undercutting is inconsistent. E.g. slides have " $\text{Conc}(A) = \neg n(r)$ for some B' with defeasible top rule r" where the notation $\neg n(r)$ is used but the exercises use $\neg n(r)$
2. Why justifications have are named sceptical and credulous? Both names seem to suggest that a the justification is not very strong or certain.
3. Is spelling sceptical as skeptical correct? Or is it a different word?
A. Could you explain the intuitive meaning of labelling arguments as "sceptically" and "credulously" justified? Why were these words chosen?

Question

The formal argumentation was not all clear to me. The construction of the arguments and linking them to attacks can be covered more extensively.
If we have a rule that is $r1: q \Rightarrow a$, is $\neg a \Rightarrow \neg q$ also a rule in formal argumentation? (because in propositional logic : $q \Rightarrow a \Leftrightarrow \neg a \Rightarrow \neg q$)

\Rightarrow is an inference rule (can be also $p, q, r \Rightarrow s$), converse does not hold in general
It does not hold for defeasible rules: In the presence of LLE and RW (from Lecture 13, the last video), Contraposition implies Monotonicity (Monotonicity \approx not defeasible)

Your questions 4

Question

slides: Lecture 14: Formal argumentation

I have a question, exercise 1 answers on slide 15/25

part 2 of the question 1

I don't understand why you include 'd' in the sceptically justified arguments for 3 and 4, but you don't include it in the credulously justified arguments.

For example, preferred semantic (number 3 of the question answers) consists of:
 $E2 = c, d$ $E3 = b, d$ So I understand that 'c' and 'b' are credulously justified, since they are not in all preferred extensions but in at least one. I understand that 'd' is sceptically justified, because it is in all preferred extensions
However, why is 'd' not also credulously justified, because it is also in at least one extension?

Question

It's very difficult for me to understand the first video about formal argumentation. I watched it a few times and I still don't know what do the relations (complete, preferred) mean.

in Lec13, slide P10, why e also defends b?

More examples would be nice ^ _ ^

Your questions 5

Question

The completeness, preferability, stability, etc. are quite hard to remember. Some examples of them would also be fantastic please.

Semantics from the previous two lectures are also difficult and very unclear for me still.

I find it quite hard to find the complete, preferred, and stable extensions. Is there some sort of algorithm for finding these, like there is with the grounded?

Question

I'm not sure if i understand undercutting correctly.

During the lecture you talked about attacking the inference in "prof B says .." -> "lower taxes increase productivity" with the statement "prof B is not objective"

Does that mean undercutting plays out like " $A \rightarrow B$ " and then we attack the inference with something like " $(A \rightarrow C \wedge \neg C) \rightarrow \text{???}$ "

How do you represent the attack of an inference in such a scenario?

Can you give more examples how check preferred, stable and grounded? Does it need to be complete before preferred, stable or grounded is possible?

If i understood correctly: so undercutting is attacking the relation, undermining is attacking the argument and rebuttal is attacking the conclusion?

Difference between preferred extensions and complete extensions?

Your questions 6

Question

Could you go into the knowledge bases and arguments a bit more (questions 4 and 5 from this quiz)

I also noticed that in your answers for the exercises of part 1 that a sceptically justified argument is not also credulously justified, this seems strange to me since a sceptically justified argument belongs to all extensions, therefore it must also belong to at least one extension and thus be credulously justified. Is this a mistake or is credulous actually defined as belonging to at least one, but not all extensions? The semantics from the abstract argumentation are kind of difficult, could you maybe go over it again and explain in more detail how to get to the answers? (for example, the steps on how to find the grounded/preferred/etc extensions of a certain figure)

Question

Are all L13 bonus on microsoft Teams?

Yes! NMR - not at the exam