

Lecture 13: Non-monotonic reasoning

Dragan Doder

Methods in AI Research



Non-monotonic reasoning

- ▶ *Commonsense* reasoning \Rightarrow jumping to conclusions
 - ▶ The concert is scheduled for March 12th
 - ▶ I have the ticket

Non-monotonic reasoning

- ▶ *Commonsense* reasoning \Rightarrow jumping to conclusions
 - ▶ The concert is scheduled for March 12th
 - ▶ I have the ticket
 - ▶ Therefore, I will attend the concert on March 12th

Non-monotonic reasoning

- ▶ *Commonsense* reasoning \Rightarrow jumping to conclusions
 - ▶ The concert is scheduled for March 12th
 - ▶ I have the ticket
 - ▶ Therefore, I will attend the concert on March 12th
 - ▶ Pandemic \Rightarrow I will not attend the concert on March 12th

Non-monotonic reasoning

- ▶ *Commonsense* reasoning \Rightarrow jumping to conclusions
 - ▶ The concert is scheduled for March 12th
 - ▶ I have the ticket
 - ▶ Therefore, I will attend the concert on March 12th
 - ▶ Pandemic \Rightarrow I will not attend the concert on March 12th
- ▶ *Non-monotonicity – some conclusions are retracted after receiving new information*

What is non-monotonicity?

Monotonicity

M If $KB \models \alpha$, then $KB \cup \{\beta\} \models \alpha$

Monotonicity:

- ▶ consequences are robust under the addition of information
- ▶ $KB \subseteq KB' \Rightarrow \text{Conseq}(KB) \subseteq \text{Conseq}(KB')$

What is non-monotonicity?

Monotonicity

M If $KB \models \alpha$, then $KB \cup \{\beta\} \models \alpha$

Monotonicity:

- ▶ consequences are robust under the addition of information
- ▶ $KB \subseteq KB' \Rightarrow \text{Conseq}(KB) \subseteq \text{Conseq}(KB')$

A non-monotonic consequence relations violates monotony.

Usually denoted by \sim

What is non-monotonicity?

Monotonicity

M If $KB \models \alpha$, then $KB \cup \{\beta\} \models \alpha$

Monotonicity:

- ▶ consequences are robust under the addition of information
- ▶ $KB \subseteq KB' \Rightarrow \text{Conseq}(KB) \subseteq \text{Conseq}(KB')$

A non-monotonic consequence relations violates monotony.

Usually denoted by \sim

Two restricted variants of monotonicity:

Cautious monotonicity

CM If $KB \sim \alpha$ and $KB \sim \beta$, then $KB \cup \{\beta\} \sim \alpha$

Rational monotonicity

RM If $KB \sim \alpha$ and $KB \not\sim \neg\beta$, then $KB \cup \{\beta\} \sim \alpha$

Example 1

Tweety

Example 1

Tweety

KB : “Tweety is a bird”

α : “Tweety flies”

$$KB \sim \alpha$$

Example 1

Tweety

KB : “Tweety is a bird”

α : “Tweety flies”

$$KB \sim \alpha$$

β : “Tweety is a penguin”

$$KB \cup \{\beta\} \not\sim \alpha$$

Example 2

Nixon Diamond

- ▶ Quakers are pacifists
- ▶ Republicans are not pacifists

Example 2

Nixon Diamond

- ▶ Quakers are pacifists
- ▶ Republicans are not pacifists
- ▶ Nixon is both a quaker and a republican
(Richard Milhous Nixon – the 37th president of US)

Example 2

Nixon Diamond

- ▶ Quakers are pacifists
- ▶ Republicans are not pacifists
- ▶ Nixon is both a quaker and a republican
(Richard Milhous Nixon – the 37th president of US)
- ▶ Is Nixon a pacifist?

Circumscription

Circumscription

- ▶ **particular predicates** are assumed to be “as false as possible”
 - ▶ false for every object *except* those for which they are known to be true
- ▶ $Bird(x) \wedge \neg Abnormal_1(x) \rightarrow Flies(x)$

Circumscription

- ▶ **particular predicates** are assumed to be “as false as possible”
 - ▶ false for every object *except* those for which they are known to be true
- ▶ $Bird(x) \wedge \neg Abnormal_1(x) \rightarrow Flies(x)$
 - ▶ We **assume** $\neg Abnormal_1(Tweety)$, if we do not already know that $Abnormal_1(Tweety)$ holds
 - ▶ In that case, **we can derive** $Flies(Tweety)$
 - ▶ **but** the conclusion no longer holds if $Abnormal_1(Tweety)$ is asserted

Circumscription

- ▶ **particular predicates** are assumed to be “as false as possible”
 - ▶ false for every object *except* those for which they are known to be true
- ▶ $Bird(x) \wedge \neg Abnormal_1(x) \rightarrow Flies(x)$
 - ▶ We **assume** $\neg Abnormal_1(Tweety)$, if we do not already know that $Abnormal_1(Tweety)$ holds
 - ▶ In that case, **we can derive** $Flies(Tweety)$
 - ▶ **but** the conclusion no longer holds if $Abnormal_1(Tweety)$ is asserted
- ▶ an example of *model preference* logic
 - ▶ one model is preferred to another if it has *fewer* abnormal objects

Multiple inheritance

Nixon Diamond

$Republican(Nixon) \wedge Quaker(Nixon)$

$Republican(x) \wedge \neg Abnormal_2(x) \rightarrow \neg Pacifist(x)$

$Quaker(x) \wedge \neg Abnormal_3(x) \rightarrow Pacifist(x)$

Multiple inheritance

Nixon Diamond

$Republican(Nixon) \wedge Quaker(Nixon)$

$Republican(x) \wedge \neg Abnormal_2(x) \rightarrow \neg Pacifist(x)$

$Quaker(x) \wedge \neg Abnormal_3(x) \rightarrow Pacifist(x)$

- ▶ two preferred models:
 - ▶ m_1 : $Abnormal_2(Nixon)$ and $Pacifist(Nixon)$ hold and
 - ▶ m_2 : $Abnormal_3(Nixon)$ and $\neg Pacifist(Nixon)$ hold

Multiple inheritance

Nixon Diamond

$Republican(Nixon) \wedge Quaker(Nixon)$

$Republican(x) \wedge \neg Abnormal_2(x) \rightarrow \neg Pacifist(x)$

$Quaker(x) \wedge \neg Abnormal_3(x) \rightarrow Pacifist(x)$

- ▶ two preferred models:
 - ▶ m_1 : $Abnormal_2(Nixon)$ and $Pacifist(Nixon)$ hold and
 - ▶ m_2 : $Abnormal_3(Nixon)$ and $\neg Pacifist(Nixon)$ hold
- ▶ a variant – *prioritized circumscription*
 - ▶ giving priority to religious beliefs $\Rightarrow Abnormal_3$ minimized
 - ▶ conclusion: $Pacifist(Nixon)$

Default logic

Default logic

- ▶ Default rules:

$$P : J_1, \dots, J_n / C$$

- ▶ P – prerequisite, C – conclusion, J_i – justifications
- ▶ if P , then infer C , unless some J_i can be proven false

- ▶ Example:

$$Bird(x) : Flies(x) / Flies(x)$$

- ▶ $Bird(x)$ is true and $Flies(x)$ is consistent with what is inferred, then $Flies(x)$ may be concluded by default

Multiple inheritance

Nixon Diamond

$Republican(Nixon) \wedge Quaker(Nixon)$

$Republican(x) : \neg Pacifist(x) / \neg Pacifist(x)$

$Quaker(x) : Pacifist(x) / Pacifist(x)$

- ▶ *extension* – a maximal set of consequences of the theory
 - ▶ if we apply one rule first, we extend KB in a way that another rule can be blocked
- ▶ Nixon Diamond has two extensions

Multiple inheritance

Nixon Diamond

$Republican(Nixon) \wedge Quaker(Nixon)$

$Republican(x) : \neg Pacifist(x) / \neg Pacifist(x)$

$Quaker(x) : Pacifist(x) / Pacifist(x)$

- ▶ *extension* – a maximal set of consequences of the theory
 - ▶ if we apply one rule first, we extend *KB* in a way that another rule can be blocked
- ▶ Nixon Diamond has two extensions

What follows from a default theory:

- ▶ *Sceptical* consequences – formulas that are contained in **every** extension
- ▶ *Credulous* consequences – formulas that are contained in **some** extension

Argumentation-based approach

Argumentation-based approach to NMR

1. Formalize the problem: build a knowledge base KB and a rule base R
2. Construct arguments and attacks (ASPIC+)
3. Calculate extensions (choose a semantics S)
4. Derive conclusions of *justified* arguments

Argumentation-based approach to NMR

1. Formalize the problem: build a knowledge base KB and a rule base R
2. Construct arguments and attacks (ASPIC+)
3. Calculate extensions (choose a semantics S)
4. Derive **conclusions** of *justified* arguments
 - ▶ α is sceptically S –acceptable if and only if all S –extensions contain an argument with **conclusion** α
 - ▶ α is credulously S –acceptable if and only if at least one S –extension contains an argument with **conclusion** α

Tweety & argumentation

Rules:

- ▶ Birds fly
- ▶ Penguins don't fly

Tweety & argumentation


Rules:

- ▶ Birds fly
- ▶ Penguins don't fly
- ▶ ...but also: penguins are exceptions for the first rule

Tweety & argumentation

Rules:


- ▶ Birds fly
- ▶ Penguins don't fly
- ▶ ...but also: penguins are exceptions for the first rule



Tweety & argumentation

Rules:

- ▶ Birds fly
- ▶ Penguins don't fly
- ▶ ...but also: penguins are exceptions for the first rule



- ▶ One extension: $\{a, c\}$
- ▶ Conclusion of *c* accepted \Rightarrow Tweety does not fly!

System P

Idea: preferences over models

- ▶ Classical logic: $\alpha \models \beta$ iff *all* models of α are also models of β

Idea: preferences over models

- ▶ Classical logic: $\alpha \models \beta$ iff *all* models of α are also models of β
- ▶ Idea: $\alpha \sim \beta$ iff *all most normal (preferred)* models of α are also models of β

Idea: preferences over models

- ▶ Classical logic: $\alpha \models \beta$ iff *all* models of α are also models of β
- ▶ Idea: $\alpha \sim \beta$ iff *all most normal (preferred)* models of α are also models of β

For example:

$m_1 : p = r = \text{true}; q = \text{false}$

$m_2 : p = q = \text{true}; r = \text{false}$

$m_1 < m_2$ – m_1 is preferred

Idea: preferences over models

- ▶ Classical logic: $\alpha \models \beta$ iff *all* models of α are also models of β
- ▶ Idea: $\alpha \sim \beta$ iff *all most normal (preferred)* models of α are also models of β

For example:

$m_1 : p = r = \text{true}; q = \text{false}$

$m_2 : p = q = \text{true}; r = \text{false}$

$m_1 < m_2$ – m_1 is preferred

Then:

- ▶ $p \sim r$
- ▶ $p \wedge q \not\sim r$

System P – The core properties of non-monotonic reasoning

REF $\alpha \sim \alpha$ [reflexivity]

LLE
$$\frac{\models \alpha \leftrightarrow \beta \quad \alpha \sim \gamma}{\beta \sim \gamma}$$
 [left logical equivalence]

RW
$$\frac{\models \alpha \rightarrow \beta \quad \gamma \sim \alpha}{\gamma \sim \beta}$$
 [right weakening]

CUT
$$\frac{\alpha \wedge \beta \sim \gamma \quad \alpha \sim \beta}{\alpha \sim \gamma}$$

OR
$$\frac{\alpha \sim \gamma \quad \beta \sim \gamma}{\alpha \vee \beta \sim \gamma}$$

CM
$$\frac{\alpha \sim \beta \quad \alpha \sim \gamma}{\alpha \wedge \beta \sim \gamma}$$
 [cautious monotonicity]

Characterization result

Preferential structure S :

- ▶ a set of states Ω (the sets contain models)
- ▶ an irreflexive, transitive relation $<$ on Ω

Characterization result

Preferential structure S :

- ▶ a set of states Ω (the sets contain models)
 - ▶ an irreflexive, transitive relation $<$ on Ω
-
- ▶ Each S defines one relation \sim_S
 - ▶ $\alpha \sim_S \beta$ iff β holds in all *$<$ -minimal models of α*

Characterization result

Preferential structure S :

- ▶ a set of states Ω (the sets contain models)
 - ▶ an irreflexive, transitive relation $<$ on Ω
-
- ▶ Each S defines one relation \vdash_S
 - ▶ $\alpha \vdash_S \beta$ iff β holds in all *$<$ -minimal models of α*

Theorem (KLM '90)

A consequence relation \vdash satisfies System P iff $\vdash = \vdash_S$ for some preferential structure S .

Rational consequence relations

► *Rational relation* = System P + RM

$$\text{RM} \quad \frac{\alpha \sim \gamma \quad \alpha \not\sim \neg\beta}{\alpha \wedge \beta \sim \gamma},$$

Rational consequence relations

- ▶ *Rational relation* = System P + RM

RM
$$\frac{\alpha \sim \gamma \quad \alpha \not\sim \neg\beta}{\alpha \wedge \beta \sim \gamma},$$

- ▶ Characterized by *ranked structures* = preferential structures + modularity