

safeAI | checking logical models

ANNELINE DAGGELINCKX, MATTHIJS KEMP, and OTTO MÄTTAS, Utrecht University, The Netherlands

1 WEEK 8 ASSIGNMENTS

1.1 Defining Concurrent Epistemic Game Structures


Consider a CEGS $M_{chicken}$, where $(\mathbb{A}gt, St, Act, d, out)$ is a concurrent game structure, and \sim_a are indistinguishability relations over St , one per agent in $\mathbb{A}gt$. We can now define the CEGS as a tuple

$$M_{chicken} = (\mathbb{A}gt, St, \sim_a \mid a \in \mathbb{A}gt, Act, d, out) \quad (1)$$

, where

- $\mathbb{A}gt = \{a_1, a_2\}$
- $St =$
 - q_0 = left-hand traffic
 - q_1 = right-hand traffic
 - q_2 = left-hand traffic; a_1 drives left; a_2 drives left
 - q_3 = left-hand traffic; a_1 drives left; a_2 drives right
 - q_4 = left-hand traffic; a_1 drives right; a_2 drives left
 - q_5 = left-hand traffic; a_1 drives right; a_2 drives right
 - q_6 = right-hand traffic; a_1 drives right; a_2 drives right
 - q_7 = right-hand traffic; a_1 drives right; a_2 drives left
 - q_8 = right-hand traffic; a_1 drives left; a_2 drives right
 - q_9 = right-hand traffic; a_1 drives left; a_2 drives left
- $\sim_a = \{\{q_0, q_1\}, \{q_3, q_8\}, \{q_4, q_7\}, \{q_2\}, \{q_5\}, \{q_6\}, \{q_9\}\}$
- $Act = \{drive_left, drive_right\}$
- $d(\mathbb{A}gt, q_i) = \{drive_left, drive_right\}, \forall i \in \{0, \dots, 9\}$
- $out =$
 - $out(q_0, drive_left, drive_left) = q_2$
 - $out(q_0, drive_left, drive_right) = q_3$
 - $out(q_0, drive_right, drive_left) = q_4$
 - $out(q_0, drive_right, drive_right) = q_5$
 - $out(q_1, drive_left, drive_left) = q_9$
 - $out(q_1, drive_left, drive_right) = q_8$
 - $out(q_1, drive_right, drive_left) = q_7$
 - $out(q_1, drive_right, drive_right) = q_6$
- let the evaluations be V , where
 - $V(crash) = \{q_3, q_4, q_5, q_7, q_8, q_9\}$
 - $V(lft) = \{q_0, q_2, q_3, q_4, q_5\}$

As there is no propositional argument matching the action $drive_right$, we are evaluating q_6 implicitly.



1.2 Validating Concurrent Epistemic Game Structures through Memoryless Strategies

For the defined CEGS $M_{chicken}$ in 1.1, it is **untrue** that under the independent combination of ATL semantics with epistemic semantics (no uniform strategies requirement) agent a_1 has a memoryless strategy in q_0 to enforce $\neg crash$ in the next state ($\langle\langle 1 \rangle\rangle X \neg crash$).

This is because in q_0 , the only way not to crash is for both agents to take action $drive_left$. Agent a_1 cannot force this protocol alone, agent a_2 needs to adhere to it as well.

1.3 Validating Concurrent Epistemic Game Structures through Indistinguishability

For the defined CEGS $M_{chicken}$ in 1.1, it is **untrue** that under ATL_{ir} , $M_{chicken}, q_0 \models_{ir} \langle\langle 1 \rangle\rangle X \neg crash$ holds.

This is because agent a_1 does not know whether it is in q_0 or q_1 . Therefore it does not know whether the action to take is $drive_left$ or $drive_right$. Even more, if agent a_1 would choose the correct action ($drive_left$), agent 2 can still cause a crash by executing $drive_right$.

1.4 Validating Concurrent Epistemic Game Structures through Memoryless Strategies

For the defined CEGS $M_{chicken}$ in 1.1, it is **true** that under the independent combination of ATL semantics with epistemic semantics (no uniform strategies requirement), both agents together have a memoryless strategy in q_0 to enforce $\neg crash$ in the next state, namely $s_{a_1}(q_0) = drive_left$.

This is because there is a strategy in q_0 which leads to a state with $\neg crash$ from both agents' perspective. To make it a complete strategy in the formal sense, we would need a strategy that also covers state q_1 . Then, the strategy becomes $s_i(q_0) = drive_left \ \forall i \in \{1, 2\}$; $s_i(q_1) = drive_right \ \forall i \in \{1, 2\}$.

1.5 Validating Concurrent Epistemic Game Structures through Indistinguishability

For the defined CEGS $M_{chicken}$ in 1.1, it is **true** that under ATL_{ir} , $M_{chicken}, q_0 \models_{ir} \langle\langle 1, 2 \rangle\rangle X \neg crash$ holds.

This is because agents do not know whether they are in q_0 or q_1 . Therefore, they do not know whether the action to take is *drive_left* or *drive_right*, not being able to create a uniform strategy.

1.6 Validating Concurrent Epistemic Game Structures through Knowledge

For the defined CEGS $M_{chicken}$ in 1.1, it is **true** that under the independent combination of ATL semantics with epistemic semantics (no uniform strategies requirement), both agents together know that they have a memoryless strategy in q_0 to enforce $\neg crash$ in the next state ($K_1 \langle\langle 1, 2 \rangle\rangle X \neg crash \wedge K_2 \langle\langle 1, 2 \rangle\rangle X \neg crash$).

This is because the only state indistinguishable for both agents from q_0 is q_1 . For $q \in \{q_0, q_1\}$, it holds that $M_{chicken}, q \models \langle\langle 1, 2 \rangle\rangle X \neg crash$, using the following strategy $s_i(q_0) = drive_left \ \forall i \in \{1, 2\}$; $s_i(q_1) = drive_right \ \forall i \in \{1, 2\}$.

1.7 Validating Concurrent Epistemic Game Structures through Indistinguishable Knowledge

For the defined CEGS $M_{chicken}$ in 1.1, it is **untrue** that under ATL_{ir} , $M_{chicken}, q_0 \models_{ir} K_1 \langle\langle 1, 2 \rangle\rangle X \neg crash \wedge K_2 \langle\langle 1, 2 \rangle\rangle X \neg crash$ holds.

This is because there is a state q_1 indistinguishable from q_0 for both agents. For $q \in \{q_0, q_1\}$, there is no uniform strategy to satisfy the requirement.

1.8 Formalising ATL_{ir}

To say in ATL_{ir} that agent a_1 can ensure that eventually it knows whether it is in a country that drives on the left or a country that drives on the right, we can specify a formula as follows

$$M_{chicken}, q_0 \models_{ir} K_1 \langle\langle 1 \rangle\rangle F(q_0 \vee q_1) \quad (2)$$

This formula is **untrue** in q_0 . This is because agent a_1 can not come to the knowledge on its own volition as agent a_2 has to also participate in order for agent a_1 to know this.

1.9 Formalising ATL_{ir}

To say in ATL_{ir} that it is inevitable that if in the next state there is no crash, then agent a_1 knows whether it is in a country that drives on the left or a country that drives on the right, we can specify a formula as follows

$$\langle\langle 1 \rangle\rangle X \neg crash \wedge E_1 \langle\langle 1 \rangle\rangle G(q_0 \vee q_1) \quad (3)$$

This formula is **true** in q_0 . This is because for agent a_1 , there are two states (q_2 and q_6) without a crash which both are reachable by a distinguishable strategy from q_0 . Namely, q_2 can be reached by taking action *drive_left* and q_6 can be reached by taking action *drive_right*.

1.10 Specifying model checking algorithms

To say in ATL_{ir} that there is a strategy which in two steps guarantees enforcing of φ from any state indistinguishable from q , we can

specify an algorithm as follows

$$1 + 1 = 3 \quad (4)$$

The big O complexity of the algorithm as a function of the model size and formula size is ...