

e.

mysql> SELECT * FROM emps;

```

+-----+-----+-----+-----+
| empno | ename | deptno | mgr |
+-----+-----+-----+-----+
| 1 | Amit | 10 | 4 |
| 2 | Rahul | 10 | 3 |
| 3 | Niles | 20 | 4 |
| 4 | Nitin | 50 | 5 |
| 5 | Sarang | 50 | NULL |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)

```

d.

mysql> SELECT * FROM depts;

```

+-----+-----+
| deptno | dname |
+-----+-----+
| 10 | DEV |
| 20 | QA |
| 30 | OPS |
| 40 | ACC |
+-----+-----+
4 rows in set (0.00 sec)

```

a.

mysql> SELECT * FROM addr;

```

+-----+-----+-----+
| empno | tal | dist |
+-----+-----+-----+
| 1 | Gad | Kolhapur |
| 2 | Karad | Satara |
| 3 | Junnar | Pune |
| 4 | Wai | Satara |
| 5 | Karad | Satara |
+-----+-----+-----+
5 rows in set (0.00 sec)

```

```

SELECT e.ename, d.dname, a.dist
FROM emps e INNER JOIN depts d
ON e.deptno = d.deptno
INNER JOIN addr a
ON e.empno = a.empno;

```