

ONE to MANY Relation

```
mysql> SELECT * FROM depts;
```

deptno	dname
10	DEV
20	QA
30	OPS
40	ACC

4 rows in set (0.00 sec)

```
mysql> SELECT * FROM emps;
```

empno	ename	deptno	mgr
1	Amit	10	4
2	Rahul	10	3
3	Nilesh	20	4
4	Nitin	50	5
5	Sarang	50	NULL

5 rows in set (0.00 sec)

From the depts table, There is One to Many relation.
One Dept can have MANY employees
Here there is One to Many relation.

From the emps table, There are many emps
Working in One dept.
Here there is Many to One relation

One To One

```
mysql> SELECT * FROM emps;
```

empno	ename	deptno	mgr
1	Amit	10	4
2	Rahul	10	3
3	Nilesh	20	4
4	Nitin	50	5
5	Sarang	50	NULL

5 rows in set (0.00 sec)

```
mysql> SELECT * FROM addr;
```

empno	tal	dist
1	Gad	Kolhapur
2	Karad	Satara
3	Junnar	Pune
4	Wai	Satara
5	Karad	Satara

5 rows in set (0.02 sec)

From the emps table, One emp has one permanent
Address, so, there is One to One relation From emp
To addr table.

From the addr table, one addr belongs to one emp.
So there is one to one relation between the addr and
emp table.

Many to Many

```
mysql> SELECT * FROM emps;
```

empno	ename	deptno	mgr
1	Amit	10	4
2	Rahul	10	3
3	Nilesh	20	4
4	Nitin	50	5
5	Sarang	50	NULL

5 rows in set (0.00 sec)

```
mysql> SELECT * FROM meeting;
```

meetno	topic	venue
100	Scheduling	Director Cabin
200	Annual meet	Board Room
300	App Design	Co-director Cabin

3 rows in set (0.02 sec)

One Emp attends
many meetings.

One meeting attended
by many emps.

```
mysql> SELECT * FROM emp_meeting;
```

meetno	empno
100	3
100	4
200	2
200	3
200	4
200	5
300	2
300	4

10 rows in set (0.00 sec)

Auxiliary
Table.

meetno	topic	venue	Empno
100	Scheduling	DC	1
100	"	"	2
100	"	"	3
200	Annual meet	BR	1
200	"	"	2
200	"	"	3
200	"	"	4
200	"	"	5

Empno	Sname	dno	mgr	meetno
1	Amit	10	4	200
1	Amit	10	4	300
4	Nitin	50	5	100
4	Nitin	50	5	200
4	Nitin	50	5	300