
Trainer : Nisha Dingare

Email : nisha.dingare@sunbeaminfo.com



DDL – ALTER statement

- ALTER statement is used to do modification into table, view, function, procedure, ...
- ALTER TABLE is used to change table structure.
- Add new column(s) into the table.
 - ALTER TABLE table ADD col TYPE;
 - ALTER TABLE table ADD c1 TYPE, c2 TYPE;
- Modify column of the table.
 - ALTER TABLE table MODIFY col NEW_TYPE;
- Rename column.
 - ALTER TABLE CHANGE old_col new_col TYPE;
- Drop a column
 - ALTER TABLE DROP COLUMN col;
- Rename table
 - ALTER TABLE table RENAME TO new_table;



Views

- RDBMS view represents view (projection) of the data.
- View is based on SELECT statement.
- Typically it is restricted view of the data (limited rows or columns) from one or more tables (joins and/or sub-queries) or summary of the data (grouping).
- Data of view is not stored on server hard-disk; but its SELECT statement is stored in compiled form. It speed up execution of view.



Views

- Views are of two types: Simple view and Complex view
- Usually if view contains computed columns, group by, joins or sub-queries, then the views are said to be complex. DML operations are not supported on these views.
- DML operations on view affects underlying table.
- View can be created with CHECK OPTION to ensure that DML operations can be performed only the data visible in that view.



View

- Views can be differentiated with: SHOW FULL TABLES.
- Views can be dropped with DROP VIEW statement.
- View can be based on another view.

- Applications of views
 - Security: Providing limited access to the data.
 - Hide source code of the table.
 - Simplifies complex queries.



Thank You

