

ffprobe Documentation

Table of Contents

- 1 Synopsis
- 2 Description
- 3 Options
 - 3.1 Stream specifiers
 - 3.2 Generic options
 - 3.3 AVOptions
 - 3.4 Main options
- 4 Writers
 - 4.1 default
 - 4.2 compact, csv
 - 4.3 flat
 - 4.4 ini
 - 4.5 json
 - 4.6 xml
- 5 Timecode
- 6 See Also
- 7 Authors

1 Synopsis

`ffprobe [options] [input_url]`

2 Description

`ffprobe` gathers information from multimedia streams and prints it in human- and machine-readable fashion.

For example it can be used to check the format of the container used by a multimedia stream and the format and type of each media stream contained in it.

If a url is specified in input, `ffprobe` will try to open and probe the url content. If the url cannot be opened or recognized as a multimedia file, a positive exit code is returned.

`ffprobe` may be employed both as a standalone application or in combination with a textual filter, which may perform more sophisticated processing, e.g. statistical processing or plotting.

Options are used to list some of the formats supported by `ffprobe` or for specifying which information to display, and for setting how `ffprobe` will show it.

`ffprobe` output is designed to be easily parsable by a textual filter, and consists of one or more sections of a form defined by the selected writer, which is specified by the `print_format` option.

Sections may contain other nested sections, and are identified by a name (which may be shared by other sections), and an unique name. See the output of `sections`.

Metadata tags stored in the container or in the streams are recognized and printed in the corresponding "FORMAT", "STREAM" or "PROGRAM_STREAM" section.

3 Options

All the numerical options, if not specified otherwise, accept a string representing a number as input, which may be followed by one of the SI unit prefixes, for example: 'K', 'M', or 'G'.

If 'i' is appended to the SI unit prefix, the complete prefix will be interpreted as a unit prefix for binary multiples, which are based on powers of 1024 instead of powers of 1000. Appending 'B' to the SI unit prefix multiplies the value by 8. This allows using, for example: 'KB', 'MiB', 'G' and 'B' as number suffixes.

Options which do not take arguments are boolean options, and set the corresponding value to true. They can be set to false by prefixing the option name with "no". For example using "--nofoo" will set the boolean option with name "foo" to false.

3.1 Stream specifiers

Some options are applied per-stream, e.g. bitrate or codec. Stream specifiers are used to precisely specify which stream(s) a given option belongs to.

A stream specifier is a string generally appended to the option name and separated from it by a colon. E.g. `--codec:a:1 ac3` contains the `a:1` stream specifier, which matches the second audio stream. Therefore, it would select the ac3 codec for the second audio stream.

A stream specifier can match several streams, so that the option is applied to all of them. E.g. the stream specifier in `--b:a 128k` matches all audio streams.

An empty stream specifier matches all streams. For example, `--codec copy` or `--codec: copy` would copy all the streams without reencoding.

Possible forms of stream specifiers are:

stream_index

Matches the stream with this index. E.g. `--threads:1 4` would set the thread count for the second stream to 4. If *stream_index* is used as an additional stream specifier (see below), then it selects stream number *stream_index* from the matching streams. Stream numbering is based on the order of the streams as detected by libavformat except when a program ID is also specified. In this case it is based on the ordering of the streams in the program.

stream_type[:additional_stream_specifier]

stream_type is one of following: 'v' or 'V' for video, 'a' for audio, 's' for subtitle, 'd' for data, and 't' for attachments. 'v' matches all video streams, 'V' only matches video streams which are not attached pictures, video thumbnails or cover arts. If *additional_stream_specifier* is used, then it matches streams which both have this type and match the *additional_stream_specifier*. Otherwise, it matches all streams of the specified type.

p:program_id[:additional_stream_specifier]

Matches streams which are in the program with the id *program_id*. If *additional_stream_specifier* is used, then it matches streams which both are part of the program and match the *additional_stream_specifier*.

#stream_id* or *i:stream_id

Match the stream by stream id (e.g. PID in MPEG-TS container).

m:key[:value]

Matches streams with the metadata tag *key* having the specified value. If *value* is not given, matches streams that contain the given tag with any value.

u

Matches streams with usable configuration, the codec must be defined and the essential information such as video dimension or audio sample rate must be present.

Note that in `ffmpeg`, matching by metadata will only work properly for input files.

3.2 Generic options

These options are shared amongst the `ff*` tools.

-L

Show license.

-h, -?, -help, --help [arg]

Show help. An optional parameter may be specified to print help about a specific item. If no argument is specified, only basic (non advanced) tool options are shown.

Possible values of *arg* are:

long

Print advanced tool options in addition to the basic tool options.

full

Print complete list of options, including shared and private options for encoders, decoders, demuxers, muxers, filters, etc.

decoder=decoder_name

Print detailed information about the decoder named *decoder_name*. Use the `-decoders` option to get a list of all decoders.

encoder=encoder_name

Print detailed information about the encoder named *encoder_name*. Use the `-encoders` option to get a list of all encoders.

demuxer=demuxer_name

Print detailed information about the demuxer named *demuxer_name*. Use the `-formats` option to get a list of all demuxers and muxers.

muxer=muxer_name

Print detailed information about the muxer named *muxer_name*. Use the `-formats` option to get a list of all muxers and demuxers.

filter=filter_name

Print detailed information about the filter name *filter_name*. Use the `-filters` option to get a list of all filters.

bsf=bitstream_filter_name

Print detailed information about the bitstream filter name *bitstream_filter_name*. Use the `-bsfs` option to get a list of all bitstream filters.

-version

Show version.

-formats

Show available formats (including devices).

-demuxers

Show available demuxers.

-muxers

Show available muxers.

-devices

Show available devices.

-codecs

Show all codecs known to libavcodec.

Note that the term 'codec' is used throughout this documentation as a shortcut for what is more correctly called a media bitstream format.

-decoders

Show available decoders.

-encoders

Show all available encoders.

-bsfs

Show available bitstream filters.

-protocols

Show available protocols.

-filters

Show available libavfilter filters.

-pix_fmts

Show available pixel formats.

-sample_fmts

Show available sample formats.

-layouts

Show channel names and standard channel layouts.

-colors

Show recognized color names.

-sources *device* [,*opt1=val1* [,*opt2=val2*] ...]

Show autodetected sources of the input device. Some devices may provide system-dependent source names that cannot be autodetected. The returned list cannot be assumed to be always complete.

```
ffmpeg -sources pulse,server=192.168.0.4
```

-sinks *device* [,*opt1=val1* [,*opt2=val2*] ...]

Show autodetected sinks of the output device. Some devices may provide system-dependent sink names that cannot be autodetected. The returned list cannot be assumed to be always complete.

```
ffmpeg -sinks pulse,server=192.168.0.4
```

-loglevel [*flags+*] *loglevel* | -v [*flags+*] *loglevel*

Set logging level and flags used by the library.

The optional *flags* prefix can consist of the following values:

‘repeat’

Indicates that repeated log output should not be compressed to the first line and the "Last message repeated n times" line will be omitted.

‘level’

Indicates that log output should add a `[level]` prefix to each message line. This can be used as an alternative to log coloring, e.g. when dumping the log to file.

Flags can also be used alone by adding a `’+’/’-’` prefix to set/reset a single flag without affecting other *flags* or changing *loglevel*. When setting both *flags* and *loglevel*, a `’+’` separator is expected between the last *flags* value and before *loglevel*.

loglevel is a string or a number containing one of the following values:

‘quiet, -8’

Show nothing at all; be silent.

‘panic, 0’

Only show fatal errors which could lead the process to crash, such as an assertion failure. This is not currently used for anything.

‘fatal, 8’

Only show fatal errors. These are errors after which the process absolutely cannot continue.

‘error, 16’

Show all errors, including ones which can be recovered from.

‘warning, 24’

Show all warnings and errors. Any message related to possibly incorrect or unexpected events will be shown.

‘info, 32’

Show informative messages during processing. This is in addition to warnings and errors. This is the default value.

‘verbose, 40’

Same as `info`, except more verbose.

‘debug, 48’

Show everything, including debugging information.

‘trace, 56’

For example to enable repeated log output, add the `level` prefix, and set *loglevel* to `verbose`:

```
ffmpeg -loglevel repeat+level+verbose -i input output
```

Another example that enables repeated log output without affecting current state of `level` prefix flag or *loglevel*:

```
ffmpeg [...] -loglevel +repeat
```

By default the program logs to `stderr`. If coloring is supported by the terminal, colors are used to mark errors and warnings. Log coloring can be disabled setting the environment variable `AV_LOG_FORCE_NOCOLOR`, or can be forced setting the environment variable `AV_LOG_FORCE_COLOR`.

-report

Dump full command line and log output to a file named *program-YYYYMMDD-HHMMSS.log* in the current directory. This file can be useful for bug reports. It also implies `-loglevel debug`.

Setting the environment variable `FFREPORT` to any value has the same effect. If the value is a `:`-separated key=value sequence, these options will affect the report; option values must be escaped if they contain special characters or the options delimiter `:` (see the “Quoting and escaping” section in the `ffmpeg-utils` manual).

The following options are recognized:

file

set the file name to use for the report; `%p` is expanded to the name of the program, `%t` is expanded to a timestamp, `%%` is expanded to a plain `%`

level

set the log verbosity level using a numerical value (see `-loglevel`).

For example, to output a report to a file named `ffreport.log` using a log level of `32` (alias for log level `info`):

```
FFREPORT=file=ffreport.log:level=32 ffmpeg -i input output
```

Errors in parsing the environment variable are not fatal, and will not appear in the report.

-hide_banner

Suppress printing banner.

All FFmpeg tools will normally show a copyright notice, build options and library versions. This option can be used to suppress printing this information.

-cpuflags flags (global)

Allows setting and clearing cpu flags. This option is intended for testing. Do not use it unless you know what you’re doing.

```
ffmpeg -cpuflags -sse+mmx ...
ffmpeg -cpuflags mmx ...
ffmpeg -cpuflags 0 ...
```

Possible flags for this option are:

‘x86’

- ‘mmx’**
- ‘mmxext’**
- ‘sse’**
- ‘sse2’**
- ‘sse2slow’**
- ‘sse3’**
- ‘sse3slow’**
- ‘ssse3’**
- ‘atom’**
- ‘sse4.1’**
- ‘sse4.2’**
- ‘avx’**
- ‘avx2’**
- ‘xop’**

```

'fma3'
'fma4'
'3dnow'
'3dnowext'
'bmi1'
'bmi2'
'cmov'

```

```

'ARM'
'armv5te'
'armv6'
'armv6t2'
'vfp'
'vfpv3'
'neon'
'setend'

```

```

'AArch64'
'armv8'
'vfp'
'neon'

```

```

'PowerPC'
'altivec'

```

```

'Specific Processors'
'pentium2'
'pentium3'
'pentium4'
'k6'
'k62'
'athlon'
'athlonxp'
'k8'

```

3.3 AVOptions

These options are provided directly by the libavformat, libavdevice and libavcodec libraries. To see the list of available AVOptions, use the `-help` option. They are separated into two categories:

generic

These options can be set for any container, codec or device. Generic options are listed under AVFormatContext options for containers/devices and under AVCodecContext options for codecs.

private

These options are specific to the given container, device or codec. Private options are listed under their corresponding containers/devices/codecs.

For example to write an ID3v2.3 header instead of a default ID3v2.4 to an MP3 file, use the `id3v2_version` private option of the MP3 muxer:

```
ffmpeg -i input.flac -id3v2_version 3 out.mp3
```

All codec AVOptions are per-stream, and thus a stream specifier should be attached to them:

```
ffmpeg -i multichannel.mxf -map 0:v:0 -map 0:a:0 -map 0:a:0 -c:a:0 ac3 -b:a:0 640k -ac:
```

In the above example, a multichannel audio stream is mapped twice for output. The first instance is encoded with codec ac3 and bitrate 640k. The second instance is downmixed to 2 channels and encoded with codec aac. A bitrate of 128k is specified for it using absolute index of the output stream.

Note: the `-nooption` syntax cannot be used for boolean AVOptions, use `-option 0/-option 1`.

Note: the old undocumented way of specifying per-stream AVOptions by prepending v/a/s to the options name is now obsolete and will be removed soon.

3.4 Main options

-f *format*

Force format to use.

-unit

Show the unit of the displayed values.

-prefix

Use SI prefixes for the displayed values. Unless the `"-byte_binary_prefix"` option is used all the prefixes are decimal.

-byte_binary_prefix

Force the use of binary prefixes for byte values.

-sexagesimal

Use sexagesimal format HH:MM:SS.MICROSECONDS for time values.

-pretty

Prettify the format of the displayed values, it corresponds to the options `"-unit -prefix -byte_binary_prefix -sexagesimal"`.

-of, -print_format *writer_name*[=*writer_options*]

Set the output printing format.

writer_name specifies the name of the writer, and *writer_options* specifies the options to be passed to the writer.

For example for printing the output in JSON format, specify:

```
-print_format json
```

For more details on the available output printing formats, see the Writers section below.

-sections

Print sections structure and section information, and exit. The output is not meant to be parsed by a machine.

-select_streams *stream_specifier*

Select only the streams specified by *stream_specifier*. This option affects only the options related to streams (e.g. `show_streams` , `show_packets` , etc.).

For example to show only audio streams, you can use the command:

```
ffprobe -show_streams -select_streams a INPUT
```

To show only video packets belonging to the video stream with index 1:

```
ffprobe -show_packets -select_streams v:1 INPUT
```

-show_data

Show payload data, as a hexadecimal and ASCII dump. Coupled with `-show_packets`, it will dump the packets' data. Coupled with `-show_streams`, it will dump the codec extradata.

The dump is printed as the "data" field. It may contain newlines.

-show_data_hash *algorithm*

Show a hash of payload data, for packets with `-show_packets` and for codec extradata with `-show_streams`.

-show_error

Show information about the error found when trying to probe the input.

The error information is printed within a section with name "ERROR".

-show_format

Show information about the container format of the input multimedia stream.

All the container format information is printed within a section with name "FORMAT".

-show_format_entry *name*

Like `-show_format`, but only prints the specified entry of the container format information, rather than all. This option may be given more than once, then all specified entries will be shown.

This option is deprecated, use `show_entries` instead.

-show_entries *section_entries*

Set list of entries to show.

Entries are specified according to the following syntax. *section_entries* contains a list of section entries separated by `:`. Each section entry is composed by a section name (or unique name), optionally followed by a list of entries local to that section, separated by `,`.

If section name is specified but is followed by no `=`, all entries are printed to output, together with all the contained sections. Otherwise only the entries specified in the local section entries list are printed. In particular, if `=` is specified but the list of local entries is empty, then no entries will be shown for that section.

Note that the order of specification of the local section entries is not honored in the output, and the usual display order will be retained.

The formal syntax is given by:

```
LOCAL_SECTION_ENTRIES ::= SECTION_ENTRY_NAME[,LOCAL_SECTION_ENTRIES]
SECTION_ENTRY          ::= SECTION_NAME[=[LOCAL_SECTION_ENTRIES]]
SECTION_ENTRIES        ::= SECTION_ENTRY[:SECTION_ENTRIES]
```

For example, to show only the index and type of each stream, and the PTS time, duration time, and stream index of the packets, you can specify the argument:

```
packet=pts_time,duration_time,stream_index : stream=index,codec_type
```

To show all the entries in the section "format", but only the codec type in the section "stream", specify the argument:

```
format : stream=codec_type
```

To show all the tags in the stream and format sections:

```
stream_tags : format_tags
```

To show only the `title` tag (if available) in the stream sections:

```
stream_tags=title
```

-show_packets

Show information about each packet contained in the input multimedia stream.

The information for each single packet is printed within a dedicated section with name "PACKET".

-show_frames

Show information about each frame and subtitle contained in the input multimedia stream.

The information for each single frame is printed within a dedicated section with name "FRAME" or "SUBTITLE".

-show_log *loglevel*

Show logging information from the decoder about each frame according to the value set in *loglevel*, (see `-loglevel`). This option requires `-show_frames`.

The information for each log message is printed within a dedicated section with name "LOG".

-show_streams

Show information about each media stream contained in the input multimedia stream.

Each media stream information is printed within a dedicated section with name "STREAM".

-show_programs

Show information about programs and their streams contained in the input multimedia stream.

Each media stream information is printed within a dedicated section with name "PROGRAM_STREAM".

-show_chapters

Show information about chapters stored in the format.

Each chapter is printed within a dedicated section with name "CHAPTER".

-count_frames

Count the number of frames per stream and report it in the corresponding stream section.

-count_packets

Count the number of packets per stream and report it in the corresponding stream section.

-read_intervals *read_intervals*

Read only the specified intervals. *read_intervals* must be a sequence of interval specifications separated by ",". *ffprobe* will seek to the interval starting point, and will continue reading from that.

Each interval is specified by two optional parts, separated by "%".

The first part specifies the interval start position. It is interpreted as an absolute position, or as a relative offset from the current position if it is preceded by the "+" character. If this first part is not specified, no seeking will be performed when reading this interval.

The second part specifies the interval end position. It is interpreted as an absolute position, or as a relative offset from the current position if it is preceded by the "+" character. If the offset specification starts with "#", it is interpreted as the number of packets to read (not including the flushing packets) from the interval start. If no second part is specified, the program will read until the end of the input.

Note that seeking is not accurate, thus the actual interval start point may be different from the specified position. Also, when an interval duration is specified, the absolute end time will be computed by adding the duration to the interval start point found by seeking the file, rather than to the specified start value.

The formal syntax is given by:

```
INTERVAL ::= [START|+START_OFFSET] [%[END|+END_OFFSET]]
INTERVALS ::= INTERVAL [,INTERVALS]
```

A few examples follow.

- Seek to time 10, read packets until 20 seconds after the found seek point, then seek to position 01:30 (1 minute and thirty seconds) and read packets until position 01:45 .

```
10%+20,01:30%01:45
```

- Read only 42 packets after seeking to position 01:23 :

```
01:23%+#42
```

- Read only the first 20 seconds from the start:

```
%+20
```

- Read from the start until position 02:30 :

```
%02:30
```

-show_private_data, -private

Show private data, that is data depending on the format of the particular shown element. This option is enabled by default, but you may need to disable it for specific uses, for example when creating XSD-compliant XML output.

-show_program_version

Show information related to program version.

Version information is printed within a section with name "PROGRAM_VERSION".

-show_library_versions

Show information related to library versions.

Version information for each library is printed within a section with name "LIBRARY_VERSION".

-show_versions

Show information related to program and library versions. This is the equivalent of setting both `-show_program_version` and `-show_library_versions` options.

-show_pixel_formats

Show information about all pixel formats supported by FFmpeg.

Pixel format information for each format is printed within a section with name "PIXEL_FORMAT".

-bitexact

Force bitexact output, useful to produce output which is not dependent on the specific build.

-i *input_url*

Read *input_url*.

4 Writers

A writer defines the output format adopted by `ffprobe`, and will be used for printing all the parts of the output.

A writer may accept one or more arguments, which specify the options to adopt. The options are specified as a list of *key=value* pairs, separated by ":".

All writers support the following options:

string_validation, sv

Set string validation mode.

The following values are accepted.

‘fail’

The writer will fail immediately in case an invalid string (UTF-8) sequence or code point is found in the input. This is especially useful to validate input metadata.

‘ignore’

Any validation error will be ignored. This will result in possibly broken output, especially with the json or xml writer.

‘replace’

The writer will substitute invalid UTF-8 sequences or code points with the string specified with the `string_validation_replacement`.

Default value is ‘replace’.

string_validation_replacement, svr

Set replacement string to use in case `string_validation` is set to ‘replace’.

In case the option is not specified, the writer will assume the empty string, that is it will remove the invalid sequences from the input strings.

A description of the currently available writers follows.

4.1 default

Default format.

Print each section in the form:

```
[SECTION]
key1=val1
...
keyN=valN
[/SECTION]
```

Metadata tags are printed as a line in the corresponding `FORMAT`, `STREAM` or `PROGRAM_STREAM` section, and are prefixed by the string "TAG:".

A description of the accepted options follows.

nokey, nk

If set to 1 specify not to print the key of each field. Default value is 0.

noprint_wrappers, nw

If set to 1 specify not to print the section header and footer. Default value is 0.

4.2 compact, csv

Compact and CSV format.

The `csv` writer is equivalent to `compact`, but supports different defaults.

Each section is printed on a single line. If no option is specified, the output has the form:

```
section|key1=val1| ... |keyN=valN
```

Metadata tags are printed in the corresponding "format" or "stream" section. A metadata tag key, if printed, is prefixed by the string "tag:".

The description of the accepted options follows.

item_sep, s

Specify the character to use for separating fields in the output line. It must be a single printable character, it is "|" by default ("," for the `csv` writer).

nokey, nk

If set to 1 specify not to print the key of each field. Its default value is 0 (1 for the `csv` writer).

escape, e

Set the escape mode to use, default to "c" ("csv" for the `csv` writer).

It can assume one of the following values:

c

Perform C-like escaping. Strings containing a newline ('`\n`'), carriage return ('`\r`'), a tab ('`\t`'), a form feed ('`\f`'), the escaping character ('`\`') or the item separator character *SEP* are escaped using C-like fashioned escaping, so that a newline is converted to the sequence '`\n`', a carriage return to '`\r`', '`\`' to '`\\`' and the separator *SEP* is converted to '`\SEP`'.

csv

Perform CSV-like escaping, as described in RFC4180. Strings containing a newline ('`\n`'), a carriage return ('`\r`'), a double quote ('`"`'), or *SEP* are enclosed in double-quotes.

none

Perform no escaping.

print_section, p

Print the section name at the beginning of each line if the value is 1, disable it with value set to 0. Default value is 1.

4.3 flat

Flat format.

A free-form output where each line contains an explicit key=value, such as "streams.stream.3.tags.foo=bar". The output is shell escaped, so it can be directly embedded in sh scripts as long as the separator character is an alphanumeric character or an underscore (see *sep_char* option).

The description of the accepted options follows.

sep_char, s

Separator character used to separate the chapter, the section name, IDs and potential tags in the printed field key.

Default value is '.'.

hierarchical, h

Specify if the section name specification should be hierarchical. If set to 1, and if there is more than one section in the current chapter, the section name will be prefixed by the name of the chapter. A value of 0 will disable this behavior.

Default value is 1.

4.4 ini

INI format output.

Print output in an INI based format.

The following conventions are adopted:

- all key and values are UTF-8
- '.' is the subgroup separator
- newline, '\t', '\f', '\b' and the following characters are escaped
- '\' is the escape character
- '#' is the comment indicator
- '=' is the key/value separator
- ':' is not used but usually parsed as key/value separator

This writer accepts options as a list of *key=value* pairs, separated by ':'.

The description of the accepted options follows.

hierarchical, h

Specify if the section name specification should be hierarchical. If set to 1, and if there is more than one section in the current chapter, the section name will be prefixed by the name of the chapter. A value of 0 will disable this behavior.

Default value is 1.

4.5 json

JSON based format.

Each section is printed using JSON notation.

The description of the accepted options follows.

compact, c

If set to 1 enable compact output, that is each section will be printed on a single line. Default value is 0.

For more information about JSON, see <http://www.json.org/> (<http://www.json.org/>).

4.6 xml

XML based format.

The XML output is described in the XML schema description file `ffprobe.xsd` installed in the FFmpeg datadir.

An updated version of the schema can be retrieved at the url <http://www.ffmpeg.org/schema/ffprobe.xsd> (<http://www.ffmpeg.org/schema/ffprobe.xsd>), which redirects to the latest schema committed into the FFmpeg development source code tree.

Note that the output issued will be compliant to the `ffprobe.xsd` schema only when no special global output options (`unit`, `prefix`, `byte_binary_prefix`, `sexagesimal` etc.) are specified.

The description of the accepted options follows.

fully_qualified, q

If set to 1 specify if the output should be fully qualified. Default value is 0. This is required for generating an XML file which can be validated through an XSD file.

xsd_strict, x

If set to 1 perform more checks for ensuring that the output is XSD compliant. Default value is 0. This option automatically sets `fully_qualified` to 1.

For more information about the XML format, see <https://www.w3.org/XML/> (<https://www.w3.org/XML/>).

5 Timecode

ffprobe supports Timecode extraction:

- MPEG1/2 timecode is extracted from the GOP, and is available in the video stream details (`-show_streams`, see *timecode*).
- MOV timecode is extracted from `tmcd` track, so is available in the `tmcd` stream metadata (`-show_streams`, see *TAG:timecode*).
- DV, GXF and AVI timecodes are available in format metadata (`-show_format`, see *TAG:timecode*).

6 See Also

[ffprobe-all](#) ([ffprobe-all.html](#)), [ffmpeg](#) ([ffmpeg.html](#)), [ffplay](#) ([ffplay.html](#)), [ffmpeg-utils](#) ([ffmpeg-utils.html](#)), [ffmpeg-scaler](#) ([ffmpeg-scaler.html](#)), [ffmpeg-resampler](#) ([ffmpeg-resampler.html](#)), [ffmpeg-codecs](#) ([ffmpeg-codecs.html](#)), [ffmpeg-bitstream-filters](#) ([ffmpeg-bitstream-filters.html](#)), [ffmpeg-formats](#) ([ffmpeg-formats.html](#)), [ffmpeg-devices](#) ([ffmpeg-devices.html](#)), [ffmpeg-protocols](#) ([ffmpeg-protocols.html](#)), [ffmpeg-filters](#) ([ffmpeg-filters.html](#))

7 Authors

The FFmpeg developers.

For details about the authorship, see the Git history of the project ([git://source.ffmpeg.org/ffmpeg](https://source.ffmpeg.org/ffmpeg)), e.g. by typing the command `git log` in the FFmpeg source directory, or browsing the online repository at <http://source.ffmpeg.org> (<http://source.ffmpeg.org>).

Maintainers for the specific components are listed in the file `MAINTAINERS` in the source code tree.

This document was generated on *March 16, 2020* using *makeinfo* (<http://www.gnu.org/software/texinfo/>).

Hosting provided by telepoint.bg (<https://telepoint.bg>)