

iMR500 Performance parameter table

Indoor general robot chassis parameters		
Category	Parameter	Index
Basic parameter	Product size	D500*H310mm
	Product weight	35KG(Optional add 10kg counterweight)
	No load working time	12h
	Charging time	4h
	Max load	50kg
	Battery capacity	24V/20AH
	Chassis form	2* drive wheel +4* universal wheel +1* directional wheel
	Hardware configuration	Laser radar:TOF20m*1
		6.5 "servo hub motor (with odometer) *2
		RGBD Depth Camera (0.6-8m) *1
		Ultrasonic ranging sensor (0.3-1.2m) *1
		IMU six-axis attitude sensor *1
		High-performance X86 industrial computer *1
Maneuvering parameter	Maximum navigation speed	0.8m/s
	Maximum speed	1.5m/s
	Angle of climb	5°
	Obstacle height	10mm
	Ditch width	40mm
	Turning radius	0mm
	Maximum rotation speed	60°/s
	Positioning accuracy	±5cm
	Map area	10000m2
	Navigation accuracy	±5cm
Extension interface	Power interface	24V (Power200W)
	USB	reserved peripherals x 2
	Network interface	RJ45, communication or routing
	Physical mounting interface	Structural mounting hole
	Other interface	System switch, emergency stop switch
Charging pile parameter	Charging mode	Contact charging
	Input	AC 110-240V
	Output	29.4V
	Max current	7A
Environmental requirement	Protection mechanism	Short circuit, overcurrent, etc
	Working environment	5°C-40°C
	Storage environment	-10°C-60°C