

Lab1: Temporal Difference Learning

Lab Objective:

In this lab, you will learn temporal difference learning (TD) algorithm by solving the 2048 game using an n -tuple network.

Important Date:

1. Submission Deadline: 9/22 (Sun) 23:59
2. Demo date: 9/23 (Mon)

Turn in:

1. Experiment report (.pdf)
2. Source code [NOT including model weights]

Notice: zip all files with name “RL_LAB1_StudentId_Name.zip”,
e.g.: 「RL_LAB1_312581015_張孝全.zip」

Lab Description:

- Understand the concept of (before-)state and after-state.
- Learn to construct and design an n -tuple network.
- Understand TD algorithm.
- Understand Q-learning network training.

Requirements:


- Implement TD(0) algorithm
 - Construct an n -tuple network.
 - Action selection according to the n -tuple network.
 - Calculate TD-target and TD-error.
 - Update $V(\text{state})$, not $V(\text{after-state})$.
 - ◆ That is, you need to use the information of $P(\text{popup tile } 2) = 0.9$ and $P(\text{popup tile } 4) = 0.1$ in your code.
 - Understand temporal difference learning mechanisms.

Game Environment – 2048:

- Introduction: 2048 is a single-player sliding block puzzle game. The game's objective is to slide numbered tiles on a grid to combine them to create a tile with the number 2048.
- Actions: **Up, Down, Left, Right**
- Reward: The score is the value of new tile when two tiles are combined.

		2	4
		4	8
	2	16	32
	2	2	16


- A sample of two-step state transition



Implementation Details:

Network Architecture

- n -tuple patterns: 4×6 -tuples with all possible isomorphisms



Training Arguments

- Learning rate: 0.1
 - Learning rate for features of n -tuple network with m features: $0.1 \div m$
- Train the network at least 100k episodes

Algorithm:**A pseudocode of the game engine and training.** (modified backward training method)

```

function PLAY GAME
   $score \leftarrow 0$ 
   $s \leftarrow \text{INITIALIZE GAME STATE}$ 
  while IS NOT TERMINAL STATE( $s$ ) do
     $a \leftarrow \underset{a' \in A(s)}{\text{argmax}} \text{EVALUATE}(s, a')$ 
     $r, s', s'' \leftarrow \text{MAKE MOVE}(s, a)$ 
    SAVE RECORD( $s, a, r, s', s''$ )
     $score \leftarrow score + r$ 
     $s \leftarrow s''$ 
  for ( $s, a, r, s', s''$ ) FROM TERMINAL DOWNT0 INITIAL do
    LEARN EVALUATION( $s, a, r, s', s''$ )
  return  $score$ 

function MAKE MOVE( $s, a$ )
   $s', r \leftarrow \text{COMPUTE AFTERSTATE}(s, a)$ 
   $s'' \leftarrow \text{ADD RANDOM TILE}(s')$ 
  return ( $r, s', s''$ )

```

TD-state

```

function EVALUATE( $s, a$ )
   $s', r \leftarrow \text{COMPUTE AFTERSTATE}(s, a)$ 
   $S'' \leftarrow \text{ALL POSSIBLE NEXT STATES}(s')$ 
  return  $r + \sum_{s'' \in S''} P(s, a, s'') V(s'')$ 


function LEARN EVALUATION( $s, a, r, s', s''$ )
   $V(s) \leftarrow V(s) + \alpha(r + V(s'') - V(s))$ 

```

Scoring Criteria:

Show your work, otherwise no credit will be granted.

- Report (20% + Bonus 20%)
 - A plot shows scores (mean) of at least 100k training episodes (20%)
E.g.



- Bonus: (20%)
 - ◆ Describe the implementation and the usage of n -tuple network. (5%)
 - ◆ Explain the mechanism of TD(0). (5%)
 - ◆ Describe your implementation in detail including action selection and TD-backup diagram. (10%)
- Demo Performance (80%)
 - The 2048-tile win rate in 1000 games, $[\text{winrate}_{2048}]$. (60%)
E.g.

1000	mean = 21355.2	max = 64492
128	100%	(0.1%)
256	99.9%	(1.4%)
512	98.5%	(11.6%)
1024	86.9%	(51.2%)
2048	35.7%	(34.6%)
4096	1.1%	(1.1%)

- Questions. (20%)

References:

- [1] Szubert, Marcin, and Wojciech Jaśkowski. "Temporal difference learning of N-tuple networks for the game 2048." 2014 IEEE Conference on Computational Intelligence and Games. IEEE, 2014.
- [2] Kun-Hao Yeh, I-Chen Wu, Chu-Hsuan Hsueh, Chia-Chuan Chang, Chao-Chin Liang, and Han Chiang, Multi-Stage Temporal Difference Learning for 2048-like Games, accepted by IEEE Transactions on Computational Intelligence and AI in Games (SCI), doi: 10.1109/TCIAIG.2016.2593710, 2016.
- [3] Oka, Kazuto, and Kiminori Matsuzaki. "Systematic selection of n-tuple networks for 2048." International Conference on Computers and Games. Springer International Publishing, 2016.
- [4] moporgic. "Basic implementation of 2048 in Python." Retrieved from Github: <https://github.com/moporgic/2048-Demo-Python>.
- [5] moporgic. "Temporal Difference Learning for Game 2048 (Demo)." Retrieved from Github: <https://github.com/moporgic/TDL2048-Demo>.
- [6] lukewayne123. "2048-Framework" Retrieved from Github: <https://github.com/lukewayne123/2048-Framework>.