

## Interactive / complex / 2

IC 1	query	Interactive / complex / 2				
IC 2	title	Recent messages by your friends				
IC 3	pattern	<pre>graph LR     Person[id = \$id] -- knows --&gt; person["person: Person id firstName lastName"]     Message[Message id content / imageFile creationDate] -- hasCreator --&gt; person</pre>				
IC 11		desc.	Given a start Person, find (the most recent) Messages from all of that Person’s friends. Only consider Messages created before the given maxDate (excluding that day).			
IC 12		params	1	Person.id	ID	personId
IC 13			2	maxDate	Date	maxDate
IC 14		result	1	Message-hasCreator->Person.id	ID	R
	2		Message-hasCreator->Person.firstName	String	R	personFirstName
	3		Message-hasCreator->Person.lastName	String	R	personLastName
	4		Message.id	ID	R	messageId
	5		Message.content or Post.imageFile	String	R	messageContent
	6		Message.creationDate	DateTime	R	messageCreationDate
	sort	1	Message.creationDate	↓		
		2	Message.id	↑		
	limit	20				
	CPs	1.1, 2.2, 2.3, 3.2, 8.5				
	relevance	This is a navigational query looking for paths of length two, starting from a given Person, going to their friends and from them, moving to their published Posts and Comments. This query exercises both the optimizer and how data is stored. It tests the ability to create execution plans taking advantage of the orderings induced by some operators to avoid performing expensive sorts. This query requires selecting Posts and Comments based on their creation date, which might be correlated with their identifier and therefore, having intermediate results with interesting orders. Also, messages could be stored in an order correlated with their creation date to improve data access locality. Finally, as many of the attributes required in the projection are not needed for the execution of the query, it is expected that the query optimizer will move the projection to the end.				